```c
#include <stdio.h>
#include <stdlib.h>

struct Node {
    int data;
    struct Node* next;
};

int main() {
    struct Node* head = NULL;
    struct Node* second = NULL;
    struct Node* third = NULL;

    head = (struct Node*)malloc(sizeof(struct Node));
    second = (struct Node*)malloc(sizeof(struct Node));
    third = (struct Node*)malloc(sizeof(struct Node));

    head->data = 10;
    head->next = second;

    second->data = 20;
    second->next = third;

    third->data = 30;
    third->next = NULL;

    struct Node* temp = head;
    printf("Linked List: ");
```

```
abhaygupta@192 main.c % gcc main.c
abhaygupta@192 main.c % ./a.out
Linked List: 10 -> 20 -> 30 -> NULL
abhaygupta@192 main.c %
```

Expt.No: 10 (Dynamic Memory Allocation)

Date

Page No. 1

Experiment - 10.1

```
#include <stdio.h>
#include <stdlib.h>

struct Node {
        int data;
        struct Node* next
};
int main() {
     struct Node* head = NULL;
     struct Node* second = NULL;
     struct Node* third = NULL;

head = (struct Node*) malloc (sizeof (struct Node));
second = (struct Node*) malloc ( size of (struct Node));
third = (struct Node*) malloc ( size of (struct Node));

head -> data = 10;
head -> next = second;

second -> data = 20;
second -> next = third;
```

Teacher's Signature :

```
thind -> data = 30;
thind ->next = NULL;

struct Node* temp = head;
Printf ("Linked List :");
while (temp != NULL) {
      Printf(" %d ->", temp -> data);
      temp = temp ->next;
}
 Printf ("NULL\n");

return 0;
}
```