

```
# Importing libraries
import nltk
import numpy as np
import pandas as pd
import random
from sklearn.model_selection import train_test_split
import pprint, time

#download the treebank corpus from nltk
nltk.download('treebank')

#download the universal tagset from nltk
nltk.download('universal_tagset')

# reading the Treebank tagged sentences
nltk_data = list(nltk.corpus.treebank.tagged_sents(tagset='universal'))
#print the first two sentences along with tags
print(nltk_data[:2])
```

 [nltk\_data] Downloading package treebank to /root/nltk\_data...  
 [nltk\_data] Unzipping corpora/treebank.zip.  
 [nltk\_data] Downloading package universal\_tagset to /root/nltk\_data...  
 [nltk\_data] Unzipping taggers/universal\_tagset.zip.  
 [[('Pierre', 'NOUN'), ('Vinken', 'NOUN'), ('', '.'), ('61', 'NUM'), ('years', 'NOUN'), ('old', 'ADJ'), ('', '.'), ('will', 'VERB')

```
#print each word with its respective tag for first two sentences
for sent in nltk_data[:2]:
    for tuple in sent:
        print(tuple)
```

```

('Pierre', 'NOUN')
('Vinken', 'NOUN')
('', '.')
('61', 'NUM')
('years', 'NOUN')
('old', 'ADJ')
('', '.')
('will', 'VERB')
('join', 'VERB')
('the', 'DET')
('board', 'NOUN')
('as', 'ADP')
('a', 'DET')
('nonexecutive', 'ADJ')
('director', 'NOUN')
('Nov.', 'NOUN')
('29', 'NUM')
('.', '.')
('Mr.', 'NOUN')
('Vinken', 'NOUN')
('is', 'VERB')
('chairman', 'NOUN')
('of', 'ADP')
('Elsevier', 'NOUN')
('N.V.', 'NOUN')
('', '.')
('the', 'DET')
('Dutch', 'NOUN')
('publishing', 'VERB')
('group', 'NOUN')
('.', '.')

```

```
# split data into training and validation set in the ratio 80:20
train_set, test_set = train_test_split(nltk_data, train_size=0.80, test_size=0.20, random_state=101)
# create list of train and test tagged words
train_tagged_words = [tup for sent in train_set for tup in sent]
test_tagged_words = [tup for sent in test_set for tup in sent]
print(len(train_tagged_words))
print(len(test_tagged_words))
```

```

80310
20366

```

```
train_tagged_words[:5]
```

```

[('Drink', 'NOUN'),
 ('Carrier', 'NOUN'),
 ('Competes', 'VERB'),
 ('With', 'ADP'),
 ('Cartons', 'NOUN')]

```

```

tags = {tag for word, tag in train_tagged_words}
print(len(tags))
print(tags)

```

```

vocab= {word for word , tag in train_tagged_words}

12
{'.', 'PRT', 'ADP', 'PRON', 'NOUN', 'ADV', 'X', 'CONJ', 'VERB', 'DET', 'NUM', 'ADJ'}

#compute Emission Probability
def word_given_tag(word, tag, train_bag = train_tagged_words):
    tag_list = [pair for pair in train_bag if pair[1]==tag]
    count_tag = len(tag_list)#total number of times the passed tag occurred in train_bag
    w_given_tag_list= [pair[0] for pair in tag_list if pair[0]==word]
#now calculate the total number of times the passed word occurred as the passed tag.
    count_w_given_tag = len(w_given_tag_list)
    return (count_w_given_tag, count_tag)

#compute Transition Probability
def t2_given_t1(t2, t1, train_bag = train_tagged_words):
    tags= [pair[1] for pair in train_bag]
    count_t1 = len([t for t in tags if t==t1])
    count_t2_t1 = 0
    for index in range(len(tags)-1):
        if tags[index]==t1 and tags[index+1] == t2:
            count_t2_t1 += 1
    return (count_t2_t1, count_t1)

# creating t x t transition matrix of tags, t= no of tags
# Matrix(i, j) represents P(jth tag after the ith tag)
tags_matrix = np.zeros((len(tags), len(tags)), dtype='float32')
for i, t1 in enumerate(list(tags)):
    for j, t2 in enumerate(list(tags)):
        tags_matrix[i, j] = t2_given_t1(t2, t1)[0]/t2_given_t1(t2, t1)[1]
print(tags_matrix)

[[9.23720598e-02 2.78940029e-03 9.29084867e-02 6.87694475e-02
 2.18538776e-01 5.25694676e-02 2.56410260e-02 6.00793920e-02
 8.96899477e-02 1.72191828e-01 7.82104954e-02 4.61323895e-02]
 [4.50097844e-02 1.17416831e-03 1.95694715e-02 1.76125243e-02
 2.50489235e-01 9.39334650e-03 1.21330721e-02 2.34833662e-03
 4.01174158e-01 1.01369865e-01 5.67514673e-02 8.29745606e-02]
 [3.87243740e-02 1.26550242e-03 1.69577319e-02 6.96026310e-02
 3.23588967e-01 1.45532778e-02 3.45482156e-02 1.01240189e-03
 8.47886596e-03 3.20931405e-01 6.32751212e-02 1.07061505e-01]
 [4.19134386e-02 1.41230067e-02 2.23234631e-02 6.83371304e-03
 2.12756261e-01 3.69020514e-02 8.83826911e-02 5.01138950e-03
 4.84738052e-01 9.56719834e-03 6.83371304e-03 7.06150308e-02]
 [2.40094051e-01 4.39345129e-02 1.76826611e-01 4.65906132e-03
 2.62344331e-01 1.68945398e-02 2.88252197e-02 4.24540639e-02
 1.49133503e-01 1.31063312e-02 9.14395228e-03 1.25838192e-02]
 [1.39255241e-01 1.47401085e-02 1.19472459e-01 1.20248254e-02
 3.21955010e-02 8.14584941e-02 2.28859577e-02 6.98215654e-03
 3.39022487e-01 7.13731572e-02 2.98681147e-02 1.30721495e-01]
 [1.60868734e-01 1.85085520e-01 1.42225638e-01 5.41995019e-02
 6.16951771e-02 2.57543717e-02 7.57255405e-02 1.03786280e-02
 2.06419379e-01 5.68902567e-02 3.07514891e-03 1.76821072e-02]
 [3.51262353e-02 4.39077942e-03 5.59824370e-02 6.03732169e-02
 3.49066973e-01 5.70801310e-02 9.33040585e-03 5.48847427e-04
 1.50384188e-01 1.23490669e-01 4.06147093e-02 1.13611415e-01]
 [3.48066315e-02 3.06629837e-02 9.23572779e-02 3.55432779e-02
 1.10589318e-01 8.38858187e-02 2.15930015e-01 5.43278083e-03
 1.67955801e-01 1.33609578e-01 2.28360966e-02 6.63904250e-02]
 [1.73925534e-02 2.87480245e-04 9.91806854e-03 3.30602261e-03
 6.35906279e-01 1.20741697e-02 4.51343954e-02 4.31220367e-04
 4.02472317e-02 6.03708485e-03 2.28546783e-02 2.06410810e-01]
 [1.19243130e-01 2.60621198e-02 3.74866128e-02 1.42806140e-03
 3.51660132e-01 3.57015361e-03 2.02427700e-01 1.42806144e-02
 2.07068902e-02 3.57015361e-03 1.84219927e-01 3.53445187e-02]
 [6.60194159e-02 1.14563107e-02 8.05825219e-02 1.94174761e-04
 6.96893215e-01 5.24271838e-03 2.09708735e-02 1.68932043e-02
 1.14563107e-02 5.24271838e-03 2.17475723e-02 6.33009672e-02]]

tags_df= pd.DataFrame(tags_matrix, columns = list(tags), index= list(tags))
display(tags_df)

```

	.	PRT	ADP	PRON	NOUN	ADV	X	CONJ	VERB	DET	NUM	ADJ
.	0.092372	0.002789	0.092908	0.068769	0.218539	0.052569	0.025641	0.060079	0.089690	0.172192	0.078210	0.046132
<b>PRT</b>	0.045010	0.001174	0.019569	0.017613	0.250489	0.009393	0.012133	0.002348	0.401174	0.101370	0.056751	0.082975
<b>ADP</b>	0.038724	0.001266	0.016958	0.069603	0.323589	0.014553	0.034548	0.001012	0.008479	0.320931	0.063275	0.107062
<b>PRON</b>	0.041913	0.014123	0.022323	0.006834	0.212756	0.036902	0.088383	0.005011	0.484738	0.009567	0.006834	0.070615
<b>NOUN</b>	0.240094	0.043935	0.176827	0.004659	0.262344	0.016895	0.028825	0.042454	0.149134	0.013106	0.009144	0.012584

```
def Viterbi (words, train_bag = train_tagged_words):
    state = []
    T = list(set([pair[1] for pair in train_bag]))
    for key, word in enumerate(words):
        #initialise list of probability column for a given observation
        p = []
        for tag in T:
            if key == 0:
                transition_p = tags_df.loc['.', tag]
            else:
                transition_p = tags_df.loc[state[-1], tag]
            # compute emission and state probabilities
            emission_p = word_given_tag(words[key], tag)[0]/word_given_tag(words[key], tag)[1]
            state_probability = emission_p* transition_p
            p.append(state_probability)

        pmax = max(p)
        # getting state for which probability is maximum
        state_max= T[p.index(pmax)]
        state.append(state_max)
    return list(zip(words, state))

#Let's test our Viterbi algorithm on a few sample sentences of test dataset
random.seed(1234) #define a random seed to get same sentences when run multiple times
#choose random 10 numbers
rndom = [random.randint(1, len(test_set)) for x in range(10)]
# list of 10 sents on which we test the model
test_run = [test_set[i] for i in rndom]
# list of tagged words
test_run_base = [tup for sent in test_run for tup in sent]
# list of untagged words
test_tagged_words = [tup[0] for sent in test_run for tup in sent]

#Here We will only test 10 sentences to check the accuracy
#as testing the whole training set takes huge amount of time
start = time.time()
tagged_seq= Viterbi (test_tagged_words)
end = time.time()
difference = end-start
print("Time taken in seconds: ", difference)
# accuracy
check = [i for i, j in zip(tagged_seq, test_run_base) if i == j]
accuracy = len(check)/len (tagged_seq)
print('Viterbi Algorithm Accuracy: ',accuracy*100)

Time taken in seconds:  50.37351584434509
Viterbi Algorithm Accuracy:  93.77990430622009
```