

Degree centrality

NETWORK ANALYSIS IN PYTHON (PART 1)



Eric Ma


Data Carpentry instructor and author of
nxviz package

Important nodes

- Which nodes are important?
 - Degree centrality
 - Betweenness centrality



Important nodes

- Which center node might be more important?



Important nodes

Which center node might be more important?



Degree centrality

- Definition:

$$\frac{\text{Number of Neighbors I Have}}{\text{Number of Neighbors I Could Possibly Have}}$$

- Examples of node with high degree centrality:
 - Twitter broadcasters
 - Airport transportation hubs
 - Disease super-spreaders

Number of neighbors

```
G.edges()
```

```
[(1, 2), (1, 3), (1, 4), (1, 5), (1, 6), (1, 7), (1, 8), (1, 9)]
```

```
G.neighbors(1)
```

```
[2, 3, 4, 5, 6, 7, 8, 9]
```

```
G.neighbors(8)
```

```
[1]
```

```
G.neighbors(10)
```

```
NetworkXError: The node 10 is not in the graph.
```

Degree centrality

```
nx.degree_centrality(G)
```

```
{1: 1.0,  
 2: 0.125,  
 3: 0.125,  
 4: 0.125,  
 5: 0.125,  
 6: 0.125,  
 7: 0.125,  
 8: 0.125,  
 9: 0.125}
```

Let's practice!

NETWORK ANALYSIS IN PYTHON (PART 1)

Graph algorithms

NETWORK ANALYSIS IN PYTHON (PART 1)



Eric Ma


Data Carpentry instructor and author of
nxviz package

Finding paths

- Pathfinding is important for
 - Optimization: e.g. shortest transport paths
 - Modeling: e.g. disease spread, information passing
- Algorithm: Breadth-first search


Breadth-first search (BFS)

- Example: Shortest path between two nodes




Breadth-first search (BFS)

- Example: Shortest path between two nodes




Breadth-first search (BFS)

- Example: Shortest path between two nodes



Breadth-first search (BFS)

- Example: Shortest path between two nodes



Recall: Neighbors

```
G
```

```
<networkx.classes.graph.Graph at 0x10cc08828>
```

```
len(G.edges())
```

```
57
```

```
len(G.nodes())
```

```
20
```

Recall: Neighbors

```
G.neighbors(1)
```

```
[10, 5, 14, 7]
```

```
G.neighbors(10)
```

```
[1, 19, 5, 17, 8, 9, 13, 14]
```


Let's practice!

NETWORK ANALYSIS IN PYTHON (PART 1)

Betweenness centrality

NETWORK ANALYSIS IN PYTHON (PART 1)



Eric Ma

Data Carpentry instructor and author of
nxviz package

All shortest paths

- Set of paths
- Each path is shortest path between a given pair of nodes
- Done for all node pairs

Betweenness centrality


- Definition:

$$\frac{\text{num. shortest paths through node}}{\text{all possible shortest paths}}$$

- Application:
 - Bridges between liberal- and conservative-leaning Twitter users
 - Critical information transfer links

Examples


- Singapore: Raffles Place & Jurong East



¹ Source: http://www.seacitymaps.com/singapore/singapore_mrt_map.jpg


Example

- High betweenness centrality, low degree centrality?



Betweenness centrality


```
import networkx as nx
G = nx.barbell_graph(m1=5, m2=1)
nx.betweenness_centrality(G)
```



```
{0: 0.0,
1: 0.0,
2: 0.0,
3: 0.0,
4: 0.5333333333333333,
5: 0.5555555555555556,
6: 0.5333333333333333,
7: 0.0,
8: 0.0,
9: 0.0,
10: 0.0}
```

Betweenness centrality

```
import networkx as nx
G = nx.barbell_graph(m1=5, m2=1)
nx.betweenness_centrality(G)
```



```
{0: 0.0,
1: 0.0,
2: 0.0,
3: 0.0,
4: 0.5333333333333333,
5: 0.5555555555555556,
6: 0.5333333333333333,
7: 0.0,
8: 0.0,
9: 0.0,
10: 0.0}
```


Let's practice!

NETWORK ANALYSIS IN PYTHON (PART 1)