



KIRLOSKAR CHILLERS PRIVATE LIMITED

Enriching Lives

ENGINEERING BULLETIN

From :	SPN	Engg Bulletin No. :	EB/13-14/01
Approved By:	SSN	Date of Release :	19 TH April, 2013
Subject :	7" Touch screen controller display for KWK & KWI series		

7" Touch screen controller display for KWK & KWI series:

With the immediate effect from April month, we are providing 7" touch screen controller display for KWK & KWI series as a standard feature. As of now rest of all screw series model will be continued with existing controller display pGD0.

Technical specification of Touch Screen:

Display	
Type:	TFT
Resolution:	800x480, WVGA
Active display area:	7" diagonal
Colours:	64k
Backlight:	LED
Brightness:	160 Cd/m2 typ.
Dimming:	Yes
System Resources	
Operating system:	Microsoft Windows CE 6.0
User memory:	128MB Flash
RAM CPU/MIPS:	256MB DDR
Ratings	
Power supply voltage:	24V dc (18 to 30Vdc)
Current consumption:	0.7A at 24V dc(max)
Battery:	Rechargeable lithium battery, not user replaceable
Operating conditions	
Operating temperature:	0 to 50°C
Storage temperature:	-20 to 70°C
Index of Protection (IP):	IP65(front panel) – IP20(rear)
Operating & storage humidity:	5-85% relative humidity, non condensing
Dimensions	
Faceplate LxH:	187x147 mm
Cutout AxB	176x136mm
Depth D+T	45+4mm
Weight:	Approx. 1.0 Kg