



KIRLOSKAR CHILLERS PRIVATE LIMITED

Enriching Lives

ENGINEERING BULLETIN

From :	SSN	Engg Bulletin No. :	EB/13-14/02
Approved By:	PAJ	Date of Release :	19 TH April, 2013
Subject :	Addition of KWI series in AHRI listings.		

Addition of KWI series in AHRI listings:

We are officially launching KWI series for water cooled screw chillers with VFD. We have got this series approved by AHRI and completed the mandatory procedures to update it in AHRI directory.

You can refer it at

<http://www.ahridirectory.org/ahridirectory/pages/crwc/defaultSearch.aspx>

Salient Features:

- Excellent part load performance. (IPLV=0.413)
- The range of VFD operating frequency will be from 20 Hz to 60 Hz. Please note that this frequency range is at VFD output (input to compressor).
- Very low starting current as compared to star delta starter.
- Supply power frequency is 50 Hz only.
- Capacity modulation will be done by varying compressor speed only. There will not be separate slide valve mechanism. This also results in minimum time to reach full load.
- All the models will have VFDs unit mounted.
- Flooded heat exchanges with external horizontal oil separator.

KWI series models list:

KWI 150.14,	KWI 265.24,	KWI 415.24,
KWI 170.14,	KWI 295.24,	KWI 440.24,
KWI 195.14,	KWI 320.24,	KWI 460.24,
KWI 220.14,	KWI 340.24,	KWI 485.24
KWI 240.14,	KWI 365.24,	
KWI 265.14,	KWI 390.24,	

Please also note that hence forth, we shall not be providing VFDs for the standard chillers, i.e. for the KWS and KWK series chillers. For any requirement where the client needs VFDs for water cooled screw chillers, you should only offer KWI series chillers.