



KIRLOSKAR CHILLERS PRIVATE LIMITED

Enriching Lives

ENGINEERING BULLETIN

From :	SNM	Engg Bulletin No. :	EB/13-14/08
Approved By:	SSN	Date of Release :	28 th Sept, 2013
Subject :	Release of KWS - Brine series rating chart		

Release of KWS - Brine series rating chart:

We are releasing herewith KWS-Brine series rating chart. Please refer following documents for the selection,

1. ESP/13-14/102 : KWS-R134a up to -15 deg C.
2. ESP/13-14/103 : KWS-R407C up to -20 deg C.
3. ESP/13-14/105 : Brine table (MEG & Propylene glycol)
4. ESP/13-14/106 : Fouling Correction Factor

Notes:

- 1) Up to -10 deg C requirement, use latest version (1.3.4) of Screw selection software.
- 2) From -10 deg C to -20 deg C, use rating chart released herewith.
- 3) We are not offering chillers below -20 deg C requirement as of now.
- 4) Mono ethylene glycol is a standard offering as a brine solution, Propylene glycol can also be offered as an option.
- 5) We strongly discourage the use of Methanol as brine. If at all customer is going to use methanol on his own risk, our offer should contain the WARNING which has been already drafted.
- 6) For overall dimensions & weight refer standard Physical data of corresponding model. Note that these may or may not vary during detail engineering which will be done after receipt of order. But definitely new dimensions and weight will be equal to or less than the standard model.