



KIRLOSKAR CHILLERS PRIVATE LIMITED

Enriching Lives

ENGINEERING SPECIFICATIONS

Document Name: INSULATION THICKNESS FOR DIFFERENT ITEMS OF CHILLER		
Document No: ESP-13-14-101	Revision:R01	Date:03/02/2014

TYPE	CHILLER ITEMS	INSULATION THK
SCREW CHILLER	EVAPORATOR SHELL	32 mm
	EVAPORATOR TUBE SHEET	19 mm
	EVAPORATOR DISHED END ASSLY / M.W. BOX ASSLY / Dx EVAP PP ASSLY	19 mm
	Dx EVAPORATOR HEAD COVER	32 mm
	MOTOR BODY	19 mm
	SUCTION LINE ASSEMBLY	19 mm
	LIQUID LINE ASSEMBLY	9 mm
	EVAPORATOR SUPPORT PLATE	19 mm
SCREW CHILLER (Brine app. below (-)10 deg C)	EVAPORATOR SHELL	51 mm (32 mm+ 19 mm)
	EVAPORATOR TUBE SHEET	32 mm
	EVAPORATOR DISHED END ASSLY / M.W. BOX ASSLY / Dx EVAP PP ASSLY	32 mm
	Dx EVAPORATOR HEAD COVER	51 mm (32 mm+ 19 mm)
	MOTOR BODY	28 mm (19 mm + 9 mm)
	SUCTION LINE ASSEMBLY	28 mm (19 mm + 9 mm)
	LIQUID LINE ASSEMBLY	19 mm
	EVAPORATOR SUPPORT PLATE	32 mm
CENTRIFUGAL CHILLER	EVAPORATOR SHELL	32 mm
	EVAPORATOR TUBE SHEET	19 mm
	EVAPORATOR DISHED END ASSLY / M.W.BOX ASSLY	19 mm
	MOTOR BODY	19 mm
	SUCTION LINE ASSEMBLY	19 mm
	LIQUID LINE ASSEMBLY	9 mm
	OIL COOLER WATER PIPING ASSEMBLY	9 mm (Tubular insulation)
	MOTOR COOLING RETURN LINE ASSEMBLY	9 mm (Tubular insulation)
	EVAPORATOR SUPPORT PLATE	19 mm

Notes:

1. Above mentioned thicknesses are minimum required thicknesses for our standard units.
2. Customer may specify for other thicknesses, refer BOM in such cases.
3. Refer brine chiller row for chiller with design LWT below (-) 10 deg C.