



KIRLOSKAR CHILLERS PRIVATE LIMITED

A Kirloskar Group Company

Enriching Lives

ENGINEERING SPECIFICATIONS

Document Name: Maximum limits for contents in lubricating oil of screw (K) compressor		
Document No: ESP-17-18-108	Revision: R00	Date: 12/01/2018
Prepared By: AHW	Approved By: SSN	Sheet: 1 of 1

KCPL Part No. for Oil - 55.400.81.308

Sr No.	Parameters	UOM	Maximum limit	Test Method
1.	Appearance	-	--Clear Liquid	Lab Procedure
2.	Colour	-	--Bright	Lab Procedure
3.	Kinematic Viscosity at 40 °C	cSt	140-180	ASTM D 7042 2016
4.	Total Acid Number	mg KOH/g	MAX 0.19	ASTM D 664 2011 a
5.	Water Content	ppm	MAX 150	ASTM D 6304 2016 e1
Elemental Analysis				
6.	Aluminum	ppm	6	ASTM D 6595 2011
7.	Barium	ppm	6	
8.	Boron	ppm	6	
9.	Cadmium	ppm	6	
10.	Calcium	ppm	6	
11.	Chromium	ppm	6	
12.	Copper	ppm	6	
13.	Iron	ppm	6	
14.	Lead	ppm	6	
15.	Magnesium	ppm	6	
16.	Manganese	ppm	6	
17.	Molybdenum	ppm	6	
18.	Nickel	ppm	6	
19.	Phosphorous	ppm	6	
20.	Potassium	ppm	6	
21.	Silicon	ppm	6	
22.	Silver	ppm	6	
23.	Sodium	ppm	6	
24.	Tin	ppm	6	
25.	Titanium	ppm	6	
26.	Vanadium	ppm	6	
27.	Zinc	ppm	6	