

Document No : ESP-19-20-004				
Document Name : CABLE SELECTION CHART				
Prep. By : MRM	Revised By :	Appd. By : ASP	Date : 24/10/19	Total Pages : 05

Engineering Specification

NOTES	
1	RECOMMENDED CABLES ARE HIGHLIGHTED.
2	FOR SPECIAL CASE DISCUSS WITH ENGINEERING

CABLE FOR MCCB LOOP IN CASE OF DOUBLE CIRCUIT OR WHERE EVER APPLICABLE							
MCCB		PVC CABLE			UNINYVIN CABLE		
MODEL	CURRENT	SIZE (SQ.MM.)			SIZE (AWG)		
		1R	2R	3R	1R	2R	3R
3VA/3VT	100	35	25	NA	6	8	NA
	125	50	35	25	4	8	NA
	160	70	50	25	4	6	8
	200	95	70	50	2	6	8
	250	120	70	NA	00	4	6
	320	185	95	70	0000	2	4
	400	240	120	70	NA	0	2
	500	300	150	120	NA	000	1
	630	400	120	150	NA	NA	00
	800	NA	300	240	NA	NA	0000
	1000	NA	400	300	NA	NA	NA
	1250	NA	NA	400	NA	NA	NA
	1600	NA	NA	NA	NA	NA	NA
	—						
	—						

KIRLOSKAR CHILLERS PRIVATE LIMITED

A Kirloskar Group Company



CABLE FOR CONTACTOR							
CONTACTOR (3TF)		PVC CABLE			UNINYVIN CABLE		
MODEL	CURRENT	SIZE (SQ.MM.)			SIZE (AWG)		
		1R	2R	3R	1R	2R	3R
3TF	63	25	NA		8	NA	NA
	85	35			8	NA	NA
	110	50	25	NA	6	NA	NA
	140	70	35	NA	4	8	NA
	170	70	50	35	2	6	8
	250	120	70	50	00	4	6

CABLE FOR FUSE/SFU/FSD LOOP IN CASE OF DOUBLE CIRCUIT OR WHERE EVER APPLICABLE							
FUSES		PVC CABLE			UNINYVIN CABLE		
MODEL	CURRENT	SIZE (SQ.MM.)			SIZE (AWG)		
		1R	2R	3R	1R	2R	3R
3NA/3NE	100	35	25	NA	6	NA	NA
	125	50	35	25	4	8	NA
	160	70	50	25	4	6	8
	200	95	50	35	2	6	8
	225	95	70	50	0	4	6
	250	120	70	50	00	4	6
	315	150	95	70	0000	2	4
	350	185	95	70	0000	2	4
	400	240	120	70	NA	0	2
	450	240	150	95	NA	00	2
	500	300	150	120	NA	000	1
	560	400	185	120	NA	0000	0
	630	400	240	150	NA	NA	00
	710	NA	240	185	NA	NA	000
	800	NA	300	240	NA	NA	0000

KIRLOSKAR CHILLERS PRIVATE LIMITED

A Kirloskar Group Company



CABLE FOR INCOMER TO VFD AND VFD TO MOTOR							
DANFOSS		PVC CABLE			UNINYVIN CABLE		
MODEL	RATING (KW)	SIZE (SQ.MM.)			SIZE (AWG)		
		1R	2R	3R	1R	2R	3R
FC-102 (N)	55	50	25	NA	6	NA	NA
	75	70	35	25	4	NA	NA
	90	70	50	35	2	6	8
	110	95	70	50	1	4	6
	132	120	70	50	00	4	6
	160	150	95	70	0000	2	4
	200	240	120	70	NA	0	2
	250	300	150	95	NA	00	1
	315	NA	185	150	NA	0000	00
	400	NA	300	185	NA	NA	0000
	450	NA	NA	240	NA	NA	0000

CABLE FOR INCOMER TO VFD AND VFD TO MOTOR							
SCHNEIDER		PVC CABLE			UNINYVIN CABLE		
MODEL	RATING (KW)	SIZE (SQ.MM.)			SIZE (AWG)		
		1R	2R	3R	1R	2R	3R
ATV610	55	50	25	NA	4	NA	NA
	75	70	35	25	4	8	NA
	90	70	50	35	2	6	8
	110	95	NA	NA	1	4	6
	132	120	70	50	00	4	6
	160	150	70	NA	000	2	4

KIRLOSKAR CHILLERS PRIVATE LIMITED

A Kirloskar Group Company



CABLE FOR INCOMER TO SOFTSTARTER AND SOFTSTARTER TO MOTOR							
DANFOSS		PVC CABLE			UNINYVIN CABLE		
MODEL	RATING (TYPE)	SIZE (SQ.MM.)			SIZE (AWG)		
		1R	2R	3R	1R	2R	3R
MCD5	0105B	50	25	NA	6	NA	NA
	0131B	50	35	NA	4	8	NA
	0141B	70	35	25	4	8	8
	0195B	95	50	35	2	6	8
	0215B	95	70	50	1	4	6
	0245B	120	95	50	00	4	6
	0331B	185	95	70	0000	2	4
	0396B	240	120	70	NA	0	2
	0469B	240	150	95	NA	00	1
	0525B	300	185	120	NA	000	0
	0632B	NA	240	150	NA	NA	00
	0744B	NA	300	185	NA	NA	0000
	0961B	NA	NA	300	NA	NA	NA

CABLE FOR SDU LOOP IN CASE OF DOUBLE CIRCUIT OR WHERE EVER APPLICABLE							
FUSES		PVC CABLE			UNINYVIN CABLE		
MODEL	CURRENT	SIZE (SQ.MM.)			SIZE (AWG)		
		1R	2R	3R	1R	2R	3R
3KA	100	35	25	NA	6	NA	NA
	125	50	35	25	4	8	NA
	160	70	50	25	4	6	8
	200	95	50	35	2	6	8
	225	95	70	50	0	4	6
	400	240	120	70	NA	0	2
	630	400	240	150	NA	NA	00
	800	NA	300	240	NA	NA	0000

KIRLOSKAR CHILLERS PRIVATE LIMITED

A Kirloskar Group Company



- LUGS FOR PVC CABLE SHOULD BE AS PER SQMM OF CABLE.
- LUGS FOR UNINYVIN CABLE REFER BELOW CHART.
- FOR LUG ID REFER BOM/ COMPONENT DETAILS.
- LUG SHALL BE PROPERLY CRIMP WITH CABLE.

CABLE SIZE (AWG)	LUG SIZE (SQ.MM.)
0000	120
000	95
00	70
0	50
1	50
2	35
4	25
6	16
8	10
10	6
12	4