

Mydriver.java

```
package acesslog1;

import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.Path;

import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text;

import org.apache.hadoop.mapreduce.Job;

import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;
import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;

public class Mydriver
{
    public static void main(String[] args) throws Exception
    {
        Configuration conf = new Configuration();

        Job job = Job.getInstance(conf, "Log Analysis");

        job.setJarByClass(Mydriver.class);

        job.setMapperClass(Mymapper.class);
        job.setReducerClass(Myreducer.class);

        job.setOutputKeyClass(Text.class);
        job.setOutputValueClass(IntWritable.class);

        FileInputFormat.addInputPath(job, new Path(args[0]));
        FileOutputFormat.setOutputPath(job, new Path(args[1]));

        System.exit(job.waitForCompletion(true) ? 0 : 1);
    }
}
```

Mymapper.java

```
package acesslog1;

import java.io.IOException;
```

```

import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.LongWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Mapper;

public class Mymapper extends Mapper<LongWritable, Text, Text, IntWritable>
{
    private final static IntWritable one = new IntWritable(1);
    private Text ip = new Text();

    public void map(LongWritable key, Text value, Context context)
    throws IOException, InterruptedException
    {
        String line = value.toString();

        String[] parts = line.split(" ");

        if(parts.length > 0)
        {
            ip.set(parts[0]); // IP Address
            context.write(ip, one);
        }
    }
}

```

Myreducer.java

```

package acesslog1;

import java.io.IOException;

import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Reducer;

public class Myreducer extends Reducer<Text, IntWritable, Text, IntWritable>
{
    public void reduce(Text key, Iterable<IntWritable> values, Context context)
    throws IOException, InterruptedException
    {
        int sum = 0;
    }
}

```

```
    for(IntWritable val : values)
    {
        sum += val.get();
    }

    context.write(key, new IntWritable(sum));
}
}
```

Then download it from the export to java to jar and get the path

After get the path do this

```
hadoop jar jar_filepath.jar wordcount.Mydriver /input/input.txt
/output
```

To see the output : `hdfs dfs -cat /output/part-r-00000`