

man Command - Examples

man [option] [command]

```
~/ ./. /.../.../workground git:>main man [option] [command]  
No manual entry for [option]  
No manual entry for [command]  
  
~/ ./. /.../.../workground git:>main |
```

man [command]

```
~/ ./. /.../.../workground git:>main man [command]  
No manual entry for [command]  
  
~/ ./. /.../.../workground git:>main |
```

man ls

```
~/. /.../workground git:>main man ls
LS(1)                                User Commands                                LS(1)

NAME
  ls - list directory contents

SYNOPSIS
  ls [OPTION]... [FILE]...

DESCRIPTION
  List information about the FILES (the current directory by default).
  Sort entries alphabetically if none of -cftuvSUX nor --sort is speci-
  fied.

  Mandatory arguments to long options are mandatory for short options too.

  -a, --all
      do not ignore entries starting with .

  -A, --almost-all
      do not list implied . and ..
... [output truncated for display]

~/. /.../workground git:>main |
```

man [SECTION-NUM] [COMMAND NAME]

```
~/. /.../workground git:>main man [SECTION-NUM] [COMMAND NAME]
No manual entry for [SECTION-NUM]
No manual entry for [COMMAND
No manual entry for NAME]

~/. /.../workground git:>main |
```

man 2 intro

```
~/. /.../..workground git:>main man 2 intro
intro(2)                                System Calls Manual                                intro(2)

NAME
    intro - introduction to system calls

DESCRIPTION
    Section 2 of the manual describes the Linux system calls. A system call
    is an entry point into the Linux kernel. Usually, system calls are not
    invoked directly: instead, most system calls have corresponding C li-
    brary wrapper functions which perform the steps required (e.g., trapping
    to kernel mode) in order to invoke the system call. Thus, making a sys-
    tem call looks the same as invoking a normal library function.

    In many cases, the C library wrapper function does nothing more than:

    • copying arguments and the unique system call number to the registers
      where the kernel expects them;

    • trapping to kernel mode, at which point the kernel does the real work
      of the system call;
... [output truncated for display]

~/. /.../..workground git:>main |
```

man -f [COMMAND NAME]

```
~/. /.../..workground git:>main man -f [COMMAND NAME]
[COMMAND: nothing appropriate.
NAME]: nothing appropriate.

~/. /.../..workground git:>main |
```

man -f ls

```
~/. /.../..workground git:>main man -f ls
ls (1)                                - list directory contents

~/. /.../..workground git:>main |
```

man -a [COMMAND NAME]

```
~/./../../../../workground git:>main man -a [COMMAND NAME]
No manual entry for [COMMAND
No manual entry for NAME]

~/./../../../../workground git:>main |
```

man -a intro

```
~/./../../../../workground git:>main man -a intro
intro(1)                                General Commands Manual                                intro(1)

NAME
    intro - introduction to user commands

DESCRIPTION
    Section 1 of the manual describes user commands and tools, for example,
    file manipulation tools, shells, compilers, web browsers, file and image
    viewers and editors, and so on.

NOTES
    Linux is a flavor of UNIX, and user commands under UNIX work similarly
    under Linux (and lots of other UNIX-like systems too, like FreeBSD).

    Under Linux, there are GUIs (graphical user interfaces), where you can
    point and click and drag, and hopefully get work done without first
    reading lots of documentation. The traditional UNIX environment is a
    CLI (command line interface), where you type commands to tell the com-
    puter what to do. This is faster and more powerful, but requires find-
    ing out what the commands are and how to use them. Below is a bare min-
    ... [output truncated for display]

~/./../../../../workground git:>main |
```

man -k [COMMAND NAME]

```
~/./../../../../workground git:>main man -k [COMMAND NAME]
apropos: fatal: regex `[COMMAND': Unmatched [, [^, [:, [., or [=

~/./../../../../workground git:>main |
```

man -k cd

```
~/./../../../../workground git:>main man -k cd
proc_execdomains (5) - ABI personalities (obsolete)
BN_gcd (3ossl)      - arithmetic operations on BIGNUMs
cd (1)              - bash built-in commands, see bash(1)
cd-create-profile (1) - Color Manager Profile Creation Tool
cd-drive (1)        - show CD-ROM drive characteristics
cd-fix-profile (1)   - Color Manager Testing Tool
cd-info (1)          - shows Information about a CD or CD-image
cd-it8 (1)           - Color Manager Testing Tool
cd-paranoia (1)      - an audio CD reading utility which includes extra data ...
cd-read (1)          - reads Information from a CD or CD-image
cdrecord (1)         - Emulation of CD/DVD/BD program cdrecord by program xor...
cdrwtool (1)         - perform various actions on a CD-R, CD-RW, and DVD-R
d2i_ECDSA_SIG (3ossl) - convert objects from/to ASN.1/DER representation
DateTime::Locale::fr_CD (3pm) - Locale data examples for the French Congo - K...
DateTime::Locale::ln_CD (3pm) - Locale data examples for the Lingala Congo - ...
DateTime::Locale::lu_CD (3pm) - Locale data examples for the Luba-Katanga Con...
DateTime::Locale::sw_CD (3pm) - Locale data examples for the Swahili Congo - ...
dhcpcd (8)           - a DHCP client
dhcpcd-run-hooks (8) - DHCP client configuration script
dhcpcd.conf (5)      - dhcpcd configuration file
... [output truncated for display]

~/./../../../../workground git:>main |
```

man -w [COMMAND NAME]

```
~/./../../../../workground git:>main man -w [COMMAND NAME]
No manual entry for [COMMAND
No manual entry for NAME]

~/./../../../../workground git:>main |
```

man -w ls

```
~/./../../../../workground git:>main man -w ls
/usr/share/man/man1/ls.1.gz

~/./../../../../workground git:>main |
```

man -I [COMMAND NAME]

```
~/./../../../../workground git:>main man -I [COMMAND NAME]
No manual entry for [COMMAND
No manual entry for NAME]

~/./../../../../workground git:>main |
```

man -I printf

```
~/./../../../../workground git:>main man -I printf
PRINTF(1)                                User Commands                                PRINTF(1)

NAME
    printf - format and print data

SYNOPSIS
    printf FORMAT [ARGUMENT]...
    printf OPTION

DESCRIPTION
    Print ARGUMENT(s) according to FORMAT, or execute according to OPTION:

    --help display this help and exit

    --version
        output version information and exit

    FORMAT controls the output as in C printf.  Interpreted sequences are:

    \"    double quote
    ... [output truncated for display]

~/./../../../../workground git:>main |
```