

SQL ASSIGNMENT 1

Q1: Creating sample tables and inserting values: Create the following tables with the given structures and insert sample data as specified:

```
C1-89566-ABHISHEK [assignment]>select * from SALESPEOPLE;
```

Snum	Sname	City	Comm
1001	Peel	London	0.12
1002	Serres	San Jose	0.13
1004	Motika	London	0.11
1007	Rifkin	Barcelona	0.15
1003	Axelrod	New York	0.10

5 rows in set (0.00 sec)

```
C1-89566-ABHISHEK [assignment]>select * from customers;
```

Cnum	Cname	City	Rating	Snum
2001	Hoffman	London	100	1001
2002	Giovanni	Rome	200	1003
2003	Liu	San Jose	200	1002
2004	Grass	Berlin	300	1002
2006	Clemens	London	100	1001
2008	Cisneros	San Jose	300	1007
2007	Pereira	Rome	100	1004

7 rows in set (0.00 sec)

```
C1-89566-ABHISHEK [assignment]>select * from orders;
```

Onum	Amt	Odate	Cnum	Snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002
3008	4723.00	1990-10-05	2006	1001
3010	1309.95	1990-10-06	2004	1002
3011	9891.88	1990-10-06	2006	1001

10 rows in set (0.00 sec)

1. Write a select command that produces the order number, amount, and date for all rows in the Orders table.

```
C1-89566-ABHISHEK [assignment]>select onum, amt, odate from orders;
+-----+-----+-----+
| onum | amt   | odate   |
+-----+-----+-----+
| 3001 | 18.69 | 1990-10-03 |
| 3003 | 767.19 | 1990-10-03 |
| 3002 | 1900.10 | 1990-10-03 |
| 3005 | 5160.45 | 1990-10-03 |
| 3006 | 1098.16 | 1990-10-03 |
| 3009 | 1713.23 | 1990-10-04 |
| 3007 | 75.75 | 1990-10-04 |
| 3008 | 4723.00 | 1990-10-05 |
| 3010 | 1309.95 | 1990-10-06 |
| 3011 | 9891.88 | 1990-10-06 |
+-----+-----+-----+
10 rows in set (0.00 sec)
```

2. Write a query that produces all rows from the Customers tables for which the salesperson's number is 1001.

```
C1-89566-ABHISHEK [assignment]>select * from salespeople where snum = 1001;
+-----+-----+-----+-----+
| Snum | Sname | City   | Comm |
+-----+-----+-----+-----+
| 1001 | Peel  | London | 0.12 |
+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

3. Write a query that displays the Salespeople table with the columns in the following order: city,sname,snum,comm.

```
C1-89566-ABHISHEK [assignment]>select city, sname, snum, comm from salespeople;
+-----+-----+-----+-----+
| city   | sname | snum | comm |
+-----+-----+-----+-----+
| London | Peel  | 1001 | 0.12 |
| San Jose | Serres | 1002 | 0.13 |
| London | Motika | 1004 | 0.11 |
| Barcelona | Rifkin | 1007 | 0.15 |
| New York | Axelrod | 1003 | 0.10 |
+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

4. Write a select command the produces the rating followed by the name of each customer in San Jose.

```
C1-89566-ABHISHEK [assignment]>select cname from customers where city = 'san jose';
+-----+
| cname |
+-----+
| Liu   |
| Cisneros |
+-----+
2 rows in set (0.00 sec)
```

5. Write a query that will give you all orders for more than Rs. 1,000.

```
C1-89566-ABHISHEK [assignment]>select amt from orders where amt > 1000;
+-----+
| amt |
+-----+
| 1900.10 |
| 5160.45 |
| 1098.16 |
| 1713.23 |
| 4723.00 |
| 1309.95 |
| 9891.88 |
+-----+
7 rows in set (0.00 sec)

C1-89566-ABHISHEK [assignment]>select onum, odate, cnum, snum, amt from orders where amt > 1000;
+-----+-----+-----+-----+-----+
| onum | odate      | cnum | snum | amt |
+-----+-----+-----+-----+-----+
| 3002 | 1990-10-03 | 2007 | 1004 | 1900.10 |
| 3005 | 1990-10-03 | 2003 | 1002 | 5160.45 |
| 3006 | 1990-10-03 | 2008 | 1007 | 1098.16 |
| 3009 | 1990-10-04 | 2002 | 1003 | 1713.23 |
| 3008 | 1990-10-05 | 2006 | 1001 | 4723.00 |
| 3010 | 1990-10-06 | 2004 | 1002 | 1309.95 |
| 3011 | 1990-10-06 | 2006 | 1001 | 9891.88 |
+-----+-----+-----+-----+-----+
7 rows in set (0.00 sec)
```

6. Write a query that will give you the names and cities of all salespeople in London with a commission above 0.10.

```
C1-89566-ABHISHEK [assignment]>select sname, city, comm from salespeople where comm > 0.10;
+-----+-----+-----+
| sname | city      | comm |
+-----+-----+-----+
| Peel  | London    | 0.12 |
| Serres | San Jose  | 0.13 |
| Motika | London    | 0.11 |
| Rifkin | Barcelona | 0.15 |
+-----+-----+-----+
4 rows in set (0.00 sec)
```

7. Write a query on the Customers table whose output will exclude all customers with a rating <= 100, unless they are located in Rome.

```
C1-89566-ABHISHEK [assignment]>select cname,city, rating from customers where rating <= 100 or city = 'rome';
```

cname	city	rating
Hoffman	London	100
Giovanni	Rome	200
Clemens	London	100
Pereira	Rome	100

4 rows in set (0.00 sec)

8. Write two different queries that would produce all orders taken on October 3rd or 4th, 1990.

```
C1-89566-ABHISHEK [assignment]>select * from orders where odate BETWEEN = '1990-10-03' AND '1990-10-04';
```

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '= '1990-10-03' AND '1990-10-04'' at line 1

```
C1-89566-ABHISHEK [assignment]>select * from orders where odate BETWEEN '1990-10-03' AND '1990-10-04';
```

Onum	Amt	Odate	Cnum	Snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002

7 rows in set (0.00 sec)

9. Write a query that will produce all the customers whose names begin with a letter from 'A' to 'G'.

```
C1-89566-ABHISHEK [assignment]>SELECT *
```

```
-> FROM Customers
```

```
-> WHERE Cname BETWEEN 'A' AND 'G';
```

Cnum	Cname	City	Rating	Snum
2006	Clemens	London	100	1001
2008	Cisneros	San Jose	300	1007

2 rows in set (0.00 sec)

10. Write a query that selects all orders except those with zeroes or NULLs in the amt field.

```
C1-89566-ABHISHEK [assignment]>select amt, IFNULL(AMT, 0) from orders;
```

amt	IFNULL(AMT, 0)
18.69	18.69
767.19	767.19
1900.10	1900.10
5160.45	5160.45
1098.16	1098.16
1713.23	1713.23
75.75	75.75
4723.00	4723.00
1309.95	1309.95
9891.88	9891.88

```
10 rows in set (0.00 sec)
```