

☒ Easy Level (10 MCQs)

1.

What does DNS stand for?

- A) Digital Network Server
- B) Domain Name System
- C) Dynamic Naming Service
- D) Data Network Service

Ans: B

2.

Which file is used by the client to resolve hostnames before querying DNS?

- A) /etc/dns.conf
- B) /etc/hosts
- C) /etc/named.conf
- D) /etc/resolv.dns

Ans: B

3.

Which command queries a DNS server?

- A) netstat
- B) nslookup
- C) pingdns
- D) digconf

Ans: B

4.

What is the purpose of an A record in DNS?

- A) Alias another name

- B) Define mail server
- C) Map name to IPv4 address
- D) Map IP to name

Ans: C

5.

Which file is used to configure DNS servers in Linux client?

- A) /etc/named.conf
- B) /etc/zone.conf
- C) /etc/resolv.conf
- D) /etc/hostname

Ans: C

6.

Which command checks the syntax of a BIND zone file?

- A) zone-check
- B) named-checkzone
- C) checkzonefile
- D) bind-verify

Ans: B

7.

Which record type maps an IP to a hostname?

- A) A
- B) MX
- C) PTR
- D) CNAME

Ans: C

8.

What is BIND in Linux?

- A) Boot manager
- B) DNS server software
- C) Firewall tool
- D) Package manager

Ans: B

9.

Which port does DNS operate on by default?

- A) 21
- B) 80
- C) 443
- D) 53

Ans: D

10.

Which command tests DNS using command-line?

- A) nslookup
- B) whois
- C) resolv
- D) hostedit

Ans: A

☒ **Medium Level (20 MCQs)**

11.

Which of the following creates a DNS alias?

- A) A
- B) NS
- C) CNAME
- D) TXT

Ans: C

12.

Which record defines the email server for a domain?

- A) MX
- B) A
- C) TXT
- D) NS

Ans: A

13.

In reverse DNS, which record is used?

- A) PTR
- B) MX
- C) AAAA
- D) CNAME

Ans: A

14.

Which file defines zone mappings in BIND?

- A) /etc/resolv.conf
- B) /etc/named.conf
- C) /etc/hosts

D) /etc/network/interfaces

Ans: B

15.

What does the dig command do?

- A) Digs through logs
- B) Checks disk usage
- C) Performs DNS queries
- D) Monitors services

Ans: C

16.

What is the purpose of named-checkconf?

- A) Restart DNS
- B) Validate named.conf
- C) Edit DNS entries
- D) Check hosts file

Ans: B

17.

In the zone file, what does SOA stand for?

- A) System of Access
- B) Start of Authority
- C) Set of Aliases
- D) Source of Address

Ans: B

18.

Which record maps IPv6 addresses?

- A) A
- B) CNAME
- C) AAAA
- D) PTR

Ans: C

19.

Which of the following contains the DNS server's actual data?

- A) Zone file
- B) Resolver
- C) DHCP config
- D) /etc/resolv.conf

Ans: A

20.

What happens if the serial number in zone file is not incremented?

- A) Zone won't reload on slave
- B) DNS stops resolving
- C) IP gets reset
- D) Nothing

Ans: A

21.

To restrict queries to internal IPs, modify:

- A) allow-query
- B) forwarders
- C) TTL
- D) nsupdate

Ans: A

22.

Which directive in named.conf defines a DNS zone?

- A) options
- B) zone
- C) listen
- D) acl

Ans: B

23.

Which utility can you use to find the authoritative name server?

- A) whois
- B) dig +nssearch
- C) ping
- D) ip addr

Ans: B

24.

What does TTL in DNS record mean?

- A) Time to Live
- B) Total Transfer Limit
- C) Transfer To Local
- D) TCP to LAN

Ans: A

25.

What is the main benefit of using caching DNS server?

- A) Faster response for repeat queries
- B) More accurate DNS records
- C) Prevent spam

D) Improved security

Ans: A

26.

Which service is responsible for starting BIND?

A) dns.service

B) named.service

C) bind.service

D) dnssd.service

Ans: B

27.

Which directive prevents recursive queries in BIND?

A) recursion off

B) recursion no

C) recursion deny

D) allow-recursion no

Ans: B

28.

What command flushes DNS cache in systemd-resolved?

A) systemd-resolve --flush

B) resolvectl flush-caches

C) flushdns

D) dns-clear

Ans: B

29.

What does 'forwarders' do in BIND?

- A) Define default route
- B) Define secondary DNS
- C) Forward unresolved queries to another DNS
- D) Point MX records

Ans: C

30.

Which log file helps debug DNS server issues?

- A) /var/log/dns.log
- B) /var/log/named.log
- C) /var/log/messages
- D) /var/log/resolv.log

Ans: C

☒ Hard Level (10 MCQs)

31.

How many sections does a typical DNS zone file contain?

- A) 2
- B) 3
- C) 4
- D) 5

Ans: C

(Usually SOA, NS, A/PTR, MX)

32.

Which command returns DNS trace results?

- A) dig +trace
- B) nslookup -t
- C) ping -trace
- D) traceroute dns

Ans: A

33.

Which component answers queries with recursive resolution?

- A) Resolver
- B) Authoritative server
- C) Recursive server
- D) Registrar

Ans: C

34.

What must be configured for DNSSEC to work correctly?

- A) TSIG keys
- B) Zone keys and DS records
- C) PTR records
- D) ACLs

Ans: B

35.

What is the purpose of "IN" in DNS zone files?

- A) Internal host
- B) Internet class
- C) Intranet DNS
- D) Instance type

Ans: B

36.

To avoid cache poisoning in DNS, use:

- A) DNSSEC
- B) PTR records
- C) SOA policies
- D) TTL values

Ans: A

37.

Which record is used to verify domain ownership in email services?

- A) PTR
- B) TXT
- C) CNAME
- D) SRV

Ans: B

38.

What does named mean in BIND?

- A) Network Address Management
- B) Name Daemon
- C) Namespace Deployer
- D) New Address Manager

Ans: B

39.

Which file is typically symlinked to /etc/resolv.conf in systemd systems?

- A) /run/systemd/resolve/resolv.conf
- B) /lib/systemd/dns/resolv.conf
- C) /etc/resolv.d/systemd

D) /usr/lib/systemd/dns.conf

Ans: A

40.

Which BIND utility checks zone file syntax and SOA serial?

A) bind-check

B) named-checkzone

C) zone-check

D) dns-analyze

Ans: B