

☒ Easy Level (10 MCQs)

1.

Which component handles sending and routing of emails?

- A) MUA
- B) MTA
- C) MDA
- D) DNS

Ans: B

2.

What is the role of Dovecot?

- A) Send emails
- B) Store DNS records
- C) Allow IMAP/POP3 access
- D) Block spam

Ans: C

3.

Which protocol does Postfix primarily use?

- A) HTTP
- B) SMTP
- C) IMAP
- D) FTP

Ans: B

4.

What is the purpose of SquirrelMail?

- A) Terminal client

- B) FTP service
- C) Webmail interface
- D) Antivirus

Ans: C

5.

What is the default SMTP port?

- A) 21
- B) 110
- C) 25
- D) 53

Ans: C

6.

What command installs Postfix on Ubuntu?

- A) yum install postfix
- B) apt-get install smtpd
- C) apt install postfix
- D) sudo get postfix

Ans: C

7.

Which port does IMAP use?

- A) 80
- B) 143
- C) 110
- D) 443

Ans: B

8.

Which software delivers mail into the mailbox?

- A) SMTP
- B) MTA
- C) MUA
- D) MDA

Ans: D

9.

Which folder typically stores user mail with Maildir format?

- A) /etc/mail
- B) /var/mail
- C) ~/Maildir
- D) /tmp/mail

Ans: C

10.

Which package enables webmail through browser?

- A) webmin
- B) mutt
- C) squirrelmail
- D) telnet

Ans: C

☒ Medium Level (20 MCQs)

11.

Which Dovecot directive defines mail storage format?

- A) mail_type
- B) mail_storage
- C) mail_location
- D) mbox_format

Ans: C

12.

Which protocol is used for sending email?

- A) IMAP
- B) POP3
- C) SMTP
- D) SFTP

Ans: C

13.

What is the default configuration file of Postfix?

- A) /etc/mail.conf
- B) /etc/postfix/postfix.conf
- C) /etc/postfix/main.cf
- D) /etc/postfix.conf

Ans: C

14.

Which user command creates an email user on Linux system?

- A) create-mail
- B) useradd
- C) addemail

D) mailadd

Ans: B

15.

What is the default POP3 port?

A) 110

B) 25

C) 993

D) 21

Ans: A

16.

Which file in Postfix contains domain name?

A) /etc/domain

B) /etc/mailname

C) /etc/postfix/domain

D) /var/lib/maildomain

Ans: B

17.

Which tool shows mail delivery logs in Ubuntu?

A) mailstat

B) /var/log/syslog

C) /etc/postfix.log

D) /var/log/dovecot.log

Ans: B

18.

Which daemon manages SMTP in Postfix?

- A) sendmail
- B) smtpd
- C) postfixd
- D) dovecot

Ans: B

19.

How do you test SMTP service?

- A) telnet <host> 25
- B) ping mail.example.com
- C) netstat -a
- D) dig smtp.example.com

Ans: A

20.

What command enables Postfix to reload its configuration?

- A) postfix start
- B) postfix reload
- C) systemctl reload postfix
- D) service postfix restart

Ans: B

21.

What happens if Dovecot is not running?

- A) Email cannot be sent
- B) User can't access inbox
- C) Email DNS fails
- D) Postfix crashes

Ans: B

22.

Which component is responsible for web access to email?

- A) Postfix
- B) Dovecot
- C) Maildir
- D) SquirrelMail

Ans: D

23.

How does Dovecot authenticate users?

- A) SMTP
- B) SSL keys
- C) PAM/Shadow passwords
- D) Firewall

Ans: C

24.

What does IMAP allow?

- A) Downloads and deletes mail
- B) Sends mail
- C) Reads mail from server without downloading
- D) Deletes mailbox

Ans: C

25.

Which Postfix directive determines what domains it serves?

- A) myorigin
- B) mydestination
- C) myhostname

D) relayhost

Ans: B

26.

Where is SquirrelMail accessed from?

A) Command-line

B) Thunderbird

C) Browser

D) SSH

Ans: C

27.

How do you configure mail delivery format to Maildir in Postfix?

A) mailbox_type = maildir

B) home_mailbox = Maildir/

C) mail_location = Maildir

D) delivery = maildir

Ans: B

28.

Which service allows retrieval of email?

A) SMTP

B) IMAP

C) FTP

D) DHCP

Ans: B

29.

Which command views Postfix's current mail queue?

- A) postfix queue
- B) postqueue -p
- C) mailq
- D) Both B and C

Ans: D

30.

How can users send mail from SquirrelMail?

- A) Via SMTP
- B) Via IMAP
- C) Using POP3
- D) Directly through Dovecot

Ans: A

☒ Hard Level (10 MCQs)

31.

Which file must be edited to set maildir in Dovecot?

- A) 10-auth.conf
- B) 10-mail.conf
- C) dovecot.conf
- D) 10-userdb.conf

Ans: B

32.

How do you encrypt SMTP connections?

- A) Enable POP
- B) Use port 25
- C) Use STARTTLS or port 587
- D) Use HTTP

Ans: C

33.

Which Postfix config sets the hostname of the mail server?

- A) myorigin
- B) hostname
- C) myhostname
- D) relayhost

Ans: C

34.

To connect SquirrelMail with Dovecot, which protocol is used?

- A) POP3
- B) SMTP
- C) IMAP
- D) DNS

Ans: C

35.

What is the typical log for Dovecot errors?

- A) /var/log/syslog
- B) /etc/dovecot.log
- C) /var/log/dovecot.log
- D) /var/log/mail.log

Ans: C

36.

Which protocol does SquirrelMail use to fetch mail?

- A) POP3
- B) SMTP
- C) IMAP
- D) FTP

Ans: C

37.

Which PHP file starts SquirrelMail from browser?

- A) index.php
- B) squirrelmail.php
- C) login.php
- D) webmail.php

Ans: A

38.

What does 'inet_interfaces = all' mean in Postfix?

- A) Accept mail on all IPs
- B) Use only localhost
- C) Block interfaces
- D) Send via all protocols

Ans: A

39.

Which port is commonly used for secure IMAP (IMAPS)?

- A) 110
- B) 993
- C) 995

D) 25

Ans: B

40.

To completely remove a mail from queue in Postfix:

A) postfix remove <ID>

B) postqueue -d <ID>

C) postsuper -d <ID>

D) mailq remove <ID>

Ans: C