

☒ Easy (10 MCQs)

1.

Which tool is used to install RedHat-based Linux interactively?

- A) apt
- B) Anaconda
- C) Kickstart
- D) DPKG

Ans: B

2.

What does the GRUB bootloader do?

- A) Starts the GUI
- B) Loads the Linux kernel
- C) Installs packages
- D) Formats hard disk

Ans: B

3.

Which directory stores GRUB configuration?

- A) /boot
- B) /home
- C) /root
- D) /etc/grub

Ans: A

4.

Which command installs .rpm packages?

- A) apt

- B) dnf
- C) dpkg
- D) make

Ans: B

5.

What is the function of initrd?

- A) Install packages
- B) Format disks
- C) Load temporary root system
- D) Configure users

Ans: C

6.

Which runlevel provides multi-user text mode with networking?

- A) 1
- B) 3
- C) 5
- D) 6

Ans: B

7.

Kickstart is used for:

- A) Manual package install
- B) Disk checking
- C) Unattended Linux installation
- D) Boot fixing

Ans: C

8.

Default Debian package manager is:

- A) yum
- B) rpm
- C) apt
- D) zypper

Ans: C

9.

Which system manages services in modern Linux systems?

- A) SysV
- B) systemd
- C) BIOS
- D) LILO

Ans: B

10.

Which command lists current runlevel in older systems?

- A) whoami
- B) runlevel
- C) uptime
- D) target

Ans: B

☒ **Medium (20 MCQs)**

11.

What is the first stage of the Linux boot process?

- A) Kernel
- B) GRUB
- C) BIOS
- D) init

Ans: C

12.

Which command regenerates GRUB config file?

- A) grub-install
- B) grub-mkconfig
- C) update-grub
- D) grub2-mkconfig -o /boot/grub2/grub.cfg

Ans: D

13.

In systemd, which target is equivalent to runlevel 3?

- A) graphical.target
- B) rescue.target
- C) multi-user.target
- D) reboot.target

Ans: C

14.

Which file stores persistent GRUB default settings?

- A) /boot/grub2/grub.cfg
- B) /etc/default/grub
- C) /etc/grub.d/00_header

D) /etc/init.d/grub

Ans: B

15.

What is the role of the Linux kernel during boot?

A) Starts GUI

B) Loads drivers, mounts root FS

C) Loads bootloader

D) Starts application

Ans: B

16.

To change default boot target in systemd:

A) edit /etc/inittab

B) set default.target

C) systemctl set-default

D) grub-update

Ans: C

17.

Which command creates an initial ramdisk?

A) mkinitrd

B) mkfs

C) dracut -f

D) initramfs

Ans: C

18.

What is stored in initramfs?

- A) GRUB config
- B) Kernel modules
- C) Package repo
- D) User settings

Ans: B

19.

Which command installs .deb file locally?

- A) apt
- B) rpm
- C) dpkg -i
- D) dnf

Ans: C

20.

Which section in Kickstart defines bootloader configuration?

- A) %packages
- B) %post
- C) bootloader
- D) kernel

Ans: C

21.

Which tool can configure software repositories in RHEL?

- A) yum-config-manager
- B) rpm -qa
- C) apt edit-sources
- D) update-repo

Ans: A

22.

What happens if GRUB config is corrupted?

- A) System boots normally
- B) Enters emergency mode
- C) Boot loader fails
- D) Installs kernel again

Ans: C

23.

To view active target in systemd:

- A) targetctl
- B) initctl
- C) runlevel
- D) systemctl get-default

Ans: D

24.

Purpose of Kickstart in Linux installation:

- A) Clone OS
- B) Backup data
- C) Automate installation
- D) Secure boot

Ans: C

25.

Which runlevel in SysVinit is equivalent to GUI mode?

- A) 0
- B) 1
- C) 3

D) 5
Ans: D

26.

Where is the GRUB MBR stored?

- A) /etc/mbr
- B) BIOS
- C) First sector of disk
- D) /boot

Ans: C

27.

What is /etc/yum.repos.d/ used for?

- A) Store logs
- B) GRUB files
- C) Repository configs
- D) Firewall rules

Ans: C

28.

Which command lists all RPM packages installed?

- A) rpm -qa
- B) yum list
- C) dnf check
- D) dpkg -l

Ans: A

29.

Which is NOT a systemd target?

- A) graphical.target
- B) rescue.target
- C) shutdown.target
- D) install.target

Ans: D

30.

Which component mounts the root filesystem during boot?

- A) initrd
- B) BIOS
- C) GRUB
- D) usermod

Ans: A

☒ Hard (10 MCQs)

31.

What does grub2-install /dev/sda do?

- A) Edits GRUB config
- B) Installs GRUB on MBR of sda
- C) Updates kernel
- D) Lists boot options

Ans: B

32.

Kickstart installation files must be located in:

- A) /etc/kickstart.conf
- B) Any removable media
- C) Bootable disk or network
- D) initrd

Ans: C

33.

What is the purpose of dracut?

- A) Install software
- B) Rebuild initramfs
- C) Mount partitions
- D) Load GRUB

Ans: B

34.

How does the system know which kernel to load by default?

- A) /etc/init.d
- B) GRUB_DEFAULT
- C) systemd
- D) runlevel

Ans: B

35.

In a boot issue, how can you boot into rescue mode via GRUB?

- A) Edit kernel line, add rescue
- B) Press Ctrl+R
- C) Boot and press Esc
- D) Type init 1

Ans: A

36.

What is the role of init/systemd in booting?

- A) Mount bootloader
- B) Set GRUB password
- C) Manage services and targets
- D) Load BIOS

Ans: C

37.

Which tool updates GRUB from /etc/default/grub changes?

- A) grub-edit
- B) grub2-mkconfig
- C) update-grub
- D) mkgrub

Ans: B

38.

How to add a custom repository in Debian?

- A) edit /etc/apt/sources.list
- B) yum-config-manager
- C) rpm -ivh repo
- D) dnf repo add

Ans: A

39.

A damaged initramfs file during boot will lead to:

- A) Boot as normal
- B) Kernel panic
- C) Update system

D) Reboot

Ans: B

40.

What is the effect of GRUB_TIMEOUT=0?

A) GRUB menu never shows

B) Infinite timeout

C) Shows all options

D) Enables rescue mode

Ans: A