

Easy (10 questions)

1.

What does the configuration register 0x2142 do?

- A) Boots IOS from ROM
- B) Boots normally from Flash and loads config
- C) Ignores startup-config in NVRAM
- D) Boots to setup mode

Answer: C

2.

What command shows the router's configuration register value?

- A) show config
- B) show version
- C) show running-config
- D) show boot

Answer: B

3.

What protocol is used by default for remote CLI access on Cisco routers?

- A) SSH
- B) FTP
- C) Telnet
- D) HTTP

Answer: C

4.

Which memory holds the startup configuration file?

- A) RAM

- B) Flash
- C) NVRAM
- D) ROM

Answer: C

5.

Which command is used to enable Telnet on VTY lines?

- A) transport input ssh
- B) transport input telnet
- C) enable telnet
- D) line telnet

Answer: B

6.

What is the first step in the router boot sequence?

- A) Load IOS
- B) Load startup-config
- C) POST
- D) Run bootstrap

Answer: C

7.

Which command enables hostname resolution via DNS?

- A) ip host
- B) ip domain-lookup
- C) ip dns
- D) dns server

Answer: B

8.

What command stops all active debug sessions?

- A) no debug all
- B) undebug all
- C) stop debug
- D) clear debug

Answer: B

9.

Where is the IOS image stored on a Cisco router?

- A) RAM
- B) NVRAM
- C) Flash
- D) ROM

Answer: C

10.

Which of the following commands enters privileged EXEC mode?

- A) enable
- B) configure
- C) start
- D) exec

Answer: A

Medium (30 questions)

11.

How can you change the configuration register to ignore the startup-config on the next reload?

- A) config-register 0x2102
- B) config-register 0x2142
- C) config-register 0x2101
- D) config-register 0x2000

Answer: B

12.

What happens if a router cannot find a valid IOS image in Flash?

- A) It boots normally
- B) It boots into ROMMON mode
- C) It boots with a default IOS from NVRAM
- D) It restarts the POST

Answer: B

13.

How do you save the running configuration to startup configuration?

- A) write memory
- B) copy startup-config running-config
- C) copy running-config startup-config
- D) save config

Answer: C

14.

Which command enables SSH on Cisco routers?

- A) ip ssh enable
- B) crypto key generate rsa
- C) enable ssh

D) ssh start

Answer: B

15.

What command configures a local username and password for SSH or Telnet login?

A) username [name] password [pass]

B) user add

C) set user

D) local user

Answer: A

16.

Which command shows the current debug status?

A) show debug

B) show debugging

C) debug status

D) show logs

Answer: B

17.

How do you enable Telnet and SSH access simultaneously on VTY lines?

A) transport input ssh

B) transport input telnet

C) transport input ssh telnet

D) transport input all

Answer: C

18.

What happens when you set the configuration register to 0x2101?

- A) Boots IOS from ROM
- B) Boots normally from Flash
- C) Enters setup mode
- D) Skips POST

Answer: A

19.

Which command disables DNS lookup to prevent delays on mistyped commands?

- A) no ip domain-lookup
- B) disable dns
- C) no dns
- D) ip domain-disable

Answer: A

20.

What type of output does the debug command produce?

- A) Real-time process information
- B) Static logs
- C) Configuration backup
- D) Interface status

Answer: A

21.

How do you enable the HTTP server for SDM access?

- A) ip http server
- B) enable http
- C) http server enable
- D) service http

Answer: A

22.

What command shows the interfaces and their IP addresses?

- A) show ip interface brief
- B) show interfaces
- C) show ip route
- D) show ip address

Answer: A

23.

Where is the bootstrap program stored?

- A) RAM
- B) Flash
- C) ROM
- D) NVRAM

Answer: C

24.

What is the purpose of NVRAM in a router?

- A) Store IOS image
- B) Store startup configuration
- C) Store routing tables
- D) Store logs

Answer: B

25.

Which command can be used to reload the router immediately?

- A) reload
- B) restart
- C) reset

D) boot

Answer: A

26.

Which command enables password login on VTY lines?

A) login local

B) login

C) password enable

D) enable password

Answer: B

27.

Which of the following is NOT a Cisco IOS mode?

A) User EXEC

B) Privileged EXEC

C) Global Configuration

D) Administrator Mode

Answer: D

28.

What is the purpose of the command undebg all?

A) Restart all debugging

B) Disable all debugging

C) Save debug output

D) Show all debug sessions

Answer: B

29.

Which protocol is more secure than Telnet for remote management?

- A) FTP
 - B) HTTP
 - C) SSH
 - D) SNMP
- Answer: C**

30.

Which IOS command allows you to set the router's hostname?

- A) hostname
 - B) set hostname
 - C) router hostname
 - D) name
- Answer: A**

Hard (10 questions)

31.

You have lost the enable password on your Cisco router. Which config register value helps to recover it by ignoring startup config?

- A) 0x2102
 - B) 0x2142
 - C) 0x2101
 - D) 0x2002
- Answer: B**

32.

What sequence of commands is required to configure SSH version 2 on a router?

A)

arduino

CopyEdit

Router(config)# ip ssh version 2 Router(config)# crypto key generate rsa

B)

arduino

CopyEdit

Router(config)# crypto key generate rsa Router(config)# ip ssh version 2

C)

arduino

CopyEdit

Router(config)# enable ssh version 2

D)

arduino

CopyEdit

Router(config)# ssh enable version 2

Answer: B

33.

You want to debug only incoming Telnet packets, which command would you use?

- A) debug telnet
- B) debug telnet inbound
- C) debug ip packet tcp eq 23
- D) debug ip telnet

Answer: C

34.

How can you make sure that your router does not try to resolve unknown hostnames automatically?

- A) no ip domain-lookup
- B) no ip dns
- C) disable hostname lookup
- D) no ip resolve

Answer: A

35.

What is the default number of VTY lines on a Cisco router?

- A) 2
- B) 4
- C) 5
- D) 8

Answer: C

36.

What is the command to verify the currently active configuration register setting?

- A) show config-register
- B) show version
- C) show boot
- D) show running-config

Answer: B

37.

Which file system does the router use to store the IOS image?

- A) RAM
- B) Flash
- C) NVRAM
- D) USB

Answer: B

38.

When debugging is active, which command can you use to view the debug output on the console?

- A) terminal monitor
- B) show debug
- C) debug output
- D) terminal debug

Answer: A

39.

After changing the configuration register, which command must you run to apply the change?

- A) write memory
- B) reload
- C) restart
- D) copy run start

Answer: B

40.

What is the function of the command `ip host [name] [address]`?

- A) Assigns a hostname to the router
- B) Maps hostname to IP address locally
- C) Enables DNS lookup

D) Displays host IP address

Answer: B