

☒ Easy Level (10 MCQs)

Q1. Snort is primarily used as a:

- A) Web server
- B) Firewall
- C) Network Intrusion Detection System
- D) VPN software

Answer: C

Q2. What is the file where Snort rules are configured?

- A) snort.rules
- B) snort.txt
- C) snort.conf
- D) rule.conf

Answer: C

Q3. On Linux, which interface does Snort typically monitor?

- A) lo
- B) wlan0
- C) eth0
- D) tty0

Answer: C

Q4. Snort rules detect threats based on:

- A) File extensions
- B) Packet headers
- C) Patterns in packets
- D) Wi-Fi strength

Answer: C

Q5. Which of the following is NOT a Snort mode?

- A) Sniffer
- B) Logger
- C) VPN
- D) IDS

Answer: C

Q6. Which command will test Snort in alert mode?

- A) snort -T
- B) snort -i eth0 -A console -c /etc/snort/snort.conf
- C) snort -u
- D) ping localhost

Answer: B

Q7. Which of the following log formats is NOT supported by Snort?

- A) Unified2
- B) Fast alert
- C) Full alert
- D) PNG

Answer: D

Q8. In Windows, Snort depends on which library for packet capture?

- A) LibSnort
- B) OpenSSL
- C) WinPcap/Npcap
- D) Wireshark

Answer: C

Q9. Which component analyzes packets in IDS?

- A) Sensor
- B) Manager
- C) Detection engine
- D) Logger

Answer: C

Q10. What type of tool is Snort?

- A) Open-source
- B) Paid only
- C) Cloud-only
- D) Deprecated

Answer: A

☒ Medium Level (20 MCQs)

Q11. Which Snort rule keyword is used to match specific content?

- A) detect
- B) content
- C) match
- D) rule

Answer: B

Q12. Which preprocessor helps Snort detect fragmented packets?

- A) stream5
- B) frag3
- C) decode

D) flowbits

Answer: B

Q13. What is a common method attackers use to bypass an IDS?

A) Whitelisting

B) Packet fragmentation

C) Using IPv6

D) DNS poisoning

Answer: B

Q14. Snort is considered a:

A) Host-based IDS

B) Network-based IDS

C) Hybrid IDS

D) SIEM system

Answer: B

Q15. Which of the following can help Snort handle encrypted traffic better?

A) HTTP proxy integration

B) IP blacklisting

C) Base64 encoding

D) DNS tunneling

Answer: A

Q16. Which tool is used to view and manage Snort alerts graphically?

- A) Burp Suite
- B) Wireshark
- C) BASE/Snorby
- D) Zenmap

Answer: C

Q17. Which component of an IDS generates alerts?

- A) Sensor
- B) Logging module
- C) Detection engine
- D) Proxy

Answer: C

Q18. In which mode does Snort only display packets and not log or alert?

- A) IDS mode
- B) Logger mode
- C) Sniffer mode
- D) Stealth mode

Answer: C

Q19. What protocol type does Snort inspect?

- A) Only TCP
- B) TCP and UDP
- C) TCP, UDP, ICMP, IP
- D) DNS only

Answer: C

Q20. Which Linux command helps test if Snort is capturing ICMP packets?

- A) traceroute
- B) nmap
- C) ping
- D) dig

Answer: C

Q21. What does this rule do: alert icmp any any -> any any (msg:"Ping Detected"; sid:1000002;)?

- A) Alerts for TCP
- B) Alerts for SSH
- C) Alerts on ping packets
- D) Drops ICMP traffic

Answer: C

Q22. Which of these best describes a **polymorphic shellcode**?

- A) Constant and simple
- B) Hidden via base64
- C) Changes structure but same behavior
- D) Encrypted over SSL

Answer: C

Q23. What type of log does Snort use for binary analysis?

- A) syslog
- B) unified2
- C) access.log
- D) txt

Answer: B

Q24. Which evasion technique uses **low-and-slow traffic**?

- A) UDP flood
- B) Ping of death
- C) Time-based IDS evasion
- D) Spoofed MAC

Answer: C

Q25. What Snort rule option allows checking of packet direction?

- A) offset
- B) content
- C) ->
- D) sid

Answer: C

Q26. Which field in Snort rule identifies the rule uniquely?

- A) sid
- B) msg
- C) classtype
- D) depth

Answer: A

Q27. What is the purpose of stream5 in Snort?

- A) Store logs
- B) Fragment packets
- C) Reassemble TCP streams
- D) Drop packets

Answer: C

Q28. How can Snort detect obfuscated payloads better?

- A) Disable preprocessors
- B) Use encrypted rules
- C) Enable stream5 + frag3
- D) Use fast alert only

Answer: C

Q29. Which tool allows Snort to run rules from a GUI?

- A) Nmap
- B) Suricata
- C) Snorby
- D) netcat

Answer: C

Q30. Snort can be integrated with which of the following for full DevSecOps monitoring?

- A) Jenkins
- B) SIEM
- C) GIT
- D) Docker

Answer: B

☒ Hard Level (10 MCQs)

Q31. Why might IDS miss fragmented payloads?

- A) Misconfigured port
- B) Lack of stream reassembly
- C) Memory overflow
- D) Disabled logging

Answer: B

Q32. Which of these is MOST likely to evade a Snort rule that matches cmd.exe in payload?

- A) IP spoofing
- B) Unicode encoding
- C) HTTP GET
- D) MAC flooding

Answer: B

Q33. In IDS evasion, the technique of splitting payload across many small packets is:

- A) DNS tunneling
- B) Packet reordering
- C) Fragmentation
- D) Steganography

Answer: C

Q34. What is a known limitation of signature-based IDS like Snort?

- A) Cannot detect ICMP
- B) Cannot scan large files
- C) Cannot detect unknown/zero-day attacks
- D) Logs too much data

Answer: C

Q35. Which is an advanced method of IDS evasion using timing?

- A) Fragmentation
- B) Encryption
- C) Slow HTTP header attack
- D) Shellshock

Answer: C

Q36. Why should HOME_NET be properly set in Snort?

- A) To block DNS
- B) To define internal network for correct rule application
- C) To bypass firewall
- D) To disable logs

Answer: B

Q37. Which part of Snort should be updated regularly to maintain accuracy?

- A) Kernel
- B) Logging module
- C) Rule base
- D) Ethernet driver

Answer: C

Q38. A Snort rule with content:"/bin/sh" is targeting:

- A) HTTP POST
- B) File downloads
- C) Shell access attempts
- D) DNS lookups

Answer: C

Q39. What could prevent Snort from seeing incoming traffic on Linux?

- A) Promiscuous mode enabled
- B) Interface down or incorrect
- C) snort.conf typo
- D) IPv6 packets

Answer: B

Q40. Which preprocessor helps detect overlapping TCP segments?

- A) stream5
- B) frag3
- C) http_inspect
- D) flowbits

ans -a