

☒ Easy (10 Questions)

Q1. What is Wireshark used for?

- A) Firewall configuration
- B) Network packet analysis
- C) Text editing
- D) Website development

Answer: B

Q2. Which of these is a **capture filter**?

- A) `ip.addr == 192.168.1.1`
- B) `host 192.168.1.1`
- C) `http.request.method == "GET"`
- D) `dns.qry.name`

Answer: B

Q3. Display filters in Wireshark are used:

- A) Before capturing
- B) To analyze already captured data
- C) Only on encrypted traffic
- D) To block traffic

Answer: B

Q4. What filter shows **all HTTP requests**?

- A) tcp.port == 80
- B) http.request
- C) udp.port == 53
- D) http.response

Answer: B

Q5. Which protocol filter displays ping traffic?

- A) tcp
- B) icmp
- C) http
- D) dns

Answer: B

Q6. A TCP 3-way handshake includes which packets?

- A) SYN, FIN, RST
- B) ACK, SYN, SYN-ACK
- C) SYN, SYN-ACK, ACK
- D) GET, POST, HEAD

Answer: C

Q7. To view DNS queries, use which filter?

- A) dns
- B) icmp
- C) ssl
- D) smtp

Answer: A

Q8. The part of Wireshark showing layer-wise breakdown is:

- A) Packet List
- B) Packet Details
- C) Hex Dump
- D) Filter bar

Answer: B

Q9. To capture **only HTTP traffic**, what capture filter is used?

- A) host http
- B) http.request
- C) tcp port 80
- D) ip.addr == 80

Answer: C

Q10. Which field in DNS shows the domain being queried?

- A) dns.flag
- B) dns.qry.name
- C) dns.src.port
- D) dns.tcp.payload

Answer: B

☒ Medium (20 Questions)

(Will continue in next response due to length)

Shall I go ahead with the **20 medium** and **10 hard** level MCQs?

You said:

yes

ChatGPT said:

Great! Let's continue with:

☒ Wireshark – 40 MCQs (Continued)

☒ Medium-Level Questions (20 Questions)

Q11. What does the Wireshark filter `tcp.flags.syn == 1` show?

- A) All SYN-ACK packets
- B) All completed TCP handshakes
- C) All TCP packets starting a session

D) All encrypted packets

Answer: C

☒ *It filters TCP packets that initiate a new connection (SYN packets).*

Q12. Which display filter shows packets from IP 192.168.10.1?

A) src 192.168.10.1

B) ip.src == 192.168.10.1

C) tcp.addr == 192.168.10.1

D) host == 192.168.10.1

Answer: B

Q13. What filter shows **HTTPS traffic** in Wireshark?

A) tcp.port == 80

B) udp.port == 443

C) tcp.port == 443

D) http.ssl

Answer: C

Q14. You want to **exclude** traffic from IP 10.0.0.1. Which filter would you use?

A) ip.addr == 10.0.0.1

B) not ip.addr == 10.0.0.1

C) src != 10.0.0.1

D) !tcp.port == 80

Answer: B

Q15. What filter captures **only DNS queries** and not responses?

A) dns.flags.response == 1

B) dns.qry.name

C) dns.flags.response == 0

D) udp.port == 53

Answer: C

☒ Response = 1; Query = 0.

Q16. Which field in Wireshark shows TCP retransmissions?

A) tcp.analysis.retransmission

B) tcp.ack

C) tcp.seq.analysis

D) tcp.flags.reset

Answer: A

Q17. What is the use of the filter tcp.analysis.flags?

A) Filters TCP DNS packets

B) Flags anomalies in TCP like retransmission or out-of-order

C) Captures malformed TCP headers

D) Highlights encrypted traffic

Answer: B

Q18. Which filter isolates HTTP GET requests?

A) `http.request.method == "POST"`

B) `http.response.code == 200`

C) `http.request.method == "GET"`

D) `http.uri == GET`

Answer: C

Q19. Which filter will show packets containing the string "password" in the payload?

A) `http.password == 1`

B) `tcp contains "password"`

C) `http.method contains "password"`

D) `tcp.payload == "password"`

Answer: B

Q20. To find large file transfers, which field would you analyze?

A) `tcp.window_size`

B) `frame.len`

C) `dns.qry.name`

D) `icmp.length`

Answer: B

✘ *frame.len* shows size of packet; large values hint large file transfers.

Q21. What is the purpose of the field `ssl.handshake.ciphersuite`?

- A) Shows if encryption is used
- B) Shows which hashing algorithm was used
- C) Indicates the cipher used during TLS handshake
- D) Reveals server operating system

Answer: C

Q22. Which filter finds TCP reset events?

- A) `tcp.flags.reset == 1`
- B) `tcp.flags.rst == 1`
- C) `tcp.flags.fin == 1`
- D) `tcp.analysis.retransmission == 1`

Answer: B

Q23. To trace communication **between two specific IPs**, what filter is correct?

- A) `ip.addr == x.x.x.x`
- B) `ip.src == x.x.x.x or ip.dst == y.y.y.y`
- C) `ip.addr == x.x.x.x and ip.addr == y.y.y.y`
- D) `ip.addr == x.x.x.x && y.y.y.y`

Answer: C

Q24. In DNS, which field shows **resolved IP** from a DNS response?

- A) dns.qry.name
- B) dns.flags.response
- C) dns.a
- D) dns.ptr

Answer: C

Q25. The filter tcp.port == 21 shows traffic related to:

- A) SSH
- B) Telnet
- C) FTP
- D) SNMP

Answer: C

Q26. In a TCP stream, the **sequence number** field is used for:

- A) Authentication
- B) Encryption
- C) Ordering and reliability
- D) DNS lookup

Answer: C

Q27. The field `tcp.analysis.ack_rtt` helps analyze:

- A) SYN packets
- B) Round Trip Time (RTT)
- C) TCP resets
- D) HTTP requests

Answer: B

Q28. What does the **filter expression** `http contains "username"` do?

- A) Captures HTTP packets with POST only
- B) Captures packets with login credentials
- C) Highlights payload with "username"
- D) Blocks traffic

Answer: C

Q29. What does the "Follow TCP Stream" feature allow in Wireshark?

- A) Replays video streams
- B) Filters only TCP resets
- C) Shows full conversation between client and server
- D) Captures voice packets

Answer: C

Q30. The tcp.window_size field helps identify:

- A) IP ranges
- B) Buffer sizes and congestion
- C) Application type
- D) DNS server IP

Answer: B

☒ Hard-Level Questions (10 Questions)

Q31. Which Wireshark feature automatically detects **retransmissions** and **out-of-order packets**?

- A) Frame inspector
- B) Expert Info ☒ TCP Analysis Flags
- C) SSL decode module
- D) Payload checksum

Answer: B

Q32. Which **display filter** finds all packets between TCP ports 20 and 25?

- A) tcp.port == 20-25
- B) tcp.port >= 20 && tcp.port <= 25
- C) tcp.port in 20-25

D) tcp.port = 20 to 25

Answer: B

Q33. Which option enables **decryption of SSL/TLS traffic** in Wireshark?

A) Load firewall certificate

B) Use filter tls.decrypted == true

C) Provide the server private key or keylog file

D) Enable proxy settings

Answer: C

Q34. What happens if you apply both a **capture filter** and a **display filter**?

A) Only capture filter is used

B) Only display filter is active

C) Capture filter limits data; display filter refines it

D) They override each other

Answer: C

Q35. In HTTP POST data, which field shows **form submission values**?

A) http.form.data

B) http.request.uri

C) tcp.payload

D) http.file_data

Answer: D

Q36. Which of the following best helps in detecting **DNS tunneling attacks**?

- A) `dns.flags.response == 1`
- B) High frequency and unusually long `dns.qry.name` entries
- C) `dns` contains "google.com"
- D) DNS source port fixed at 53

Answer: B

Q37. What is a **sign** of SYN flood attack in Wireshark?

- A) Multiple SYN followed by ACKs
- B) High number of SYN without ACK
- C) DNS spikes
- D) Large TCP window sizes

Answer: B

Q38. Which filter identifies large UDP payloads, often suspicious in **data exfiltration**?

- A) `udp.length > 500`
- B) `udp.flags == 1`
- C) `udp.dstport == 443`
- D) `udp.data_size == 0`

Answer: A

Q39. How to filter all TLS handshake failures?

- A) `tls.handshake.failed == 1`
- B) `tls.alert_message.level == 2`
- C) `ssl.version == none`
- D) `tcp.analysis.flags == true`

Answer: B

Q40. Which color rule highlights TCP retransmissions in default Wireshark profiles?

- A) Light purple
- B) Black
- C) Red
- D) Dark blue

Answer: C

☒ *Red indicates anomalies, including retransmissions.*