

1. Which OWASP category describes storing sensitive data unencrypted on a mobile device?

- A) Insecure Authentication
- B) Insecure Data Storage
- C) Improper Platform Usage
- D) Reverse Engineering

Answer: B

Explanation: Insecure Data Storage refers to improper handling of sensitive information on the device.

2. What Android feature allows apps to communicate and is often exploited in intent spoofing attacks?

- A) Services
- B) Activities
- C) Intents
- D) Broadcast Receivers

Answer: C

Explanation: Intents are messages passed between components, and spoofed intents can cause vulnerabilities.

3. Which type of attack exploits apps sending data over unencrypted channels?

- A) Replay Attack
- B) Man-in-the-Middle (MITM)
- C) SQL Injection
- D) Buffer Overflow

Answer: B

Explanation: MITM attacks intercept data sent over unencrypted or weakly encrypted connections.

4. Reverse engineering an Android APK is possible because Android apps are distributed as:

- A) Source code
- B) Bytecode in .dex files inside APK
- C) Compiled binaries
- D) Encrypted containers

Answer: B

Explanation: APKs contain Dalvik bytecode (.dex files), which can be decompiled.

5. Which of the following helps protect Android apps from reverse engineering?

- A) Using SSL
- B) Code obfuscation
- C) Storing passwords in SharedPreferences
- D) Disabling intents

Answer: B

Explanation: Obfuscation makes code harder to understand after decompilation.

6. Which OWASP Mobile Risk relates to improper use of platform-specific security features?

- A) Insecure Communication
- B) Improper Platform Usage
- C) Code Tampering
- D) Insufficient Cryptography

Answer: B

Explanation: Improper Platform Usage covers misuse of platform features like intents, biometrics.

7. What is a common issue when apps load code dynamically?

- A) Increased performance
- B) Security risk from untrusted code
- C) Easier debugging
- D) Lower battery consumption

Answer: B

Explanation: Dynamic code loading can allow malicious code injection if untrusted sources are

used.

8. An Android app requesting all device permissions without justification is an example of:

- A) Over-privileged Permissions
- B) Insecure Authentication
- C) Code Injection
- D) Buffer Overflow

Answer: A

Explanation: Over-requesting permissions increases attack surface and risk.

9. What does the OWASP category "Extraneous Functionality" mean in mobile apps?

- A) Features intended only for debugging or testing left in production apps
- B) Hidden malware
- C) Secure data encryption
- D) Proper session management

Answer: A

Explanation: Debug or backdoor features left in production can be exploited by attackers.

10. In Android, which component is vulnerable if WebView does not properly restrict JavaScript execution?

- A) Broadcast Receiver
- B) Activity
- C) WebView
- D) Service

Answer: C

Explanation: Improperly secured WebViews can be exploited via JavaScript injection.

11. Which tool is commonly used for reverse engineering

Android apps?

- A) Wireshark
- B) Apktool
- C) Metasploit
- D) Nmap

Answer: B

Explanation: Apktool is used to decompile and analyze APK files.

12. What kind of attack involves sending malicious intents to an Android app?

- A) Buffer Overflow
- B) Intent Spoofing
- C) SQL Injection
- D) Cross-Site Scripting

Answer: B

Explanation: Intent spoofing sends crafted intents to exploit app vulnerabilities.

13. What is a recommended security practice to protect data in transit for mobile apps?

- A) Use SSL/TLS for network communication
- B) Store data in plain text on the device
- C) Disable network encryption to improve speed
- D) Use HTTP instead of HTTPS

Answer: A

Explanation: SSL/TLS encrypts data to protect against interception.

14. Which OWASP Mobile risk is most related to improper session or token management?

- A) Insecure Authentication
- B) Code Tampering
- C) Reverse Engineering
- D) Insufficient Cryptography

Answer: A

Explanation: Poor session management can allow attackers to hijack user sessions.

15. Which of the following is NOT a typical symptom of code tampering?

- A) App crashes unexpectedly
- B) Modified app behavior
- C) App size remains unchanged
- D) Presence of unauthorized features

Answer: C

Explanation: Modified apps usually have changes in size or content.

16. Why is it risky for an Android app to hardcode API keys or secrets?

- A) It improves performance
- B) Attackers can extract them via reverse engineering
- C) It reduces app size
- D) It enhances app security

Answer: B

Explanation: Hardcoded secrets are easily extracted and abused.

17. Which Android file system location is safest for storing sensitive app data?

- A) External storage (SD card)
- B) Internal app storage with encryption
- C) Public Downloads folder
- D) Cache folder

Answer: B

Explanation: Internal storage with encryption protects data from other apps and users.

18. Which of the following attacks targets the Android Binder IPC mechanism?

- A) Intent Spoofing
- B) SQL Injection
- C) Buffer Overflow
- D) DNS Spoofing

Answer: A

Explanation: Binder IPC is used for inter-process communication; intents exploit it.

19. What is the effect of disabling SSL certificate validation in an Android app?

- A) Improves security
- B) Allows Man-in-the-Middle attacks
- C) Speeds up HTTPS connections
- D) Prevents data leakage

Answer: B

Explanation: Disabling SSL validation allows attackers to intercept encrypted traffic.

20. Which OWASP risk involves attackers modifying an app's APK or runtime code?

- A) Code Tampering
- B) Insecure Authentication
- C) Insufficient Cryptography
- D) Insecure Communication

Answer: A

Explanation: Code tampering is the unauthorized modification of app binaries or code.