Creating Releases using Docker



Justin Menga FULL STACK TECHNOLOGIST @jmenga pseudo.co.de

Introduction

Release Stage

- Creating application release settings
- Building a release image
- Creating a release environment
- Running acceptance tests

Continuous Delivery Workflow



Release Workflow using Docker

Create Release Environment

Create Release Settings Create Release Image


Bootstrap Release Environment

Prepare Environment Start Application


Acceptance Testing

Run Acceptance Tests Publish Release Image

Serving the Application



Serving the Application




Demo

Creating the Release Environment

- Creating application release settings
- Creating the release image
- Describing the release environment
- Testing the release image


Creating Application Release Settings

Application Configuration Settings




Creating the Release Image

Release Environment Folder Structure





Describing the Release Environment

Release Environment Design



Release Environment Folder Structure





Release Environment (Docker Host)

Testing the Release Image

Release Environment Issues

Runtime Environment

Missing requirements from base image

Encountered upon initial setup

Application container fails to start

Release environment misconfiguration

Bootstrap Tasks

Establish initial state

Required for each release stage iteration

Typically present as errors to user

E.g. Setup database schema and data

Demo


Bootstrapping the Application

- Initialisation tasks
- Starting the application

Initialisation Tasks

Collecting Static Files

docker-compose run manage.py collectstatic





Bootstrapping the Application Review

docker-compose build

docker-compose up agent

docker-compose run --rm app
manage.py collectstatic
--noinput

docker-compose run --rm app manage.py migrate --noinput

docker-compose up nginx

- Starts db service and ensures it is running
- ◆ Creates static content in the webroot volume container

- Creates schema and tables in application database
- Starts linked app service and then starts nginx front end


Demo

Acceptance Testing


- Creating a test service
- Running acceptance tests
- Publishing the release image

Creating the Test Service

Release Environment Design



Acceptance Tests Folder Structure



Running Acceptance Tests

Continuous Delivery Milestones



Unit and Integration Tests



Application Artifact and Docker Release Image



Acceptance Tests



Publish Application Artifact and Docker Release Image

Continuous Delivery Milestones



Unit and Integration Tests



Application Artifact and Docker Release Image



Acceptance Tests



Publish Application Artifact and Docker Release Image

Continuous Delivery Workflow Review


1. docker-compose build

Test Environment



Image

3. docker-compose up test



2. docker-compose up agent

target -> /wheelhouse


5. docker-compose build



Release Image


Release Environment

6. docker-compose up agent



5. docker-compose build

Release Environment



Summary

Release Stage

- Creates release image from application build artifacts
- Verifies application passes acceptance tests in a release environment
- Runs from a release environment
- Requires initialization tasks
- Release image ready to be published and deployed if all tests pass