

Creating Base Images with Packer



Paul Kirby

DEVOPS ENGINEER

www.paulkirby.me



Overview







Provisioners

- Reuse your Existing Work
- Fun with Scripts!
- Move My Files!

User Variables

Bash and Ansible

Provisioners



```
{  
  "type": "shell",  
  "script": "makeMyCowAwesome.sh",  
  "only": [ "MyCowServer-AWS" ]  
}
```

Provisioner Types

Configuration Management

File

Script



Configuration Management Provisioners



Demo



Configuration Management Provisioners

- Reuse your work!
- Ansible-Based
- “Hands-on Ansible” by Aaron Paxson




Globomantics' App



Globomantics Middle Tier



File Provisioners



Binaries, config files, HTML, graphics, etc.

Full directories!

Download too!

Move to temp directory first

- Doesn't set permissions

Demo




File Provisioners

- Configuration and binaries
- A few gotchas!
- Ties to next step, script provisioners



Globomantics Middle Tier



Script Provisioners

Local Shell

Remote Shell

Powershell

Windows Shell

Windows Restart



Demo



Script Provisioners

- Inline and file-based
- Tips and tricks for error handling



Globomantics Middle Tier



User Variables

```
{  
  "variables": {  
    "aws_region": ""  
  },  
  "builders": [{  
    "type": "amazon-ebs",  
    "region": "{{user `aws_region`}}"  
  }]  
}
```



User Variables – Environment Variables

```
{  
  "variables": {  
    "aws_region": "{{env `AWS_REGION`}}"  
  },  
  "builders": [{  
    "type": "amazon-ebs",  
    "region": "{{user `aws_region`}}"  
  }]  
}
```



Built-In Functions

`build_name`

`build_type`

`isotime [FORMAT]`

`lower`

`pwd`

`clean_ami_name`

`timestamp`

`uuid`

...



clean_ami_name



Amazon Only

Remove unwanted characters

Apply with pipe

- {{ "10:02:36" | clean_ami_name }}
- Output: 10-02-36

Commonly used with isotime

Timestamp



Replace with Unix Timestamp
Keep Image Names from Colliding

User Variables - Setting

```
> packer build -var 'aws_region=us-west-1' template.json
```

```
> packer build -var-file=variables.json template.json
```

```
{  
    "aws_region": "us-west-1"  
}
```



Demo



User Variables

- Simple usage in fields
- Fun technique – script templating!



Globomantics Middle Tier



Summary



Specialize your Cow Servers!

Reuse your Existing Work!

Infinite Flexibility

Next: Cross-Provider Images & Post-Processors

