```
ARP
    21 5.106039
                     IntelCor_7a:e4:be
                                         IntelCor 33:18:7d
                                                                       42
                                                                               Who has 10.10.41.239? Tell 10.10.43.41
Frame 21: 42 bytes on wire (336 bits), 42 bytes captured (336 bits)
   Encapsulation type: Ethernet (1)
   Arrival Time: Aug 22, 2018 23:10:43.503241000 IST
   [Time shift for this packet: 0.000000000 seconds]
   Epoch Time: 1534959643.503241000 seconds
   [Time delta from previous captured frame: 0.181580000 seconds]
   [Time delta from previous displayed frame: 0.181580000 seconds]
   [Time since reference or first frame: 5.106039000 seconds]
   Frame Number: 21
   Frame Length: 42 bytes (336 bits)
   Capture Length: 42 bytes (336 bits)
   [Frame is marked: False]
   [Frame is ignored: False]
   [Protocols in frame: eth:ethertype:arp]
   [Coloring Rule Name: ARP]
   [Coloring Rule String: arp]
Ethernet II, Src: IntelCor_7a:e4:be (d4:25:8b:7a:e4:be), Dst: IntelCor_33:18:7d (a0:a8:cd:33:18:7d)
   Destination: IntelCor_33:18:7d (a0:a8:cd:33:18:7d)
       Address: IntelCor_33:18:7d (a0:a8:cd:33:18:7d)
       .... ..0. .... = LG bit: Globally unique address (factory default)
       .... = IG bit: Individual address (unicast)
   Source: IntelCor_7a:e4:be (d4:25:8b:7a:e4:be)
       Address: IntelCor_7a:e4:be (d4:25:8b:7a:e4:be)
       ..... ..0. .... = LG bit: Globally unique address (factory default)
       .... = IG bit: Individual address (unicast)
   Type: ARP (0x0806)
Address Resolution Protocol (request)
   Hardware type: Ethernet (1)
   Protocol type: IPv4 (0x0800)
   Hardware size: 6
   Protocol size: 4
   Opcode: request (1)
   Sender MAC address: IntelCor_7a:e4:be (d4:25:8b:7a:e4:be)
   Sender IP address: 10.10.43.41
   Target MAC address: IntelCor_33:18:7d (a0:a8:cd:33:18:7d)
   Target IP address: 10.10.41.239
```