

Good question 🙄 Let's carefully unpack **what REST means in REST API**.

---

### ◆ REST = Representational State Transfer

It is an **architectural style** for designing APIs over HTTP.

- **Representational** → You don't send the actual resource (like a restaurant), you send a **representation** (JSON, XML, etc.) of it.
  - **State Transfer** → When the client interacts with the server, the "state" of the resource is transferred (for example, getting restaurant details, updating an order, etc.).
- 

### ◆ Key Principles of REST

1. **Client-Server** → Client (Swiggy app) and Server (Swiggy backend) are separate.
2. **Stateless** → Each request from the client contains all the information needed (no server memory of previous requests).
3. **Uniform Interface** → Standard HTTP methods are used (GET, POST, PUT, DELETE).
4. **Representations** → Resources (like `Restaurant` , `Order` ) are represented as JSON/XML, not Java objects directly.
5. **Resource-Based** → Everything is treated as a "resource" with a unique URL.

Good question 🙄 Let's carefully unpack **what REST means in REST API**.

---

### ◆ REST = Representational State Transfer

It is an **architectural style** for designing APIs over HTTP.

- **Representational** → You don't send the actual resource (like a restaurant), you send a **representation** (JSON, XML, etc.) of it.
  - **State Transfer** → When the client interacts with the server, the "state" of the resource is transferred (for example, getting restaurant details, updating an order, etc.).
- 

### ◆ Key Principles of REST

1. **Client-Server** → Client (Swiggy app) and Server (Swiggy backend) are separate.
2. **Stateless** → Each request from the client contains all the information needed (no server memory of previous requests).
3. **Uniform Interface** → Standard HTTP methods are used (GET, POST, PUT, DELETE).
4. **Representations** → Resources (like `Restaurant` , `Order` ) are represented as JSON/XML, not Java objects directly.
5. **Resource-Based** → Everything is treated as a "resource" with a unique URL.

## ◆ REST API in a Swiggy Example 🍔

- **Resource:** Restaurant
- **URL (Resource Identifier):**  
`https://swiggy.com/api/restaurants`
- **Operations (HTTP Methods):**
  - `GET /restaurants` → Get list of restaurants.
  - `GET /restaurants/101` → Get details of restaurant with ID=101.
  - `POST /orders` → Place a new order.
  - `PUT /orders/55` → Update order with ID=55.
  - `DELETE /orders/55` → Cancel order with ID=55.

Here:

- "Restaurant" and "Order" are **resources**.
- JSON returned to the app is the **representation** of those resources.

---

### ✅ In Short:

- **REST** is a set of rules for how web services should be built.
- **REST API** is an API that follows these REST rules.
- Data is exchanged as **representations (usually JSON)** via **HTTP methods**.

## ◆ REST API in a Swiggy Example 🍔

- **Resource:** Restaurant
- **URL (Resource Identifier):**  
`https://swiggy.com/api/restaurants`
- **Operations (HTTP Methods):**
  - `GET /restaurants` → Get list of restaurants.
  - `GET /restaurants/101` → Get details of restaurant with ID=101.
  - `POST /orders` → Place a new order.
  - `PUT /orders/55` → Update order with ID=55.
  - `DELETE /orders/55` → Cancel order with ID=55.

Here:

- "Restaurant" and "Order" are **resources**.
- JSON returned to the app is the **representation** of those resources.

---

### ✅ In Short:

- **REST** is a set of rules for how web services should be built.
- **REST API** is an API that follows these REST rules.
- Data is exchanged as **representations (usually JSON)** via **HTTP methods**.

Great follow-up 🙌

Let's break down what `Rest` means in `@RestController`.

### ◆ `@RestController` in Spring Boot

- `@RestController` is a **specialized version** of `@Controller`.
- It is basically:

java

Copy Edit

```
@RestController = @Controller + @ResponseBody
```

- Meaning: every method in that class returns **data directly in the HTTP response body**, instead of resolving to a view (like JSP/Thymeleaf).

### ◆ Why the word REST?

The “**Rest**” in `@RestController` comes from **RESTful Web Services** (Representational State Transfer).

- A class annotated with `@RestController` is meant to **build REST APIs**.
- These APIs typically return **JSON/XML representations** of resources.
- Instead of returning HTML pages (as in MVC `@Controller`), it returns raw data that clients (mobile apps, browsers, other services) consume.

Great follow-up 🙌

Let's break down what `Rest` means in `@RestController`.

### ◆ `@RestController` in Spring Boot

- `@RestController` is a **specialized version** of `@Controller`.
- It is basically:

java

Copy Edit

```
@RestController = @Controller + @ResponseBody
```

- Meaning: every method in that class returns **data directly in the HTTP response body**, instead of resolving to a view (like JSP/Thymeleaf).

### ◆ Why the word REST?

The “**Rest**” in `@RestController` comes from **RESTful Web Services** (Representational State Transfer).

- A class annotated with `@RestController` is meant to **build REST APIs**.
- These APIs typically return **JSON/XML representations** of resources.
- Instead of returning HTML pages (as in MVC `@Controller`), it returns raw data that clients (mobile apps, browsers, other services) consume.

## ◆ Example

java

📄 Copy 🗑 Edit

```
@RestController
@RequestMapping("/api")
public class RestaurantController {

    @GetMapping("/restaurant")
    public Restaurant getRestaurant() {
        return new Restaurant(1, "Pizza Palace");
    }
}
```

👉 Here, `getRestaurant()` returns a **Java object**.

👉 `@RestController` ensures it is **automatically converted to JSON** and sent in the HTTP response.

### ✅ In short:

- The “Rest” in `@RestController` signals that the controller is designed for **RESTful APIs**.
- Instead of returning views, it returns **resource data** (usually JSON) directly.

## ◆ Example

java

📄 Copy 🗑 Edit

```
@RestController
@RequestMapping("/api")
public class RestaurantController {

    @GetMapping("/restaurant")
    public Restaurant getRestaurant() {
        return new Restaurant(1, "Pizza Palace");
    }
}
```

👉 Here, `getRestaurant()` returns a **Java object**.

👉 `@RestController` ensures it is **automatically converted to JSON** and sent in the HTTP response.

### ✅ In short:

- The “Rest” in `@RestController` signals that the controller is designed for **RESTful APIs**.
- Instead of returning views, it returns **resource data** (usually JSON) directly.



If it return java object directly in http response ..then when it change in json by jackson

Super sharp question 🧐 — you're digging into the **internals of Spring Boot**.  
Let's walk through step by step.

### ◆ Flow of a `@RestController` Response

1. You return a Java object from your controller method.

```
java

@GetMapping("/restaurant")
public Restaurant getRestaurant() {
    return new Restaurant(1, "Pizza Palace");
}
```

📄 Copy 🖋 Edit

👉 Here you are just returning a **plain Java object**, not JSON.

2. **DispatcherServlet** (the front controller) gets the return value.

- It doesn't know yet if it should become JSON, XML, or something else.
- It asks the **HandlerAdapter** to process it. ⬇

### 3. HandlerAdapter → `HttpMessageConverter`

- Spring Boot looks at:
  - The `Accept` header from the client request ( `application/json` , `application/xml` , etc.).
  - The **return type** (Java object).
- Based on this, it picks an appropriate `HttpMessageConverter`.

### 4. Jackson's `MappingJackson2HttpMessageConverter` (default for JSON)

- If the client asked for JSON ( `Accept: application/json` ), Spring delegates to **Jackson**.
- Jackson takes the Java object and converts it into a JSON string.

json

Copy Edit

```
{
  "id": 1,
  "name": "Pizza Palace"
}
```

### 5. HTTP Response

- The JSON string is written directly to the **HTTP response body**.
- The client (e.g., Postman, browser, or Swiggy app) receives pure JSON.

### ◆ Where does Jackson come in?

Jackson comes in **after your controller method returns** the Java object, but **before Spring writes to the HTTP response**.

It's invoked inside the `HttpMessageConverter` layer.

---

### ✅ So in simple terms:

- You return Java object → Spring hands it to `HttpMessageConverter`.
- `HttpMessageConverter` uses **Jackson** to turn it into JSON.
- JSON is sent in the HTTP response body.

### ◆ What is `@RestController` ?

- `@RestController` is a **specialized version of** `@Controller` in Spring.
- It tells Spring:
  1. **This class is a Controller** (handles HTTP requests).
  2. **Return values of methods should be written directly into the HTTP response body** (instead of rendering a view like JSP/Thymeleaf).

👉 It is basically `@Controller` + `@ResponseBody` combined.

## ◆ Example

java

📄 Copy 🖋 Edit

```
@RestController
@RequestMapping("/api/hello")
public class HelloController {

    @GetMapping
    public String sayHello() {
        return "Hello, Abhishek! 🍌";
    }
}
```

### What happens here?

- Client hits: `GET http://localhost:8080/api/hello`
- `sayHello()` returns a **String**.
- Because of `@RestController`, Spring writes `"Hello, Abhishek! 🍌"` **directly in the HTTP response body**.
- No `ViewResolver` / `JSP` / `Thymeleaf` needed.

## ◆ Real-World Example (Swiggy 🍔)

java

📄 Copy 🗑 Edit

```
@RestController
@RequestMapping("/api/restaurants")
public class RestaurantController {

    private final RestaurantService service;

    public RestaurantController(RestaurantService service) {
        this.service = service;
    }

    @GetMapping
    public List<Restaurant> getRestaurants() {
        return service.getAllRestaurants();
    }
}
```

- **Client:** Mobile app calls `GET /api/restaurants`.
- **Controller:** Runs `getRestaurants()`.
- **Return:** List of restaurants → automatically converted to JSON by **Jackson**.

Response looks like:

json

📄 Copy ✎ Edit

```
[
  {"id": 1, "name": "Pizza Palace"},
  {"id": 2, "name": "Biryani House"}
]
```

## ✅ In Short

- `@RestController` = `@Controller` + `@ResponseBody` .
- Used in REST APIs (JSON/XML output).
- No **ViewResolver** needed → perfect for APIs.

### ◆ What is `@ResponseBody` ?

- `@ResponseBody` tells Spring MVC that the **return value of a method** should be **written directly into the HTTP response body**, instead of being resolved as a **view name**.
- It is used on methods inside a `@Controller` class.

👉 Without it, Spring thinks your method is returning the name of a view (like `"home.jsp"` ).

---

### ◆ Example 1: Without `@ResponseBody`

java

📄 Copy ✎ Edit

```
@Controller
public class HelloController {

    @GetMapping("/hello")
    public String sayHello() {
        return "hello"; // interpreted as view name (hello.jsp or hello.html)
    }
}
```

Here Spring will try to resolve `hello` as a **view template**, not as plain text.



### ◆ Example 3: Returning JSON

java

Copy Edit

```
@Controller
public class RestaurantController {

    @GetMapping("/restaurant")
    @ResponseBody
    public Restaurant getRestaurant() {
        return new Restaurant(1, "Pizza Palace");
    }
}
```

Response:

json

Copy Edit

```
{
  "id": 1,
  "name": "Pizza Palace"
}
```

👉 Spring Boot uses **Jackson** under the hood to automatically convert Java objects to JSON when `@ResponseBody` is present.

## ◆ How `@RestController` Works

- When you annotate a class with `@RestController` :
  - Every method in that class returns data **directly in the HTTP response body**.
  - Spring Boot automatically uses **HTTP Message Converters** (like Jackson) to turn Java objects into **JSON** (or XML, if requested).



## ◆ Example

java

📄 Copy ✎ Edit

```
@RestController
@RequestMapping("/api")

public class RestaurantController {

    @GetMapping("/restaurant")
    public Restaurant getRestaurant() {
        return new Restaurant(1, "Pizza Palace");
    }
}
```

**Response to Client (Browser/Postman/Swiggy app):**

json

📄 Copy ✎ Edit

```
{
  "id": 1,
  "name": "Pizza Palace"
}
```


👉 No JSP, Thymeleaf, or HTML view involved.



👉 Data goes straight from Java → JSON → HTTP response → Client.

@RestController class method return directly java object



Yes  you're spot on — a method in a `@RestController` class **returns a Java object directly**, and then **Spring Boot** does the work of converting that Java object into JSON (or XML, etc.) before sending it in the HTTP response.

`@GetMapping` is a **shortcut annotation** in Spring MVC/Spring Boot used to **map HTTP GET requests** onto specific controller methods.

It is equivalent to:

java

Copy Edit

```
@RequestMapping(method = RequestMethod.GET, value = "/path")
```

So basically:

👉 `@GetMapping("/path")` = `@RequestMapping(value="/path", method=RequestMethod.GET)`

---

### ◆ Why GET?

- HTTP **GET** is used to **fetch/read data** from the server.
- It should **not modify** data (idempotent).

## ◆ Example

```
java 📄 Copy  ✎ Edit  
  
@RestController  
@RequestMapping("/api")  
public class RestaurantController {  
  
    // Maps GET request at /api/restaurant  
    @GetMapping("/restaurant")  
    public Restaurant getRestaurant() {  
        return new Restaurant(1, "Pizza Palace");  
    }  
  
    // Maps GET request at /api/restaurants  
    @GetMapping("/restaurants")  
    public List<Restaurant> getAllRestaurants() {  
        return List.of(  
            new Restaurant(1, "Pizza Palace"),  
            new Restaurant(2, "Burger Hub")  
        );  
    }  
}
```

## What happens here:

1. Client calls → `GET /api/restaurant`
  - Controller returns **Java object** `Restaurant`.
  - Spring → `HttpMessageConverter` → Jackson → JSON in response.
2. Client calls → `GET /api/restaurants`
  - Controller returns a **List of objects**.
  - Spring automatically converts the list into a JSON array.

---

### ◆ Real World (Swiggy Example 🍔)

- `GET /api/restaurants` → fetches list of restaurants near you.
- `GET /api/restaurants/101` → fetches details of restaurant with ID = 101.

👉 Both would be handled with `@GetMapping`.

---

### ✅ In short:

`@GetMapping` = handles **HTTP GET requests** and maps them to controller methods, usually to return **data (JSON)** to the client.





### ◆ @GetMapping Attributes

The `@GetMapping` annotation is **meta-annotated** with `@RequestMapping`, so it inherits most of the same attributes.

Here are the key ones:

#### 1. `value` / `path`

- Defines the **URI path(s)** for the GET request.
- Both `value` and `path` do the same thing.

java

📄 Copy ✎ Edit

```
@GetMapping("/restaurants")  
@GetMapping(path = "/restaurants")  // same as above
```

---

## 2. params

- Restricts mapping based on **HTTP request parameters**.

java

Copy Edit

```
@GetMapping(value = "/restaurants", params = "cuisine=italian")
public String getItalianRestaurants() {
    return "Only Italian restaurants";
}
```

👉 Matches only when query param `?cuisine=italian` is present.

---

## 3. headers

- Restricts mapping based on **HTTP headers**.

java

Copy Edit

```
@GetMapping(value = "/restaurants", headers = "X-API-VERSION=1")
public String getRestaurantsV1() {
    return "API version 1";
}
```

#### 4. consumes

- Defines what **Content-Type** the method can consume (request body).
  - 👉 Rarely used with `GET` because GET usually has no body.

java

📄 Copy ✎ Edit

```
@GetMapping(value = "/data", consumes = "application/json")
public String consumeJson() {
    return "Consumes JSON input";
}
```

#### 5. produces

- Defines what **Content-Type** the method produces (response).

java

📄 Copy ✎ Edit

```
@GetMapping(value = "/restaurants", produces = "application/json")
public List<Restaurant> getRestaurants() { ... }

@GetMapping(value = "/restaurants", produces = "application/xml")
public List<Restaurant> getRestaurantsXml() { ... }
```



- 👉 Useful for returning JSON or XML depending on client request.

### ◆ Example (with multiple attributes)

java

Copy Edit

```
@GetMapping(  
    value = "/restaurants",  
    params = "city=delhi",  
    headers = "X-API-VERSION=2",  
    produces = "application/json"  
)  
public List<Restaurant> getDelhiRestaurantsV2() {  
    return List.of(new Restaurant(1, "Delhi Dhaba"));  
}
```

👉 This method will only respond if:

- URL contains `?city=delhi`
- Header has `X-API-VERSION=2`
- Client accepts `application/json`



## 📌 Summary.

Main attributes of `@GetMapping`:

- `value` / `path` → URI
- `params` → request parameters
- `headers` → request headers
- `consumes` → expected input type
- `produces` → response type



When we use the path attribute in @GetMapping .... What is checked by the dispatcherServlet and which controller methods run ...And what get http request checked with path

Excellent 🧨 — you're now asking **how DispatcherServlet decides which method to call when we use path (or value) inside @GetMapping.**

Let's go step by step:

---

### ♦ What happens when a request comes in?

#### 1. Client sends HTTP request

Example:

```
bash
```

📄 Copy ✎ Edit

```
GET /restaurants
```

👉 The **path** here is `/restaurants`.

## 2. Tomcat receives the HTTP request

- Since Spring Boot runs on an embedded Tomcat, the request is passed to **DispatcherServlet** (the front controller).

## 3. DispatcherServlet checks HandlerMapping

- Spring maintains a **HandlerMapping registry** (a big map of URL paths → controller methods).
- Example mapping table:

Path (from <code>@GetMapping</code> )	HTTP Method	Controller Method
<code>/restaurants</code>	GET	<code>getRestaurants()</code>
<code>/restaurants/{id}</code>	GET	<code>getRestaurantById(Long id)</code>
<code>/orders</code>	POST	<code>createOrder()</code>

## 4. DispatcherServlet matches request path

- It takes the path from the HTTP request ( `/restaurants` )
- Compares it against registered mappings ( `@GetMapping(path="/restaurants")` ).
- Also checks **HTTP method** (must be GET for `@GetMapping` ).

👉 If both path **and** method match → that controller method is chosen.



## 5. Matched method runs

Example:

java

 Copy  Edit

```
@RestController
class RestaurantController {
    @GetMapping(path="/restaurants")
    public List<Restaurant> getRestaurants() {
        return List.of(new Restaurant(1, "Pizza Palace"));
    }
}
```

- If client calls `GET /restaurants`, `DispatcherServlet` chooses `getRestaurants()`.
  - If client calls `POST /restaurants`, this method **won't run** (since method mismatch).
-

## ◆ Real Swiggy Example 🍔

- **Request:** GET /api/restaurants
  - Path = /api/restaurants
  - HTTP Method = GET
- DispatcherServlet looks into mappings and finds:

java

📄 Copy ✎ Edit

```
@GetMapping(path="/api/restaurants")
public List<Restaurant> getAllRestaurants() { ... }
```

- ✓ Match found → method runs → returns JSON list of restaurants.

---

## ◆ In short:

- path / value in @GetMapping tells DispatcherServlet *which URL this method listens to*.
- DispatcherServlet checks the **request's URL path + HTTP method**.
- If they match → that controller method is executed.

Dynamic URL Paths to get the data in the url

Perfect 🚀 — you're asking about **dynamic URL paths** in Spring Boot (often called **Path Variables**) so you can pass data inside the URL itself.

---

### ◆ What is a Dynamic URL Path?

Instead of always using fixed URLs like:

```
bash
GET /restaurants
```

Copy code

You sometimes want to pass **data inside the URL** like:

```
bash
GET /restaurants/5
```

Copy code


Here `5` is the **restaurant ID**.

## ◆ How to Handle in Spring Boot

Spring provides `@PathVariable` for this.

### Example

java

 Copy code

```
@RestController
@RequestMapping("/restaurants")
public class RestaurantController {

    // GET /restaurants/5
    @GetMapping("/{id}")
    public String getRestaurantById(@PathVariable int id) {
        return "Restaurant with ID = " + id;
    }
}
```


👉 If client calls `GET /restaurants/5`

- DispatcherServlet matches `{id}`
- Extracts `id = 5`
- Passes it into method parameter

Response:

csharp



 Copy code

Restaurant with ID = 5

## ◆ Multiple Dynamic Parts

java

 Copy code

```
// GET /restaurants/5/menu/10
@GetMapping("/{restaurantId}/menu/{itemId}")
public String getMenuItem(
    @PathVariable int restaurantId,
    @PathVariable int itemId) {
    return "Restaurant " + restaurantId + ", Menu Item " + itemId;
}
```

Call → GET /restaurants/5/menu/10

Response →

mathematica

 Copy code

Restaurant 5, Menu Item 10

## ◆ What is `@PathVariable`?

- `@PathVariable` is used to **extract values from the URL path itself**.
  - It maps a **dynamic part of the URL** (like `/users/10`) to a **method parameter** in your controller.
  - Works with `@GetMapping`, `@PostMapping`, etc.
- 

## ◆ When to Use `@PathVariable`

- ✓ Use when the value is a **unique identifier** or part of the **resource's identity**.

Examples:

- `/restaurants/5` → Get restaurant with id = 5
- `/orders/123/status` → Get status of order 123
- `/users/42/profile` → Get profile of user 42

✗ Don't use it for **filtering or optional data** (that's better with `@RequestParam` like `/restaurants?city=Delhi`).

## ◆ Key Points about `@PathVariable`

1. **Binding:** It binds URL template variables ( `{id}` ) to method parameters.
  2. **Mandatory by default** → if missing, you get `404 Not Found`.
    - Use `required=false` if optional (but usually for optional values, `@RequestParam` is better).
  3. **Works with any HTTP method** → `@GetMapping`, `@PostMapping`, etc.
  4. **Type Conversion:** Spring automatically converts from `String` → `int`, `long`, etc.
    - If it fails (e.g., `/restaurants/abc` but expecting `int`), you get `400 Bad Request`.
- 


## ◆ REST Best Practice

- Use `PathVariable` for resource identifiers ( `/users/5`, `/orders/123` )
- Use `RequestParam` for filtering, searching, pagination, optional parameters ( `/restaurants?city=Delhi&page=2` ).

### ◆ Example 3: Custom Variable Names

Sometimes your path variable name  $\neq$  method parameter name.

java

 Copy code

```
// GET /orders/123
@GetMapping("/orders/{orderId}")
public String getOrder(@PathVariable("orderId") String id) {
    return "Order ID = " + id;
}
```

👉 Path part `{orderId}` maps to parameter `id`.

---



## What `@RequestParam` is

Binds **query-string** or **form data** parameters to controller method arguments.

- Works with:
    - `GET /search?q=pizza&page=2` → `q`, `page` are query params
    - `POST` with `application/x-www-form-urlencoded` or `multipart/form-data`
  - Not for JSON bodies — use `@RequestBody` for that.
- 

## When to use it (and when not)

Use `@RequestParam` for:

- Filters/search/pagination/sorting: `/restaurants?city=Delhi&page=2&size=20`
- Small scalar inputs (Strings, numbers, booleans, enums)
- Form fields and **file uploads** (`MultipartFile`)
- Optional knobs/toggles

Don't use it for:

- Resource identity: use `@PathVariable` (`/restaurants/42`)
  - Complex nested data (JSON): use `@RequestBody`
-

## Core attributes

```
java                                                                    Copy code


@GetMapping("/restaurants")
public List<Restaurant> list(
    @RequestParam(name="city") String city,           // 1) name/value
    @RequestParam(required=false) String cuisine,     // 2) required (default true)
    @RequestParam(defaultValue="1") int page,         // 3) defaultValue -> also makes it not required
    @RequestParam(defaultValue="20") int size
) { ... }
```

1. **name/value** (alias): the query key. If omitted, Spring uses the **parameter name**.
2. **required**: default `true`. Missing param  $\Rightarrow$  **400 Bad Request**.
3. **defaultValue**: sets a fallback value **and** implicitly sets `required=false`.

Tip: If using `required=false`, prefer wrapper types ( `Integer`, `Boolean` ) so `null` is possible.


## 2) Custom param name

sql

 Copy code

```
GET /search?q=pizza
```


java

 Copy code

```
@GetMapping("/search")  
public List<Item> search(@RequestParam("q") String keyword) { ... }
```


## 3) Collections & repeated params

bash

 Copy code

```
GET /menu?ids=1&ids=2&ids=3
```

java

 Copy code

```
@GetMapping("/menu")  
public List<MenuItem> getMenu(@RequestParam List<Integer> ids) { ... }  
// also works with Set<Integer>
```

#### 4) Grab all params dynamically

java

 Copy code

```
@GetMapping("/report")
public Map<String,String> report(@RequestParam Map<String,String> params) { ... }

// For repeated keys:
public MultiValueMap<String,String> report(@RequestParam MultiValueMap<String,String> params) { ..
```

#### 5) Dates & formatting

vbnet

 Copy code

```
GET /orders?from=2025-08-01&to=2025-08-31
```

java

 Copy code

```
@GetMapping("/orders")
public List<Order> orders(
    @RequestParam @DateTimeFormat(iso = DateTimeFormat.ISO.DATE) LocalDate from,
    @RequestParam @DateTimeFormat(iso = DateTimeFormat.ISO.DATE) LocalDate to
) { ... }
```


## 6) Booleans and enums

bash

 Copy code

```
GET /restaurants?vegOnly=true&sort=RATING
```

java

 Copy code

```
enum SortBy { NAME, RATING }
@GetMapping("/restaurants")
public List<Restaurant> list(
    @RequestParam(defaultValue="false") boolean vegOnly,
    @RequestParam(defaultValue="NAME") SortBy sort
) { ... }
```

## 7) Validation on params


java

 Copy code

```
@Validated
@RestController
class RestaurantController {
    @GetMapping("/restaurants")
    public List<Restaurant> list(
        @RequestParam @Min(1) int page,
        @RequestParam @Max(100) int size,
        @RequestParam(required=false) @Pattern(regexp="^(name|rating)$") String sortBy
    ) { ... }
```

## 8) File upload (multipart form)


java

 Copy code

```
@PostMapping(value="/menu/upload", consumes=MediaType.MULTIPART_FORM_DATA_VALUE)
public String upload(@RequestParam("file") MultipartFile file) {
    return "Uploaded " + file.getOriginalFilename();
}
```


## 9) With `@PathVariable` together

bash

 Copy code

```
GET /restaurants/42/menu?vegOnly=true
```

java

 Copy code

```
@GetMapping("/restaurants/{id}/menu")
public List<MenuItem> menu(
    @PathVariable long id,
    @RequestParam(defaultValue="false") boolean vegOnly
) { ... }
```

## How binding & errors work

- Spring converts strings → target types (int, long, boolean, enum, `LocalDate`, etc.).
  - If conversion fails ( `page=abc` for `int` ) ⇒ **400 Bad Request**.
  - Missing required param ⇒ **400**.
  - `defaultValue` avoids 400 by supplying a value.
  - You can add **custom converters/formatters** if needed.
- 

## Best practices (quick checklist)

- **Identity in path, filters in query:** `/orders/123` + `?includeItems=true` .
- Provide **defaults** for page/size; cap size server-side.
- **Allowlist** sortable fields to avoid injection ( `sort=name` / `rating` only).
- Keep query params **small and simple**; move complex data to a DTO with `@RequestBody` .
- Prefer **wrapper types** for optional params.

```
@GetMapping(path="/employees/{employeeId}")
```

```
public EmployeeDTO getEmployeeById(@PathVariable Long  
employeeId) {}
```

```
@GetMapping(path="/employees/{employeeName}")
```

27

```
public EmployeeDTO  
getEmployeeByIdd(@PathVariable(name="employeeName") String  
Name){}
```

Is these both are considered same as when I am searching it by url in chrome it is showing error



## Your code:

```
java                                                                    Copy code

@GetMapping(path="/employees/{employeeId}")
public EmployeeDTO getEmployeeById(@PathVariable Long employeeId) { ... }

@GetMapping(path="/employees/{employeeName}")
public EmployeeDTO getEmployeeByIdd(@PathVariable(name="employeeName") String name) { ... }
```

## ✅ What Spring sees

- Both mappings have the **same URL pattern**:

```
bash                                                                    Copy code

/employees/{something}
```

It doesn't matter whether you name it `{employeeId}` or `{employeeName}` — to Spring MVC, both are just **wildcards for one path segment**.

- So Spring can't distinguish them → **Ambiguous mapping exception** at startup (or strange runtime errors if somehow loaded).

That's why in Chrome/Postman when you hit `/employees/27` ↓, Spring doesn't know whether to call method 1 (expecting an ID) or method 2 (expecting a name). Hence the error.

### ▶ Key point:

The **placeholder name** inside `{ }` is only for binding to the method parameter.

For the URL pattern itself, `{employeeId}` and `{employeeName}` are treated the same: one wildcard segment.

So the two methods are **considered the same mapping**.

---

### ✅ How to fix / differentiate

If you want **two separate endpoints** (one by ID, one by name), you must make the paths **different**:

java

Copy code

```
@GetMapping(path="/employees/id/{employeeId}")
public EmployeeDTO getEmployeeById(@PathVariable Long employeeId) { ... }

@GetMapping(path="/employees/name/{employeeName}")
public EmployeeDTO getEmployeeByName(@PathVariable String employeeName) { ... }
```

Now Spring can clearly distinguish:


- `/employees/id/27` → goes to the ID method
- `/employees/name/John` → goes to the name method ↓

### ◆ What is `@PostMapping`?

- `@PostMapping` is a Spring MVC annotation that handles **HTTP POST requests**.
  - It is a **specialized version** of `@RequestMapping(method = RequestMethod.POST)`.
  - Typically used to **create a new resource** on the server (e.g., adding an employee, placing an order, registering a user).
- 

### ◆ Example 1: Basic usage

java


 Copy code

```
@RestController
@RequestMapping("/employees")
public class EmployeeController {

    @PostMapping
    public String createEmployee() {
        return "New employee created successfully!";
    }
}
```

👉 If you send a `POST` request to `/employees`, it will return:

```
sql
```

 Copy code


```
New employee created successfully!
```

## ◆ Example 2: Sending data in request body

Usually, POST requests carry data in the **HTTP request body** (JSON, XML, or form data).

Spring uses `@RequestBody` to read that data and bind it to a Java object.


java

 Copy code

```
@PostMapping
public EmployeeDTO createEmployee(@RequestBody EmployeeDTO employee) {
    // Normally you'd save employee in DB here
    return employee; // return the saved employee as response
}
```

👉 Request (POST /employees):

json

 Copy code

```
{
  "id": 101,
  "name": "Alice",
  "department": "IT"
}
```

👉 **Response** (JSON automatically returned because of Jackson):

json

 Copy code

```
{
  "id": 101,
  "name": "Alice",
  "department": "IT"
}
```

### ◆ Example 3: With Path + Body

java

 Copy code

```
@PostMapping("/{department}")
public EmployeeDTO createEmployeeInDept(
    @PathVariable String department,
    @RequestBody EmployeeDTO employee) {
    employee.setDepartment(department);
    return employee;
}
```

👉 POST /employees/HR with body:

json

 Copy code

```
{ "id": 102, "name": "Bob" }
```

👉 Response:

json

 Copy code

```
{ "id": 102, "name": "Bob", "department": "HR" }
```

---

### ◆ When to use `@PostMapping`

- When you want to **create** a new resource.
  - When you need to send **sensitive or large data** in the request body.
  - Example real-world APIs:
    - `POST /orders` → place a new order on Swiggy.
    - `POST /users/register` → create a new user.
    - `POST /employees` → add an employee in HR system.
- 

### ◆ Difference from `@GetMapping`

- `@GetMapping` → Fetch data (idempotent, safe, no side-effects).
  - `@PostMapping` → Submit data / create new resource (has side-effects).
- 

### ✅ Summary


- `@PostMapping` maps **HTTP POST** requests.
  - Often combined with `@RequestBody` for JSON input.
  - Used for **creating resources** in REST APIs.
-



### ◆ What is `@PutMapping`?

- `@PutMapping` is a Spring MVC annotation that handles **HTTP PUT requests**.
- It's a **specialized shortcut** for:

java


 Copy code

```
@RequestMapping(method = RequestMethod.PUT)
```

- In REST APIs, **PUT is used to update an existing resource** (replace it entirely).
  - It is **idempotent** → calling it multiple times with the same data will always produce the same result.
-

### ◆ Example 1: Basic PUT Mapping

java

 Copy code

```
@RestController
@RequestMapping("/employees")
public class EmployeeController {

    @PutMapping("/{id}")
    public String updateEmployee(@PathVariable Long id) {
        return "Employee with ID " + id + " updated successfully!";
    }
}
```

👉 Request:

PUT /employees/101

👉 Response:

csharp

 Copy code


Employee with ID 101 updated successfully!

---

## ◆ Example 2: Updating with JSON body

Usually, you pass new values in the **request body** with `@RequestBody` .

java

 Copy code

```
@PutMapping("/{id}")
public EmployeeDTO updateEmployee(
    @PathVariable Long id,
    @RequestBody EmployeeDTO updatedEmployee) {


    updatedEmployee.setId(id);
    // Normally, save this updatedEmployee to the DB
    return updatedEmployee;
}
```

👉 Request:

PUT /employees/101

Body:

json

 Copy code

```
{
  "name": "Alice Johnson",
  "department": "Finance"
}
```



👉 Response:

json

📋 Copy code

```
{  
  "id": 101,  
  "name": "Alice Johnson",  
  "department": "Finance"  
}
```

---

### ◆ Example 3: Difference between `@PutMapping` and `@PatchMapping`

- **PUT** → Replaces the **entire resource**.
  - If fields are missing in request, they may get overwritten with `null`.
- **PATCH** → Updates **partially** (only given fields).

Example:

- Employee = `{id:101, name:"Alice", dept:"IT"}`
  - **PUT** request with body: `{name:"Bob"}` → may overwrite dept to `null`.
  - **PATCH** request with body: `{name:"Bob"}` → only changes the name, dept remains `"IT"`.
- 

### ◆ Real-world examples

- Swiggy/Zomato: `PUT /users/123/address` → update your saved address.
  - Banking app: `PUT /accounts/456` → update account details.
  - HR system: `PUT /employees/789` → replace full employee info.
- 

### ✅ Summary

- `@PutMapping` → maps HTTP **PUT** requests.
- Used to **update/replace existing resources**.
- Works with `@PathVariable` (to identify the resource) and `@RequestBody` (new data).
- **Idempotent** → multiple identical calls = same result.

## ◆ What is Lombok?

- **Project Lombok** is a Java library that helps reduce **boilerplate code** like getters, setters, constructors, `toString()`, `equals()`, `hashCode()`, and builders.
- Instead of writing them manually, Lombok uses **annotations** to generate them **at compile time**.

👉 This makes your code **cleaner, shorter, and easier to maintain**.

---

## ◆ How to use Lombok?

1. Add Lombok dependency in your `pom.xml` (Maven):

xml

📋 Copy code

```
<dependency>
  <groupId>org.projectlombok</groupId>
  <artifactId>lombok</artifactId>
  <version>1.18.32</version> <!-- Latest version -->
  <scope>provided</scope>
</dependency>
```

For Gradle:

gradle

📋 Copy code

```
compileOnly 'org.projectlombok:lombok'
annotationProcessor 'org.projectlombok:lombok'
```

## ◆ What is Lombok?

- **Project Lombok** is a Java library that helps reduce **boilerplate code** like getters, setters, constructors, `toString()`, `equals()`, `hashCode()`, and builders.
- Instead of writing them manually, Lombok uses **annotations** to generate them **at compile time**.

👉 This makes your code **cleaner, shorter, and easier to maintain**.

---

## ◆ How to use Lombok?

1. Add Lombok dependency in your `pom.xml` (Maven):

xml

📋 Copy code

```
<dependency>
  <groupId>org.projectlombok</groupId>
  <artifactId>lombok</artifactId>
  <version>1.18.32</version> <!-- latest version -->
  <scope>provided</scope>
</dependency>
```

For Gradle:

gradle

📋 Copy code

```
compileOnly 'org.projectlombok:lombok'
annotationProcessor 'org.projectlombok:lombok'
```


2. Install the **Lombok plugin** in IntelliJ or Eclipse (so your IDE understands the generated code).

## ◆ Common Lombok Annotations

### 1. @Getter and @Setter

Generates getters and setters automatically.

java

 Copy code

```
import lombok.Getter;
import lombok.Setter;

@Getter
@Setter
public class Employee {
    private Long id;
    private String name;
}
```

👉 No need to manually write `getId()`, `setId()`, etc.



## 2. @Data

Generates:

- Getters
- Setters
- toString()
- equals() and hashCode()
- RequiredArgsConstructor

java

 Copy code


```
import lombok.Data;

@Data
public class Employee {
    private Long id;
    private String name;
}
```

### 3. @NoArgsConstructor, @AllArgsConstructor, @RequiredArgsConstructor

Generates constructors automatically.

java

 Copy code

```
import lombok.*;

@AllArgsConstructor
@NoArgsConstructor
public class Employee {
    private Long id;
    private String name;
}
```

#### 4. @Builder

Creates a builder pattern for objects.

java

 Copy code

```
import lombok.Builder;
import lombok.Data;

@Data
@Builder
public class Employee {
    private Long id;
    private String name;
    private String department;
}
```

👉 Usage:

java

 Copy code

```
Employee emp = Employee.builder()
    .id(101L)
    .name("Alice")
    .department("IT")
    .build();
```

## 5. @Value

Makes a class **immutable** (all fields `final`, private, getters only).

java

 Copy code

```
import lombok.Value;

@Value
public class Employee {
    Long id;
    String name;
}
```

---

### ◆ Real-world use in Spring Boot

- DTOs (Data Transfer Objects)
- Entities (if not overriding equals/hashCode manually)
- Request/Response models in REST APIs
- Builder pattern for test data or complex objects

is during JSON body given to dispatcher during using `@RequestBody`,  
JSON body is converted into the java object by lombok

Ahh ⚡ great catch! This is where people often get confused between **Lombok** and **Jackson** in Spring Boot.  
Let's clear it step by step 📌


### ♦ What happens with `@RequestBody` ?

When you send a request like:

```
http

POST /employees
Content-Type: application/json

{
  "id": 101,
  "name": "Alice",
  "department": "IT"
}
```

 Copy code

and your controller is:

```
java

@PostMapping("/employees")
public Employee createEmployee(@RequestBody Employee employee) {
    return employee;
}
```

 Copy code



#### 👉 Process:

1. The HTTP request comes into **DispatcherServlet**.
  2. **Spring uses Jackson (a JSON library) to deserialize JSON → Java object ( `Employee` ).**
  3. For deserialization, Jackson needs:
    - A **default constructor** (no-args constructor).
    - **Setters** (or direct field access).
  4. Once the object is created, Spring injects it into the `employee` parameter.
- 

#### 💡 Where does Lombok come in?

- Lombok itself **does not convert JSON**.
- Lombok only generates boilerplate code (getters, setters, constructors) at **compile-time**.
- Jackson **uses those generated setters & constructors** to do the conversion.

So effectively:

- **Jackson = does the JSON ↔ Java conversion**
  - **Lombok = just provides setters/getters/constructors automatically** so Jackson can use them
-