

C. Maximum Median

time limit per test: 2 seconds
 memory limit per test: 256 megabytes
 input: standard input
 output: standard output

You are given an array a of n integers, where n is odd. You can make the following operation with it:

- Choose one of the elements of the array (for example a_i) and increase it by 1 (that is, replace it with $a_i + 1$).

You want to make the median of the array the largest possible using at most k operations.

The median of the odd-sized array is the middle element after the array is sorted in non-decreasing order. For example, the median of the array $[1, 5, 2, 3, 5]$ is 3.

Input

The first line contains two integers n and k ($1 \leq n \leq 2 \cdot 10^5$, n is odd, $1 \leq k \leq 10^9$) — the number of elements in the array and the largest number of operations you can make.

The second line contains n integers a_1, a_2, \dots, a_n ($1 \leq a_i \leq 10^9$).

Output

Print a single integer — the maximum possible median after the operations.

Examples

input	Copy
3 2 1 3 5	
output	Copy
5	
input	Copy
5 5 1 2 1 1 1	
output	Copy
3	
input	Copy
7 7 4 1 2 4 3 4 4	
output	Copy
5	

Note

In the first example, you can increase the second element twice. Then array will be $[1, 5, 5]$ and its median is 5.

In the second example, it is optimal to increase the second number and then increase third and fifth. This way the answer is 3.

Codeforces Round #577 (Div. 2)

Finished

→ Practice?

Want to solve the contest problems after the official contest ends? Just register for practice and you will be able to submit solutions.

[Register for practice](#)

→ Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ACM-ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

[Start virtual contest](#)

→ Problem tags

[binary search](#) [greedy](#) [math](#) [sortings](#)
 No tag edit access

→ Contest materials

- [Announcement \(en\)](#) [×](#)

In the third example, you can make four operations: increase first, fourth, sixth, seventh element. This way the array will be $[5, 1, 2, 5, 3, 5, 5]$ and the median will be 5.

[Codeforces](#) (c) Copyright 2010-2019 Mike Mirzayanov
The only programming contests Web 2.0 platform
Server time: Aug/05/2019 03:51:38^{UTC} (g1).
Desktop version, switch to [mobile version](#).
[Privacy Policy](#).

Supported by



ITMO UNIVERSITY