Name: Abhishek Chaurasiya

Div: D15B / 9

ADV DEVOPS PRACTICAL 10

Aim: To perform Port, Service monitoring, Windows/Linux server monitoring using

Nagios.

Steps:

Prerequisites: AWS Free Tier, Nagios Server running on Amazon Linux Machine.

1. To Confirm that Nagios is running **on the server side**, run this *sudo systemctl status nagios* on the "NAGIOS HOST".

```
Starting nagios (via systemctl): [ OK ]

[ec2-user@ip-172-31-44-218 nagios-plugins-2.0.3]$ sudo systemctl status nagios
• nagios.service - LSB: Starts and stops the Nagios monitoring server

Loaded: loaded (/etc/rc.d/init.d/nagios; generated)

Active: active (running) since Sat 2024-10-12 09:59:46 UTC; 51s ago

Docs: man:systemd-sysv-generator(8)

Process: 66468 ExecStart=/etc/rc.d/init.d/nagios start (code=exited, status=0/SUCCESS)

Tasks: 6 (limit: 1112)

Memory: 2.1M

CPU: 51ms

CGroup: /system.slice/nagios.service


-66490 /usr/local/nagios/bin/nagios -d /usr/local/nagios/etc/nagios.cfg
-66492 /usr/local/nagios/bin/nagios --worker /usr/local/nagios/var/rw/nagios.qh
-66493 /usr/local/nagios/bin/nagios --worker /usr/local/nagios/var/rw/nagios.qh
-66494 /usr/local/nagios/bin/nagios --worker /usr/local/nagios/var/rw/nagios.qh
```

You can proceed if you get this message.

2. Before we begin,

To monitor a Linux machine, create an Ubuntu 20.04 server EC2 Instance in AWS.

Provide it with the same security group as the Nagios Host and name it 'linux-client' alongside the host.



For now, leave this machine as is, and go back to your nagios HOST machine.

3. On the server, run this command

ps -ef | grep nagios

```
Oct 12 10:00:35 ip-172-31-44-218.ec2.internal nagios[66490]: Error: Unable to create temp file '/usr/local/nagios/var/nagios.tmpGAHZhK
     user@ip-172-31-44-218 nagios-plugins-2.0.3]$ ps -ef | grep nagios
                                                                        os/bin/nagios -d /usr/local/nagios/e
os/bin/nagios --worker /usr/local/na
           66490
                                              00:00:00 /usr/local/na
                        1 0 09:59 ?
                                                                                                         ios/etc/nag
           66492
                    66490
                          0 09:59 ?
                                              00:00:00 /usr/local/n
                                                                                                                ios/var/rw/
                                                                                 agios --worker /usr/local/r
           66493
                    66490
                           0 09:59 ?
                                              00:00:00 /usr/local/m
                                                                         s/bin/n
           66494
                    66490
                           0 09:59 ?
                                              00:00:00 /usr/local/na
                                                                         s/bin/n
                                                                                    s --worker /usr/local/
                                                                                  gios --worker /usr/local/ma
                                                                         s/bin/n
           66495
                    66490
                          0 09:59 ?
                                              00:00:00 /usr/local/n
                                                                                  gios -d /usr/local/nagios/etc/nag
           66496
                    66490
                           0 09:59 ?
                                              00:00:00 /usr/local/n
                                                                         s/bin/na
           69105
                     2589 0 10:44 pts/0
                                              00:00:00 grep --color=auto n
  c2-user@ip-172-31-44-218 nagios-plugins-2.0.3]$
```

4. Become a root user and create 2 folders

```
sudo su
mkdir /usr/local/nagios/etc/objects/monitorhosts
mkdir /usr/local/nagios/etc/objects/monitorhosts/linuxhosts
```

- 5. Copy the sample localhost.cfg file to linuxhost folder
- cp /usr/local/nagios/etc/objects/localhost.cfg
 /usr/local/nagios/etc/objects/monitorhosts/linuxhosts/linuxserver.cfg6.

Open linuxserver.cfg using nano and make the following changes

nano

/usr/local/nagios/etc/objects/monitorhosts/linuxhosts/linuxserver.cfg

Change the hostname to linux server (EVERYWHERE ON THE FILE) Change address to the public IP address of your LINUX CLIENT.

Change hostgroup_name under hostgroup to linux-servers1

Everywhere else on the file, change the hostname to linuxserver instead of localhost.

7. Open the Nagios Config file and add the following line nano /usr/local/nagios/etc/nagios.cfg

##Add this line
cfg_dir=/usr/local/nagios/etc/objects/monitorhosts/

```
# EXPERIMENTAL load controlling options
# To get current defaults based on your system issue a command to
# the query handler. Please note that this is an experimental feature
# and not meant for production use. Used incorrectly it can induce
# enormous latency.
# foore loadctl
# jobs_max - The maximum amount of jobs to run at one time
# jobs min - The minimum amount of jobs the current load lets us run
# backoff_limit - The minimum backoff_change
# backoff_change - # of jobs to remove from jobs_limit when backing off
# rampup_limit - Minimum rampup_change
# rampup_change - # of jobs to add to jobs_limit when ramping up
# NOTE: The backoff_limit and rampup_limit are NOT used by anything currently,
# so if your system is under load nothing will actively modify the jobs
# even if you have these options enabled, they are for external
# connector information only. However, if you change the jobs_max or
# jobs_min manually here or through the query handler interface that
# WILL affect your system
#loadctl options=jobs_max=100;backoff_limit=10;rampup_change=5

cfg_dir=/usr/local/nagios/etc/objects/monitorhosts/

**G Help **O Write Out **O Where Is **C Cut **O Execute **O Location **O Cot Current **O Current **O Cot Current **O Cot Current **O Current **O Cot Current **O Current *
```

8. Verify the configuration files

```
Checking for circular paths...

Checked 2 hosts

Checked 8 service dependencies

Checked 0 host dependencies

Checked 5 timeperiods

Checking global event handlers...

Checking obsessive compulsive processor commands...

Checking misc settings...

Total Warmings: 0

Total Errors: 0

Things look okay - No serious problems were detected during the pre-flight check

[root@ip-172-31-46-218 ec2-user]# |
```

You are good to go if there are no errors.

9. Restart the nagios service

service nagios restart

```
Starting nagios (via systemctl): [ OK ]

[ec2-user@ip-172-31-44-218 nagios-plugins-2.0.3]$ sudo systemctl status nagios

• nagios.service - LSB: Starts and stops the Nagios monitoring server

Loaded: loaded (/etc/rc.d/init.d/nagios; generated)

Active: active (running) since Sat 2024-10-12 09:59:46 UTC; 51s ago

Docs: man:systemd-sysv-generator(8)

Process: 66468 Execstart=/etc/rc.d/init.d/nagios start (code=exited, status=0/SUCCESS)

Tasks: 6 (limit: 1112)

Memory: 2.1M

CPU: 51ms

CGroup: /system.slice/nagios.service

-66490 /usr/local/nagios/bin/nagios -d /usr/local/nagios/etc/nagios.cfg
-66492 /usr/local/nagios/bin/nagios --worker /usr/local/nagios/var/rw/nagios.qh
-66493 /usr/local/nagios/bin/nagios --worker /usr/local/nagios/var/rw/nagios.qh
-66494 /usr/local/nagios/bin/nagios --worker /usr/local/nagios/var/rw/nagios.qh
```

Now it is time to switch to the client machine.

10. SSH into the machine or simply use the EC2 Instance Connect feature

```
≥ ubuntu@ip-172-31-32-54:- × + ∨
ubuntu@ip-172-31-32-54:~$
```

11. Make a package index update and install gcc, nagios-nrpe-server and the plugins.

```
sudo apt update -y
sudo apt install gcc -y
sudo apt install -y nagios-nrpe-server nagios-plugins
```

```
ubuntu@ip-172-31-42-197:~$ sudo apt update -y
apt install gcc -y
sudo apt install -y nagios-nrpe-server nagios-plugins
sudo apt install gcc -y
sudo apt install -y nagios-nrpe-server nagios-plugins
Hit:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble InRelease
Get:2 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates InRelease [126 kB]
Get:3 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-backports InRelease [126 kB]
Get:4 http://security.ubuntu.com/ubuntu noble-security InRelease [126 kB]
Get:5 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/universe amd64 Packages [15.0 MB]
Get:6 http://security.ubuntu.com/ubuntu noble-security/main amd64 Packages [384 kB]
Get:7 http://security.ubuntu.com/ubuntu noble-security/main Translation-en [84.6 kB]
Get:8 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/universe Translation-en [5982 kB]
Get:9 http://security.ubuntu.com/ubuntu noble-security/main amd64 c-n-f Metadata [4708 B]
Get:10 http://security.ubuntu.com/ubuntu noble-security/universe amd64 Packages [278 kB]
Get:11 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/universe amd64 Components [3871 kB]
Get:12 http://security.ubuntu.com/ubuntu noble-security/universe Translation-en [117 kB]
Get:13 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/universe amd64 c-n-f Metadata [301 kB]
Get:14 http://security.ubuntu.com/ubuntu noble-security/universe amd64 Components [8632 B]
Get:15 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/multiverse amd64 Packages [269 kB]
Get:16 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/multiverse Translation-en [118 kB]
Get:17 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/multiverse amd64 Components [35.0 kB]
```

12. Open nrpe.cfg file to make changes.

sudo nano /etc/nagios/nrpe.cfg
Under allowed_hosts, add your nagios host IP address like so

```
GNU nano 4.8

# file to allow only the specified host to connect
# you are running this daemon on.

#

# NOTE: This option is ignored if NRPE is running
allowed_hosts=127.0.0.1,13.233.227.254
```

13. Restart the NRPE server


sudo systemctl restart nagios-nrpe-server

14. Now, check your nagios dashboard and you'll see a new host being added.


Click on Hosts.



Click on linuxserver to see the host details



You can click Services to see all services and ports being monitored.



As you can see, we have our linuxserver up and running. It is showing critical status on HTTP due to permission errors and swap because there is no partition created.

In this case, we have monitored -

Servers: 1 linux server

Services: swap

Ports: 22, 80 (ssh, http)

Processes: User status, Current load, total processes, root partition, etc.

Recommended Cleanup

• Terminate both of your EC-2 instances to avoid charges.

• Delete the security group if you created a new one (it won't affect your bill, you may avoid it)

Conclusion:

Thus, we learned about service monitoring using Nagios and successfully monitored a Linux Server and monitored its different ports and services using Nagios and NRPE.