CAPS.ai Meetings Organizer

Quick Startup & Database Guide | macOS and VS Code | Updated 29 October 2026

1. Open the renamed project

```
cd /Users/abhilekhborah/Desktop/Assigment_1/CAPS_ai
code .
```

If the code command is unavailable, use VS Code > File > Open Folder and select CAPS_ai. Open separate integrated terminals for the commands below.

2. Start local PostgreSQL

```
brew services start postgresql@16
export PATH="$(brew --prefix postgresql@16)/bin:$PATH"
pg_isready -h localhost -p 5432
```

Expected result: localhost:5432 - accepting connections. The local database name remains **SmartMeetDB**; renaming the project did not rename its database.

3. Start the .NET backend - terminal 1

```
cd /Users/abhilekhborah/Desktop/Assigment_1/CAPS_ai
dotnet restore CAPS_ai.slnx
dotnet run --project CAPS_ai.API
```

Keep this terminal running. API: http://localhost:5050/api/meetings
Swagger: http://localhost:5050/swagger/index.html
Do not run dotnet ef database update for normal startup on this existing local database. Its migration history was previously removed. Restore verified matching history before applying future migrations. No migration is required just to rename project folders.

4. Start Angular - terminal 2

```
cd /Users/abhilekhborah/Desktop/Assigment_1/CAPS_ai/CAPS_ai-frontend
npm ci
npm start
```

Open http://localhost:4200. Use npm ci after cloning or dependency changes; for later starts, npm start is normally enough. Use an installed .NET 10 SDK and Node.js 24. Temporary SDK paths under /tmp are not needed.

View Local Database Tables

5. Connect with psql - terminal 3

```
export PATH="$(brew --prefix postgresql@16)/bin:$PATH"
psql -h localhost -p 5432 -d SmartMeetDB
```

This uses your current macOS username as the PostgreSQL role. If your configured role differs, add -U YOUR_USERNAME. The commands here inspect the local database, not the separate Render cloud database.

6. List tables and inspect columns

```
\conninfo
\dt
\d "Meeting"
\d "MeetingAttendees"
\d "MeetingQuestions"
```

The application tables are **Meeting**, **MeetingAttendees**, and **MeetingQuestions**. The old Meetings/Questions names and vote/announcement tables are not the current schema. Migration history may be absent locally; retain it in the cloud database.

7. View records

```
SELECT "MeetingId", "Title", "MeetingCode", "Status"
FROM "Meeting" ORDER BY "MeetingId";

SELECT "UserId", "MeetingId", "Name", "Organization", "Role"
FROM "MeetingAttendees" ORDER BY "UserId";

SELECT "QuestionId", "MeetingId", "UserId",
       "QuestionText", "Status"
FROM "MeetingQuestions" ORDER BY "SubmittedAt", "QuestionId";
```

SQL statements end with a semicolon. Keep double quotes around mixed-case table and column names. These attendee queries omit private token hashes.

```
\x
\pset pager off
\q
```

Use \x to toggle expanded rows, \pset pager off to disable paging, and \q to exit psql. Exiting psql does not stop PostgreSQL.

8. Verify and stop

Create a meeting, open its invitation in another browser session, join as a visitor, and submit a question. Rerun the SQL queries to see the new records. Stop the frontend and backend with Ctrl+C in their terminals.

```
lsof -nP -iTCP:4200 -iTCP:5050 -sTCP:LISTEN
```

The deployed site can be used without starting local servers:
https://caps-ai-meetings-organizer.onrender.com/
It uses a separate cloud database; local psql queries will not show cloud records.