






CS 228 : Logic in Computer Science

Krishna. S



ϵ -NFA





ϵ -NFA





ϵ -NFA



ϵ -NFA



ϵ -NFA




ϵ -NFA and DFA

- ▶ ϵ -close the initial states of the ϵ -NFA to obtain initial state of DFA
- ▶ From a state S , compute $\Delta(S, a)$ and ϵ -close it
- ▶ All states in the DFA are ϵ -closed
- ▶ Final states are those which contain a final state of the ϵ -NFA


Closure under Concatenation

- ▶ Given regular languages L_1, L_2 , is $L_1.L_2$ regular



Closure under Concatenation

- Given regular languages L_1, L_2 , is $L_1.L_2$ regular?



Formulae to Automaton


- ▶ FO-definable \Rightarrow regular
- ▶ Given an FO formula φ , construct a DFA A_φ such that $L(\varphi) = L(A_\varphi)$
- ▶ If $L(A_\varphi) = \emptyset$, then φ is unsatisfiable
- ▶ If $L(A_\varphi) \neq \emptyset$, then φ is satisfiable

FO to Regular Languages

- ▶ Every FO sentence φ over words can be converted into a DFA A_φ such that $L(\varphi) = L(A_\varphi)$.
- ▶ Start with atomic formulae, construct DFA for each of them.
- ▶ Conjunctions, disjunctions, negation of formulae easily handled via union, intersection and complementation of of respective DFA
- ▶ Handling quantifiers?

Atomic Formulae to DFA

- ▶ $Q_a(x)$: All words which have an a . Need to fix a position for x , where a holds.
- ▶ $baab$ satisfies $Q_a(x)$ with assignment $x = 1$ or $x = 2$.
- ▶ Think of this as $\begin{matrix} baab \\ 0010 \end{matrix}$ or $\begin{matrix} baab \\ 0100 \end{matrix}$
- ▶ The first row is over Σ , and the second row captures a possible assignment to x
- ▶ Think of an extended alphabet $\Sigma' = \Sigma \times \{0, 1\}$, and construct an automaton over Σ' .
- ▶ Deterministic, not complete.




Atomic Formulae to DFA : $S(x, y)$

- ▶ bab satisfies $S(x, y)$ with assignment $x = 0$ or $y = 1$ or $x = 1, y = 2$.


- ▶ Think of this as

bab		bab
100	or	010
010		001
- ▶ The first row is over Σ , and the second, third rows capture a possible assignment to x, y
- ▶ Think of an extended alphabet $\Sigma' = \Sigma \times \{0, 1\}^2$, and construct an automaton over Σ' .
- ▶ Deterministic, not complete.



Atomic Formulae to DFA : $x < y$

- *bab* satisfies $x < y$ with assignment $x = 0$ or $y = 1$ or $x = 1, y = 2$ or $x = 0, y = 2$.



Simple Formulae to DFA

- ▶ $x < y \wedge Q_a(y)$
- ▶ $\Sigma' = \Sigma \times \{0, 1\} \times \{0, 1\}$
- ▶ Obtain intersection of DFA for $x < y$ and $Q_a(y)$

