



# **CS 228 : Logic in Computer Science**

Krishna. S

# Free and Bound Variables in MSO

---

- ▶ Free, Bound Variables and Scope same as in FO
- ▶ In a wff  $\varphi = \forall X\psi$  or  $\exists X\psi$  every occurrence of  $X$  in  $\psi$  is bound
- ▶ A sentence is a formula with no free first order and second order variables

# Assignments on $\tau$ -structures

## Assignments

For a  $\tau$ -structure  $\mathcal{A}$ , an assignment over  $\mathcal{A}$  is a pair of functions  $(\alpha_1, \alpha_2)$ , where

- ▶  $\alpha_1 : \mathcal{V}_1 \rightarrow u(\mathcal{A})$  assigns every first order variable  $x \in \mathcal{V}_1$  a value  $\alpha_1(x) \in u(\mathcal{A})$ . If  $t$  is a constant symbol  $c$ , then  $\alpha_1(t)$  is  $c^{\mathcal{A}}$ .
- ▶  $\alpha_2 : \mathcal{V}_2 \rightarrow 2^{u(\mathcal{A})}$  assigns to every second order variable  $X \in \mathcal{V}_2$ ,  $\alpha_2(X) \subseteq u(\mathcal{A})$ .

## Binding on a Variable

For an assignment  $\alpha = (\alpha_1, \alpha_2)$  over  $\mathcal{A}$ , and  $x \in \mathcal{V}_i$ ,  $i = 1, 2$ ,  $\alpha_i[x \mapsto a]$  is the assignment  $\alpha_i[x \mapsto a](y) = \begin{cases} \alpha_i(y), & y \neq x, \\ a, & y = x \end{cases}$

# Satisfaction

---

We define the relation  $\mathcal{A} \models_{\alpha} \varphi$  (read as  $\varphi$  is true in  $\mathcal{A}$  under the assignment  $\alpha$ ) inductively:

- ▶  $\mathcal{A} \not\models_{\alpha} \perp$
- ▶  $\mathcal{A} \models_{\alpha} t_1 = t_2$  iff  $\alpha_1(t_1) = \alpha_1(t_2)$
- ▶  $\mathcal{A} \models_{\alpha} R(t_1, \dots, t_k)$  iff  $(\alpha_1(t_1), \dots, \alpha_1(t_k)) \in R^{\mathcal{A}}$
- ▶  $\mathcal{A} \models_{\alpha} X(t)$  iff  $\alpha_1(t) \in \alpha_2(X)$  (new)
- ▶  $\mathcal{A} \models_{\alpha} (\varphi \rightarrow \psi)$  iff  $\mathcal{A} \not\models_{\alpha} \varphi$  or  $\mathcal{A} \models_{\alpha} \psi$
- ▶  $\mathcal{A} \models_{\alpha} (\forall x)\varphi$  iff for every  $a \in u(\mathcal{A})$ ,  $\mathcal{A} \models_{\alpha[x \mapsto a]} \varphi$
- ▶  $\mathcal{A} \models_{\alpha} (\forall X)\varphi$  iff for every  $S \subseteq u(\mathcal{A})$ ,  $\mathcal{A} \models_{\alpha[X \mapsto S]} \varphi$  (new)

# Examples

---

Recall the signature for the graph structure,  $\tau = \{E\}$

- ▶ The graph is 3-colorable

# Examples

---

Recall the signature for the graph structure,  $\tau = \{E\}$

- ▶ The graph is 3-colorable

$$\exists X \exists Y \exists Z (\forall x [X(x) \vee Y(x) \vee Z(x)] \wedge$$

$$\forall x \forall y [E(x, y) \rightarrow \{\neg(X(x) \wedge X(y)) \wedge \neg(Y(x) \wedge Y(y)) \wedge \neg(Z(x) \wedge Z(y))\}])$$

# Examples

---

Recall the signature for the graph structure,  $\tau = \{E\}$

- ▶ The graph has an independent set of size  $\geq k$

# Examples

---

Recall the signature for the graph structure,  $\tau = \{E\}$

- ▶ The graph has an independent set of size  $\geq k$

$$\exists I \{ \forall x \forall y [ (\neg(x = y) \wedge I(x) \wedge I(y)) \rightarrow \neg E(x, y) ] \wedge$$

$$\exists x_1 \dots x_k [ \bigwedge_{i \neq j} \neg(x_i = x_j) \wedge \bigwedge_i I(x_i) ] \}$$



# Examples

---

Recall the signature  $\tau$  for the word structure,  $\tau = \{Q_a, Q_b, <, S\}$  for  $\Sigma = \{a, b\}$

- ▶ Words of even length

# Examples

---

Recall the signature  $\tau$  for the word structure,  $\tau = \{Q_a, Q_b, <, S\}$  for  $\Sigma = \{a, b\}$

- ▶ Words of even length

$$\exists E \exists O \{ \forall x [(first(x) \rightarrow E(x)) \wedge (last(x) \rightarrow O(x))] \}$$

# Examples

---

Recall the signature  $\tau$  for the word structure,  $\tau = \{Q_a, Q_b, <, S\}$  for  $\Sigma = \{a, b\}$

- Words of even length

$$\exists E \exists O \{ \forall x [(first(x) \rightarrow E(x)) \wedge (last(x) \rightarrow O(x))] \}$$

$$\wedge \forall x [(E(x) \vee O(x)) \wedge \neg(E(x) \wedge O(x))]$$

# Examples

---

Recall the signature  $\tau$  for the word structure,  $\tau = \{Q_a, Q_b, <, S\}$  for  $\Sigma = \{a, b\}$

- Words of even length

$$\exists E \exists O \{ \forall x [(first(x) \rightarrow E(x)) \wedge (last(x) \rightarrow O(x))] \}$$

$$\wedge \forall x [(E(x) \vee O(x)) \wedge \neg(E(x) \wedge O(x))]$$

$$\wedge \forall x \forall y [S(x, y) \wedge O(x) \rightarrow E(y)]$$

$$\wedge \forall x \forall y [S(x, y) \wedge E(x) \rightarrow O(y)] \}$$

## MSO on Words : Satisfiability

# MSO on Words

---

- ▶ Signature  $\tau = (Q_\Sigma, <, S)$ , domain or universe = set of positions of a word
- ▶ MSO over words: Atomic formulae

$$X(x) \mid Q_\Sigma(x) \mid x = y \mid x < y \mid S(x, y)$$

- ▶ Given a MSO sentence  $\varphi$ ,  $L(\varphi)$  defined as usual
- ▶ A language  $L \subseteq \Sigma^*$  is MSO definable iff there is an MSO formula  $\varphi$  such that  $L = L(\varphi)$
- ▶ Given an MSO sentence  $\varphi$ , is it satisfiable/valid?

# MSO Expressiveness

---

- ▶ Clearly,  $FO \subseteq MSO$
- ▶  $MSO = \text{Regular}$