



भारतीय प्रौद्योगिकी संस्थान मुंबई
Indian Institute of Technology Bombay

CS 6001: Game Theory and Algorithmic Mechanism Design

Week 7

Swaprava Nath

Slide preparation acknowledgments: C. R. Pradhit and Adit Akarsh

ज्ञानम् परमम् ध्येयम्

Knowledge is the supreme goal



- ▶ Mechanism Design
- ▶ Revelation Principle
- ▶ Arrow's Impossibility Result
- ▶ Proof of Arrow's Impossibility Result

Mechanism Design (Inverse Game Theory)



The objective/desired are set - the task is to set the rules of the game. Examples : Election, license scarce resource (spectrum, cloud), matching students to universities.

Mechanism Design (Inverse Game Theory)



The objective/desired are set - the task is to set the rules of the game. Examples : Election, license scarce resource (spectrum, cloud), matching students to universities.

General Model

- N : set of players

Mechanism Design (Inverse Game Theory)



The objective/desired are set - the task is to set the rules of the game. Examples : Election, license scarce resource (spectrum, cloud), matching students to universities.

General Model

- N : set of players
- X : set of outcomes, e.g, winner in an election, which resource allocated to whom etc.

Mechanism Design (Inverse Game Theory)



The objective/desired are set - the task is to set the rules of the game. Examples : Election, license scarce resource (spectrum, cloud), matching students to universities.

General Model

- N : set of players
- X : set of outcomes, e.g, winner in an election, which resource allocated to whom etc.
- Θ_i : set of private information of agent i (**type**). A type $\theta_i \in \Theta_i$.

Mechanism Design (Inverse Game Theory)



The objective/desired are set - the task is to set the rules of the game. Examples : Election, license scarce resource (spectrum, cloud), matching students to universities.

General Model

- N : set of players
- X : set of outcomes, e.g, winner in an election, which resource allocated to whom etc.
- Θ_i : set of private information of agent i (**type**). A type $\theta_i \in \Theta_i$.
- The type may manifest in the preferences over the outcomes in different ways

Mechanism Design (Inverse Game Theory)



The objective/desired are set - the task is to set the rules of the game. Examples : Election, license scarce resource (spectrum, cloud), matching students to universities.

General Model

- N : set of players
- X : set of outcomes, e.g, winner in an election, which resource allocated to whom etc.
- Θ_i : set of private information of agent i (**type**). A type $\theta_i \in \Theta_i$.
- The type may manifest in the preferences over the outcomes in different ways
 - ① Ordinal : θ_i defines an ordering over the outcome.



The objective/desired are set - the task is to set the rules of the game. Examples : Election, license scarce resource (spectrum, cloud), matching students to universities.

General Model

- N : set of players
- X : set of outcomes, e.g, winner in an election, which resource allocated to whom etc.
- Θ_i : set of private information of agent i (**type**). A type $\theta_i \in \Theta_i$.
- The type may manifest in the preferences over the outcomes in different ways
 - ① Ordinal : θ_i defines an ordering over the outcome.
 - ② Cardinal : an utility function u_i maps an (outcome, type) pair to real numbers,

Mechanism Design (Inverse Game Theory)



The objective/desired are set - the task is to set the rules of the game. Examples : Election, license scarce resource (spectrum, cloud), matching students to universities.

General Model

- N : set of players
- X : set of outcomes, e.g, winner in an election, which resource allocated to whom etc.
- Θ_i : set of private information of agent i (**type**). A type $\theta_i \in \Theta_i$.
- The type may manifest in the preferences over the outcomes in different ways
 - ① Ordinal : θ_i defines an ordering over the outcome.
 - ② Cardinal : an utility function u_i maps an (outcome, type) pair to real numbers,
 - $u_i : X \times \Theta_i \rightarrow \mathbb{R}$ (private value model)



The objective/desired are set - the task is to set the rules of the game. Examples : Election, license scarce resource (spectrum, cloud), matching students to universities.

General Model

- N : set of players
- X : set of outcomes, e.g, winner in an election, which resource allocated to whom etc.
- Θ_i : set of private information of agent i (**type**). A type $\theta_i \in \Theta_i$.
- The type may manifest in the preferences over the outcomes in different ways
 - ① Ordinal : θ_i defines an ordering over the outcome.
 - ② Cardinal : an utility function u_i maps an (outcome, type) pair to real numbers,
 - $u_i : X \times \Theta_i \rightarrow \mathbb{R}$ (private value model)
 - $u_i : X \times \Theta \rightarrow \mathbb{R}$ (interdependent value model)



Voting

- X is the set of candidates.



Voting

- X is the set of candidates.
- θ_i is a ranking over this candidates, e.g., $\theta_i = (a, b, c)$, i.e., a is preferred more than b which is in turn more preferred than c .



Voting

- X is the set of candidates.
- θ_i is a ranking over this candidates, e.g., $\theta_i = (a, b, c)$, i.e., a is preferred more than b which is in turn more preferred than c .



Voting

- X is the set of candidates.
- θ_i is a ranking over this candidates, e.g., $\theta_i = (a, b, c)$, i.e., a is preferred more than b which is in turn more preferred than c .

Single Object allocation: an outcome is $x = (\underline{a}, \underline{p}) \in X$

- $\underline{a} = (a_1, a_2, \dots, a_n)$, $a_i \in \{0, 1\}$, $\sum_{i \in N} a_i \leq 1$, allocations.



Voting

- X is the set of candidates.
- θ_i is a ranking over this candidates, e.g., $\theta_i = (a, b, c)$, i.e., a is preferred more than b which is in turn more preferred than c .

Single Object allocation: an outcome is $x = (\underline{a}, \underline{p}) \in X$

- $\underline{a} = (a_1, a_2, \dots, a_n)$, $a_i \in \{0, 1\}$, $\sum_{i \in N} a_i \leq 1$, allocations.
- $\underline{p} = (p_1, p_2, \dots, p_n)$, p_i is the payment charged to i .



Voting

- X is the set of candidates.
- θ_i is a ranking over this candidates, e.g., $\theta_i = (a, b, c)$, i.e., a is preferred more than b which is in turn more preferred than c .

Single Object allocation: an outcome is $x = (\underline{a}, \underline{p}) \in X$

- $\underline{a} = (a_1, a_2, \dots, a_n)$, $a_i \in \{0, 1\}$, $\sum_{i \in N} a_i \leq 1$, allocations.
- $\underline{p} = (p_1, p_2, \dots, p_n)$, p_i is the payment charged to i .
- θ_i : value of i for the object.



Voting

- X is the set of candidates.
- θ_i is a ranking over this candidates, e.g., $\theta_i = (a, b, c)$, i.e., a is preferred more than b which is in turn more preferred than c .

Single Object allocation: an outcome is $x = (\underline{a}, \underline{p}) \in X$

- $\underline{a} = (a_1, a_2, \dots, a_n)$, $a_i \in \{0, 1\}$, $\sum_{i \in N} a_i \leq 1$, allocations.
- $\underline{p} = (p_1, p_2, \dots, p_n)$, p_i is the payment charged to i .
- θ_i : value of i for the object.
- $u_i(x, \theta_i) = a_i \theta_i - p_i$



- The designer has an objective and this is captured through a **Social Choice Function (SCF)**.

$$f : \Theta_1 \times \Theta_2 \times \dots \times \Theta_n \rightarrow X$$

Examples



- The designer has an objective and this is captured through a **Social Choice Function (SCF)**.

$$f : \Theta_1 \times \Theta_2 \times \dots \times \Theta_n \rightarrow X$$

Examples

- in voting, if there is a candidate who beats everyone else in pairwise contests the he/she must be chosen as a winner.



- The designer has an objective and this is captured through a **Social Choice Function (SCF)**.

$$f : \Theta_1 \times \Theta_2 \times \dots \times \Theta_n \rightarrow X$$

Examples

- in voting, if there is a candidate who beats everyone else in pairwise contests the he/she must be chosen as a winner.
- in public project choice, where $\theta_i : X \rightarrow \mathbb{R}$, value for each project pick,
 $f(\theta) \in \arg \max_{a \in X} \sum_{i \in N} \theta_i(a)$



- The designer has an objective and this is captured through a **Social Choice Function (SCF)**.

$$f : \Theta_1 \times \Theta_2 \times \dots \times \Theta_n \rightarrow X$$

Examples

- in voting, if there is a candidate who beats everyone else in pairwise contests the he/she must be chosen as a winner.
- in public project choice, where $\theta_i : X \rightarrow \mathbb{R}$, value for each project pick,
 $f(\theta) \in \arg \max_{a \in X} \sum_{i \in N} \theta_i(a)$



- The designer has an objective and this is captured through a **Social Choice Function (SCF)**.

$$f : \Theta_1 \times \Theta_2 \times \dots \times \Theta_n \rightarrow X$$

Examples

- in voting, if there is a candidate who beats everyone else in pairwise contests the he/she must be chosen as a winner.
- in public project choice, where $\theta_i : X \rightarrow \mathbb{R}$, value for each project pick,
 $f(\theta) \in \arg \max_{a \in X} \sum_{i \in N} \theta_i(a)$

Question

How can we create a game where $f(\theta)$ emerges as an outcome of an equilibrium?



- The designer has an objective and this is captured through a **Social Choice Function (SCF)**.

$$f : \Theta_1 \times \Theta_2 \times \dots \times \Theta_n \rightarrow X$$

Examples

- in voting, if there is a candidate who beats everyone else in pairwise contests the he/she must be chosen as a winner.
- in public project choice, where $\theta_i : X \rightarrow \mathbb{R}$, value for each project pick,
 $f(\theta) \in \arg \max_{a \in X} \sum_{i \in N} \theta_i(a)$

Question

How can we create a game where $f(\theta)$ emerges as an outcome of an equilibrium?

Answer: We need mechanisms, but they can be complicated



Definition

An **indirect** mechanism is a collection of message spaces and a decision rule $\langle M_1, M_2, \dots, M_n, g \rangle$

- M_i is the message space of agent i
- $g : M_1 \times M_2 \times \dots \times M_n \rightarrow X$

E.g., equipping every agent with a card deck M_i and asking to pick some m_i .



Definition

An **indirect** mechanism is a collection of message spaces and a decision rule $\langle M_1, M_2, \dots, M_n, g \rangle$

- M_i is the message space of agent i
- $g : M_1 \times M_2 \times \dots \times M_n \rightarrow X$

E.g., equipping every agent with a card deck M_i and asking to pick some m_i . A **direct** mechanism is the same as above with $M_i = \Theta_i, \forall i \in N, g \equiv f$.



Definition

An **indirect** mechanism is a collection of message spaces and a decision rule $\langle M_1, M_2, \dots, M_n, g \rangle$

- M_i is the message space of agent i
- $g : M_1 \times M_2 \times \dots \times M_n \rightarrow X$

E.g., equipping every agent with a card deck M_i and asking to pick some m_i . A **direct** mechanism is the same as above with $M_i = \Theta_i, \forall i \in N, g \equiv f$.

Question

Why these are not so commonplace?



Definition

An **indirect** mechanism is a collection of message spaces and a decision rule $\langle M_1, M_2, \dots, M_n, g \rangle$

- M_i is the message space of agent i
- $g : M_1 \times M_2 \times \dots \times M_n \rightarrow X$

E.g., equipping every agent with a card deck M_i and asking to pick some m_i . A **direct** mechanism is the same as above with $M_i = \Theta_i, \forall i \in N, g \equiv f$.

Question

Why these are not so commonplace?

Answer

Due to a result that will follow.



Definition

In a mechanism $\langle M_1, M_2, \dots, M_n, g \rangle$, a message m_i is **weakly dominant** for player i at θ_i if

$$u_i(g(m_i, \tilde{m}_{-i}), \theta_i) \geq u_i(g(m'_i, \tilde{m}_{-i}), \theta_i), \forall \tilde{m}_{-i}, \forall m'_i$$

All subsequent definitions assume cardinal preferences, however they can be replaced with ordinal, e.g., the above one could be defined as

$$g(m_i, \tilde{m}_{-i}) \succeq_i g(m'_i, \tilde{m}_{-i}), \forall \tilde{m}_{-i}, \forall m'_i$$

Dominant Strategy Implementable (DSI)



Definition

An SCF $f : \Theta \rightarrow X$ is **implemented in dominant strategies** by $\langle M_1, M_2, \dots, M_n, g \rangle$ if

Dominant Strategy Implementable (DSI)



Definition

An SCF $f : \Theta \rightarrow X$ is **implemented in dominant strategies** by $\langle M_1, M_2, \dots, M_n, g \rangle$ if

- \exists message mappings $s_i : \Theta_i \rightarrow M_i$, s.t. $s_i(\theta_i)$ is a dominant strategy for agent i at θ_i , $\forall \theta_i \in \Theta_i$, $\forall i \in N$.

Dominant Strategy Implementable (DSI)



Definition

An SCF $f : \Theta \rightarrow X$ is **implemented in dominant strategies** by $\langle M_1, M_2, \dots, M_n, g \rangle$ if

- \exists message mappings $s_i : \Theta_i \rightarrow M_i$, s.t, $s_i(\theta_i)$ is a dominant strategy for agent i at θ_i , $\forall \theta_i \in \Theta_i$, $\forall i \in N$.
- $g(s_1(\theta_1), \dots, s_n(\theta_n)) = f(\theta)$, $\forall \theta \in \Theta$



Dominant Strategy Implementable (DSI)

Definition

An SCF $f : \Theta \rightarrow X$ is **implemented in dominant strategies** by $\langle M_1, M_2, \dots, M_n, g \rangle$ if

- \exists message mappings $s_i : \Theta_i \rightarrow M_i$, s.t. $s_i(\theta_i)$ is a dominant strategy for agent i at θ_i , $\forall \theta_i \in \Theta_i$, $\forall i \in N$.
- $g(s_1(\theta_1), \dots, s_n(\theta_n)) = f(\theta)$, $\forall \theta \in \Theta$

We call this an indirect implementation, i.e., SCF f is **dominant strategy implementable (DSI)** by $\langle M_1, M_2, \dots, M_n, g \rangle$.

Dominant Strategy Incentive Compatible (DSIC)



Definition

A direct mechanism $\langle \Theta_1, \Theta_2, \dots, \Theta_n, f \rangle$ is **dominant strategy incentive compatible (DSIC)** if

$$u_i(f(\theta_i, \tilde{\theta}_{-i}), \theta_i) \geq u_i(f(\theta'_i, \tilde{\theta}_{-i}), \theta_i), \forall \tilde{\theta}_{-i}, \theta'_i, \theta_i, \forall i \in N$$

Dominant Strategy Incentive Compatible DSIC)



Definition

A direct mechanism $\langle \Theta_1, \Theta_2, \dots, \Theta_n, f \rangle$ is **dominant strategy incentive compatible (DSIC)** if

$$u_i(f(\theta_i, \tilde{\theta}_{-i}), \theta_i) \geq u_i(f(\theta'_i, \tilde{\theta}_{-i}), \theta_i), \forall \tilde{\theta}_{-i}, \theta'_i, \theta_i, \forall i \in N$$

- To find if an SCF f is dominant strategy implementable, we need to search over all possible indirect mechanisms $\langle M_1, M_2, \dots, M_n, g \rangle$.

Dominant Strategy Incentive Compatible (DSIC)



Definition

A direct mechanism $\langle \Theta_1, \Theta_2, \dots, \Theta_n, f \rangle$ is **dominant strategy incentive compatible (DSIC)** if

$$u_i(f(\theta_i, \tilde{\theta}_{-i}), \theta_i) \geq u_i(f(\theta'_i, \tilde{\theta}_{-i}), \theta_i), \forall \tilde{\theta}_{-i}, \theta'_i, \theta_i, \forall i \in N$$

- To find if an SCF f is dominant strategy implementable, we need to search over all possible indirect mechanisms $\langle M_1, M_2, \dots, M_n, g \rangle$.
- But luckily, there is a result that reduces the search space.



- ▶ Mechanism Design
- ▶ Revelation Principle
- ▶ Arrow's Impossibility Result
- ▶ Proof of Arrow's Impossibility Result

Relationship between DSI and DSIC



Revelation Principle (for DSI SCFs)

If there exists an indirect mechanism that implements f in dominant strategies, then f is DSIC.

Relationship between DSI and DSIC



Revelation Principle (for DSI SCFs)

If there exists an indirect mechanism that implements f in dominant strategies, then f is DSIC.

Implication: Can focus on DSIC mechanisms WLOG.

Proof.

Let f is implemented by $\langle M_1, M_2, \dots, M_n, g \rangle$,

Relationship between DSI and DSIC



Revelation Principle (for DSI SCFs)

If there exists an indirect mechanism that implements f in dominant strategies, then f is DSIC.

Implication: Can focus on DSIC mechanisms WLOG.

Proof.

Let f is implemented by $\langle M_1, M_2, \dots, M_n, g \rangle$, hence $\exists s_i : \Theta_i \rightarrow M_i, i \in N$, s.t.,

$$u_i(g(s_i(\theta_i), \tilde{m}_{-i}), \theta_i) \geq u_i(g(m'_i, \tilde{m}_{-i}), \theta_i), \forall m'_i, \tilde{m}_{-i}, \theta_i, \forall i \in N, \text{ and} \quad (1)$$

$$g(s_i(\theta_i), s_{-i}(\theta_{-i})) = f(\theta_i, \theta_{-i}), \forall \theta_i, \theta_{-i} \quad (2)$$

Relationship between DSI and DSIC



Revelation Principle (for DSI SCFs)

If there exists an indirect mechanism that implements f in dominant strategies, then f is DSIC.

Implication: Can focus on DSIC mechanisms WLOG.

Proof.

Let f is implemented by $\langle M_1, M_2, \dots, M_n, g \rangle$, hence $\exists s_i : \Theta_i \rightarrow M_i, i \in N$, s.t.,

$$u_i(g(s_i(\theta_i), \tilde{m}_{-i}), \theta_i) \geq u_i(g(m'_i, \tilde{m}_{-i}), \theta_i), \forall m'_i, \tilde{m}_{-i}, \theta_i, \forall i \in N, \text{ and} \quad (1)$$

$$g(s_i(\theta_i), s_{-i}(\theta_{-i})) = f(\theta_i, \theta_{-i}), \forall \theta_i, \theta_{-i} \quad (2)$$

Eq. (1) holds for all m'_i, \tilde{m}_{-i} , in particular, $m'_i = s_i(\theta'_i), \tilde{m}_{-i} = s_{-i}(\tilde{\theta}_{-i})$ where θ'_i and $\tilde{\theta}_{-i}$ are arbitrary.

Relationship between DSI and DSIC



Revelation Principle (for DSI SCFs)

If there exists an indirect mechanism that implements f in dominant strategies, then f is DSIC.

Implication: Can focus on DSIC mechanisms WLOG.

Proof.

Let f is implemented by $\langle M_1, M_2, \dots, M_n, g \rangle$, hence $\exists s_i : \Theta_i \rightarrow M_i, i \in N$, s.t.,

$$u_i(g(s_i(\theta_i), \tilde{m}_{-i}), \theta_i) \geq u_i(g(m'_i, \tilde{m}_{-i}), \theta_i), \forall m'_i, \tilde{m}_{-i}, \theta_i, \forall i \in N, \text{ and} \quad (1)$$

$$g(s_i(\theta_i), s_{-i}(\theta_{-i})) = f(\theta_i, \theta_{-i}), \forall \theta_i, \theta_{-i} \quad (2)$$

Eq. (1) holds for all m'_i, \tilde{m}_{-i} , in particular, $m'_i = s_i(\theta'_i), \tilde{m}_{-i} = s_{-i}(\tilde{\theta}_{-i})$ where θ'_i and $\tilde{\theta}_{-i}$ are arbitrary. Hence,

$$u_i(\underbrace{g(s_i(\theta_i), s_{-i}(\tilde{\theta}_{-i}))}_{=f(\theta_i, \tilde{\theta}_{-i})}, \theta_i) \geq u_i(\underbrace{g(s_i(\theta'_i), s_{-i}(\tilde{\theta}_{-i}))}_{=f(\theta'_i, \tilde{\theta}_{-i})}, \theta_i)$$

$\Rightarrow f$ is DSIC.





- Agents may have probabilistic information about other's types.



- Agents may have probabilistic information about other's types.
- Types are generated from a common prior (common knowledge) and are revealed only to the respective agents.



- Agents may have probabilistic information about other's types.
- Types are generated from a common prior (common knowledge) and are revealed only to the respective agents.
- Recall : Bayesian games $\langle N, (M_i)_{i \in N}, (\Theta_i)_{i \in N}, P, (\Gamma_\theta)_{\theta \in \Theta} \rangle$



Definition

An **indirect** mechanism $\langle M_1, M_2, \dots, M_n, g \rangle$ **implements an SCF f in Bayesian strategies** if



Bayesian extension

Definition

An **indirect** mechanism $\langle M_1, M_2, \dots, M_n, g \rangle$ **implements an SCF f in Bayesian strategies** if

- \exists a message mapping profile (s_1, \dots, s_n) , s.t., $s_i(\theta_i)$ maximizes the ex-interim utility of every agent, i.e.,

$$\mathbb{E}_{\theta_{-i}|\theta_i}[u_i(g(s_i(\theta_i), s_{-i}(\theta_{-i})), \theta_i)] \geq \mathbb{E}_{\theta_{-i}|\theta_i}[u_i(g(m'_i, s_{-i}(\theta_{-i})), \theta_i)] \quad \forall m'_i, \theta_i, \forall i \in N$$

Expectations are taken w.r.t. a common prior P



Bayesian extension

Definition

An **indirect** mechanism $\langle M_1, M_2, \dots, M_n, g \rangle$ **implements an SCF f in Bayesian strategies** if

- \exists a message mapping profile (s_1, \dots, s_n) , s.t., $s_i(\theta_i)$ maximizes the ex-interim utility of every agent, i.e.,

$$\mathbb{E}_{\theta_{-i}|\theta_i}[u_i(g(s_i(\theta_i), s_{-i}(\theta_{-i})), \theta_i)] \geq \mathbb{E}_{\theta_{-i}|\theta_i}[u_i(g(m'_i, s_{-i}(\theta_{-i})), \theta_i)] \quad \forall m'_i, \theta_i, \forall i \in N$$

Expectations are taken w.r.t. a common prior P

- $g(s_i(\theta_i), s_{-i}(\theta_{-i})) = f(\theta_i, \theta_{-i}), \forall \theta$



Bayesian extension

Definition

An **indirect** mechanism $\langle M_1, M_2, \dots, M_n, g \rangle$ **implements an SCF f in Bayesian strategies** if

- \exists a message mapping profile (s_1, \dots, s_n) , s.t., $s_i(\theta_i)$ maximizes the ex-interim utility of every agent, i.e.,

$$\mathbb{E}_{\theta_{-i}|\theta_i}[u_i(g(s_i(\theta_i), s_{-i}(\theta_{-i})), \theta_i)] \geq \mathbb{E}_{\theta_{-i}|\theta_i}[u_i(g(m'_i, s_{-i}(\theta_{-i})), \theta_i)] \quad \forall m'_i, \theta_i, \forall i \in N$$

Expectations are taken w.r.t. a common prior P

- $g(s_i(\theta_i), s_{-i}(\theta_{-i})) = f(\theta_i, \theta_{-i}), \forall \theta$

We call f is Bayesian implementable via $\langle M_1, M_2, \dots, M_n, g \rangle$ under a common prior P .



Bayesian extension

Definition

An **indirect** mechanism $\langle M_1, M_2, \dots, M_n, g \rangle$ **implements an SCF f in Bayesian strategies** if

- \exists a message mapping profile (s_1, \dots, s_n) , s.t., $s_i(\theta_i)$ maximizes the ex-interim utility of every agent, i.e.,

$$\mathbb{E}_{\theta_{-i}|\theta_i}[u_i(g(s_i(\theta_i), s_{-i}(\theta_{-i})), \theta_i)] \geq \mathbb{E}_{\theta_{-i}|\theta_i}[u_i(g(m'_i, s_{-i}(\theta_{-i})), \theta_i)] \quad \forall m'_i, \theta_i, \forall i \in N$$

Expectations are taken w.r.t. a common prior P

- $g(s_i(\theta_i), s_{-i}(\theta_{-i})) = f(\theta_i, \theta_{-i}), \forall \theta$

We call f is Bayesian implementable via $\langle M_1, M_2, \dots, M_n, g \rangle$ under a common prior P .

Observation: If an SCF f dominant strategy implementable, then it is Bayesian implementable.



Definition

A direct mechanism $\langle \Theta_1, \Theta_2, \dots, \Theta_n, f \rangle$ is **Bayesian Incentive Compatible (BIC)** if

$$\mathbb{E}_{\theta_{-i}|\theta_i}[u_i(f(\theta_i, \theta_{-i}), \theta_{-i}), \theta_i] \geq \mathbb{E}_{\theta_{-i}|\theta_i}[u_i(f(\theta'_i, \theta_{-i}), \theta_{-i}), \theta_i], \forall \theta_i, \theta'_i, \forall i \in N$$

Revelation Principle for Bayesian Implementable SCFs



Revelation Principle (for Bayesian implementable SCFs)

If an SCF f is implementable in Bayesian equilibrium, then f is BIC.

- Proof idea is similar to the DSI, with expected utilities at appropriate places.
- For truthfulness of these two kinds, we will only consider incentive compatibility.
- These results hold even for ordinal preferences and mechanisms.
- Detailed proof: homework



- ▶ Mechanism Design
- ▶ Revelation Principle
- ▶ Arrow's Impossibility Result
- ▶ Proof of Arrow's Impossibility Result

Arrow's Social Welfare Function Setup



Question

Ignoring the truthful revelation for a moment, can we reasonably aggregate opinions for a general setup?

Objective: create **social preferences** from **individual preferences**

Arrow's Social Welfare Function Setup



Question

Ignoring the truthful revelation for a moment, can we reasonably aggregate opinions for a general setup?

Objective: create **social preferences** from **individual preferences**

- Finite set of alternatives $A = \{a_1, a_2, \dots, a_m\}$

Arrow's Social Welfare Function Setup



Question

Ignoring the truthful revelation for a moment, can we reasonably aggregate opinions for a general setup?

Objective: create **social preferences** from **individual preferences**

- Finite set of alternatives $A = \{a_1, a_2, \dots, a_m\}$
- Finite set of players $N = \{1, 2, \dots, n\}$



Arrow's Social Welfare Function Setup

Question

Ignoring the truthful revelation for a moment, can we reasonably aggregate opinions for a general setup?

Objective: create **social preferences** from **individual preferences**

- Finite set of alternatives $A = \{a_1, a_2, \dots, a_m\}$
- Finite set of players $N = \{1, 2, \dots, n\}$
- Each player i has a **preference relation** R_i over A (A binary relation over A , $aR_i b$ means alternative a is at least as good as b to i)



Arrow's Social Welfare Function Setup

Question

Ignoring the truthful revelation for a moment, can we reasonably aggregate opinions for a general setup?

Objective: create **social preferences** from **individual preferences**

- Finite set of alternatives $A = \{a_1, a_2, \dots, a_m\}$
- Finite set of players $N = \{1, 2, \dots, n\}$
- Each player i has a **preference relation** R_i over A (A binary relation over A , aR_ib means alternative a is at least as good as b to i)
- Properties of R_i

Arrow's Social Welfare Function Setup



Question

Ignoring the truthful revelation for a moment, can we reasonably aggregate opinions for a general setup?

Objective: create **social preferences** from **individual preferences**

- Finite set of alternatives $A = \{a_1, a_2, \dots, a_m\}$
- Finite set of players $N = \{1, 2, \dots, n\}$
- Each player i has a **preference relation** R_i over A (A binary relation over A , aR_ib means alternative a is at least as good as b to i)
- Properties of R_i
 - ① **Completeness:** for every pair of alternatives $a, b \in A$, either aR_ib or bR_ia or both



Arrow's Social Welfare Function Setup

Question

Ignoring the truthful revelation for a moment, can we reasonably aggregate opinions for a general setup?

Objective: create **social preferences** from **individual preferences**

- Finite set of alternatives $A = \{a_1, a_2, \dots, a_m\}$
- Finite set of players $N = \{1, 2, \dots, n\}$
- Each player i has a **preference relation** R_i over A (A binary relation over A , $aR_i b$ means alternative a is at least as good as b to i)
- Properties of R_i
 - 1 **Completeness:** for every pair of alternatives $a, b \in A$, either $aR_i b$ or $bR_i a$ or both
 - 2 **Reflexivity:** $\forall a \in A, aR_i a$



Arrow's Social Welfare Function Setup

Question

Ignoring the truthful revelation for a moment, can we reasonably aggregate opinions for a general setup?

Objective: create **social preferences** from **individual preferences**

- Finite set of alternatives $A = \{a_1, a_2, \dots, a_m\}$
- Finite set of players $N = \{1, 2, \dots, n\}$
- Each player i has a **preference relation** R_i over A (A binary relation over A , aR_ib means alternative a is at least as good as b to i)
- Properties of R_i
 - 1 **Completeness:** for every pair of alternatives $a, b \in A$, either aR_ib or bR_ia or both
 - 2 **Reflexivity:** $\forall a \in A, aR_ia$
 - 3 **Transitivity:** if aR_ib and bR_ic , then aR_ic , $\forall a, b, c \in A$ and $i \in N$

Arrow's Social Welfare Function Setup



- Set of all **preference ordering** is denoted by \mathcal{R} (the three previous properties make a relation induce an ordering)

Arrow's Social Welfare Function Setup



- Set of all **preference ordering** is denoted by \mathcal{R} (the three previous properties make a relation induce an ordering)
- An ordering R_i is **linear** if for every $a, b \in A$ s.t. aR_ib and bR_ia implies $a = b$ (**Antisymmetric**)

Arrow's Social Welfare Function Setup



- Set of all **preference ordering** is denoted by \mathcal{R} (the three previous properties make a relation induce an ordering)
- An ordering R_i is **linear** if for every $a, b \in A$ s.t. $aR_i b$ and $bR_i a$ implies $a = b$ (**Antisymmetric**)
- Set of all **linear** preference ordering is denoted by \mathcal{P}



Arrow's Social Welfare Function Setup

- Set of all **preference ordering** is denoted by \mathcal{R} (the three previous properties make a relation induce an ordering)
- An ordering R_i is **linear** if for every $a, b \in A$ s.t. $aR_i b$ and $bR_i a$ implies $a = b$ (**Antisymmetric**)
- Set of all **linear** preference ordering is denoted by \mathcal{P}
- Any arbitrary ordering R_i can be decomposed into its



Arrow's Social Welfare Function Setup

- Set of all **preference ordering** is denoted by \mathcal{R} (the three previous properties make a relation induce an ordering)
- An ordering R_i is **linear** if for every $a, b \in A$ s.t. aR_ib and bR_ia implies $a = b$ (**Antisymmetric**)
- Set of all **linear** preference ordering is denoted by \mathcal{P}
- Any arbitrary ordering R_i can be decomposed into its
 - **asymmetric** part P_i



Arrow's Social Welfare Function Setup

- Set of all **preference ordering** is denoted by \mathcal{R} (the three previous properties make a relation induce an ordering)
- An ordering R_i is **linear** if for every $a, b \in A$ s.t. aR_ib and bR_ia implies $a = b$ (**Antisymmetric**)
- Set of all **linear** preference ordering is denoted by \mathcal{P}
- Any arbitrary ordering R_i can be decomposed into its
 - Ⓐ **asymmetric** part P_i
 - Ⓑ **symmetric** part I_i



Arrow's Social Welfare Function Setup

- Set of all **preference ordering** is denoted by \mathcal{R} (the three previous properties make a relation induce an ordering)
- An ordering R_i is **linear** if for every $a, b \in A$ s.t. aR_ib and bR_ia implies $a = b$ (**Antisymmetric**)
- Set of all **linear** preference ordering is denoted by \mathcal{P}
- Any arbitrary ordering R_i can be decomposed into its
 - Ⓐ **asymmetric** part P_i
 - Ⓑ **symmetric** part I_i
- Example:

$$R_i = \begin{bmatrix} a \\ b, c \\ d \end{bmatrix} = \{(a, b), (a, c), (a, d), (b, c), (c, b), (b, d), (c, d)\}$$
$$\Rightarrow P_i = \begin{bmatrix} a & a \\ b & c \\ d & d \end{bmatrix} = \{(a, b), (a, c), (a, d), (b, d), (c, d)\}, \quad I_i = \{(b, c), (c, b)\}$$

Arrovian Social Welfare Function (ASWF)



$F : \mathcal{R}^n \rightarrow \mathcal{R}$ domain and co-domain are both rankings

- Motivation: the function F captures the collective ordering of the society, if the most preferred is not feasible, the society can move to the next and so on

Arrovian Social Welfare Function (ASWF)



$F : \mathcal{R}^n \rightarrow \mathcal{R}$ domain and co-domain are both rankings

- Motivation: the function F captures the collective ordering of the society, if the most preferred is not feasible, the society can move to the next and so on
- $F(R) = F(R_1, R_2, \dots, R_n)$ is an ordering over the alternatives

Arrovian Social Welfare Function (ASWF)



$F : \mathcal{R}^n \rightarrow \mathcal{R}$ domain and co-domain are both rankings

- Motivation: the function F captures the collective ordering of the society, if the most preferred is not feasible, the society can move to the next and so on
- $F(R) = F(R_1, R_2, \dots, R_n)$ is an ordering over the alternatives
- $\hat{F}(R)$ is the **asymmetric** part of $F(R)$

Arrovian Social Welfare Function (ASWF)



$F : \mathcal{R}^n \rightarrow \mathcal{R}$ domain and co-domain are both rankings

- Motivation: the function F captures the collective ordering of the society, if the most preferred is not feasible, the society can move to the next and so on
- $F(R) = F(R_1, R_2, \dots, R_n)$ is an ordering over the alternatives
- $\hat{F}(R)$ is the **asymmetric** part of $F(R)$
- $\bar{F}(R)$ is the **symmetric** part of $F(R)$



Definition (Weak Pareto)

An ASWF F satisfies **weak Pareto** if the following holds for all $a, b \in A$ and for every strict preference profile R :

$$[aP_i b, \forall i \in N] \implies [a\hat{F}(R)b].$$

(Read as: whenever the LHS (the 'if' part) holds, the RHS holds as well)



Definition (Weak Pareto)

An ASWF F satisfies **weak Pareto** if the following holds for all $a, b \in A$ and for every strict preference profile R :

$$[aP_ib, \forall i \in N] \implies [a\hat{F}(R)b].$$

(Read as: whenever the LHS (the 'if' part) holds, the RHS holds as well)

Important: there can be P 's where the 'if' condition does not hold, then the implication is **vacuously** true, and therefore $\hat{F}(R)$ can have any order over those alternatives



Pareto or Unanimity

Definition (Weak Pareto)

An ASWF F satisfies **weak Pareto** if the following holds for all $a, b \in A$ and for every strict preference profile R :

$$[aP_ib, \forall i \in N] \implies [a\hat{F}(R)b].$$

(Read as: whenever the LHS (the 'if' part) holds, the RHS holds as well)

Important: there can be P 's where the 'if' condition does not hold, then the implication is **vacuously** true, and therefore $\hat{F}(R)$ can have any order over those alternatives

Definition (Strong Pareto)

An ASWF F satisfies **strong Pareto** if the following holds for all $a, b \in A$ and for every preference profile R :

$$[aR_ib, \forall i \in N \text{ and } aP_jb, \text{ for some } j \in N] \implies [a\hat{F}(R)b].$$



Pareto or Unanimity

Definition (Weak Pareto)

An ASWF F satisfies **weak Pareto** if the following holds for all $a, b \in A$ and for every strict preference profile R :

$$[aP_ib, \forall i \in N] \implies [a\hat{F}(R)b].$$

(Read as: whenever the LHS (the 'if' part) holds, the RHS holds as well)

Important: there can be P 's where the 'if' condition does not hold, then the implication is **vacuously** true, and therefore $\hat{F}(R)$ can have any order over those alternatives

Definition (Strong Pareto)

An ASWF F satisfies **strong Pareto** if the following holds for all $a, b \in A$ and for every preference profile R :

$$[aR_ib, \forall i \in N \text{ and } aP_jb, \text{ for some } j \in N] \implies [a\hat{F}(R)b].$$

Which property implies the other?

Independence of Irrelevant Alternatives



- We say $R_i, R'_i \in \mathcal{R}$ **agree** on $\{a, b\}$ for agent i if

$$aP_ib \Leftrightarrow aP'_ib, bP_ia \Leftrightarrow bP'_ia, aI_ib \Leftrightarrow aI'_ib$$

Independence of Irrelevant Alternatives



- We say $R_i, R'_i \in \mathcal{R}$ **agree** on $\{a, b\}$ for agent i if

$$aP_ib \Leftrightarrow aP'_ib, bP_ia \Leftrightarrow bP'_ia, aI_ib \Leftrightarrow aI'_ib$$

- We use the shorthand $R_i|_{a,b} = R'_i|_{a,b}$ to denote this for agent i

Independence of Irrelevant Alternatives



- We say $R_i, R'_i \in \mathcal{R}$ **agree** on $\{a, b\}$ for agent i if

$$aP_ib \Leftrightarrow aP'_ib, bP_ia \Leftrightarrow bP'_ia, aI_ib \Leftrightarrow aI'_ib$$

- We use the shorthand $R_i|_{a,b} = R'_i|_{a,b}$ to denote this for agent i
- If this holds for every $i \in N$, $R|_{a,b} = R'|_{a,b}$

Independence of Irrelevant Alternatives



- We say $R_i, R'_i \in \mathcal{R}$ **agree** on $\{a, b\}$ for agent i if

$$aP_ib \Leftrightarrow aP'_ib, bP_ia \Leftrightarrow bP'_ia, aI_ib \Leftrightarrow aI'_ib$$

- We use the shorthand $R_i|_{a,b} = R'_i|_{a,b}$ to denote this for agent i
- If this holds for every $i \in N$, $R|_{a,b} = R'|_{a,b}$



Independence of Irrelevant Alternatives

- We say $R_i, R'_i \in \mathcal{R}$ **agree** on $\{a, b\}$ for agent i if

$$aP_ib \Leftrightarrow aP'_ib, bP_ia \Leftrightarrow bP'_ia, aI_ib \Leftrightarrow aI'_ib$$

- We use the shorthand $R_i|_{a,b} = R'_i|_{a,b}$ to denote this for agent i
- If this holds for every $i \in N$, $R|_{a,b} = R'|_{a,b}$

Definition (Independence of Irrelevant Alternatives)

An ASWF F satisfies **independence of irrelevant alternatives** (IIA) if for all $a, b \in A$, and for every pair of preference profiles R and R' , if $R|_{a,b} = R'|_{a,b}$, then $F(R)|_{a,b} = F(R')|_{a,b}$.



Independence of Irrelevant Alternatives

- We say $R_i, R'_i \in \mathcal{R}$ **agree** on $\{a, b\}$ for agent i if

$$aP_ib \Leftrightarrow aP'_ib, bP_ia \Leftrightarrow bP'_ia, aI_ib \Leftrightarrow aI'_ib$$

- We use the shorthand $R_i|_{a,b} = R'_i|_{a,b}$ to denote this for agent i
- If this holds for every $i \in N$, $R|_{a,b} = R'|_{a,b}$

Definition (Independence of Irrelevant Alternatives)

An ASWF F satisfies **independence of irrelevant alternatives** (IIA) if for all $a, b \in A$, and for every pair of preference profiles R and R' , if $R|_{a,b} = R'|_{a,b}$, then $F(R)|_{a,b} = F(R')|_{a,b}$.

If the relative positions of two alternatives are the same in two different preference profiles, then the aggregate should also match the relative positions of those two alternatives

Example



If the relative positions of two alternatives are the same in two different preference profiles, then the aggregate should also match the relative positions of those two alternatives

R				R'			
a	a	c	d	d	c	b	b
b	c	b	c	a	a	c	a
c	b	a	b	b	b	a	d
d	d	d	a	c	d	d	c

Example



If the relative positions of two alternatives are the same in two different preference profiles, then the aggregate should also match the relative positions of those two alternatives

R				R'			
a	a	c	d	d	c	b	b
b	c	b	c	a	a	c	a
c	b	a	b	b	b	a	d
d	d	d	a	c	d	d	c

- IIA says $F(R)|_{a,b} = F(R')|_{a,b}$



Example

If the relative positions of two alternatives are the same in two different preference profiles, then the aggregate should also match the relative positions of those two alternatives

R				R'			
a	a	c	d	d	c	b	b
b	c	b	c	a	a	c	a
c	b	a	b	b	b	a	d
d	d	d	a	c	d	d	c

- IIA says $F(R)|_{a,b} = F(R')|_{a,b}$
- Simple aggregation rules, e.g., **scoring rules**: each position of each agent gets a score $(s_1, s_2, \dots, s_m), s_i \geq s_{i+1}, i = 1, 2, \dots, m-1$, the final ordering is in the decreasing order of the scores



Example

If the relative positions of two alternatives are the same in two different preference profiles, then the aggregate should also match the relative positions of those two alternatives

R				R'			
a	a	c	d	d	c	b	b
b	c	b	c	a	a	c	a
c	b	a	b	b	b	a	d
d	d	d	a	c	d	d	c

- IIA says $F(R)|_{a,b} = F(R')|_{a,b}$
- Simple aggregation rules, e.g., **scoring rules**: each position of each agent gets a score $(s_1, s_2, \dots, s_m), s_i \geq s_{i+1}, i = 1, 2, \dots, m-1$, the final ordering is in the decreasing order of the scores
- One special scoring rule: **plurality**, $s_1 = 1, s_i = 0, i = 2, \dots, m$.

Satisfaction of IIA



Question

Does plurality satisfy IIA?

R			
a	a	c	d
b	c	b	c
c	b	a	b
d	d	d	a

R'			
d	c	b	b
a	a	c	a
b	b	a	d
c	d	d	c

Satisfaction of IIA



Question

Does plurality satisfy IIA?

R			
a	a	c	d
b	c	b	c
c	b	a	b
d	d	d	a

R'			
d	c	b	b
a	a	c	a
b	b	a	d
c	d	d	c

Check: $aF_{\text{plu}}(R)b$, but $bF_{\text{plu}}(R')a$, even though $R|_{a,b} = R'|_{a,b}$

Satisfaction of IIA



Question

Does plurality satisfy IIA?

R				R'			
a	a	c	d	d	c	b	b
b	c	b	c	a	a	c	a
c	b	a	b	b	b	a	d
d	d	d	a	c	d	d	c

Check: $aF_{\text{plu}}(R)b$, but $bF_{\text{plu}}(R')a$, even though $R|_{a,b} = R'|_{a,b}$

Question

Does **dictatorship** satisfy IIA?

A **dictatorship** ASWF is where there exists a pre-determined agent d and $F^d(R) = R_d$

Arrow's impossibility result



Theorem (Arrow 1951)

For $|A| \geq 3$, if an ASWF F satisfies WP and IIA, then it must be dictatorial.

Arrow's impossibility result



Theorem (Arrow 1951)

For $|A| \geq 3$, if an ASWF F satisfies WP and IIA, then it must be dictatorial.

We cannot aggregate reasonably even when there is no truthfulness constraint



- ▶ Mechanism Design
- ▶ Revelation Principle
- ▶ Arrow's Impossibility Result
- ▶ Proof of Arrow's Impossibility Result



Definition

Let $F : \mathcal{R}^n \rightarrow \mathcal{R}$ be given, $G \subseteq N, G \neq \emptyset$.



Definition

Let $F : \mathcal{R}^n \rightarrow \mathcal{R}$ be given, $G \subseteq N, G \neq \emptyset$.

① G is **almost decisive** over $\{a, b\}$ if for every R :

$$[aP_ib, \forall i \in G, \quad bP_ja, \forall j \in N \setminus G] \implies [a\hat{F}(R)b].$$



Definition

Let $F : \mathcal{R}^n \rightarrow \mathcal{R}$ be given, $G \subseteq N, G \neq \emptyset$.

① G is **almost decisive** over $\{a, b\}$ if for every R :

$$[aP_ib, \forall i \in G, \quad bP_ja, \forall j \in N \setminus G] \implies [a\hat{F}(R)b].$$

We will write this with the shorthand $\overline{D}_G(a, b)$: “ G is almost decisive over $\{a, b\}$ w.r.t. F ”.



Definition

Let $F : \mathcal{R}^n \rightarrow \mathcal{R}$ be given, $G \subseteq N, G \neq \emptyset$.

- ① G is **almost decisive** over $\{a, b\}$ if for every R :

$$[aP_ib, \forall i \in G, \quad bP_ja, \forall j \in N \setminus G] \implies [a\hat{F}(R)b].$$

We will write this with the shorthand $\overline{D}_G(a, b)$: “ G is almost decisive over $\{a, b\}$ w.r.t. F ”.

- ② G is **decisive** over $\{a, b\}$ if for every R :

$$[aP_ib, \forall i \in G] \implies [a\hat{F}(R)b].$$



Definition

Let $F : \mathcal{R}^n \rightarrow \mathcal{R}$ be given, $G \subseteq N, G \neq \emptyset$.

- ① G is **almost decisive** over $\{a, b\}$ if for every R :

$$[aP_i b, \forall i \in G, \quad bP_j a, \forall j \in N \setminus G] \implies [a\hat{F}(R)b].$$

We will write this with the shorthand $\overline{D}_G(a, b)$: “ G is almost decisive over $\{a, b\}$ w.r.t. F ”.

- ② G is **decisive** over $\{a, b\}$ if for every R :

$$[aP_i b, \forall i \in G] \implies [a\hat{F}(R)b].$$

We will write this with the shorthand $D_G(a, b)$: “ G is decisive over $\{a, b\}$ w.r.t. F ”.



Definition

Let $F : \mathcal{R}^n \rightarrow \mathcal{R}$ be given, $G \subseteq N, G \neq \emptyset$.

- ① G is **almost decisive** over $\{a, b\}$ if for every R :

$$[aP_ib, \forall i \in G, \quad bP_ja, \forall j \in N \setminus G] \implies [a\hat{F}(R)b].$$

We will write this with the shorthand $\overline{D}_G(a, b)$: “ G is almost decisive over $\{a, b\}$ w.r.t. F ”.

- ② G is **decisive** over $\{a, b\}$ if for every R :

$$[aP_ib, \forall i \in G] \implies [a\hat{F}(R)b].$$

We will write this with the shorthand $D_G(a, b)$: “ G is decisive over $\{a, b\}$ w.r.t. F ”.

Observation: $D_G(a, b) \implies \overline{D}_G(a, b)$

Proof of Arrow's theorem



The proof proceeds in two parts:

Proof of Arrow's theorem



The proof proceeds in two parts:

Part 1 Field expansion lemma: If a group is **almost decisive** over a pair of alternatives, it is **decisive** over all pairs of alternatives

Proof of Arrow's theorem



The proof proceeds in two parts:

Part 1 Field expansion lemma: If a group is **almost decisive** over a pair of alternatives, it is **decisive** over all pairs of alternatives

Part 2 Group contraction lemma: If a group is decisive, then a strict non-empty subset of that group is also decisive.

Proof of Arrow's theorem



The proof proceeds in two parts:

Part 1 Field expansion lemma: If a group is **almost decisive** over a pair of alternatives, it is **decisive** over all pairs of alternatives

Part 2 Group contraction lemma: If a group is decisive, then a strict non-empty subset of that group is also decisive.

Note: these two lemmas immediately proves the theorem

Field expansion lemma



Lemma

Let F satisfy WP and IIA, then $\forall a, b, x, y, G \subseteq N, G \neq \emptyset, a \neq b, x \neq y$

$$\overline{D}_G(a, b) \Rightarrow D_G(x, y).$$

Field expansion lemma



Lemma

Let F satisfy WP and IIA, then $\forall a, b, x, y, G \subseteq N, G \neq \emptyset, a \neq b, x \neq y$

$$\overline{D}_G(a, b) \Rightarrow D_G(x, y).$$

It implies that under WP and IIA, the two notions of decisiveness are equivalent.



Field expansion lemma

Lemma

Let F satisfy WP and IIA, then $\forall a, b, x, y, G \subseteq N, G \neq \emptyset, a \neq b, x \neq y$

$$\overline{D}_G(a, b) \Rightarrow D_G(x, y).$$

It implies that under WP and IIA, the two notions of decisiveness are equivalent.

Cases to consider (ordered for the convenience of the proof):

① $\overline{D}_G(a, b) \Rightarrow D_G(a, y), y \neq a, b$



Field expansion lemma

Lemma

Let F satisfy WP and IIA, then $\forall a, b, x, y, G \subseteq N, G \neq \emptyset, a \neq b, x \neq y$

$$\overline{D}_G(a, b) \Rightarrow D_G(x, y).$$

It implies that under WP and IIA, the two notions of decisiveness are equivalent.

Cases to consider (ordered for the convenience of the proof):

- 1 $\overline{D}_G(a, b) \Rightarrow D_G(a, y), y \neq a, b$
- 2 $\overline{D}_G(a, b) \Rightarrow D_G(x, b), x \neq a, b$



Field expansion lemma

Lemma

Let F satisfy WP and IIA, then $\forall a, b, x, y, G \subseteq N, G \neq \emptyset, a \neq b, x \neq y$

$$\overline{D}_G(a, b) \Rightarrow D_G(x, y).$$

It implies that under WP and IIA, the two notions of decisiveness are equivalent.

Cases to consider (ordered for the convenience of the proof):

- 1 $\overline{D}_G(a, b) \Rightarrow D_G(a, y), y \neq a, b$
- 2 $\overline{D}_G(a, b) \Rightarrow D_G(x, b), x \neq a, b$
- 3 $\overline{D}_G(a, b) \Rightarrow D_G(x, y), x, y \neq a, b$



Field expansion lemma

Lemma

Let F satisfy WP and IIA, then $\forall a, b, x, y, G \subseteq N, G \neq \emptyset, a \neq b, x \neq y$

$$\overline{D}_G(a, b) \Rightarrow D_G(x, y).$$

It implies that under WP and IIA, the two notions of decisiveness are equivalent.

Cases to consider (ordered for the convenience of the proof):

- ① $\overline{D}_G(a, b) \Rightarrow D_G(a, y), y \neq a, b$
- ② $\overline{D}_G(a, b) \Rightarrow D_G(x, b), x \neq a, b$
- ③ $\overline{D}_G(a, b) \Rightarrow D_G(x, y), x, y \neq a, b$
- ④ $\overline{D}_G(a, b) \Rightarrow D_G(x, a), x \neq a, b$



Field expansion lemma

Lemma

Let F satisfy WP and IIA, then $\forall a, b, x, y, G \subseteq N, G \neq \emptyset, a \neq b, x \neq y$

$$\overline{D}_G(a, b) \Rightarrow D_G(x, y).$$

It implies that under WP and IIA, the two notions of decisiveness are equivalent.

Cases to consider (ordered for the convenience of the proof):

- ① $\overline{D}_G(a, b) \Rightarrow D_G(a, y), y \neq a, b$
- ② $\overline{D}_G(a, b) \Rightarrow D_G(x, b), x \neq a, b$
- ③ $\overline{D}_G(a, b) \Rightarrow D_G(x, y), x, y \neq a, b$
- ④ $\overline{D}_G(a, b) \Rightarrow D_G(x, a), x \neq a, b$
- ⑤ $\overline{D}_G(a, b) \Rightarrow D_G(b, y), y \neq a, b$



Field expansion lemma

Lemma

Let F satisfy WP and IIA, then $\forall a, b, x, y, G \subseteq N, G \neq \emptyset, a \neq b, x \neq y$

$$\overline{D}_G(a, b) \Rightarrow D_G(x, y).$$

It implies that under WP and IIA, the two notions of decisiveness are equivalent.

Cases to consider (ordered for the convenience of the proof):

- ① $\overline{D}_G(a, b) \Rightarrow D_G(a, y), y \neq a, b$
- ② $\overline{D}_G(a, b) \Rightarrow D_G(x, b), x \neq a, b$
- ③ $\overline{D}_G(a, b) \Rightarrow D_G(x, y), x, y \neq a, b$
- ④ $\overline{D}_G(a, b) \Rightarrow D_G(x, a), x \neq a, b$
- ⑤ $\overline{D}_G(a, b) \Rightarrow D_G(b, y), y \neq a, b$
- ⑥ $\overline{D}_G(a, b) \Rightarrow D_G(a, b)$



Field expansion lemma

Lemma

Let F satisfy WP and IIA, then $\forall a, b, x, y, G \subseteq N, G \neq \emptyset, a \neq b, x \neq y$

$$\overline{D}_G(a, b) \Rightarrow D_G(x, y).$$

It implies that under WP and IIA, the two notions of decisiveness are equivalent.

Cases to consider (ordered for the convenience of the proof):

- ① $\overline{D}_G(a, b) \Rightarrow D_G(a, y), y \neq a, b$
- ② $\overline{D}_G(a, b) \Rightarrow D_G(x, b), x \neq a, b$
- ③ $\overline{D}_G(a, b) \Rightarrow D_G(x, y), x, y \neq a, b$
- ④ $\overline{D}_G(a, b) \Rightarrow D_G(x, a), x \neq a, b$
- ⑤ $\overline{D}_G(a, b) \Rightarrow D_G(b, y), y \neq a, b$
- ⑥ $\overline{D}_G(a, b) \Rightarrow D_G(a, b)$
- ⑦ $\overline{D}_G(a, b) \Rightarrow D_G(b, a)$



- **Case 1:** $\overline{D}_G(a,b) \Rightarrow D_G(a,y), y \neq a,b$



- **Case 1:** $\overline{D}_G(a, b) \Rightarrow D_G(a, y), y \neq a, b$
- Pick an arbitrary $R \in \mathcal{R}^n$, s.t., $aP_iy, \forall i \in G$



- **Case 1:** $\overline{D}_G(a, b) \Rightarrow D_G(a, y), y \neq a, b$
- Pick an arbitrary $R \in \mathcal{R}^n$, s.t., $aP_i y, \forall i \in G$
- Need to show: $a\hat{F}(R)y$



Proof of FEL

- **Case 1:** $\overline{D}_G(a, b) \Rightarrow D_G(a, y), y \neq a, b$
- Pick an arbitrary $R \in \mathcal{R}^n$, s.t., $aP_i y, \forall i \in G$
- Need to show: $a\hat{F}(R)y$
- Construct R' s.t.

G		$N \setminus G$	
a	a	b	b
\vdots	\vdots	\vdots	\vdots
b	b	a	y
\vdots	\vdots	\vdots	\vdots
y	y	y	a

positions of a and y in $N \setminus G$ s.t. $R'|_{a,y} = R|_{a,y}$



Proof of FEL

- **Case 1:** $\overline{D}_G(a, b) \Rightarrow D_G(a, y), y \neq a, b$
- Pick an arbitrary $R \in \mathcal{R}^n$, s.t., $aP_i y, \forall i \in G$
- Need to show: $a\hat{F}(R)y$
- Construct R' s.t.

G		$N \setminus G$	
a	a	b	b
\vdots	\vdots	\vdots	\vdots
b	b	a	y
\vdots	\vdots	\vdots	\vdots
y	y	y	a

positions of a and y in $N \setminus G$ s.t. $R'|_{a,y} = R|_{a,y}$

- $\overline{D}_G(a, b) \Rightarrow a\hat{F}(R')b$



Proof of FEL

- **Case 1:** $\overline{D}_G(a, b) \Rightarrow D_G(a, y), y \neq a, b$
- Pick an arbitrary $R \in \mathcal{R}^n$, s.t., $aP_i y, \forall i \in G$
- Need to show: $a\hat{F}(R)y$
- Construct R' s.t.

G		$N \setminus G$	
a	a	b	b
\vdots	\vdots	\vdots	\vdots
b	b	a	y
\vdots	\vdots	\vdots	\vdots
y	y	y	a

positions of a and y in $N \setminus G$ s.t. $R'|_{a,y} = R|_{a,y}$

- $\overline{D}_G(a, b) \Rightarrow a\hat{F}(R')b$
- WP over $b, y, \Rightarrow b\hat{F}(R')y$, transitivity $\Rightarrow a\hat{F}(R')y$



Proof of FEL

- **Case 1:** $\overline{D}_G(a, b) \Rightarrow D_G(a, y), y \neq a, b$
- Pick an arbitrary $R \in \mathcal{R}^n$, s.t., $aP_i y, \forall i \in G$
- Need to show: $a\hat{F}(R)y$
- Construct R' s.t.

G		$N \setminus G$	
a	a	b	b
\vdots	\vdots	\vdots	\vdots
b	b	a	y
\vdots	\vdots	\vdots	\vdots
y	y	y	a

positions of a and y in $N \setminus G$ s.t. $R'|_{a,y} = R|_{a,y}$

- $\overline{D}_G(a, b) \Rightarrow a\hat{F}(R')b$
- WP over $b, y, \Rightarrow b\hat{F}(R')y$, transitivity $\Rightarrow a\hat{F}(R')y$
- IIA $\Rightarrow a\hat{F}(R)y$. Hence, $D_G(a, y)$

Proof of FEL (contd.)



- **Case 2:** $\overline{D}_G(a,b) \Rightarrow D_G(x,b), x \neq a,b$

Proof of FEL (contd.)



- **Case 2:** $\overline{D}_G(a, b) \Rightarrow D_G(x, b), x \neq a, b$
- Pick an arbitrary $R \in \mathcal{R}^n$, s.t., $xP_i b, \forall i \in G$

Proof of FEL (contd.)



- **Case 2:** $\overline{D}_G(a, b) \Rightarrow D_G(x, b), x \neq a, b$
- Pick an arbitrary $R \in \mathcal{R}^n$, s.t., $xP_i b, \forall i \in G$
- Need to show: $x\hat{F}(R)b$



Proof of FEL (contd.)

- **Case 2:** $\overline{D}_G(a, b) \Rightarrow D_G(x, b), x \neq a, b$
- Pick an arbitrary $R \in \mathcal{R}^n$, s.t., $xP_ib, \forall i \in G$
- Need to show: $x\hat{F}(R)b$
- Construct R' s.t.

G		$N \setminus G$	
x	x	x	b
\vdots	\vdots	\vdots	\vdots
a	a	b	x
\vdots	\vdots	\vdots	\vdots
b	b	a	a

positions of x and b in $N \setminus G$ s.t. $R'|_{x,b} = R|_{x,b}$



Proof of FEL (contd.)

- **Case 2:** $\overline{D}_G(a, b) \Rightarrow D_G(x, b), x \neq a, b$
- Pick an arbitrary $R \in \mathcal{R}^n$, s.t., $xP_ib, \forall i \in G$
- Need to show: $x\hat{F}(R)b$
- Construct R' s.t.

G		$N \setminus G$	
x	x	x	b
\vdots	\vdots	\vdots	\vdots
a	a	b	x
\vdots	\vdots	\vdots	\vdots
b	b	a	a

positions of x and b in $N \setminus G$ s.t. $R'|_{x,b} = R|_{x,b}$

- $\overline{D}_G(a, b) \Rightarrow a\hat{F}(R')b$



Proof of FEL (contd.)

- **Case 2:** $\overline{D}_G(a, b) \Rightarrow D_G(x, b), x \neq a, b$
- Pick an arbitrary $R \in \mathcal{R}^n$, s.t., $xP_ib, \forall i \in G$
- Need to show: $x\hat{F}(R)b$
- Construct R' s.t.

G		$N \setminus G$	
x	x	x	b
\vdots	\vdots	\vdots	\vdots
a	a	b	x
\vdots	\vdots	\vdots	\vdots
b	b	a	a

positions of x and b in $N \setminus G$ s.t. $R'|_{x,b} = R|_{x,b}$

- $\overline{D}_G(a, b) \Rightarrow a\hat{F}(R')b$
- WP over $x, a, \Rightarrow x\hat{F}(R')a$, transitivity $\Rightarrow x\hat{F}(R')b$



Proof of FEL (contd.)

- **Case 2:** $\overline{D}_G(a, b) \Rightarrow D_G(x, b), x \neq a, b$
- Pick an arbitrary $R \in \mathcal{R}^n$, s.t., $xP_i b, \forall i \in G$
- Need to show: $x\hat{F}(R)b$
- Construct R' s.t.

G		$N \setminus G$	
x	x	x	b
\vdots	\vdots	\vdots	\vdots
a	a	b	x
\vdots	\vdots	\vdots	\vdots
b	b	a	a

positions of x and b in $N \setminus G$ s.t. $R'|_{x,b} = R|_{x,b}$

- $\overline{D}_G(a, b) \Rightarrow a\hat{F}(R')b$
- WP over $x, a, \Rightarrow x\hat{F}(R')a$, transitivity $\Rightarrow x\hat{F}(R')b$
- IIA $\Rightarrow x\hat{F}(R)b$. Hence, $D_G(x, b)$

Proof of FEL (other cases)



- **Case 3:** $\bar{D}_G(a, b) \xRightarrow{(\text{case } 1)} D_G(a, y) \ (y \neq a, b) \xRightarrow{(\text{definition})} \bar{D}_G(a, y) \xRightarrow{(\text{case } 2)} D_G(x, y) \ (x \neq a, y)$
- **Case 4:** $\bar{D}_G(a, b) \xRightarrow{(\text{case } 2)} D_G(x, b) \ (x \neq a, b) \xRightarrow{(\text{definition})} \bar{D}_G(x, b) \xRightarrow{(\text{case } 1)} D_G(x, a) \ (x \neq a, b)$
- **Case 5:** $\bar{D}_G(a, b) \xRightarrow{(\text{case } 1)} D_G(a, y) \ (y \neq a, b) \xRightarrow{(\text{definition})} \bar{D}_G(a, y) \xRightarrow{(\text{case } 2)} D_G(b, y) \ (y \neq a, b)$
- **Case 6:** $\bar{D}_G(a, b) \xRightarrow{(\text{case } 2)} D_G(x, b) \ (x \neq a, b) \xRightarrow{(\text{definition})} \bar{D}_G(x, b) \xRightarrow{(\text{case } 2)} D_G(a, b)$
- **Case 7:** $\bar{D}_G(a, b) \xRightarrow{(\text{case } 5)} D_G(b, y) \ (y \neq a, b) \xRightarrow{(\text{definition})} \bar{D}_G(b, y) \xRightarrow{(\text{case } 1)} D_G(b, a)$

Group contraction lemma



Lemma

Let F satisfy WP and IIA, and let $G \subseteq N, G \neq \emptyset, |G| \geq 2$ be decisive. Then $\exists G' \subset G, G' \neq \emptyset$ which is also decisive.

Proof:

- $G, |G| \geq 2$ is given. Let $G_1 \subset G, G_2 = G \setminus G_1, G_1, G_2 \neq \emptyset$, arbitrary.

Group contraction lemma



Lemma

Let F satisfy WP and IIA, and let $G \subseteq N, G \neq \emptyset, |G| \geq 2$ be decisive. Then $\exists G' \subset G, G' \neq \emptyset$ which is also decisive.

Proof:

- $G, |G| \geq 2$ is given. Let $G_1 \subset G, G_2 = G \setminus G_1, G_1, G_2 \neq \emptyset$, arbitrary.
- Construct R

G_1	G_2	$N \setminus G$
a	c	b
b	a	c
c	b	a

$$aP_i b, \forall i \in G \text{ and } G \text{ decisive} \Rightarrow a\hat{F}(R)b$$

Group contraction lemma



Lemma

Let F satisfy WP and IIA, and let $G \subseteq N, G \neq \emptyset, |G| \geq 2$ be decisive. Then $\exists G' \subset G, G' \neq \emptyset$ which is also decisive.

Proof:

- $G, |G| \geq 2$ is given. Let $G_1 \subset G, G_2 = G \setminus G_1, G_1, G_2 \neq \emptyset$, arbitrary.
- Construct R

G_1	G_2	$N \setminus G$
a	c	b
b	a	c
c	b	a

$$aP_i b, \forall i \in G \text{ and } G \text{ decisive} \Rightarrow a\hat{F}(R)b$$

- Where can c stand in $F(R)$ w.r.t. a ? We will show in every possible case, either G_1 or G_2 will be decisive



Case 1: $a\hat{F}(R)c$

- Consider G_1

G_1	G_2	$N \setminus G$	
a	c	b	have seen $\Rightarrow a\hat{F}(R)b$
b	a	c	
c	b	a	



Case 1: $a\hat{F}(R)c$

G_1	G_2	$N \setminus G$
a	c	b
b	a	c
c	b	a

have seen $\Rightarrow a\hat{F}(R)b$

- Consider G_1
- $aP_ic, \forall i \in G_1, cP_ia, \forall i \in N \setminus G_1$



Case 1: $a\hat{F}(R)c$

G_1	G_2	$N \setminus G$
a	c	b
b	a	c
c	b	a

have seen $\Rightarrow a\hat{F}(R)b$

- Consider G_1
- $aP_ic, \forall i \in G_1, cP_ia, \forall i \in N \setminus G_1$
- Consider each R' where the above relation holds



Case 1: $a\hat{F}(R)c$

G_1	G_2	$N \setminus G$	
a	c	b	have seen $\Rightarrow a\hat{F}(R)b$
b	a	c	
c	b	a	

- Consider G_1
- $aP_ic, \forall i \in G_1, cP_ia, \forall i \in N \setminus G_1$
- Consider each R' where the above relation holds
- by IIA $a\hat{F}(R')c$



Case 1: $a\hat{F}(R)c$

G_1	G_2	$N \setminus G$
a	c	b
b	a	c
c	b	a

have seen $\Rightarrow a\hat{F}(R)b$

- Consider G_1
- $aP_ic, \forall i \in G_1, cP_ia, \forall i \in N \setminus G_1$
- Consider each R' where the above relation holds
- by IIA $a\hat{F}(R')c$
- Hence $\overline{D}_{G_1}(a, c) \xRightarrow{\text{(FEL)}} D_{G_1}$

Proof of GCL (contd.)



Case 2: $\neg(a\hat{F}(R)c) \implies cF(R)a$

- $a\hat{F}(R)b$ and $cF(R)a$ give $c\hat{F}(R)b$

G_1	G_2	$N \setminus G$	
a	c	b	have seen $\implies a\hat{F}(R)b$
b	a	c	
c	b	a	

Proof of GCL (contd.)



Case 2: $\neg(a\hat{F}(R)c) \implies cF(R)a$

- $a\hat{F}(R)b$ and $cF(R)a$ give $c\hat{F}(R)b$
- Consider G_2

G_1	G_2	$N \setminus G$	
a	c	b	have seen $\implies a\hat{F}(R)b$
b	a	c	
c	b	a	

Proof of GCL (contd.)



Case 2: $\neg(a\hat{F}(R)c) \implies cF(R)a$

G_1	G_2	$N \setminus G$	
a	c	b	have seen $\implies a\hat{F}(R)b$
b	a	c	
c	b	a	

- $a\hat{F}(R)b$ and $cF(R)a$ give $c\hat{F}(R)b$
- Consider G_2
- $cP_i b, \forall i \in G_2, bP_i c, \forall i \in N \setminus G_2$

Proof of GCL (contd.)



Case 2: $\neg(a\hat{F}(R)c) \implies cF(R)a$

G_1	G_2	$N \setminus G$	
a	c	b	have seen $\implies a\hat{F}(R)b$
b	a	c	
c	b	a	

- $a\hat{F}(R)b$ and $cF(R)a$ give $c\hat{F}(R)b$
- Consider G_2
- $cP_ib, \forall i \in G_2, bP_ic, \forall i \in N \setminus G_2$
- Consider each R' where the above relation holds

Proof of GCL (contd.)



Case 2: $\neg(a\hat{F}(R)c) \implies cF(R)a$

G_1	G_2	$N \setminus G$	
a	c	b	have seen $\implies a\hat{F}(R)b$
b	a	c	
c	b	a	

- $a\hat{F}(R)b$ and $cF(R)a$ give $c\hat{F}(R)b$
- Consider G_2
- $cP_i b, \forall i \in G_2, bP_i c, \forall i \in N \setminus G_2$
- Consider each R' where the above relation holds
- by IIA $c\hat{F}(R')b$



Case 2: $\neg(a\hat{F}(R)c) \implies cF(R)a$

G_1	G_2	$N \setminus G$	
a	c	b	have seen $\implies a\hat{F}(R)b$
b	a	c	
c	b	a	

- $a\hat{F}(R)b$ and $cF(R)a$ give $c\hat{F}(R)b$
- Consider G_2
- $cP_i b, \forall i \in G_2, bP_i c, \forall i \in N \setminus G_2$
- Consider each R' where the above relation holds
- by IIA $c\hat{F}(R')b$
- Hence $\overline{D}_{G_2}(c, b) \xRightarrow{\text{(FEL)}} D_{G_2}$



भारतीय प्रौद्योगिकी संस्थान मुंबई

Indian Institute of Technology Bombay