


CS 228 : Logic in Computer Science

Krishna. S


Recap

- ▶ FOL over words : Satisfiability
- ▶ Translation from formulae φ to equivalent DFA A , $L(\varphi) = L(A)$
- ▶ Proof by structural induction, with \neg, \wedge, \vee mapping to complementation, intersection and union
 - ▶ Union in DFA \rightarrow disjunction in logic
 - ▶ Intersection in DFA \rightarrow conjunction in logic
 - ▶ Complementation in DFA \rightarrow Negation in logic
- ▶ How to handle quantifiers?

Non-determinism




Non-determinism




- ▶ Assume we relax the condition on transitions, and allow
 - ▶ $\delta : Q \times \Sigma \rightarrow 2^Q$
 - ▶ $\delta(q_0, a) = \{q_0, q_1\}, \delta(q_2, a) = \emptyset$

Non-determinism




- ▶ Assume we relax the condition on transitions, and allow
 - ▶ $\delta : Q \times \Sigma \rightarrow 2^Q$
 - ▶ $\delta(q_0, a) = \{q_0, q_1\}, \delta(q_2, a) = \emptyset$
 - ▶ Is *aabb* accepted?

Non-determinism




- ▶ Assume we relax the condition on transitions, and allow

- ▶ $\delta : Q \times \Sigma \rightarrow 2^Q$
- ▶ $\delta(q_0, a) = \{q_0, q_1\}, \delta(q_2, a) = \emptyset$
- ▶ Is *aabb* accepted?




One run of *aabb*

Is *aabb* accepted?




One run of *aabb*

Is *aabb* accepted?



One run of *aabb*


Is *aabb* accepted?



- ▶ A non-accepting run for *aabb*


Another run of *aabb*

Is *aabb* accepted?




Another run of *aabb*

Is *aabb* accepted?




Another run of *aabb*

Is *aabb* accepted?



Another run of *aabb*


Is *aab****b*** accepted?



- ▶ A non-accepting run for *aabb*


A run of *aaab*

Is *aaab* accepted?




A run of *aaab*

Is *a***a***ab* accepted?




A run of *aaab*

Is *aaab* accepted?



A run of *aaab*


Is *aaab* accepted?



- A non-accepting run for *aaab*


Another run of *aaab*

Is *aaab* accepted?




Another run of *aaab*

Is *a***a***ab* accepted?




Another run of *aaab*

Is *aaab* accepted?



Another run of *aaab*

Is *aaab* accepted?




- An accepting run for *aaab*


Nondeterministic Finite Automata(NFA)

- ▶ $N = (Q, \Sigma, \delta, Q_0, F)$
 - ▶ Q is a finite set of states
 - ▶ $Q_0 \subseteq Q$ is the set of initial states
 - ▶ $\delta : Q \times \Sigma \rightarrow 2^Q$ is the transition function
 - ▶ $F \subseteq Q$ is the set of final states
- ▶ Acceptance condition : A word w is accepted iff it has atleast one accepting path


Run Tree of *aaab*




Run Tree of *aaab*




Run Tree of *aaab*




Run Tree of *aaab*




Run Tree of *aaab*




Run Tree of *aaab*




Run Tree of *aaab*




Run Tree of *aaab*



Run Tree of *aaab*



The Single Run



NFA and DFA

- ▶ Any DFA is also an NFA

NFA and DFA

- ▶ Any DFA is also an NFA
- ▶ Any NFA can be converted into a language equivalent DFA

NFA and DFA

- ▶ Any DFA is also an NFA
- ▶ Any NFA can be converted into a language equivalent DFA
 - ▶ Combine all the runs of w in the NFA into a single run in the DFA

NFA and DFA

- ▶ Any DFA is also an NFA
- ▶ Any NFA can be converted into a language equivalent DFA
 - ▶ Combine all the runs of w in the NFA into a single run in the DFA
 - ▶ Combine states occurring in various runs to obtain a set of states

NFA and DFA

- ▶ Any DFA is also an NFA
- ▶ Any NFA can be converted into a language equivalent DFA
 - ▶ Combine all the runs of w in the NFA into a single run in the DFA
 - ▶ Combine states occurring in various runs to obtain a set of states
 - ▶ A set of states evolves into another set of states

NFA and DFA

- ▶ Any DFA is also an NFA
- ▶ Any NFA can be converted into a language equivalent DFA
 - ▶ Combine all the runs of w in the NFA into a single run in the DFA
 - ▶ Combine states occurring in various runs to obtain a set of states
 - ▶ A set of states evolves into another set of states
 - ▶ Use $\delta : Q \times \Sigma \rightarrow 2^Q$, obtain $\Delta : 2^Q \times \Sigma \rightarrow 2^Q$

NFA and DFA

- ▶ Any DFA is also an NFA
- ▶ Any NFA can be converted into a language equivalent DFA
 - ▶ Combine all the runs of w in the NFA into a single run in the DFA
 - ▶ Combine states occurring in various runs to obtain a set of states
 - ▶ A set of states evolves into another set of states
 - ▶ Use $\delta : Q \times \Sigma \rightarrow 2^Q$, obtain $\Delta : 2^Q \times \Sigma \rightarrow 2^Q$
 - ▶ Δ is an extension of δ

NFA and DFA

- ▶ Any DFA is also an NFA
- ▶ Any NFA can be converted into a language equivalent DFA
 - ▶ Combine all the runs of w in the NFA into a single run in the DFA
 - ▶ Combine states occurring in various runs to obtain a set of states
 - ▶ A set of states evolves into another set of states
 - ▶ Use $\delta : Q \times \Sigma \rightarrow 2^Q$, obtain $\Delta : 2^Q \times \Sigma \rightarrow 2^Q$
 - ▶ Δ is an extension of δ
 - ▶ Accept if the obtained set of states contains a final state

NFA and DFA

Given NFA $N = (Q, \Sigma, Q_0, \delta, F)$, obtain the DFA $D = (2^Q, \Sigma, Q_0, \Delta, F')$

NFA and DFA

Given NFA $N = (Q, \Sigma, Q_0, \delta, F)$, obtain the DFA $D = (2^Q, \Sigma, Q_0, \Delta, F')$

- ▶ $\Delta : 2^Q \times \Sigma \rightarrow 2^Q$ is defined by $\Delta(A, a) = \bigcup_{q \in A} \delta(q, a)$

NFA and DFA

Given NFA $N = (Q, \Sigma, Q_0, \delta, F)$, obtain the DFA $D = (2^Q, \Sigma, Q_0, \Delta, F')$

- ▶ $\Delta : 2^Q \times \Sigma \rightarrow 2^Q$ is defined by $\Delta(A, a) = \bigcup_{q \in A} \delta(q, a)$
- ▶ $F' = \{S \in 2^Q \mid S \cap F \neq \emptyset\}$

NFA and DFA

Given NFA $N = (Q, \Sigma, Q_0, \delta, F)$, obtain the DFA $D = (2^Q, \Sigma, Q_0, \Delta, F')$

- ▶ $\Delta : 2^Q \times \Sigma \rightarrow 2^Q$ is defined by $\Delta(A, a) = \bigcup_{q \in A} \delta(q, a)$
- ▶ $F' = \{S \in 2^Q \mid S \cap F \neq \emptyset\}$

Note that $\hat{\delta}(A, a) = \bigcup_{q \in A} \delta(q, a) = \Delta(A, a)$

NFA and DFA

Given NFA $N = (Q, \Sigma, Q_0, \delta, F)$, obtain the DFA $D = (2^Q, \Sigma, Q_0, \Delta, F')$

- ▶ $\Delta : 2^Q \times \Sigma \rightarrow 2^Q$ is defined by $\Delta(A, a) = \bigcup_{q \in A} \delta(q, a)$
- ▶ $F' = \{S \in 2^Q \mid S \cap F \neq \emptyset\}$

Note that $\hat{\delta}(A, a) = \bigcup_{q \in A} \delta(q, a) = \Delta(A, a)$

Show that

- ▶ $\hat{\Delta} : 2^Q \times \Sigma^* \rightarrow 2^Q$ is same as $\hat{\delta} : 2^Q \times \Sigma^* \rightarrow 2^Q$ (recall $\delta : Q \times \Sigma \rightarrow 2^Q$)

NFA and DFA

Given NFA $N = (Q, \Sigma, Q_0, \delta, F)$, obtain the DFA $D = (2^Q, \Sigma, Q_0, \Delta, F')$

- ▶ $\Delta : 2^Q \times \Sigma \rightarrow 2^Q$ is defined by $\Delta(A, a) = \bigcup_{q \in A} \delta(q, a)$
- ▶ $F' = \{S \in 2^Q \mid S \cap F \neq \emptyset\}$

Note that $\hat{\delta}(A, a) = \bigcup_{q \in A} \delta(q, a) = \Delta(A, a)$

Show that

- ▶ $\hat{\Delta} : 2^Q \times \Sigma^* \rightarrow 2^Q$ is same as $\hat{\delta} : 2^Q \times \Sigma^* \rightarrow 2^Q$ (recall $\delta : Q \times \Sigma \rightarrow 2^Q$)
- ▶ $\hat{\Delta}(A, xa) = \Delta(\hat{\Delta}(A, x), a) = \bigcup_{q \in \hat{\Delta}(A, x)} \delta(q, a)$

NFA and DFA

Given NFA $N = (Q, \Sigma, Q_0, \delta, F)$, obtain the DFA $D = (2^Q, \Sigma, Q_0, \Delta, F')$

- ▶ $\Delta : 2^Q \times \Sigma \rightarrow 2^Q$ is defined by $\Delta(A, a) = \bigcup_{q \in A} \delta(q, a)$
- ▶ $F' = \{S \in 2^Q \mid S \cap F \neq \emptyset\}$

Note that $\hat{\delta}(A, a) = \bigcup_{q \in A} \delta(q, a) = \Delta(A, a)$

Show that

- ▶ $\hat{\Delta} : 2^Q \times \Sigma^* \rightarrow 2^Q$ is same as $\hat{\delta} : 2^Q \times \Sigma^* \rightarrow 2^Q$ (recall $\delta : Q \times \Sigma \rightarrow 2^Q$)
- ▶ $\hat{\Delta}(A, xa) = \Delta(\hat{\Delta}(A, x), a) = \bigcup_{q \in \hat{\Delta}(A, x)} \delta(q, a)$
- ▶ $\hat{\delta}(A, xa) = \bigcup_{q \in \hat{\delta}(A, x)} \delta(q, a)$

NFA = DFA

$$x \in L(D) \leftrightarrow \hat{\Delta}(Q_0, x) \in F'$$

$$\leftrightarrow$$

$$\hat{\delta}(Q_0, x) \in F'$$

$$\leftrightarrow$$

$$\hat{\delta}(Q_0, x) \cap F \neq \emptyset$$


$$\leftrightarrow$$

$$x \in L(N)$$



Regularity

A language L is regular iff there exists an NFA A such that $L = L(A)$



ϵ -NFA





ϵ -NFA





ϵ -NFA



ϵ -NFA



ϵ -NFA




ϵ -NFA and DFA

- ▶ ϵ -close the initial states of the ϵ -NFA to obtain initial state of DFA
- ▶ From a state S , compute $\Delta(S, a)$ and ϵ -close it
- ▶ All states in the DFA are ϵ -closed
- ▶ Final states are those which contain a final state of the ϵ -NFA

Closure under Concatenation

- Given regular languages L_1, L_2 , is $L_1.L_2$ regular



Closure under Concatenation

- Given regular languages L_1, L_2 , is $L_1.L_2$ regular?

