



CS 228 : Logic in Computer Science

Krishna. S

Derived Operators

- ▶ $true = \varphi \vee \neg\varphi$
- ▶ $false = \neg true$
- ▶ $\diamond\varphi = true \text{ U } \varphi$ (Eventually φ)
- ▶ $\Box\varphi = \neg\diamond\neg\varphi$ (Forever φ)

Precedence

- ▶ Unary Operators bind stronger than Binary
- ▶ \bigcirc and \neg equally strong
- ▶ U takes precedence over $\wedge, \vee, \rightarrow$
 - ▶ $a \vee b \text{ U } c \equiv a \vee (b \text{ U } c)$
 - ▶ $\bigcirc a \text{ U } \neg b \equiv (\bigcirc a) \text{ U } (\neg b)$

Examples

- ▶ Whenever the traffic light is red, it cannot become green immediately:

Examples

- ▶ Whenever the traffic light is red, it cannot become green immediately:

$$\Box(\text{red} \rightarrow \neg \bigcirc \text{green})$$

Examples

- ▶ Whenever the traffic light is red, it cannot become green immediately:
 $\Box(\text{red} \rightarrow \neg \bigcirc \text{green})$
- ▶ Eventually the traffic light will become yellow

Examples

- ▶ Whenever the traffic light is red, it cannot become green immediately:
 $\Box(\text{red} \rightarrow \neg \bigcirc \text{green})$
- ▶ Eventually the traffic light will become yellow
 $\Diamond \text{yellow}$

Examples

- ▶ Whenever the traffic light is red, it cannot become green immediately:
 $\Box(\text{red} \rightarrow \neg \bigcirc \text{green})$
- ▶ Eventually the traffic light will become yellow
 $\Diamond \text{yellow}$
- ▶ Once the traffic light becomes yellow, it will eventually become green

Examples

- ▶ Whenever the traffic light is red, it cannot become green immediately:
 $\Box(\text{red} \rightarrow \neg \bigcirc \text{green})$
- ▶ Eventually the traffic light will become yellow
 $\Diamond \text{yellow}$
- ▶ Once the traffic light becomes yellow, it will eventually become green
 $\Box(\text{yellow} \rightarrow \Diamond \text{green})$

Semantics over Infinite Words

Given LTL formula φ over AP ,

$$L(\varphi) = \{\sigma \in (2^{AP})^\omega \mid \sigma \models \varphi\}$$

Let $\sigma = A_0A_1A_2\dots$, with $A_i \subseteq AP$.

Semantics over Infinite Words

Given LTL formula φ over AP ,

$$L(\varphi) = \{\sigma \in (2^{AP})^\omega \mid \sigma \models \varphi\}$$

Let $\sigma = A_0A_1A_2\dots$, with $A_i \subseteq AP$.

- ▶ $\sigma \models a$ iff $a \in A_0$
- ▶ $\sigma \models \varphi_1 \wedge \varphi_2$ iff $\sigma \models \varphi_1$ and $\sigma \models \varphi_2$
- ▶ $\sigma \models \neg\varphi$ iff $\sigma \not\models \varphi$
- ▶ $\sigma \models \bigcirc\varphi$ iff $A_1A_2\dots \models \varphi$
- ▶ $\sigma \models \varphi \mathbf{U} \psi$ iff
 $\exists j \geq 0$ such that $A_jA_{j+1}\dots \models \psi \wedge \forall 0 \leq i < j, A_iA_{i+1}\dots \models \varphi$

Semantics over Infinite Words

Given LTL formula φ over AP ,

$$L(\varphi) = \{\sigma \in (2^{AP})^\omega \mid \sigma \models \varphi\}$$

Let $\sigma = A_0A_1A_2\dots$, with $A_i \subseteq AP$.

- ▶ $\sigma \models \Diamond\varphi$ iff $\exists j \geq 0, A_jA_{j+1}\dots \models \varphi$
- ▶ $\sigma \models \Box\varphi$ iff $\forall j \geq 0, A_jA_{j+1}\dots \models \varphi$
- ▶ $\sigma \models \Box\Diamond\varphi$ iff $\forall j \geq 0, \exists i \geq j, A_iA_{i+1}\dots \models \varphi$
- ▶ $\sigma \models \Diamond\Box\varphi$ iff $\exists j \geq 0, \forall i \geq j, A_iA_{i+1}\dots \models \varphi$

If $\sigma = A_0A_1A_2\dots$, $\sigma \models \varphi$ is also written as $\sigma, 0 \models \varphi$. This simply means $A_0A_1A_2\dots \models \varphi$. One can also define $\sigma, i \models \varphi$ to mean $A_iA_{i+1}A_{i+2}\dots \models \varphi$ to talk about a suffix of the word σ satisfying a property.

Transition System Semantics $TS \models \varphi$

Let $TS = (S, S_0, \rightarrow, AP, L)$ be a transition system, and φ an LTL formula over AP

- ▶ For an infinite path fragment π of TS ,

$$\pi \models \varphi \text{ iff } \text{trace}(\pi) \models \varphi$$

Transition System Semantics $TS \models \varphi$

Let $TS = (S, S_0, \rightarrow, AP, L)$ be a transition system, and φ an LTL formula over AP

- ▶ For an infinite path fragment π of TS ,

$$\pi \models \varphi \text{ iff } \text{trace}(\pi) \models \varphi$$

- ▶ For $s \in S$,

$$s \models \varphi \text{ iff } \forall \pi \in \text{Paths}(s), \pi \models \varphi$$

Transition System Semantics $TS \models \varphi$

Let $TS = (S, S_0, \rightarrow, AP, L)$ be a transition system, and φ an LTL formula over AP

- ▶ For an infinite path fragment π of TS ,

$$\pi \models \varphi \text{ iff } \text{trace}(\pi) \models \varphi$$

- ▶ For $s \in S$,

$$s \models \varphi \text{ iff } \forall \pi \in \text{Paths}(s), \pi \models \varphi$$


- ▶ $TS \models \varphi$ iff $\text{Traces}(TS) \subseteq L(\varphi)$

Transition System Semantics $TS \models \varphi$

Assume all states in TS are reachable from S_0 .


- ▶ $TS \models \varphi$ iff $TS \models L(\varphi)$ iff $Traces(TS) \subseteq L(\varphi)$
- ▶ $TS \models L(\varphi)$ iff $\pi \models \varphi \ \forall \pi \in Paths(TS)$
- ▶ $\pi \models \varphi \ \forall \pi \in Paths(TS)$ iff $s_0 \models \varphi \ \forall s_0 \in S_0$

Example




► $TS \models \Box a,$

Example




- ▶ $TS \models \Box a$,
- ▶ $TS \not\models \bigcirc(a \wedge b)$

Example



- ▶ $TS \models \Box a,$
- ▶ $TS \not\models \bigcirc(a \wedge b)$
- ▶ $TS \not\models (b \cup (a \wedge \neg b))$

Example



- ▶ $TS \models \Box a$,
- ▶ $TS \not\models \bigcirc(a \wedge b)$
- ▶ $TS \not\models (b \cup (a \wedge \neg b))$
- ▶ $TS \models \Box(\neg b \rightarrow \Box(a \wedge \neg b))$

More Semantics

- ▶ For paths π , $\pi \models \varphi$ iff $\pi \not\models \neg\varphi$


More Semantics

- ▶ For paths π , $\pi \models \varphi$ iff $\pi \not\models \neg\varphi$
 $trace(\pi) \in L(\varphi)$ iff $trace(\pi) \notin L(\neg\varphi) = \overline{L(\varphi)}$
- ▶ $TS \not\models \varphi$ iff $TS \models \neg\varphi$?

More Semantics

- ▶ For paths π , $\pi \models \varphi$ iff $\pi \not\models \neg\varphi$
 $trace(\pi) \in L(\varphi)$ iff $trace(\pi) \notin L(\neg\varphi) = \overline{L(\varphi)}$
- ▶ $TS \not\models \varphi$ iff $TS \models \neg\varphi$?
 - ▶ $TS \models \neg\varphi \rightarrow \forall$ paths π of TS , $\pi \models \neg\varphi$
 - ▶ Thus, $\forall\pi$, $\pi \not\models \varphi$. Hence, $TS \not\models \varphi$
 - ▶ Now assume $TS \not\models \varphi$
 - ▶ Then \exists some path π in TS such that $\pi \models \neg\varphi$
 - ▶ However, there could be another path π' such that $\pi' \models \varphi$
 - ▶ Then $TS \not\models \neg\varphi$ as well
- ▶ Thus, $TS \not\models \varphi \not\equiv TS \models \neg\varphi$.

An Example



$TS \not\models \Diamond a$ and $TS \not\models \Box \neg a$

Equivalence of LTL Formulae

Equivalence

φ and ψ are equivalent ($\varphi \equiv \psi$) iff $L(\varphi) = L(\psi)$.

Expansion Laws

- ▶ $\varphi \text{ U } \psi \equiv \psi \vee (\varphi \wedge \bigcirc(\varphi \text{ U } \psi))$
- ▶ $\diamond\varphi \equiv \varphi \vee \bigcirc\diamond\varphi$
- ▶ $\Box\varphi \equiv \varphi \wedge \bigcirc\Box\varphi$

Equivalence of LTL Formulae

φ and ψ are equivalent iff $L(\varphi) = L(\psi)$.

Equivalence of LTL Formulae

φ and ψ are equivalent iff $L(\varphi) = L(\psi)$.

Distribution

$$\bigcirc(\varphi \vee \psi) \equiv \bigcirc\varphi \vee \bigcirc\psi,$$


$$\bigcirc(\varphi \wedge \psi) \equiv \bigcirc\varphi \wedge \bigcirc\psi,$$

$$\bigcirc(\varphi \mathbf{U} \psi) \equiv (\bigcirc\varphi) \mathbf{U} (\bigcirc\psi),$$

$$\Diamond(\varphi \vee \psi) \equiv \Diamond\varphi \vee \Diamond\psi,$$

$$\Box(\varphi \wedge \psi) \equiv \Box\varphi \wedge \Box\psi$$

Equivalence of LTL Formulae



$$TS \models \Diamond a \wedge \Diamond b, TS \not\models \Diamond(a \wedge b)$$

$$TS \models \Box(a \vee b), TS \not\models \Box a \vee \Box b$$

Satisfiability, Model Checking of LTL

Two Questions

Given transition system TS , and an LTL formula φ . Does $TS \models \varphi$?

Given an LTL formula φ , is $L(\varphi) = \emptyset$?

ω -automata

An ω -automaton is a tuple $\mathcal{A} = (Q, \Sigma, \delta, q_0, Acc)$ where

- ▶ Q is a finite set of states
- ▶ Σ is a finite alphabet
- ▶ $\delta : Q \times \Sigma \rightarrow 2^Q$ is a state transition function (if non-deterministic, otherwise, $\delta : Q \times \Sigma \rightarrow Q$)
- ▶ $q_0 \in Q$ is an initial state and Acc is an acceptance condition

ω -automata

An ω -automaton is a tuple $\mathcal{A} = (Q, \Sigma, \delta, q_0, Acc)$ where

- ▶ Q is a finite set of states
- ▶ Σ is a finite alphabet
- ▶ $\delta : Q \times \Sigma \rightarrow 2^Q$ is a state transition function (if non-deterministic, otherwise, $\delta : Q \times \Sigma \rightarrow Q$)
- ▶ $q_0 \in Q$ is an initial state and Acc is an acceptance condition

Run

A run ρ of \mathcal{A} on an ω -word $\alpha = a_1 a_2 \dots \in \Sigma^\omega$ is an infinite state sequence $\rho(0)\rho(1)\rho(2)\dots$ such that

- ▶ $\rho(0) = q_0$,
- ▶ $\rho(i) = \delta(\rho(i-1), a_i)$ if \mathcal{A} is deterministic,
- ▶ $\rho(i) \in \delta(\rho(i-1), a_i)$ if \mathcal{A} is non-deterministic,

ω -automata

An ω -automaton is a tuple $\mathcal{A} = (Q, \Sigma, \delta, q_0, Acc)$ where

- ▶ Q is a finite set of states
- ▶ Σ is a finite alphabet
- ▶ $\delta : Q \times \Sigma \rightarrow 2^Q$ is a state transition function (if non-deterministic, otherwise, $\delta : Q \times \Sigma \rightarrow Q$)
- ▶ $q_0 \in Q$ is an initial state and Acc is an acceptance condition

Run


A run ρ of \mathcal{A} on an ω -word $\alpha = a_1 a_2 \dots \in \Sigma^\omega$ is an infinite state sequence $\rho(0)\rho(1)\rho(2)\dots$ such that

- ▶ $\rho(0) = q_0$,
- ▶ $\rho(i) = \delta(\rho(i-1), a_i)$ if \mathcal{A} is deterministic,
- ▶ $\rho(i) \in \delta(\rho(i-1), a_i)$ if \mathcal{A} is non-deterministic,

Büchi Acceptance

For Büchi Acceptance, Acc is specified as a set of states, $G \subseteq Q$. The ω -word α is accepted if there is a run ρ of α such that $Inf(\rho) \cap G \neq \emptyset$.



ω -Automata with Büchi Acceptance







$$L(\mathcal{A}) = \{\alpha \in \Sigma^\omega \mid \alpha \text{ has a run } \rho \text{ such that } \text{Inf}(\rho) \cap G \neq \emptyset\}$$

Language accepted=Infinitely many b 's.





Comparing NFA and NBA



Comparing NFA and NBA




ω -Automata with Büchi Acceptance



- ▶ Left (T-B): Inf many b 's, Inf many a 's
- ▶ Right (T-B): Finitely many b 's, $(a + b)^\omega$



NBA and DBA

- ▶ Is every DBA as expressible as a NBA, like in the case of DFA and NFA?
- ▶ Can we do subset construction on NBA and obtain DBA?



NBA and DBA

- ▶ Is every DBA as expressible as a NBA, like in the case of DFA and NFA?
- ▶ Can we do subset construction on NBA and obtain DBA?




NBA and DBA

There does not exist a deterministic Büchi automata capturing the language finitely many a 's.


NBA and DBA

There does not exist a deterministic Büchi automata capturing the language finitely many a 's.




NBA and DBA

There does not exist a deterministic Büchi automata capturing the language finitely many a 's.




NBA and DBA

There does not exist a deterministic Büchi automata capturing the language finitely many a 's.



NBA and DBA

There does not exist a deterministic Büchi automata capturing the language finitely many a 's.



NBA and DBA

There does not exist a deterministic Büchi automata capturing the language finitely many a 's.

