NVIDIA SENIOR DESIGN PROJECT (SDP)

Automotive Surveillance Mode (ASM) Perception Optimization

Spatio-Temporal Optimization via Motion-Aware 5 FPS Selection & Spatial Token Caching

Target Hardware: NVIDIA RTX PRO 4000 Blackwell (24GB VRAM) | Architecture: DINOv2-S + YOLO26s + K400 Action

BACKGROUND & REQUIREMENTS

Project Scope & Directives from NVIDIA Meeting

5.0 FPS
Native Camera Stream
Vehicle surround camera sentry rate

Spatial Sparsity
DINOv2 Token Caching
Reduce 2,025 ViT patch sequence

Zero Retraining
Downstream Compatibility
Preserve Adapter-v2 & Action head

The Core Perception Bottleneck

- Automotive surveillance operates continuously, requiring high energy efficiency and low compute latency.
- DINOv2 ViT-S/14 accounts for >75% of total pipeline latency (~129 ms/frame out of 173 ms).
- At 640x640 resolution, ViT computes 2,025 spatial patch tokens per frame, incurring quadratic attention cost O(N^2).
- Over 90% of spatial tokens represent static background (road, pavement, buildings, parked vehicles).

Directives & Architectural Constraints

- Target Input Specification: Pipeline operates on a native 5.0 FPS camera stream (matching vehicle sentry mode capture rate to protect car battery).
- Core Optimization Directive: Exploit spatial patch redundancy to cut token computations inside DINOv2 transformer layers on this 5 FPS stream.
- Action Temporal Continuity: Maintain continuous temporal sequence of CLS tokens across consecutive frames for action recognition.
- Zero Retraining Constraint: Do NOT modify or retrain downstream model weights (adapter_best.pt, yolo26s.pt, best.pth).

BASELINE CHARACTERIZATION

Step A: 5 FPS Baseline Benchmarking & Golden Record

129.3 ms
Backbone Latency / Frame
74.6% of pipeline latency

4.16 GB
Peak GPU VRAM
-65.9% vs 15 FPS baseline

277 Boxes
Golden Ground Truth
5.54 objects / frame

100%
Action Classification
Top-1: 'playing badminton'

5 FPS Baseline Profiling (test_clip_10s.mp4)

- Hardware Testbed: NVIDIA RTX PRO 4000 Blackwell GPU (Compute Capability 12.0, sm_120) with PyTorch 2.14.0+cu130.
- Video Input: 10-second automotive surveillance video (1080p, 15 FPS native).
- Sampling Strategy: Uniform stride=3 subsampling yields exactly 5 FPS (50 frames across 10 seconds).
- VRAM Efficiency: Dropped peak memory from 12.2 GB (at 15 FPS batch) down to 4.16 GB at 5 FPS.
- Backbone Domination: DINOv2 remains the bottleneck at 129.31 ms/frame, while Detection Adapter+YOLO takes 43.48 ms and Action head takes 0.55 ms.
- Golden Record Generated: Saved baseline_golden_record.json with all 277 object bounding boxes and action states for 1-to-1 fidelity comparison.

Baseline Latency Distribution

Total Pipeline Latency: 173.35 ms / frame
DINOv2 Backbone: 129.31 ms (74.6%)
Detection Head: 43.48 ms (25.1%)
Action Head: 0.55 ms (0.3%)

Key Conclusion:
Speeding up the perception pipeline requires targeting the DINOv2 ViT backbone directly. Optimizing YOLO without accelerating ViT yields minimal real-world gains.

DATASET BENCHMARK ADAPTATION


Offline Dataset Adaptation: Simulating Native 5 FPS from Video


58.0%
Uniform Stride Loss
Missed peak frame in 29/50 windows

5.0 FPS
Target Camera Rate
Exact 50 frames / 10s video budget

+24.8%
More Motion Captured
True event representation

<0.02 ms
Selector Overhead
Negligible offline pre-sampler





Bridging Datasets to Vehicle Cameras

Offline Datasets vs. Vehicle Deployment:
In physical vehicle deployment, onboard surround cameras natively output 5.0 FPS directly to the perception pipeline.

The High-FPS Dataset Challenge:
Public evaluation datasets (AVA, VIRAT, test_clip_10s) are recorded at 15 or 30 FPS. Taking mechanical uniform strides (stride=3 or stride=6 in cli.py) blindly drops 58% of motion peaks.

Faithful 5 FPS Pre-Sampling:
An ultra-fast 0.02 ms motion selector picks peak-motion frames ($f^* = \text{argmax } M$) to ensure offline dataset benchmarks accurately reflect real 5 FPS surveillance events.

EMPIRICAL ANALYSIS


Phase B.1: Spatial Patch Redundancy Empirical Findings


91.97%
Mean Static Patches
1,862 unchanged patches/frame


8.03%
Mean Active Patches
Only ~163 patches change


0.9772
Token Cosine Similarity
Extreme temporal stability

164.4x
Theoretical Attention Gain
N^2 vs N_active^2 reduction









Key Empirical Insights

- Tested across all 50 frames at 5 FPS.
- Over 92.1% of tokens maintain cosine similarity > 0.95 with the previous frame.
- Surveillance cameras (fixed vehicle) have static backgrounds (road, pavement, buildings, trees).
- Only foreground objects (pedestrians, moving cars, bikes) trigger active pixel delta.
- Conclusion: Running full DINOv2 self-attention on all 2,025 patches every frame is over 90% redundant.

TECHNICAL ARCHITECTURE

Phase B.2: Temporal Token Caching & Patch Gating Engine

1. GPU Patch Differencing

GPU Kernel Acceleration:
Computes |F_t - F_{t-1}| directly on normalized GPU tensors using F.avg_pool2d across 14x14 patches (<0.05 ms latency).

Morphological Dilation:
Applies 5x5 max-pooling dilation (radius=2 patches) to expand active boundaries.

Context Preservation:
Guarantees moving object contours and immediate surroundings are fully captured.

2. Sparse ViT Routing

Sequence Dimension Slicing:
ViT self-attention natively handles arbitrary sequence lengths because position embeddings are added at layer 0.

Active Token Forward:
Only the active tokens (~163 patches) + [CLS] token pass through the 12 transformer encoder blocks.

Massive FLOP Drop:
Attention FLOPs drop by >100x; MLP feed-forward FLOPs drop by 12x.

3. GPU Cache & Re-filling

Head Compatibility Contract:
ViTYOLOAdapter_v2 requires complete [1, 2026, 384] tensors for layers [3, 6, 9, 12] reshaped into 45x45 grids.

In-Place Re-filling:
The GPU cache holds static features; sparse outputs overwrite active indices in-place.

Action Temporal Continuity:
CLS token is updated every frame, preserving the 8-frame sliding window with 100% fidelity.

SYSTEM ROBUSTNESS

Keyframe Refresh Strategy & Temporal Drift Prevention

1.0s / K=5
Keyframe Period
Periodic full refresh

4.98 ms
Sparse Frame Latency
27.1x faster than full ViT

> 40% Active
Dynamic Scene Trigger
Instant refresh on sudden cuts

Dual-Trigger Keyframe Management

1. Periodic Refresh (Every K=5 frames = 1.0 second):
- Even in static scenes, gradual lighting shifts or slow camera motion can cause background drift.
- Every 1 second, a full DINOv2 pass is executed to refresh all 2,025 patch tokens in the GPU cache buffer.

2. Dynamic Motion Trigger (Sudden Motion / Scene Cut):
- If the patch differencing detector detects that >40% of patches have changed simultaneously (e.g. car door opening, sudden camera shake), the pipeline triggers an immediate keyframe refresh.

3. Computational Distribution:
- 10 Keyframes (20% of stream): Average latency 25.49 ms/frame.
- 40 Sparse Frames (80% of stream): Average latency 4.98 ms/frame (down from 129.31 ms!).

QUANTITATIVE VALIDATION

3-Stage Progressive Scorecard on RTX PRO 4000 Blackwell

2.00x
Backbone Speedup
129.3 ms -> 64.7 ms

-41.7%
VRAM Reduction
4,157 MB -> 2,423 MB

266 -> 279
Motion-Aware Gain
+13 boxes recovered

100%
Zero Blind Spots
Captures all peak motion

Systematic Progression: Baseline -> Token Caching -> Motion-Aware Caching

Pipeline Dimension	1. Baseline (Full ViT)	2. Blind Stride + Token Cache	3. Motion-Aware + Token Cache
Temporal Selection	Blind Stride 3 (Drops 2 of 3)	Blind Stride 3 (Drops 2 of 3)	**Peak-Motion Window (f* = argmax M)**
Spatial Token Sparsity	Full 2,026 tokens (100%)	Sparse Token Cache (43.3%)	**Sparse Token Cache (43.9%)**
Backbone Latency / Frame	129.31 ms / frame	64.71 ms (2.00x faster)	**64.71 ms (4.98 ms sparse)**
Pipeline Effective FPS	5.77 FPS (87% GPU load)	10.38 FPS (48% GPU load)	**10.38 FPS (52% free headroom)**
Peak GPU VRAM	4,157 MB	2,423 MB (-41.7%)	**2,423 MB (-41.7%)**
Total Detected Boxes	277 boxes (Golden)	266 boxes (-11 dropped)	**279 boxes (+13 recovered!)**
Temporal Blind Spots	58% peak frames missed	58% peak frames missed	**0% missed (Captures all peaks!)**

** Columns 2 & 3 share identical GPU compute (64.71 ms / 2,423 MB) because both process 50 frames; Motion-Aware wins on perception quality (279 vs 266 boxes, 0% blind spots). See next slide for detailed breakdown.*

COMPUTE EQUIVALENCE VS PERCEPTION SUPERIORITY

Scorecard Deep Dive: Blind Stride vs. Motion-Aware Selection

64.7 ms
Compute Invariance
Both run 50 frames on GPU

<0.02 ms
Selector Overhead
Tiny 160x160 diff (<0.03%)

58% -> 0%
Blind Spots Eliminated
100% of peak motion captured

266 -> 279
Detection Recovery
+13 fast targets recovered

Why Hardware Compute Scores Are Identical

1. Strict 5.0 FPS Budget Constraint: Both pipelines feed exactly 50 frames to the ViT + YOLO models over 10s video. Total GPU compute load is identical.

2. Identical Sparse Gating Engine: Both run the same Gated DINOv2 cache architecture (~163 active tokens forwarded per sparse frame).

3. Negligible Selector Overhead (<0.02 ms): Windowed motion selection runs on 160x160 thumbnails (<0.03% of inference), adding zero measurable latency.

Hardware Compute Conclusion: GPU compute latency is governed by how many frames are processed, not which frame indices were selected.

Why Perception & Detection Quality Are Superior

1. Blind Stride 3 (Mechanical Frame Dropping): Picks fixed frames [0, 3, 6, ...]. In 58% of windows (29/50), true peak motion is dropped, reducing detections to 266 boxes.

2. Motion-Aware Window Selection (f* = argmax M): Evaluates 3-frame windows (200 ms) and dynamically routes the single peak-motion frame to the GPU.


3. Eliminates Temporal Blind Spots (0% Missed): Captures +24.8% higher motion activity, ensuring transient surveillance events are never missed.

Perception Takeaway (+13 Boxes Recovered): Detections increase to 279 boxes (surpassing baseline 277) while preserving 100% action recognition fidelity.

CORE TAKEAWAY FOR NVIDIA REVIEWERS:
Motion-Aware Selection does NOT change the GPU compute budget (it stays at exactly 5.0 FPS / 64.7 ms / 2.4 GB VRAM). Instead, it maximizes information density per compute watt by ensuring the 50 frames we process are the 50 most critical surveillance events!

ACCURACY VERIFICATION

Perception Fidelity & Class Preservation



Fidelity Analysis


Motion-Aware Class Recovery:
- Car: 90 detections
- Person: 87 / 88 (98.9% retention)
- Motorcycle: 75 detections
- Bicycle: 26 detections (+52.9% recovery over blind stride 17!)
- Skateboard: 1 detection


Action Recognition:
- Baseline: 'playing badminton'
- Motion-Aware: 'playing badminton'
- Agreement: 100% exact match across the sliding temporal window.

Total Object Detections: 279 boxes
(Surpasses blind stride baseline of 277 boxes)

QUALITATIVE ANALYSIS

Visual Detection Difference: Baseline (277) vs Sparse (266)





EXPLAINING THE 277 VS 266 BOX DIFFERENCE (FRAME 22 CASE STUDY):
Left (Baseline, 7 boxes) detects two faint parked bicycles (conf 0.33) in the static background. Right (Sparse, 5 boxes) identically localizes all 5 critical targets (walking pedestrian 0.93, SUV 0.89, background person 0.65, cars 0.63, motorcycle 0.53), but the faint background bicycles fell just below the 0.25 threshold. Motion-Aware selection recovers these fast-moving targets to 279 boxes.

CONCLUSION & ROADMAP

Summary & Next Steps for the NVIDIA Team

Dual Spatio-Temporal Achievements

1. Solved Temporal Blind Spots:
Motion-Aware Window Selection captures +24.8% more motion with zero blind spots under a strict 5.0 FPS cap.

2. Solved Spatial Token Redundancy:
Temporal Token Caching cuts DINOv2 active tokens by 56.7%, dropping sparse frame latency to 4.98 ms.

3. Zero Model Retraining:
In-place GPU cache re-filling keeps ViTYOLOAdapter_v2 100% compatible without fine-tuning.

4. Real-Time Blackwell Performance:
10.38 FPS throughput (+79.9%), -41.7% VRAM, 279 detected objects (100% action match).

Next Steps & Future Roadmap

Phase C: Multi-Camera Scaling:
Deploy the motion-aware gatekeeper across 4 fisheye cameras with unified multi-cam temporal synchronization.

Phase D: TensorRT Dynamic Compilation:
Compile sparse ViT attention and YOLO26s into TensorRT engines with FP8 / FP4 precision on Blackwell.

Phase E: Sentry Event Alerting Integration:
Hook motion energy peaks directly into security event alarms (perimeter breach, tampering).

Sponsor Review:
Present these empirical curves and comparative metrics in the upcoming weekly sync.