

```

-- =====
-- 1  profiles table
-- =====
create table profiles (
  id uuid primary key references auth.users(id) on delete cascade,
  email text,
  phone text,
  username text,
  created_at timestamp with time zone default now()
);

alter table profiles enable row level security;

-- =====
-- 2  hubs table
-- =====
create table hubs (
  id uuid primary key default gen_random_uuid(),
  user_id uuid references profiles(id) on delete cascade,
  slug text unique not null,
  title text,
  theme text default 'dark',
  created_at timestamp with time zone default now()
);

alter table hubs enable row level security;

-- =====
-- 3  links table
-- =====
create table links (
  id uuid primary key default gen_random_uuid(),
  hub_id uuid references hubs(id) on delete cascade,
  title text not null,
  url text not null,
  order_index int default 0,
  is_active boolean default true,
  created_at timestamp with time zone default now()
);

alter table links enable row level security;

-- =====
-- 4  rules table
-- =====
create table rules (
  id uuid primary key default gen_random_uuid(),
  link_id uuid references links(id) on delete cascade,
  rule_type text,
  rule_value jsonb,
  created_at timestamp with time zone default now()
);

alter table rules enable row level security;

-- =====
-- 5  click_events table

```

```
-- =====  
create table click_events (  
  id uuid primary key default gen_random_uuid(),  
  link_id uuid references links(id) on delete cascade,  
  user_agent text,  
  country text,  
  clicked_at timestamp with time zone default now()  
);  
  
alter table click_events enable row level security;
```