



# What is a Kubelet?

Kubernetes has tiny robots running inside every node, making sure your pods stay healthy and alive.

## What is a Kubelet?

- It's like the **"caretaker"** of a Kubernetes node.
- It ensures that containers in a pod are running as expected.
- If a pod crashes, the kubelet restarts it automatically! 🔄

🎯 **Think of Kubelet as a personal assistant for your node:**

- ✅ Checks if the pods should be running
- ✅ Talks to the API Server to get instructions
- ✅ Monitors pod health and reports back

## 1 What is Kubelet?

- A **node agent** that runs on each worker node in a Kubernetes cluster.
- Ensures that **Pods and containers are running** as expected.
- Continuously **monitors the node's health and status**.

## 2 Why Do We Need Kubelet?

- ✅ Ensures **Pods are running** according to the desired state.
- ✅ **Communicates with the Kubernetes API Server** to receive instructions.
- ✅ **Monitors node health** and reports status back to the control plane.

## 3 How Kubelet Works?

- Watches the **API Server** for assigned **Pods**.
- Pulls **container images** and starts containers using **Container Runtime (Docker, containerd, CRI-O)**.
- Continuously **monitors running Pods** and restarts them if needed.

- Sends **Pod and node status** back to the **Kubernetes Control Plane**.

#### 4 Key Responsibilities of Kubelet

Feature	Description
<b>Pod Lifecycle Management</b>	Ensures Pods and their containers are running.
<b>Health Monitoring</b>	Checks Pod and Node health, restarts failed containers.
<b>Container Runtime Interaction</b>	Communicates with Docker, containerd, or CRI-O.
<b>Logs and Metrics Collection</b>	Collects logs and sends them to the API Server.
<b>Node Status Reporting</b>	Sends node status (CPU, memory, disk) to Kubernetes.

---

## Check Kubelet Status in Kind Cluster

### 1 Get the list of nodes in your Kind cluster:

```
sh
-----
kubectl get nodes -o wide
```

### 2 Enter a Kind node container (since Kind runs nodes as Docker containers):

```
sh
-----
docker ps # List running containers
docker exec -it <kind-node-name> bash # Replace <kind-node-name> with actual
node name
```

For example, if your Kind cluster is named kind, a node might be kind-control-plane:

```
sh
-----
docker exec -it kind-control-plane bash
```

### 3 Check if Kubelet is running inside the node

Inside the Kind node, run:

```
sh
-----
ps aux | grep kubelet
```

or

```
sh
-----
pgrep -af kubelet
```

### 4 Check Kubelet logs (useful for debugging issues)

```
sh
-----
journalctl -u kubelet # Not available in Kind (systemd not used)
```

Instead, check logs using:

```
sh
-----
docker logs kind-control-plane | grep kubelet
```

---

## Alternative: Checking Node Health from Kubernetes

If you don't want to enter the container, you can check the node status from outside:

```
sh
-----
kubectl describe node kind-control-plane
```

Look for **Kubelet version** and **Ready status** in the output.

---

### Key Benefits of Kubelet

- ✅ Ensures high availability by restarting failed containers.
- ✅ Improves observability by reporting logs and metrics.
- ✅ Ensures correct scheduling by reporting node capacity and health.

### What is the primary role of the Kubelet in a Kubernetes cluster?

- a) Managing Kubernetes control plane components
- b) Managing network policies
- c) Ensuring containers are running in a Pod
- d) Scheduling Pods to worker nodes

1.

**Answer:** c) Ensuring containers are running in a Pod

### 2. Which of the following best describes how the Kubelet interacts with the API Server?

- a) It registers nodes and updates node status
- b) It schedules Pods across nodes
- c) It deploys network policies
- d) It manages etcd database directly

**Answer:** a) It registers nodes and updates node status

### 3. Where does Kubelet get Pod specifications from?

- a) Only from the Kubernetes API server
- b) From etcd directly
- c) From the Docker daemon
- d) Only from a YAML file on the node

**Answer:** a) Only from the Kubernetes API server

