TITLE OF THE PROJECT-

ENFORCE LEAST-PRIVILEGE ACCESS THROUGH IDENTITY-AWARE,

APPLICATION-SPECIFIC ACCESS POLICIES USING ZSCALER PRIVATE ACCESS (ZPA).

List of teammates-

Team ID : SWTID-2026-4641

s.no	**Name**	**Collage**	**contact**
1	ABHIJITH S	SREE NARAYANA GURU COLLEGE	abhijithsanthosh0006@ gmail.com
2	MUHAMMED ASHIK C K	SREE NARAYANA GURU COLLEGE	mohashik50@gmail.com
3	SREERAM V	SREE NARAYANA GURU COLLEGE	sreeramprasanna733@ gmail.com
4	SRIKANTH S	SREE NARAYANA GURU COLLEGE	srikanthsri200618@gmail.com
5	SREEHARI K G	SREE NARAYANA GURU COLLEGE	sreehari01087@gmail.com

PROJECT DETAILS:

TITLE:

Enforce least-privilege access through identity-aware, application-specific access policies using Zscaler Private Access (ZPA).

INTRODUCTION:

In an era where the digital landscape is constantly evolving, organizations face an ever-increasing threat from cyberattacks. The need for swift and effective incident response has become paramount to safeguard sensitive data, protect digital assets, and maintain the trust of stakeholders. In response to this growing challenge, we present a visionary project: the development of an AI-driven incident response platform that empowers cybersecurity teams with the tools to automate and enhance incident triage and response tasks. In response to the evolving threat landscape and the dissolution of the traditional network perimeter, modern enterprises are rapidly shifting away from legacy VPN-centric remote access models. These conventional approaches often grant excessive network-level access, creating a significant attack surface and increasing the risk of lateral threat movement. To address these challenges, this project centers on the implementation of a Zero Trust security architecture, fundamentally operating on the principle of "never trust, always verify." By moving beyond location-based access, we aim to establish a security posture where trust is no longer implicit, and access is determined by granular context rather than network connectivity. The core of this initiative involves the deployment of Zscaler Private Access (ZPA), a cloud-delivered Zero Trust Access solution designed to create identity-aware, application-specific connectivity. Unlike traditional VPNs that place users on the internal network, ZPA leverages a "service-initiated" model to establish direct, one-to-one connections between authorized users and specific applications, completely hiding the corporate network and IP address space from the internet. This ensures that users connect exclusively to the applications they are permitted to access, based on continuous identity verification and context, rendering the applications invisible to unauthorized users and preventing common attack vectors such as port scanning and distributed denial-of-service (DDoS) attacks. Ultimately, this project will enforce a least-privilege access model, ensuring users and devices are granted the minimum required access necessary to perform their functions. By decoupling application access from network access, we will eliminate the risk of lateral movement across the network, as users have no visibility or connectivity to other hosts. This strategic move not only significantly enhances security by reducing the attack surface but also simplifies the user experience and reduces operational overhead associated with legacy remote access infrastructure, positioning the organization at the forefront of secure and efficient access management.

ABSTRACT

The proliferation of hybrid work and cloud-based resources has rendered traditional perimeter-based security models, such as VPNs, obsolete and increasingly dangerous. These legacy solutions often provide overly broad network access, exposing organizations to significant risks including lateral threat movement and an expanded attack surface. This project addresses these vulnerabilities by implementing a Zero Trust Architecture (ZTA) utilizing Zscaler Private Access (ZPA). The primary objective is to transition from network-centric to identity-centric access, thereby enforcing the principle of least privilege. The methodology involves deploying ZPA's cloud-based service to create application-specific, identityaware micro-tunnels. Unlike conventional VPNs that place users on the internal network, this solution establishes direct, one-to-one connections between verified users and authorized applications. The network infrastructure and all non-authorized applications remain completely invisible to the end-user, effectively eliminating surface for reconnaissance and attack. Access policies are dynamically governed by user identity, device posture, and contextual attributes, ensuring that connectivity is strictly limited to what is explicitly required for specific job functions. The implementation of ZPA successfully decouples application access from network access, resulting in a demonstrable reduction in the organization's attack surface and the complete prevention of lateral movement. This project delivers a robust, scalable, and user-friendly remote access framework that aligns with modern security best practices. By shifting to an identity-aware, least-privilege model, the organization significantly enhances its security posture while simultaneously reducing operational complexity and improving the end-user experience.

Use Case Scenarios:

Scenario 1:Finance Department Access to ERP System

A senior accountant in the finance department needs to access the corporate Enterprise Resource Planning (ERP) system to process monthly payroll. The user connects from a remote location using their company-managed laptop. Upon launching the ZPA Client Connector, they authenticate via Azure Active Directory with multi-factor authentication (MFA). ZPA evaluates the user's identity, group membership (Finance_ERP_Users), device posture (antivirus active, disk encryption enabled), and connection context. The policy engine determines that the user is authorized and brokers a secure, direct micro-tunnel to the ERP application only. The user can interact with the ERP interface, but has no visibility or network- level access to any other internal systems, such as development servers or the HR database.

Output:

• User authenticated and authorized based on identity and group membership
• Direct micro-tunnel established specifically to the ERP application
• All other internal applications and network segments remain invisible and inaccessible

Scenario 2: Contractor Access to Specific Project Repository

An external software consultant is hired for a three-month project and requires access only to a specific Git repository hosted on an internal server. The contractor is onboarded as a guest user in the identity provider and assigned to the "Project_X_Contractors" group. When the contractor connects using the ZPA client, the system verifies their identity and checks the device for basic security compliance (OS patch level, firewall enabled). ZPA enforces a policy that grants access exclusively to the Git repository application (port 22/SSH or port 443/HTTPS) during business hours (9 AM to 5 PM). The contractor can clone, push, and pull code, but cannot discover or connect to any other internal resources, including the corporate intranet or file servers.

Output:

• Time-bound and role-specific access enforced
• Contractor restricted to a single application (Git repository)
• Lateral movement to adjacent systems completely blocked

Scenario 3: Executive Access to Confidential Board Documents

Acompany executive needsto access a confidentialfolder containing board meeting materials hosted on an internal file server. The executive connects from a tablet device while traveling internationally. ZPA integrates with the mobile device management (MDM) solution to verify that the tablet is compliant (not jailbroken, passcode enabled, encryption active). Upon successful authentication, ZPA evaluates the policy: "If user is in 'Executive_Board' group AND device is MDM-compliant AND connection is from a trusted country (allowlist), THEN grant access to 'Board_Documents' application." The executive is connected directly to the specific file share, and all data in transit is encrypted via TLS. Any attempt to access other shares or network resources is automatically blocked and logged.

Output:

• Context-aware access based on user role, device posture, and geographic location
• Granular access to a specific file share (Board_Documents)
• Comprehensive logging of access events for audit and compliance

Scenario 4: IT Administrator Access to Server Management Interfaces

A systems administrator requires access to management interfaces (SSH for Linux servers and RDP for Windows servers) to perform routine maintenance. Instead of granting VPN access to the entire management network, ZPA is configured to treat each server or management interface as a separate application segment. The administrator authenticates and is presented only with the specific servers they are authorized to manage based on their IT subgroup (e.g., "Linux_Admins" see only Linux servers; "Windows_Admins" see only Windows servers). When the admin connects via SSH to a Linux server, ZPA creates a direct micro-tunnel to that specific IP and port combination. The admin cannot scan the subnet, access other servers, or initiate connections to non-authorized ports.

Output:

- Micro-segmentation at the individual server/interface level
- Role-based access controlling visibility of specific management consoles
- Elimination of network-level reconnaissance capabilities for admins

Scenario 5: Mergers and Acquisitions Integration

Acompany acquires a smaller firm and needs toprovide the acquired company's HR team with temporary access to the parent company's benefits enrollment application. The acquired company's users are added as external collaborators in the identity provider with limited attributes. ZPA policies are created that specifically grant the "Acquired_HR" group access only to the "Benefits_App" (a web application hosted internally). The acquired users install the ZPA client, authenticate, and are connected directly to the benefits application. Because ZPA provides access without network connectivity, the parent company's entire internal network remains completely hidden and protected. The acquired users cannot ping, scan, or access any other corporate resource. After six months, when the integration is complete and users are migrated to the parent identity system, the temporary policies are revoked.

Output:

- Secure, temporary access provided without network exposure
- Complete network invisibility protecting the parent company's infrastructure
- Simplified deprovisioning through policy revocation rather than complex network changes

Stage-1

Title:

Enforce least-privilege access through identity-aware, application-specific access policies using Zscaler Private Access (ZPA)

Overview:

In response to the evolving threat landscape and the dissolution of the traditional network perimeter, modern enterprises are rapidly shifting away from legacy VPN-centric remote access models. These conventional approaches often grant excessive network-level access, creating a significant attack surface and increasing the risk of lateral threat movement. To address these challenges, this project centers on the implementation of a Zero Trust security architecture, fundamentally operating on the principle of "never trust, always verify." By moving beyond location-based access, we aim to establish a security posture where trust is no longer implicit, and access is determined by granular context rather than network connectivity. The core of this initiative involves the deployment of Zscaler Private Access (ZPA), a cloud- delivered Zero Trust Access solution designed to create identity-aware, application-specific connectivity. Unlike traditional VPNs that place users on the internal network, ZPA leverages a "service-initiated" model to establish direct, one-to-one connections between authorized users and specific applications, completely hiding the corporate network and IP address space from the internet. This ensures that users connect exclusively to the applications they are permitted to access, based on continuous identity verification and context, rendering the applications invisible to unauthorized users and preventing common attack vectors such as port scanning and distributed denial-of-service (DDoS) attacks. Ultimately, this project will enforce a least- privilege access model, ensuring users and devices are granted the minimum required access necessary to perform their functions. By decoupling application access from network access, we will eliminate the risk of lateral movement across the network, as users have no visibility or connectivity to other hosts. This strategic move not only significantly enhances security by reducing the attack surface but also simplifies the user experience and reduces operational overhead associated with legacy remote access infrastructure, positioning the organization at the forefront of secure and efficient access management.

List of Vulnerability Table:

s.no	Vulnerability Name	CWE/CVE-NO
1	Cross-site scripting (stored)	79
2	Broken Access Control	285
3 4	SQL Injection	89 285 639 732
5 6	Broken Authentication	352 319 1021
7 8	Insecure Direct Object Reference	310 79 79 200
9 10	Security Misconfiguration	
11	Cross-Site Request Forgery	
12	Cleartext Transmission ofSensitive Information	
13	ClickJacking	
	webserver allows password auto-completion	
	Cross-site scripting (DOM-based XSS)	
	JQuery 1.2 < 3.5.0 Multiple XSS	
	Information Exposure (Web ServerHTTPHeader Internal IP Disclosure)	
14	Information Exposure (SSL (Multiple Issues))	200
15	Information Exposure (HTTP (Multiple Issues))	200
16	OS Identification Failed	200

Report:-

Vulnerability name:Cross site scripting (stored)
CWE: 79
OWASP category: A03:2021 -Injections

Description:

It occurs when a malicious script is injected directly into a vulnerable web application. Reflected XSS involves the reflection of a malicious script of a web application, onto a user's browser.

Business Impact:

The application stores dangerous data in a database, message forum, visitor log, or other trusted data store. Later, the dangerous data is subsequently read back into the application and included in dynamic content. From an attacker's perspective, the optimal place to inject malicious content is in an area that is displayed to either many users or particularly interesting users. Interesting users typically have elevated privileges in the application or interact with sensitive data that is valuable to the attacker. If one of these users executes malicious content, the attacker may be able to perform privileged operations on behalf of the user or gain access to sensitive data belonging to the user.



Stage-2
Title:nessus scan

Overview:

A Nessus scan is a cybersecurity process used to identify vulnerabilities, misconfigurations, and security weaknesses in computer systems, networks, and applications. Developed by Tenable, Nessus is one of the most widely used vulnerability assessment tools by security professionals and organizations around the world. The primary purpose of a Nessus scan is to detect potential security risks before attackers can exploit them. It works by scanning target devices such as servers, desktops, routers, firewalls, and web applications to find known vulnerabilities, missing software patches, outdated services, weak configurations, and other security issues. During a scan, Nessus uses thousands of regularly updated plugins that check systems against a large database of known vulnerabilities and security flaws, including publicly disclosed vulnerabilities like those listed in MITRE's Common Vulnerabilities and Exposures database. The scanning process usually begins when a security administrator defines a target, which could be a single IP address, a range of addresses, or a domain. Nessus then performs different types of tests such as port scanning, service detection, configuration checks, and vulnerability validation. Scans can be performed in two main ways: unauthenticated scans and credentialed scans. An unauthenticated scan checks systems from an external perspective without logging into the target device, similar to how an attacker might attempt to probe a system from outside the network. In contrast, a credentialed scan uses authorized login credentials, such as SSH for Linux systems or administrative credentials for Windows machines, allowing Nessus to inspect the system more deeply and detect vulnerabilities that may not be visible externally. Once the scanning process is completed, Nessus generates a detailed report that lists discovered vulnerabilities categorized by severity levels such as critical, high, medium, low, and informational. Each vulnerability entry usually includes a description of the issue, its potential impact, the affected software or configuration, and recommended remediation steps such as installing security patches or changing configuration settings. These reports help system administrators and security teams prioritize and fix security problems efficiently. Nessus scans are widely used in penetration testing, vulnerability management programs, compliance audits, and routine security assessments. Organizations often run regular scans to ensure their systems remain secure and compliant with security standards such as industry best practices. By identifying vulnerabilities early, Nessus helps organizations strengthen their cybersecurity posture, reduce the risk of cyberattacks, and maintain a more secure IT environment.

sl.no	Vulnerability Name	Severity	Plugins
1	**Nessus SYN scanner**	Info	11219
2	**Service Detection**	Info	22964
3	**Web Server No 404 Error Code Check**	Info	10386
4	**ICMP Timestamp Request Remote Date Disclosure**	Low	10114
5	**Nessus Scan Information**	Info	19506

Report: Vulnerability Name:**Nessus SYN scanner** Severity:info Plugins:11219

Description:This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution:Protect your target with an IP filter.

Business Impact:The **Nessus SYN Scanner** finding indicates that the target system responds to SYN-based port scanning, allowing external entities to identify open TCP ports and running services. Although this is an informational finding and does not represent a direct vulnerability, it exposes the system to reconnaissance activities commonly used by attackers to map network services and identify potential entry points. If malicious actors are able to discover exposed services, they may attempt further exploitation of known vulnerabilities associated with those services. Additionally, frequent or large-scale scanning may place minor strain on network devices such as firewalls if they are not properly configured. From a business perspective, the ability to perform such scans highlights a potential gap in network filtering and monitoring controls, which could increase the risk of targeted attacks if not properly managed. Implementing appropriate IP filtering, firewall restrictions, and monitoring mechanisms can help reduce exposure to unauthorized scanning and reconnaissance attempts.

Vulnerability name:**Service Detection**

Severity:info

Plugins:22964

DescriptionNessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Vulnerability name:**Web Server No 404 Error Code Check**

Severity:info Plugins:10386 Description:The remote web server is configured such that it does

not return '404 Not Found'
error codes when a nonexistent file is requested, perhaps returning instead a site map, search page or authentication page.

Nessus has enabled some counter measures for this. However, they might be insufficient. If a great number of security holes are produced for this port, they might not all be accurate.

Vulnerability name:**ICMP Timestamp Request Remote Date Disclosure**

Severity:Low Plugins:10114 Description:the remote host answers to an ICMP timestamp request. This allows an attacker to
know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.
solution:Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Vulnerability name:**Nessus Scan Information**

Severity:info

Plugins:19506

Description:

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.

- The type of scanner (Nessus or Nessus Home).

- The version of the Nessus Engine.

- The port scanner(s) used.

- The port range scanned.

- The ping round trip time

- Whether credentialed or third-party patch management checks are possible.

- Whether the display of superseded patches is enabled

- The date of the scan.

- The duration of the scan.

- The number of hosts scanned in parallel.

Stage-3

Title: Enforce least-privilege access through identity-aware, application-specific access policies using Zscaler Private Access (ZPA).

Zero Trust Network Access (ZTNA) ZeroTrust Network Access (ZTNA) is a cybersecurity framework that shifts access control from a network-centric model to an identity-centric model. The foundational principle of ZTNA is "never trust, always verify," meaning that no user or device is trusted by default, regardless of whether they are connecting from inside or outside the corporate network. Unlike traditional remote access solutions that grant users broad access to the entire network, ZTNA creates a secure, application-specific tunnel between the user and the resources they are authorized to access. This ensures that the application remains invisible to unauthorized users and the broader internet, effectively shrinking the attack surface and eliminating the risk of lateral movement across the network.

Zscaler Private Access (ZPA)
Zscaler Private Access(ZPA) is a cloud-delivered ZTNA solution that provides identity- and contextbased access to private applications without granting network- level access. ZPA operates on a "serviceinitiated" model, where users connect to the Zscaler cloud, and the cloud brokers a secure connection to the specific application via ZPA App Connectors deployed in the data center or cloud environment. Because ZPA never places the user on the corporate network, internal IP addresses and network infrastructure are completely hidden. Access policies are dynamically enforced based on user identity, group membership, device posture, and location, ensuring that each user sees only the applications they are explicitly permitted to use.

Identity-Aware
Access Identity-aware access is a security model that bases access decisions on who the user is, rather than where they are connecting from. ZPA integrates directly with existing identity providers (IdPs) such as Microsoft Active Directory, Azure AD, Okta, or Ping Identity. This integration allows security teams to leverage existing user attributes, group memberships, and roles to build granular access policies. For example, a policy can state that only members of the "Finance" group, using a company-managed device, can access the "SAP Finance" application during business hours. This ensures that access is tightly coupled with the user's identity and context, reducing reliance on static IP addresses or network segments.

Application-Specific Access Policies

Application-specific access policiesare the core enforcement mechanism within ZPA. Instead of creating rules that allow traffic to entire subnets or IP ranges, administrators define policies that target individual applications or groups of applications. These policies are written in plain language logic and can incorporate multiple conditions, including user identity, device posture, location, and time of day. ZPA allows for the segmentation of internal applications—such as HR systems, internal wikis, development servers, and database interfaces—so that each application has its own unique access policy. This micro-segmentation ensures that a user authenticated for one application has no visibility or connectivity to any other application.

conclusion:

Stage 1: In conclusion, web application testing is a crucial process that ensures the security, functionality, and reliability of web-based software. It involves a comprehensive evaluation of various aspects, including user interface, functionality, performance, and security to identify and rectify issues before they impact end-users. This process not only enhances the quality of web applications but also bolsters their resilience against potential threats and vulnerabilities. In an age where online services and applications are integral to our daily lives, effective web application testing is essential to deliver a seamless and secure user experience.

Stage 2: The Nessus report for the specific website has highlighted key security insights. It identified vulnerabilities, categorized by severity, with a focus on critical and high-risk issues that need immediate attention. Recommendations for addressing these vulnerabilities include patching, reconfiguration, and other security measures, with a priority on actions that can have the most significant impact. Compliance with industry standards and best practices is considered, ensuring alignment with recognized security benchmarks like OWASP guidelines. The report underscores the need for continuous monitoring, regular updates, and ongoing security efforts to maintain a strong security posture. In summary, the Nessus report offers a clear view of the website's security state, provides guidance on mitigating vulnerabilities, and stresses the importance of sustained vigilance against evolving threats.

Stage 3: The implementation of Zscaler Private Access marks a pivotal shift from a vulnerable, networkcentric security model to a resilient, identity-centric Zero Trust architecture. By enforcing leastprivilege access and rendering private applications invisible to the internet, this project effectively neutralizes the threats of lateral movement and network-based attacks. The solution not only fortifies the organization's security posture against modern cyber threats but also delivers a seamless and high-performance experience for a distributed workforce. Furthermore, the decoupling of access from the network simplifies IT operations, reduces dependency on legacy VPN infrastructure, and provides granular visibility into user-application interactions. Ultimately, this initiative establishes a future-ready foundation for secure digital transformation

Future scope:

Stage 1: future scope of web application testing

The future scope of web application testing is promising and evolving rapidly, driven by the continuous growth of the internet and web-based applications. Here are some key aspects of its future scope:

▪ Increased Demand: As more businesses and services move online, the demand for web applications continues to grow. This, in turn, increases the demand for web application testing to ensure security, reliability, and functionality.

▪ Advanced Technologies: The complexity of web applications is rising with the integration of advanced technologies like AI, IoT, and blockchain. Testing these cutting-edge applications will require specialized skills and tools.

▪ Security Emphasis: With the growing number of cyber threats and data breaches, security testing for web applications will become even more critical. Testers will need to focus on vulnerabilities, data protection, and compliance with regulations like GDPR.

▪ Mobile and Cross-Browser Testing: Mobile usage is on the rise, and web applications must be responsive and functional on various devices and browsers. Testing for cross-compatibility will be essential.

▪ Performance Testing: As user expectations for speed and performance increase, load testing, stress testing, and other performance testing types will be crucial to ensure web applications can handle traffic spikes.

Stage 2: future scope of the testing process you understood. The future scope of the web application testing process, particularly in terms of identifying vulnerabilities, is exceedingly promising due to the continuous growth of digital platforms, the escalating importance of cybersecurity, and the ever-evolving threat landscape. Here are some key aspects that highlight the prospective scope of web application testing for vulnerability discovery:

▪ AI-Driven Testing: The integration of artificial intelligence (AI) and machine learning (ML) into web application testing tools will revolutionize the way vulnerabilities are identified. AI algorithms can swiftly scan vast amounts of code and data to pinpoint vulnerabilities that might elude human testers.

▪ IoT and Mobile App Testing: With the proliferation of Internet of Things (IoT) devices and the increasing usage of mobile applications, the scope of web application testing will extend to encompass these areas. Ensuring the security of IoT devices and the interfaces they use will become critical.

▪ Blockchain and Cryptocurrency Security: As blockchain technology and cryptocurrencies continue to gain traction, security testing will be imperative to safeguard transactions and digital assets. Ensuring the robustness of blockchain-based

applications will be a specialized niche in web application testing. Serverless Architectures: With the adoption of serverless computing, web application testing will need to adapt to assess the security of serverless functions and APIs. Ensuring that serverless components are free from vulnerabilities will be paramount. ▪ Container Security: As containerization technologies like Docker and Kubernetes become ubiquitous, web application testing will extend to cover container security. This includes ensuring that container images and orchestration configurations are free from vulnerabilities.

Stage 3: future scope of Zero Trust

The successful deployment of ZPA lays the groundwork for a broader, more integrated security ecosystem. Future enhancements can be explored to further mature the organization's security capabilities:

▪ Integration with Zscaler Internet Access (ZIA): Converging Private Access (ZPA) with Internet Access (ZIA) to create a unified Secure Access Service Edge (SASE) platform, managing all web and private traffic through a single policy framework.

▪ Advanced Device Posture Checking: Moving beyond basic compliance to incorporate real-time risk scores from EDR tools, blocking access if a device shows signs of active compromise.

▪ Privileged Remote Access: Extending ZPA to third-party vendors and contractors with time-bound, audited access to specific critical systems, replacing jump boxes and bastion hosts.

▪ IoT/OT Segmentation: Applying the same micro-tunneling principles to Internet of Things (IoT) and Operational Technology (OT) devices to ensure they can only communicate with specific management servers.

▪ AI-Driven Anomaly Detection: Leveraging machine learning on ZPA logs to detect behavioral anomalies, such as a user accessing an application at an unusual hour or from a strange location, triggering automated MFA challenges or access revocation.

▪ Cloud Workload Protection: Utilizing ZPA to secure connections between containers and microservices in multi-cloud environments (AWS, Azure, GCP), ensuring east-west traffic between workloads is encrypted and authenticated.

▪ Automated Provisioning/Deprovisioning: Enhancing the identity provider integration to automatically revoke application access the moment an employee is terminated or changes roles, ensuring near real-time access control.

▪ Digital Experience Monitoring (DEM): Implementing DEM tools to proactively monitor the enduser experience, identifying network latency or application performance issues before they impact productivity.

Topics explored:

1. Zscaler
2. Zero trust
3. ZPA
4. VPN
5. MISP
6. College Network Information
7. Deployment of SOC in the College
8. Threat Intelligence
9. Incident Response

Tools Explored:

- Nessus Scanner