

Problem Set #4

- Rules of the game remain the same. Submissions must be single file in L^AT_EX format at the upload link set up in cse moodle page of the course.

- (15 points) Argue whether the following functions qualify to be called as a *resource* according to Blum's resource axioms.

$$(a) \text{ (3 points) } \text{VALUE}(M, x) = \begin{cases} 0 & \text{if } M \text{ rejects } x, \\ 1 & \text{if } M \text{ accepts } x, \\ \text{undefined} & \text{if } M \text{ does not halts on } x \end{cases}$$

Answer

The above resource function satisfies Blums first axiom i.e. it is defined only when M halts on x . However, given a M, x, k , it is not decidable to check if $\text{VALUE}(M, x) = k$. Hence it is not a resource.

Consider $R = \{(M, x) : \text{VALUE}(M, x) = k\}$

Suppose R was decidable via a total TM N , then MP can be decided by giving $(M, x, 1)$ as input to N . But, MP is not decidable and hence R is not decidable.

- (5 points) A *turn* of tape head is defined as movement of tape head from $L \rightarrow R$ or $R \rightarrow L$.

$$\text{TURN}(M, x) = \begin{cases} \text{No. of turns that tape head makes when } M \text{ runs on } x & \text{if } M \text{ halts on } x \\ \text{undefined} & \text{otherwise} \end{cases}$$

$$(c) \text{ (5 points) } \text{COUNT}(M, x) = \begin{cases} \text{No. of times } M \text{ visits a state } q & \text{if } M \text{ halts on } x \\ \text{undefined} & \text{otherwise} \end{cases}$$

- (5 points) Show that if $\text{NTIME}(n) = \text{DTIME}(n)$ then $P = NP$. (Padding !!)
- (10 points) Space Hierarchy theorem implies the following: For any $k > 0$, There is a language in $\text{DSpace}(n^{k+1})$ that is not in $\text{DSpace}(n^k)$. Use this and a padding argument to show that: $P \neq \text{DSpace}(n)$. (6pts)

(Note that we do not know the containment in either direction.)

You can do this in two steps:

- For every language L define, $L_{pad} = \{x01^{|x|^2} : x \in L\}$.
Argue that L_{pad} is in $P \implies L \in P$.

- Show an L_{pad} which is in $\text{DSpace}(n)$ but whose corresponding L is not in $\text{DSpace}(n)$.

- (5 points) Show that if $\text{SAT} \in NP \cap \text{coNP}$ then $NP = \text{coNP}$. (Definitions !)
- (5 points) If L, L' are in NP , then show that $L \cup L', L \cap L'$ are in NP . (Definitions !)

6. (5 points) If L, L' are in $\text{NP} \cap \text{coNP}$, then show that $L \oplus L'$ defined as

$$L \oplus L' = \{x : x \text{ is in one of } L \text{ or } L' \text{ but not both.}\}$$

is in $\text{NP} \cap \text{coNP}$. (Definitions !)

7. (15 points) Consider the following language: $\text{PRIMES} = \{n \mid n \text{ is a prime}\}$ where the input n is in binary. Without using the known result that PRIMES is in P , solve the following:

- (a) (5 points) Show that PRIMES is in coNP .
- (b) (10 points) Here is Lucas test for primality (you don't need prove it) : n is prime if and only if there is an integer $a \in \{2, \dots, n-1\}$ with $a^{n-1} \equiv 1 \pmod{n}$, and for every prime factor q of $n-1$: $a^{\frac{n-1}{q}} \not\equiv 1 \pmod{n}$. Use this test to show that PRIMES is in NP .

Hence conclude that PRIMES is in $\text{NP} \cap \text{coNP}$.

8. (10 points) Prove that reachability in undirected forests (a possibly disconnected acyclic undirected graph) can be solved in log-space. That is, given (T, s, t) where T is an undirected forest, it can be tested in log-space whether s is connected to t by a path.
9. (18 points) Let $\text{E} = \bigcup_{c>0} \text{DTIME}(2^{cn})$ and $\text{NE} = \bigcup_{c>0} \text{NTIME}(2^{cn})$. A set A is called *sparse* if there is a polynomial p , such that $|\{x \in A : |x| = n\}| \leq p(n)$. A set A is called *tally set* if $A \subseteq \{1\}^*$. Prove that following are equivalent.
1. Restricted to tally sets $\text{NP} = \text{P}$. That is all tally sets in NP are in P .
 2. Restricted to sparse sets $\text{NP} = \text{P}$. That is all sparse sets in NP are in P .
 3. $\text{E} = \text{NE}$

Hence conclude that $\text{E} \neq \text{NE} \implies \text{P} \neq \text{NP}$.

Hint : Try for $(b) \implies (a) \implies (c) \implies (b)$. For the second implication : consider the language $L_{\text{tally}} = \{1^{2^{|x|}} : x \in L\}$. This will not work, but a slight modification of this language which includes some more information about x will work !.

For the third implication, consider the language

$$L_{\text{order}} = \{(k, i, c) : \text{the } i^{\text{th}} \text{ bit of the } k^{\text{th}} \text{ string (in lex order) in } L \text{ is } c\}$$

10. (7 points) Imagine a world in which $\text{P} = \text{NP}$. Now show that there is a polynomial time algorithm which given a Boolean formula ϕ produces a satisfying assignment for ϕ if ϕ is satisfiable. (Hint : Use queries to SAT).