

Problem Set #6

1. (10 points) Oracle Queries.

- (a) Argue that $P^P = P$. Why does not the same argument work for NP and give $NP^{NP} = NP$?
- (b) If $NP = coNP$, argue that $PH = \Sigma_1^P$.

Solution:

(a) $P^P \subseteq P$

Let $L \in P^P$. There exists an oracle TM N such that, it runs in polynomial time and has access to a language in P as an oracle. This can be simulated by deterministic polynomial time machine M without the oracle as follows :

M runs on the input in the same way as N . Except whenever N makes query to the oracle to check if $x \in K$ where K is the oracle, M runs the machine corresponding to the oracle language on x and gets the answer. It then proceeds in the similar way as the machine N . Since the oracle is a language in P , the simulation of the query to oracle takes deterministic polynomial time. Hence , M runs in polynomial time.

$P \subseteq P^P$

This containment is trivially true, since the machine accepting P need not use the oracle and hence belongs to P^P

From above two containments, $P^P = P$

The above argument wont work for NP because, when the oracle gives the answer as no, the same thing cannot be determined by simulating a NP machine in polynomial time. Since , the time for a non deterministic machine is defined as the length of the shortest accepting path. Hence, the rejecting paths in the non deterministic tree may not be of polynomial length.

(b) This can be shown using induction on i of Σ_i^P .

Base case. $i = 2$.

we have to show $NP^{NP} = NP$. The reverse containment is trivially true. To show the forward containment, we can simulate the queries on the oracle by simulating the two non deterministic machines corresponding to L (say M) and

\overline{L} (say N) . There exists a non deterministic polynomial time machine for \overline{L} because $\text{NP} = \text{coNP}$.

Whenever the original machine made a query to oracle, simulate both the non deterministic machine in time sharing fashion. If M accepts, interpret as a yes answer by the oracle and continue calculation as the original machine. If N accepts, interpret as a no answer by the oracle and continue calculation as the original machine. Since, both M and N accepts in polynomial time, this new machine also runs in polynomial time. Hence, $\Sigma_2^P = \Sigma_1^P$.

Let for some $k > 2$, $\Sigma_k^P = \Sigma_1^P$.

Σ_{k+1}^P is language which can be accepted in NP time given an oracle to Σ_k^P . Since, from induction hypothesis, $\Sigma_k^P = \Sigma_1^P$, this can be accepted by a machine in NP time which has oracle access to NP . Similar to the above case, let M be a machine which accepts the language corresponding to $L \in \text{NP}$ and $\overline{L} \in \text{coNP}$. Now, the oracle query can be replaced by simulating both the machines in a time sharing manner. If M accepts, interpret as a yes answer from oracle. If N accepts, interpret as a no answer from oracle. Then continue computation normally as the oracle machine from there. Since, both M and N accepts in polynomial time, hence the entire simulation can be done in NP time. Therefore, $\Sigma_{k+1}^P = \Sigma_1^P$.

2. (10 points) (a) Reading Assignment : Read the proof (Section 3.4, Theorem 3.21, Page 93) of the claim : $\text{DTIME}(2^{O(s(n))}) \subseteq \text{SPACE}(s(n))$. Determine an upper bound on the number of children for any universal configuration in the alternating Turing machine produced in the construction.
- (b) Conclude that $AL = P$. Show that all CFLs are in P by giving an alternating Turing machine running in log space for checking membership. (Assume that the CFL is given at the input in the CNF form.).
3. (10 points) Define the language:

$\text{SHORTESTPATH} = \{(G, k, s, t) \mid \text{the shortest path from } s \text{ to } t \text{ in } G \text{ has length } k\}$

- (a) (5 points) Prove that SHORTESTPATH is in NL .
- (b) (5 points) Prove that SHORTESTPATH is in L if and only if $L = \text{NL}$.

Solution:

- (a) We can show $\text{SHORTESTPATH} \in \text{NL}$ similar to the way we showed $\text{REACH} \in \text{NL}$. At every vertex, non deterministically choose the next vertex which is the neighbour of the current vertex and the edge between current vertex and

the neighbouring vertex is part of some shortest path from s to t . Since, the outdegree of a vertex can be as bad as n , therefore, in the worst case $\log(n)$ bits will be needed to make the non deterministic choice. Hence, $\text{SHORTESTPATH} \in \text{NL}$

(b) $\text{L} = \text{NL} \implies \text{SHORTESTPATH} \in \text{L}$

This direction is trivial from part a. Since $\text{SHORTESTPATH} \in \text{NL}$ and $\text{L} = \text{NL}$, hence, $\text{SHORTESTPATH} \in \text{L}$.

$\text{SHORTESTPATH} \in \text{L} \implies \text{L} = \text{NL}$

4. (15 points) An undirected graph is bipartite if its nodes can be divided into two sets such that all edges go from a node in one set to a node in the other set. Show that a graph is bipartite if and only if it does not contain a cycle that contains an odd number of nodes. Let

$$\text{BIPARTITE} = \{G \mid G \text{ is a bipartite graph} \}$$

Show that BIPARTITE is in NL . (Hint : Use Immerman-Szelecsinyi theorem !).

Solution:

(a) Bipartite graph \implies graph contains no odd cycles.

This can be shown by considering the contrapositive of the statement. If a graph contains odd cycles, then it is not bipartite. Consider any odd cycle $c_1, c_2 \dots c_{2n+1}$. To form a bipartite graph using these vertices, we have to select vertices in one set such that, no two of them are adjacent in the cycle. Selecting set of vertices and forming two such sets, will leave out one vertex, for any combination. Hence such a set of vertices can never be bipartite.

Graph contains no odd cycles \implies Bipartite graph .

Divide the set of vertices in the graph into set A and V .

Every vertex $v \in A \Leftrightarrow$ the shortest path from every vertex in A to v is of odd length.

For such a construction of set, if there is no odd cycle, the graph is bipartite. Suppose there is no odd cycle, and let v_1 and v_2 both in A be adjacent. Consider a vertex $v \in A$. the length of the closed cycle from v will be length of $v \dots v_1 +$

$v_2 \dots v + 1$. From the definition of set, this length is odd . (odd + odd + odd) . BUt our initial assumption was there is no odd cycle. Hence, there cannot be v_1 and v_2 in A such that they are adjacent. Hence graph is bipartite.

- (b) Consider the language $\overline{BIPARTITE}$ which is the complement of $BIPARTITE$. We can show that $BIPARTITE \in \text{NL}$ from the result in part(a). That is given a graph G , if there exists a odd cycle, then $G \in \overline{BIPARTITE}$. Since, we already know $\text{REACH} \in \text{NL}$, we have to check if any of $(G, v_1, v_1), (G, v_2, v_2) \dots (G, v_n, v_n)$ is in REACH . This can also be done in log space because, we can reuse the same space of (G, v_1, v_1) for checking $(G, v_2, v_2), \dots (G, v_n, v_n)$. Hence, $\overline{BIPARTITE} \in \text{NL}$ and $BIPARTITE \in \text{coNL}$.

From Immerman-Szelepsinyi Theorem, $\text{NL} = \text{coNL}$. Hence, $BIPARTITE \in \text{NL}$.

5. (25 points) We define the product of two $n \times n$ Boolean matrices A and B as another $n \times n$ Boolean matrix C such that $C_{ij} = \bigvee_{k=1}^n (A_{ik} \wedge B_{kj})$.
- (a) (5 points) Show that boolean matrix multiplication can be done in logarithmic space.
- (b) (5 points) Using repeated squaring, argue that A^p can be computed in space $O(\log n \log p)$.
- (c) (5 points) Show that if A is the adjacency matrix of a graph, then $(A^k)_{ij} = 1$ if and only if there is a path of length at most k from the vertex i to vertex j and is 0 otherwise.
- (d) (5 points) Use the above to give an alternative proof that $\text{NL} \subseteq \text{DSPACE}(\log^2 n)$. We originally proved it using Savitch's theorem.