

# KUBERNETES MASTER SETUP IN AWS

AWS AMI ID: ami-3158414e (owner: 601575382750)

OS: Ubuntu

Username: ubuntu

Password: "key\_pair.pem"

Installed Packages: Docker, Kubernetes

*Note:* the image has Docker and Kubernetes installed, but setting up Kubernetes master creates files that are tied up with the IP address of the master machine. Thus, after creating the instance, run below commands in order to setup the Kubernetes master.

Create an instance using the above image. After that, run below commands:

Step 1 # sign as root

```
sudo su -
```

Step 2 # pass bridged IPv4 traffic to iptables' chains which is required by certain CNI networks

```
sudo sysctl net.bridge.bridge-nf-call-iptables=1
```

Step 3 # initialize kubeadm (done only for master)

```
kubeadm init --pod-network-cidr=10.244.0.0/16
```

Step 4 # create kubeconfig so the user can run kubectl commands

```
mkdir -p $HOME/.kube
```

```
sudo cp -i /etc/kubernetes/admin.conf $HOME/.kube/config
```

```
sudo chown $(id -u):$(id -g) $HOME/.kube/config
```

Step 5 # install flannel networking

```
kubectl apply -f
```

```
https://raw.githubusercontent.com/coreos/flannel/v0.9.1/Documentation/kube-flannel.yml
```

Step 6 # Only when you want to use master node to host pods (since we have 1 node cluster)

```
kubectl taint nodes --all node-role.kubernetes.io/master-
```

# Test

```
kubectl get pods --all-namespaces
```

## JOIN NODE AS WORKER

AWS AMI ID: ami-3158414e (owner: 601575382750)

OS: Ubuntu

Username: ubuntu

Password: "docker\_key\_pair.pem"

Installed Packages: Docker, Kubernetes

*Note:* the image has Docker and Kubernetes installed, but setting up Kubernetes master creates files that are tied up with the IP address of the master machine. Thus, after creating the instance, run below commands in order to setup the Kubernetes master.

Create an instance using the above image. After that, run below commands:

Step 1 # sign as root

```
sudo su -
```

Step 2 # pass bridged IPv4 traffic to iptables` chains which is required by certain CNI networks

```
sudo sysctl net.bridge.bridge-nf-call-iptables=1
```

Step 3 # Get the token and sha digest from master and run in the new node

Run in master

```
kubeadm token create --print-join-command
```

This will output a command, run that command in new nodes to join the master as workers.

## 1.1 APPENDIX (Docker and Kubernetes Installation)

Steps to install Docker and Kubernetes (the one which is used to create the AMI). If you are using the provided AMI in the page 1, you do not need to follow these steps.

OS: Ubuntu

```
# update and upgrade the apt-get package manager
```

```
sudo apt-get update && sudo apt-get upgrade && sudo apt-get install -y apt-transport-https
```

```
# install docker
```

```
sudo apt install docker.io
```

```
# start and enable docker engine
```

```
sudo systemctl start docker
```

```
sudo systemctl enable docker
```

```
# download and add the key to Kubernetes install
```

```
sudo curl -s https://packages.cloud.google.com/apt/doc/apt-key.gpg | apt-key add
```

```
# Add the package to apt-get
```

```
echo "deb http://apt.kubernetes.io/ kubernetes-xenial main" >>
```

```
/etc/apt/sources.list.d/kubernetes.list
```

```
# apt-get update and install Kubernetes
```

```
sudo apt-get update && sudo apt-get install -y kubelet kubeadm kubectl kubernetes-cni
```

### Extra Services

```
-- Create Kubernetes Dashboard , and enable heapster
```

```
(https://docs.aws.amazon.com/eks/latest/userguide/dashboard-tutorial.html )
```

```
-- Create the necessary Services, Deployments, Role Bindings etc.
```

```
kubectl apply -f
```

```
https://raw.githubusercontent.com/kubernetes/dashboard/master/src/部署/recommended/kubernetes-dashboard.yaml
```

```
kubectl apply -f
```

```
https://raw.githubusercontent.com/kubernetes/heapster/master/部署/kube-config/influxdb/heapster.yaml
```

```
kubectl apply -f
https://raw.githubusercontent.com/kubernetes/heapster/master/deploy/kube-config/influxdb/influxdb.yaml
kubectl apply -f
https://raw.githubusercontent.com/kubernetes/heapster/master/deploy/kube-config/rbac/heapster-rbac.yaml
```

```
-- get the secret for joining Dashboard
kubectl -n kube-system describe secret $(kubectl -n kube-system get secret | grep
eks-admin | awk '{print $1}')
```

<https://35.171.228.253:31303/#!/overview?namespace=default> (accessing the dashboard)

<https://medium.com/cloud-academy-inc/setup-kubernetes-on-aws-using-kops-877f02d12fc1>

<https://github.com/kubernetes/dashboard/wiki/Accessing-Dashboard---1.7.X-and-above> (this is one is helpful to access the kubernetes Dashboard)

```
kubectl -n kube-system edit service kubernetes-dashboard
-- change the type to NodePort from ClusterIP
```

```
kubectl -n kube-system get service kubernetes-dashboard (this exposes the dashboard
on a port)
```

-- Error on AWS machine, this was run (this should not be done as it may expose the cluster to outside usage and tampering)

```
kubectl create clusterrolebinding --user system:serviceaccount:kube-system:default
kube-system-cluster-admin --clusterrole cluster-admin
```