

Hoare style program verification

Abhik Roychoudhury
National University of Singapore

IISc Summer Course 2007 by
Abhik Roychoudhury

Remarks

- SW Model Checking
 - Automated
 - Reason about transition systems.
 - Abstractions can make the reasoning imprecise albeit conservative.
- Theorem Proving
 - User-guided
 - Reason about programs.
 - Exact reasoning.

IISc Summer Course 2007 by
Abhik Roychoudhury

Remarks

- SW Model Checking
 - Abstractions designed for a given program and/or property.
 - Path-sensitive.
 - False alarms, but because abstraction was coarse
 - Property required.
- Static Analysis
 - Abstract domain fixed for all programs in a PL, depending on the analysis performed.
 - Usually analysis results of diff paths are merged.
 - Hence false alarms
 - Abst. domain all imp.

IISc Summer Course 2007 by
Abhik Roychoudhury

Remarks

- The approach of developing proof rules for reasoning about language constructs is radically different from model checking
 - Reason about programs (not transition systems)
 - Non-mechanized.
 - Notion of distinguished control locations ingrained
 - Reason about pre- and post-conditions holding before and after execution of a block of code.
- Consider sequential programs in this lecture
 - Can extend to develop proof rules for multi-threaded programs.

IISc Summer Course 2007 by
Abhik Roychoudhury

Hoare triple

- $\{Pre\} P \{Post\}$
 - If P is run from a state where Pre holds and P terminates, then Post holds in the end-state [Partial correctness]
 - If P is run from a state where Pre holds, then P terminates and Post holds in the end-state [Total correctness]
 - A Hoare triple involving program P is a specification about P.

IISc Summer Course 2007 by
Abhik Roychoudhury

Trivial example

- Say P is `while true do x = 0 endwhile`
- P is partially correct w.r.t. any specification of the form $\{Pre\} P \{Post\}$
- P is not totally correct w.r.t. any specification of the form $\{Pre\} P \{Post\}$
- We will develop a proof system for reasoning about partial correctness
 - First step to reasoning about total correctness

IISc Summer Course 2007 by
Abhik Roychoudhury

Notations

- $\vdash_{\text{par}} \{ \text{Pre} \} P \{ \text{Post} \}$
 - The Hoare triple can be shown to be partially correct in our proof system
- $\models_{\text{par}} \{ \text{Pre} \} P \{ \text{Post} \}$
 - The Hoare triple is partially correct.
- $\vdash_{\text{tot}} \{ \text{Pre} \} P \{ \text{Post} \}, \models_{\text{tot}} \{ \text{Pre} \} P \{ \text{Post} \}$
 - Similar
 - Standard notions of soundness/completeness

IISc Summer Course 2007 by
Abhik Roychoudhury

Factorial program

- | | |
|---------------------------|---------------------------|
| ▪ $\{ x \geq 0 \}$ | ▪ $\{ x \geq 0 \}$ |
| ▪ /* x is input */ | ▪ /* x is input */ |
| ▪ $y = 1; z = 0;$ | ▪ $y = 1;$ |
| ▪ while ($z \neq x$) do | ▪ while ($x \neq 0$) do |
| ▪ $z = z + 1;$ | ▪ $y = y * x;$ |
| ▪ $y = y * z;$ | ▪ $x = x - 1;$ |
| ▪ endwhile | ▪ endwhile |
| ▪ $\{ y = x! \}$ | ▪ $\{ ??? \}$ |

IISc Summer Course 2007 by
Abhik Roychoudhury

The problem

- x was destructively updated in Program2
 - In the end-state, we cannot say $y = x!$
 - To state correctness conditions, not enough to use program variables
 - Need to remember the original value of x
 - $\{ x = x0 / \ x \geq 0 \}$ Program2 $\{ y = x0! \}$
 - **x0 is a universally quantified logical variable.**

IISc Summer Course 2007 by
Abhik Roychoudhury

Logical variables

- $\{ x = x0 \wedge x \geq 0 \}$ Program2 $\{ y = x0! \}$
 - For all x0, if $x = x0$ and $x \geq 0$ and we run Program2 such that it terminates, we will have $y = x0!$ in the end state.
 - These variables appear only in the logical formulae of pre- and post-conditions.
 - Never appear in the program being verified.
- We now present the proof rules of our proof system.

IISc Summer Course 2007 by
Abhik Roychoudhury

Proof Rules

Premises

Conclusion

Both premises and conclusion are Hoare triples.

If premises specify properties about programs $C1, C2, \dots, Cn$

– the conclusion specifies a property about a bigger program C typically containing $C1, C2, \dots, Cn$

IISc Summer Course 2007 by
Abhik Roychoudhury

Rule for Assignment

$\{ \psi [x \rightarrow E] \} \ x = E \ \{ \psi \}$

No premises in this rule.

To prove ψ after the assignment, $\psi [x \rightarrow E]$ should hold before the assignment.

IISc Summer Course 2007 by
Abhik Roychoudhury

Why not forwards ?

- $\{\varphi\} x = E \{\psi\}$
 - How to define ψ in terms of φ ?
 - Cannot be achieved mechanically in general
 - The backwards formulation of the rule allows deducing Hoare triple by mechanically substituting x .
 - Instead define φ in terms of ψ

IISc Summer Course 2007 by
Abhik Roychoudhury

Sequential Composition

$$\frac{\{\varphi\} C1 \{\psi1\} \quad \{\psi1\} C2 \{\psi\}}{\{\varphi\} C1 ; C2 \{\psi\}}$$

Need assertion for end-state of C1 and begin-state of C2.

IISc Summer Course 2007 by
Abhik Roychoudhury

If-statement

$$\frac{\{\varphi \wedge b\} C1 \{\psi\} \quad \{\varphi \wedge \neg b\} C2 \{\psi\}}{\{\varphi\} \text{ if } b \text{ then } C1 \text{ else } C2 \{\psi\}}$$

Involves a case-split.

Pre-condition typically does not say anything about b

Needs to be augmented with truth/falsehood of b .

IISc Summer Course 2007 by
Abhik Roychoudhury

While statement

$$\frac{\{\psi \wedge b\} C \{\psi\}}{\{\psi\} \text{ while } b \text{ do } C \{\psi \wedge \neg b\}}$$

ψ is the loop invariant.

Rule for partial correctness (number of times the loop executes/ termination is not known/ not guaranteed).

IISc Summer Course 2007 by
Abhik Roychoudhury

Implications

$$\frac{\varphi' \Rightarrow \varphi \quad \{\varphi\} C \{\psi\} \quad \psi \Rightarrow \psi'}{\{\varphi'\} C \{\psi'\}}$$

1. Strengthening the pre-condition
2. Weakening the post-condition

Why do we need this rule ?

IISc Summer Course 2007 by
Abhik Roychoudhury

Example 1

- $\{y < 2\} y = y + 1 \{y < 5\}$
- **Proof:**
- $\{y < 2\}$
- $\{y + 1 < 5\}$ *implication rule*
- $y = y + 1$
- $\{y < 5\}$ *assignment rule*

IISc Summer Course 2007 by
Abhik Roychoudhury

Example 2

- $\{\text{true}\} z=x; z = z+y; u = z \{u = x+y\}$

Proof:

- $\{\text{true}\}$
- $\{x+y = x + y\}$
- $z = x;$
- $\{z+y = x+y\}$
- $z = z + y;$
- $\{z = x + y\}$
- $u = z$
- $\{u = x + y\}$

Push up the assertions starting from the post-condition of the code fragment being verified.

IISc Summer Course 2007 by
Abhik Roychoudhury

Example 3

- $\{\text{true}\} \text{ if } (x>y) z = y \text{ else } z = x \{z = \min(x,y)\}$

Proof:

- $\{x = \min(x,y)\} z = x \{z = \min(x,y)\}$
- $\{y = \min(x,y)\} z = y \{z = \min(x,y)\}$
- How to combine these triples using the rule for if-statements in our proof system ?
- Use the rule of implications

IISc Summer Course 2007 by
Abhik Roychoudhury

Example 3

- $x \leq y \Rightarrow x = \min(x,y)$
- $x > y \Rightarrow y = \min(x,y)$
- $\{\text{true} \wedge x > y\} z = y \{z = \min(x,y)\}$
- $\{\text{true} \wedge \neg(x > y)\} z = x \{z = \min(x,y)\}$
- Combine using the if-rule
- $\{\text{true}\} \text{ if } (x>y) z=y \text{ else } z=x \{z = \min(x,y)\}$

IISc Summer Course 2007 by
Abhik Roychoudhury

Reasoning about loops

- To prove $\{\phi\} \text{ while } b \text{ do } c \{ \psi \}$
- We must
 - Find a loop invariant η i.e. $\{\eta \wedge b\} c \{\eta\}$
 - this means
 - $\{\eta\} \text{ while } b \text{ do } c \{\eta \wedge \neg b\}$
 - Show that $\phi \Rightarrow \eta$
 - Show that $(\eta \wedge \neg b) \Rightarrow \psi$
 - Use rule of impl. to prove $\{\phi\} \text{ while } b \text{ do } c \{ \psi \}$

IISc Summer Course 2007 by
Abhik Roychoudhury

Loop invariant

- Synthesis involves human ingenuity
 - No unique inv. for a given loop
 - The formula **True** is an invariant for any loop
 - But our inv. η should satisfy
 - $\phi \Rightarrow \eta$
 - $(\eta \wedge \neg b) \Rightarrow \psi$
 - Usually choose invariants which capture relationships between variables whose values are modified at each iteration.

IISc Summer Course 2007 by
Abhik Roychoudhury

Guessing invariants

$\{\phi\}$	Pre-condition	
$\{??\}$		
While b do		
$\{\eta \wedge b\}$	Loop invariant	
c		Need to guess η and verify that it is an invariant
$\{\eta\}$		
endwhile		
$\{\psi\}$		

IISc Summer Course 2007 by
Abhik Roychoudhury

Verifying invariants

```

{φ}      Implication
{η}
while b do
{η ∧ b}  Implication
{η1}    ↑
C        Push up based on structure of C
{η}
endwhile
{η ∧ ¬b} Implication
{ψ}

```

1. $\eta \wedge \neg b \Rightarrow \psi$
2. $\eta \wedge b \Rightarrow \eta 1$
3. $\phi \Rightarrow \eta$

IISc Summer Course 2007 by
Abhik Roychoudhury

IISc Summer Course 2007 by
Abhik Roychoudhury

Factorial program

```

■ {true}
■ y = 1; z = 0;
■ {y = z!}
■ while (z != x) do
■   z = z + 1; y = y * z
■ endwhile
■ {y = x!}

```

Guess the loop invariant
 $y = z!$

IISc Summer Course 2007 by
Abhik Roychoudhury

Checking the post-loop states

```

{true}
y = 1; z = 0;
{y = 0!}
while (z != x) do
  z = z + 1; y = y * z;
endwhile
{y = z! ∧ ¬(z ≠ x)}
{y = x!}

```

$y = z! \wedge \neg(z \neq x)$
 $= y = z! \wedge z = x$
 $= y = x!$

Implication

IISc Summer Course 2007 by
Abhik Roychoudhury

Verifying the invariant

```

{true}
y = 1; z = 0;
{y = 0!}
while (z != x) do
  {y = z! ∧ z ≠ x}
  z = z + 1;
  y = y * z;
  {y = z!}
endwhile

```

Need to prove this Hoare triple

IISc Summer Course 2007 by
Abhik Roychoudhury

Verifying the invariant

```

{true}
y = 1; z = 0;
{y = 0!}
while (z != x) do
  {y = z! ∧ z ≠ x}
  {y * (z + 1) = (z + 1)!}
  z = z + 1;
  {y * z = z!}
  y = y * z;
  {y = z!}
endwhile

```

Implication : Easy to check
 Assignment
 Assignment

IISc Summer Course 2007 by
Abhik Roychoudhury

So-far

```

.....
{ y = z! }
while (z ≠ x) do
  { y = z! ∧ z ≠ x }
  z = z + 1 ; y = y * z
  { y = z! }
endwhile
{ y = x! }

```

Does $y = z!$ hold before the while loop ?

IISc Summer Course 2007 by
Abhik Roychoudhury

Checking pre-loop states

```

{true}
y = 1;
z = 0;
{ y = z! }
while (z ≠ x) do
.....

```

Need to prove this Hoare triple

IISc Summer Course 2007 by
Abhik Roychoudhury

Checking pre-loop states

```

{true}      Implication
{ 1 = 0! }
y = 1;      Assignment
{ y = 0! }
z = 0;      Assignment
{ y = z! }

```

IISc Summer Course 2007 by
Abhik Roychoudhury

Proof structure

- {true} Factorial-Program { $y = x!$ }
 - 1. To prove $y = x!$ at the end of the loop, we first guess a loop invariant
 - $y = z!$ is our choice
 - 2. Can the choice of loop invariant in step 1 ensure $y = x!$ at the end of the loop ?
 - Yes
 - 3. Verify that $y = z!$ is indeed a loop invariant
 - This is the premise of the while rule

IISc Summer Course 2007 by
Abhik Roychoudhury

Proof structure

- 4. Verify that the loop invariant holds before the loop.
 - Checking pre-loop states
- Steps 3 and 4 constitute a proof of the invariant by **induction** on # iterations
 - Step 3: induction step
 - Step 4: base case of the proof
- The loop invariant itself is the ind. Hypothesis, no strengthening involved in this proof.

IISc Summer Course 2007 by
Abhik Roychoudhury

Choice of Loop Invariant

- The loop invariant must be strong enough to be "proved" an invariant.
 - The while rule is essentially accomplishing induction on # of loop iterations.
- Often guided by the choice of the post-condition after the loop
 - Our post-condition was $y = x!$
 - Since $z = x$ at loop exit and z is modified at every loop iteration, choose $y = z!$ as invariant.

IISc Summer Course 2007 by
Abhik Roychoudhury

Proving total correctness

- Our proof system only shows partial correctness of triples $\{\phi\} P \{\psi\}$
- To prove total correctness
 - Need to prove termination
 - Only the proof rule for while statement needs to change.
 - To prove termination
 - Find a non-negative integer quantity which decreases in every iteration (call it **variant**)

IISc Summer Course 2007 by
Abhik Roychoudhury

Finding variant

- $a = x; y = 1;$
- while $(a > 0)$ do
 - $y = y * a; a = a - 1;$
- endwhile
- Trivial to find the variant
 - a in this case

IISc Summer Course 2007 by
Abhik Roychoudhury

Finding variant

- $y = 1; z = 0;$
- while $(z \neq x)$ do
 - $z = z + 1; y = y * z$
- endwhile
- Variant is $x - z$ (lifted from loop guard here)
- In general, finding variant cannot be automated even if the loop is guaranteed to terminate.

IISc Summer Course 2007 by
Abhik Roychoudhury

New Proof Rule

$$\frac{\{\eta \wedge b \wedge (E = E_0 \geq 0)\} \ C \ \{\eta \wedge (E_0 > E \geq 0)\}}{\{\eta \wedge E \geq 0\} \ \text{while } b \text{ do } c \ \{\eta \wedge \neg b\}}$$

E is the variant.

If it is E_0 before the loop, it strictly decreases but remains non-negative.

Of course E should be non-negative before the loop starts.

IISc Summer Course 2007 by
Abhik Roychoudhury

Factorial program

- $\{x \geq 0\}$
- $y = 1; z = 0;$ Use the variant $x - z$ to prove termination
- while $(z \neq x)$ do
 - $z = z + 1;$ Use the loop invariant $y = z!$ as before for proving partial correctness
 - $y = y * z;$
- endwhile
- $\{y = x!\}$

IISc Summer Course 2007 by
Abhik Roychoudhury

Reasoning about the loop

$\{y = z! \wedge x - z \geq 0\}$
 while $(x \neq z)$ do
 $z = z + 1; y = y * z;$
 endwhile;
 $\{y = z! \wedge x = z\}$ From the conclusion of the while rule (total correctness)
 $\{y = x!\}$ -- How to show the premise ?

IISc Summer Course 2007 by
Abhik Roychoudhury

Reasoning about an iteration

```

{ y = z! ∧ x - z ≥ 0 }
while (x != z) do
  { y = z! ∧ x ≠ z ∧ (x - z = E0 ≥ 0) }
  z = z + 1 ; y = y * z;
  { y = z! ∧ (E0 > x - z ≥ 0) }
endwhile;
{ y = z! ∧ x = z }
{ y = x! }
    
```

This triple is the premise of the while rule

IISc Summer Course 2007 by
Abhik Roychoudhury

Reasoning about an iteration

```

{ y = z! ∧ x - z ≥ 0 }
while (x != z) do
  { y = z! ∧ x ≠ z ∧ E0 = x - z ≥ 0 }
  { y*(z+1) = (z+1)! ∧ (E0 > x - (z+1) ≥ 0) }
  z = z + 1 ;
  { y*z = z! ∧ (E0 > x - z ≥ 0) }
  y = y * z;
  { y = z! ∧ (E0 > x - z ≥ 0) }
endwhile;
{ y = x! }
    
```

Implication: Check it!

IISc Summer Course 2007 by
Abhik Roychoudhury

Reasoning about pre-loop states

```

{ x ≥ 0 }
y = 1; z = 0;
{ y = z! ∧ x - z ≥ 0 }
while (x != z) do
  { y = z! ∧ x ≠ z ∧ E0 = x - z ≥ 0 }
  z = z + 1 ; y = y * z;
  { y = z! ∧ (E0 > x - z ≥ 0) }
endwhile;
{ y = x! }
    
```

Need to prove this Hoare triple

IISc Summer Course 2007 by
Abhik Roychoudhury

Reasoning about pre-loop states

```

{ x ≥ 0 }
{ 1 = 0! ∧ x ≥ 0 }
y = 1;
{ y = 0! ∧ x - 0 ≥ 0 }
z = 0;
{ y = z! ∧ x - z ≥ 0 }
while (x != z) do
  z = z + 1 ; y = y * z;
endwhile;
{ y = x! }
    
```

Implication

x ≥ 0 must hold at the initial state of the program for the program to terminate. This fact is used here in the overall proof.

IISc Summer Course 2007 by
Abhik Roychoudhury

Finally, Program Refinement

- $\{\phi\} \text{Prog} \ \{\psi\}$
 - Infers properties about pre- and post- states of a program
 - In the flavor of program verification
- Instead, you can treat (ϕ, ψ) as a specification
 - Correct by construction program synthesis from given pre- and post- conditions.
 - Many choices of implementation possible !
 - Use the specifications to guide the implementation instead of checking the implementation against the specification post-mortem.

IISc Summer Course 2007 by
Abhik Roychoudhury

Reading Material

- Chapter 4 of
 - *Logic in Computer Science*
 - By Michael R. A. Huth and Mark D. Ryan
- Additional optional reading
 - See Lesson Plan in course web-page
 - <http://drona.csa.iisc.ernet.in/~abhik>

IISc Summer Course 2007 by
Abhik Roychoudhury