

# TOT Cued Recall Analysis

Abhilasha Kumar

February 10, 2018

## 1 Reading the Data File

We first read the file into an object called TOTcuedrecall. We can also display some part of the data by calling the head() function.

```
> TOTcuedrecall = read.csv("Compiled_TOTCuedRecall.csv",  
+                           header = TRUE, sep = ",")  
> head(TOTcuedrecall[,c(1,21,22)])
```

	Subject	CuedRecallAcc	TargetAccuracy
1	1	0	1
2	1	0	0
3	1	0	0
4	1	0	0
5	1	0	0
6	1	0	0

## 2 Conditional Target Accuracy

In this section, we calculate the number of trials in which participants correctly or incorrectly recalled the item, and split that by whether they correctly recalled the target from the definition. Then, we calculate the proportion of trials from the raw number of trials.

```
> library(dplyr)  
> cued_acc = group_by(TOTcuedrecall, Subject, CuedRecallAcc) %>%  
+   summarise(recalltrials = n())  
> conditional_acc = group_by(TOTcuedrecall, Subject,  
+                             CuedRecallAcc, TargetAccuracy) %>%  
+   summarise(trials = n())  
> merge_acc = merge(conditional_acc, cued_acc,  
+                   by = c("Subject", "CuedRecallAcc"))  
> merge_acc$prop = merge_acc$trials/merge_acc$recalltrials
```

### 3 ANOVA

In this section, we perform a repeated measures ANOVA on our data, to see if we are indeed seeing a difference in the proportion of unsuccessful trials for failed and successful cued recall.

```
> merge_acc$Subject =  
+   as.factor(as.character(merge_acc$Subject))  
> merge_acc$CuedRecallAcc =  
+   as.factor(as.character(merge_acc$CuedRecallAcc))  
> merge_acc$TargetAccuracy =  
+   as.factor(as.character(merge_acc$TargetAccuracy))  
> cond_aov = aov(data = merge_acc,  
+   prop ~ CuedRecallAcc*TargetAccuracy +  
+   Error(Subject/(CuedRecallAcc*TargetAccuracy)))  
> summary(cond_aov)
```

```
Error: Subject  
      Df    Sum Sq   Mean Sq F value Pr(>F)  
Residuals  3 4.314e-32 1.438e-32
```

```
Error: Subject:CuedRecallAcc  
      Df    Sum Sq   Mean Sq F value Pr(>F)  
CuedRecallAcc  1 6.930e-33 6.933e-33  0.458  0.547  
Residuals      3 4.545e-32 1.515e-32
```

```
Error: Subject:TargetAccuracy  
      Df Sum Sq Mean Sq F value  Pr(>F)  
TargetAccuracy  1 1.1722    1.172    53.17 0.00533 **  
Residuals      3 0.0661    0.022
```

```
---  
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
Error: Subject:CuedRecallAcc:TargetAccuracy  
      Df    Sum Sq Mean Sq F value Pr(>F)  
CuedRecallAcc:TargetAccuracy  1 0.03513 0.03513  1.798  0.272  
Residuals                    3 0.05861 0.01954
```

The ANOVA output tells us that the interaction term is not significant. We will next see this in a figure, to better understand our data.

### 4 Conditional Figure

```
> library(Rmisc)  
> cond_figure = summarySE(merge_acc,  
+   measurevar = "prop",  
+   groupvars = c("CuedRecallAcc",  
+   "TargetAccuracy"))  
> library(ggplot2)
```

```

> library(ggthemes)
> cond_figure %>% mutate(Recall = factor(CuedRecallAcc,
+                                       levels = unique(CuedRecallAcc),
+                                       labels = c("Failed Recall",
+                                                  "Successful Recall")),
+                         TargetRetrieval = factor(TargetAccuracy,
+                                                  levels = unique(TargetAccuracy),
+                                                  labels = c("Failed Target Retrieval",
+                                                             "Successful Target Retrieval")))%>%
+ ggplot(aes(x = Recall, y = prop,
+            fill = TargetRetrieval, group = TargetRetrieval))+
+ geom_bar(stat = "identity", position = "dodge", width = 0.7)+
+ geom_errorbar(aes(ymin=prop - ci, ymax=prop + ci),
+               width=.2, color = "gray26",
+               position = position_dodge(0.7))+
+ theme_few()+
+ scale_fill_wsj()+
+ xlab("Cued Recall Accuracy") + ylab("Mean Proportion of Trials") +
+ ggtitle("Target Retrieval Accuracy
+         as a function of Cued Recall Accuracy") +
+ theme(axis.text = element_text(face = "bold", size = rel(1)),
+       axis.title = element_text(face = "bold", size = rel(1)),
+       legend.title = element_text(face = "bold", size = rel(1)),
+       plot.title = element_text(face = "bold",
+                                   size = rel(1.2), hjust = .5),
+       strip.text.x = element_text(face = "bold", size = rel(1.4)))

```

