Oversight That Scales

Scalable-oversight research, Coefficient Giving's Project Tailwind, and how to size and structure a proposal

Claude Code

17 September 2026

Abstract

Abhimanyu Pallavi Sudhir and Arjun Panickssery plan to propose a scalable-oversight research programme to Coefficient Giving's Project Tailwind, a call for founders of AI-safety organisations launched on 9 September 2026. This report prepares that proposal. It traces the field from 2014 to September 2026 through 183 verified entries and maps twelve schools of thought; reconstructs how Coefficient Giving has framed oversight since 2021 and profiles the four oversight groups it now funds (Resolution, Sampura Research, Palaestra Research and Arcadia Impact); derives typical grant sizes from 89 comparable grants; lays out a staged plan with milestones, gates and budgets; and assesses the legal options, including a public-benefit corporation. It recommends a pre-seed ask of about $1.47 million (range $752,000–$1.99 million), a seed application three to six months later for about $10.3 million ($5.18 million–$14.7 million), and a scale stage of about $52.8 million presented as a possibility rather than a request. It also recommends payment through a fiscal sponsor able to employ in the United States and the United Kingdom, and a programme built around the applicants' agent-score-difference (ASD) metric, measured on realistic long-horizon work, across compute, and under training. Two findings change the pitch. Warp's benchmark scorers are language-model judges rather than ground truth, which makes an audit of such judges a natural early experiment; and the published ASD paper's Propaganda baseline was very probably affected by a bug that has since been fixed in the code but not yet in the paper.

Contents

Summary 4

I The field 6

1 The starting point: the ASD paper and the team 6

1.1 What the paper argued . . . 6
1.2 What the experiment found . . . 7
1.3 The library . . . 9
1.4 The team . . . 9

2 A chronology of scalable oversight, 2014–2026 10
2.1 2014–2018: three protocols and a complexity argument . . . 11
2.2 2019–2021: first experiments and the first disappointment . 11
2.3 2022–2023: the empirical turn . . . 13
2.4 2024: the debate wave and its limits . . . 14
2.5 2025: agendas, institutions and alternatives . . . 14
2.6 2026: training, fuzzy tasks and money . . . 15
2.7 Where the field stands in September 2026 . . . 15

3 Schools of thought in September 2026 17
3.1 The disagreements that matter for a funder . . . 19
3.2 Where this proposal sits . . . 20

II The funder 21

4 How Coefficient Giving sees scalable oversight 21
4.1 The money and the speed . . . 21
4.2 Three framings of oversight, 2021–2026 . . . 22
4.3 Who reads which initiative . . . 23
4.4 What this implies for the pitch . . . 24

5 The scalable-oversight groups CG already funds 24
5.1 Resolution . . . 25
5.2 Sampura Research . . . 26
5.3 Palaestra Research . . . 27
5.4 Arcadia Impact and its alignment team . . . 27
5.5 What the four grantees imply . . . 28

III The programme 29

6 Strand 1: oversight experiments on realistic, long-horizon work 29
6.1 Why the old settings are not enough . . . 29
6.2 The Warp Factory analogy . . . 31
6.3 The paired-branch design . . . 33
6.4 From binary to graded: generalising ASD . . . 34
6.5 Four task families . . . 35
6.6 Dual use and safeguards . . . 37

7 Strands 2 and 3: how oversight scales, and what training does to it 38

7.1 Strand 2: oversight scaling curves . . . 38
7.2 Strand 3: why train, when prompted liars are weak adversaries 39
7.3 The RL design . . . 41

8 Strands 4–6: explanation, the library and capability-gap settings 42
8.1 Strand 4: training models to explain, so that oversight gets cheaper . . . 42
8.2 Strand 5: the library . . . 44
8.3 Strand 6: settings with real capability gaps . . . 45

IV The money 46

9 What Coefficient Giving pays: typical amounts 47
9.1 Other funders . . . 48
9.2 What things cost . . . 49

10 A staged plan: milestones, gates and money 50
10.1 Pre-seed: twelve months to earn a seed round . . . 50
10.2 Seed: two years to become the reference measurement . . . 50
10.3 Scale: an oversight laboratory . . . 51
10.4 When to stop or change course . . . 52

11 Legal form: nonprofit, PBC, or neither yet 53
11.1 What Tailwind says . . . 53
11.2 CG's record with companies . . . 53
11.3 Individuals, sponsors and the two countries . . . 55
11.4 The options compared . . . 55

12 Recommendations: how much to ask for, and how 57
12.1 The numbers . . . 57
12.2 How to structure the ask . . . 58
12.3 The expression of interest . . . 59
12.4 Risks a reader will raise, and the answers . . . 60
12.5 What to do now . . . 60

References 60

A Budget model 76

B Comparable grants 78

C Project Tailwind: the terms as published 79

D Method, sources and corrections 83

Summary

Three things to do first

1. **Apply for a Thinking Machines safety grant by 25 September 2026.** Up to $50,000 in Tinker training credits, with "reward hacking and oversight gaming" among the listed topics. It would pay for the policy compute of the RL runs at the two smaller scales (section 7.3).
2. **Fix the ASD paper before citing it.** The repository shows that, in the code used for the paper and in a committed pilot run, the Propaganda (RLHF baseline) agent was never told which side to argue, so the published row is very probably affected; the authors fixed this in January 2026. Re-run it, reconcile the Brier formula, and post version 2 (section 1).
3. **Write the Tailwind submission yourselves.** Coefficient Giving filters out submissions its systems judge to be AI-generated. Use this report for facts and structure, not prose.

The call. Coefficient Giving (CG), formerly Open Philanthropy, launched Project Tailwind on 9 September 2026 as its first public call for founders of AI-safety organisations. It funds in three tiers: pre-seed of $200,000 to $2 million over 9–18 months, seed of $2–20 million over 18–36 months, and scale of $20–200 million or more. A pre-seed grantee can ask for seed within about three months if the work is going well. Scalable oversight appears by name among the agendas CG says are waiting for a team; CG defines it as keeping training rewards high-quality as tasks get harder to oversee, or failing loudly when oversight breaks down. Debate appears among its "alignment moonshots" (appendix C).

The field (sections 2 and 3). Scalable oversight grew from Christiano's amplification essays and the 2018 debate paper, through a first disappointment (the obfuscated-arguments problem, 2020) and the empirical turn of 2022–23 (sandwiching, weak-to-strong generalisation, AI control), to a debate wave in 2024 whose clearest positive results depended on artificial information gaps. The year 2025 brought agendas and institutions; 2026 brought debate as a *training* method, automated researchers that outrun oversight on crisp tasks, and negative results on fuzzy ones. Twelve schools now compete, from theory-first safety cases (UK AISI's alignment team, now largely at Resolution) to control-first scepticism (Redwood). What none provides is a common, protocol-agnostic measure of whether an oversight scheme rewards truth over persuasion, across tasks, judges and compute. The applicants' agent-score-difference (ASD) metric was designed to be such a measure.

How CG sees it (sections 4 and 5). CG's framing has taken three forms: a headline direction in 2021 (up to $1 million per grant), something to stress-test in the $40 million request of 2025, and an agenda named in its own right in Tailwind. Its money has multiplied: $168 million to AI safety in 2024, $351 million in 2025, more than $1 billion expected in 2026. Four oversight groups now hold CG money. *Resolution* is Geoffrey Irving's new nonprofit; its $160 million is CG's largest AI-safety grant, and oversight is the only area it is hiring for. *Sampura Research*, from Google DeepMind's amplified-oversight team, has $11 million and builds better human and AI judges. *Palaestra Research* is moving from inference-time debate studies to RL self-play. *Arcadia Impact*'s new alignment team ($1.9 million) studies debate with UK AISI and has just reported no gain from debate on fuzzy tasks. The opening for this proposal is the measurement layer all four build ad hoc.

Typical amounts (section 9). Across CG's first grants to 14 new, small technical organisations, the median is $1.27 million ($1.41 million for 2025–26); across 7 seed-scale grants to young organisations it is $10.9 million. Sampura's $11 million is the one direct comparable. Outside CG, single technical grants top out around $1–1.5 million.

The staged plan (section 10). Pre-seed of $1.47 million for 12 months (low $752,000, high $1.99 million); a seed application in months three to six, on evidence named in advance, for $10.3 million over 24 months ($5.18 million to $14.7 million); and a scale stage of about $52.8 million over three years ($26.1 million–$103 million), presented as where the programme leads rather than as a request. Each stage has a gate and conditions for stopping.

Legal form (section 11). CG will consider a public-benefit corporation (PBC) with a clear charitable purpose but does not expect to fund other for-profits, and it is best placed to fund nonprofits. It will give pre-seed money to individuals without an entity; seed needs an entity or a 501(c)(3) fiscal sponsor. Its closest precedent gave $1 million to two founders before they had a company. Recommended: a pre-seed research grant paid to a fiscal sponsor that can employ both founders in the US and UK, as Sampura's sponsor does; autonomous businesses as sandboxed testbeds, not products; a separate PBC at seed only if an oversight product, such as audits of labs' graders, finds paying customers.

The programme (sections 1 and 6 to 8). Six strands: ASD on realistic long-horizon work (software firms, writing with human graders, research tasks); oversight scaling curves across orders of magnitude of compute; RL training, to test whether cheap prompted benchmarks predict trained behaviour; explanation training that rewards learners' ability to tell right from wrong, not their agreement; a library built as an oversight layer on UK AISI's Inspect; and

settings with real capability gaps, above all chess. Abhimanyu's Warp analogy holds, with a twist that strengthens the pitch: Warp's benchmark scorers are LLM judges, not ground truth. Warp benchmarks the worker against a trusted grader; ASD benchmarks the grader against a known worker, and could measure the reviewers that software factories already rely on (section 6.2).

Part I

The field

1 The starting point: the ASD paper and the team

The proposal starts from a paper by Abhimanyu Pallavi Sudhir, Jackson Kaunismaa and Arjun Panickssery, presented as a poster at the ICLR 2025 Workshop on Bidirectional Human-AI Alignment [Pallavi Sudhir et al., 2025].[1] Much of the programme in sections 6, 7 and 8.1 extends it, so its argument is set out here in some detail.

1.1 What the paper argued

Earlier debate experiments scored a protocol by the accuracy of its judge [Michael et al., 2023; Khan et al., 2024; Kenton et al., 2024]. The paper argues that this is the wrong target for alignment. What matters is whether the protocol makes honesty pay: whether an agent that argues for the truth earns more reward than one that argues for a falsehood. Its metric, the *agent score difference* (ASD), measures that:

$$\mathrm{ASD} \;=\; \log p_{\top} - \log p_{\bot}, \tag{1}$$

where $p_{\top}$ is the probability the judge assigns to the true answer after an agent has argued for it under the protocol, and $p_{\bot}$ the probability it assigns to the false answer after an agent has argued for that. The two numbers come from two different worlds, one in which the agent tells the truth and one in which it lies, so in general $p_{\top} \neq 1 - p_{\bot}$. Only in simultaneous debate between identical debaters are the two transcripts the same, and there ASD reduces to a monotone function of judge accuracy. The paper's worked example: a judge that believes a truthful agent with probability 0.8 and a lying one with probability 0.6 gives ASD $= \ln 0.8 - \ln 0.6 \approx 0.29$. All reported results use a Brier-score version instead, to avoid infinite logarithms.

[1] The arXiv metadata calls it *A Benchmark for Scalable Oversight Protocols*; the PDF heading and the OpenReview page (`mzLBxX84VI`) say *Mechanisms*. Only arXiv version 1 (31 March 2025) exists. The acknowledgements thank Anthropic for funding the project.

Two companion quantities separate capability from incentive. The *expected agent score* weights the two scores by the agent's propensity to argue each side, modelled as a softmax of ASD at a temperature β; it measures how persuasive the agent is. The *expected judge score* does the same for the judge's own score, and so combines how much capability the protocol keeps with how much of it the protocol turns to honest ends. Plotting ASD against expected agent score across agents of different strength gives a slope, and the sign of that slope is the paper's proxy for what will happen as agents improve.

The formulation has three consequences that matter for the proposal.

1. **Any protocol can be compared on one scale.** Consultancy no longer needs an assumption about which side the consultant argues. A judge that ignores the agent (*NaiveJudge*, the analogue of supervised learning) and a judge that hears one argument (*Propaganda*, the analogue of RLHF) become legitimate baselines.

2. **Ground truth comes from the instruction, not from the judge.** Honest and dishonest behaviour are simulated by prompting a capable model, so the experimenter knows which world is which. The paper names this as a key limitation of the benchmark: it works only while models follow instructions to behave well or badly, and behave convincingly.

3. **The answer need not be binary.** The library scores a question by the dot product of log-probabilities with "answer values". With $+1$ and -1 that is (1), and the paper's future-work section says the same scoring can in principle take quality ratings or utilities. This is the formal hook for moving from multiple-choice questions to work of graded quality (section 6.4).

1.2 What the experiment found

The demonstration was deliberately small: 100 GSM8K word problems with synthetic wrong answers, one judge (`gpt-4o-mini`) and five agent configurations (Claude 3.5 Sonnet and Claude 3.5 Haiku, each with and without a calculator, and DeepSeek-V3). The calculator added a third kind of agent–judge asymmetry, tool use, to the information asymmetry and model-size asymmetry of earlier work. By ASD (Brier form), the four debate variants scored 1.366–1.423 and beat the naive judge (1.235). All four consultancy variants came last, at 0.283–0.367, well below the naive-judge baseline: a judge who could question a single agent was easier to mislead than one who heard no agent at all. Debate also showed the positive ASD-on-capability slope that Khan et al. [2024] had found for judge accuracy, and consultancy showed none. The number of debate turns, and whether debaters spoke together or in sequence, made no significant difference.

One normalisation, which is this report's and not the paper's, makes the size of the effect clear. On the Brier scale a perfect judge scores ASD $= 2$. If each protocol's gain over the naive judge is measured as a share of the gap to that ceiling, in the spirit of the *performance gap recovered* (PGR) of Burns et al. [2023], the best debate variant recovers $(1.423 - 1.235)/(2 - 1.235) \approx 0.25$ of this *incentive gap*, and consultancy between -1.24 and -1.13. Call this share the *incentive gap recovered*. Debate helped, but modestly, in a setting where the judge already put about 0.81 on the right answer unaided. The problems were easy enough for the judge alone that little room was left for any protocol, which is the problem Arjun identifies with maths datasets and the reason for the new settings in section 8.3.

The authors were explicit about what the experiment could not show. It measured average rather than worst-case ASD, used one weak judge and easy problems, and so could not test the claim, central to the original debate proposal [Irving et al., 2018], that longer debates help on harder problems. Among the extensions they proposed, three matter here: more protocols and models, including reasoning models; worst-case ASD, since one catastrophic action matters more than an average; and graded rather than binary answers. Each reappears below as part of the programme.

Three things to fix before the proposal cites the paper

A read of the public repository turned up three problems. A reviewer who opens it could find them too, so it is better to fix them first and mention the fixes.

1. **The Propaganda (RLHF baseline) result is probably an artefact.** On 1 January 2026 the authors committed a fix for a "catastrophic error where Propaganda agent couldn't see which side it was arguing for". A committed prompt log from 9 February 2025 shows the Propaganda agent receiving an empty answer tag. The debate and consultancy prompts in the same run were correct. So the runs behind the paper's finding that RLHF does not beat supervised learning, and behind its Propaganda slope, should be re-run with the fixed code, and the results corrected in an arXiv version 2 or an erratum.
2. **The Brier formula in the code differs from the footnote.** The code computes $2[(1 - p_\perp)^2 - (1 - p_\top)^2]$; the printed footnote reduces to $2(p_\top - p_\perp)$. They agree when the two worlds are symmetric, which covers the naive judge and simultaneous debate, but not consultancy. The paper should state which formula produced its table.
3. **Smaller slips:** a figure caption says "more capable judges" where the judge was fixed and the agent varied; one table row drops a turn

count; the pseudo-code for the two debate variants is identical; and the paper does not say which of the three judge types instantiated in the code produced the reported numbers.

1.3 The library

The code, `SOlib`, lives in the `solib/` package of the repository `ArjunPanickssery/math_problems_debate`. A new protocol is added by subclassing a `Protocol` class and running its experiment method over any choice of agent models, judge models and labelled questions. Since the paper it has gained market-making and a QuALITY loader with quote verification like that of the information-asymmetry debates (both added in January 2026); it also supports best-of-N agents, three judge types (already present in the paper-era code) and loaders for MMLU, TruthfulQA and GPQA. Abhimanyu's companion package `costly` simulates the cost of an experiment before it runs. As a public good the library is still small: three stars, three forks, no release on PyPI, no tagged versions, a GPL-3.0 licence that some companies avoid, and no commits since January 2026 (table 1). Section 8.2 proposes what building it out would involve.

1.4 The team

Arjun Panickssery is sole first author of *LLM Evaluators Recognize and Favor Their Own Generations* (NeurIPS 2024, with Sam Bowman and Shi Feng) [Panickssery et al., 2024a]. It has 897 Google Scholar citations as of 17 September 2026, out of 966 across his five papers. Its subject, judges that recognise and prefer their own outputs, is a confound in every oversight experiment in which one model family plays both agent and judge. He also co-authored an Apollo Research audit showing that two of Google DeepMind's estimators of dangerous-capability solve rates are biased low [Højmark et al., 2024], a study of temporal backdoors with Bowman and Asa Cooper Stickland [Price et al., 2024], and the REBUS benchmark [Gritsevskiy et al., 2024]. He started and advised the ASD project, and now runs Zembla, an education company, which the March 2025 paper already lists as his affiliation. An operating internet business is an unusual asset for the "autonomous business" strand (section 6): it supplies real outcomes, such as sign-ups and payments, that can serve as delayed ground truth.

Abhimanyu Pallavi Sudhir is a computer-science PhD student at the University of Warwick, supervised by Long Tran-Thanh, and is UK-based. He is co-first author, with Daniel Paleka and with Florian Tramèr as senior author, of *Consistency Checks for Language Model Forecasters*, an oral at ICLR 2025 [Paleka et al., 2025]. That paper is itself a method for evaluating without

Table 1: The applicants' assets at a glance (verified 17 September 2026).

Asset	Status
ASD paper	ICLR 2025 Bi-Align workshop poster; arXiv v1 only; 14 Google Scholar citations; funded by Anthropic; three fixes needed (box above)
SOlib	419 commits (Jul 2024–Jan 2026); 3 stars, 3 forks; GPL-3.0; not on PyPI; supports debate, consultancy, Propaganda, NaiveJudge, market-making; five dataset loaders
`costly`	PyPI v2.3.7, 11 stars; simulates LLM-experiment cost before running
Arjun	NeurIPS 2024 first author (897 citations); Apollo, backdoor and REBUS co-author; founder of Zembla
Abhimanyu	ICLR 2025 oral, co-first author; AAMAS 2025; Warwick PhD (Tran-Thanh); MATS 2026
Jackson	ICLR 2026 first author; ran the ASD experiments

ground truth: it scores forecasters on the logical consistency of their predictions before any question resolves, the same problem ASD addresses for oversight. He designed the ASD framework and wrote 333 of SOlib's 419 commits. His PhD work on information markets and market-based theories of reward (AAMAS 2025) is a mechanism-design view of oversight. By his own account he was a MATS scholar in Richard Ngo's stream in 2026, and as a school student he co-founded PhysicsOverflow, a graduate-level physics Q&A site.

Jackson Kaunismaa, the paper's second author, led its engineering and experiments (82 commits) and is first author of an ICLR 2026 paper with Anthropic co-authors. Whether he would join the new organisation is for the applicants to settle; the budgets in section 9 and appendix A hire two research engineers from month three either way.

A reviewer will also see three weak points, and the pitch should address them rather than leave them to be found. The oversight paper is a workshop poster whose planned full paper never appeared. Arjun has published nothing since March 2025 while building Zembla. And Abhimanyu's PhD is finishing in 2026 with another fellowship listed on his CV for 2026–27. Tailwind is a call for founders, so the pitch should say who will work on this full time and from when.

2 A chronology of scalable oversight, 2014–2026

This section tells the history of the field in six eras, from the first essays on amplification to the funding rush of 2026. It rests on a verified chronology of

183 dated entries, 78 from before 2024 and 105 since, of which 89 are papers and the rest essays, posts, research agendas and institutional announcements. Figure 1 plots them all; table 2 collects the numbers that the argument of this report leans on. One point of terminology first. When Amodei et al. [2016] coined "scalable oversight", it meant an objective too expensive to evaluate often, a problem of label budgets. By 2018 it had come to mean supervising a system more capable than its supervisor, and that is the sense used here.

2.1 2014–2018: three protocols and a complexity argument

The field's founding documents were essays and short papers, mostly by Paul Christiano, about how a weak overseer might supervise a strong learner. Three protocols emerged. *Iterated amplification* trains a model to imitate a human who may consult copies of the model, so that the overseer's strength grows with the model's [Christiano et al., 2018]. *Recursive reward modelling* uses agents trained on one level of reward model to help humans evaluate the next [Leike et al., 2018]. And *debate* pits two copies of a model against each other before a human judge, on the premise that it is harder to lie than to refute a lie [Irving et al., 2018]. The debate paper gave the field its central analogy: in the idealised game, debate lets a polynomial-time judge answer any question in PSPACE, where direct judging reaches only NP. Meanwhile reinforcement learning from human preferences solved Atari and simulated-robot tasks with feedback on under 1% of interactions, and taught a simulated robot a backflip from about an hour of feedback, which answered the 2016 sense of the problem well enough for the field to move on [Christiano et al., 2017]. Irving and Askell [2019] argued that testing these protocols would need human subjects, and so social scientists.

2.2 2019–2021: first experiments and the first disappointment

The protocols met humans and fared less well than hoped. Ought's experiments on factored cognition found only modest, fragile gains from evaluating arguments one step at a time [Saunders et al., 2020], and a relay in which 103 programmers attempted 40 problems in short handoffs solved four [Goldhaber and Evans, 2020]. OpenAI's human debate experiments ended with the *obfuscated-arguments* problem: a dishonest debater can build an argument whose flaw exists but cannot be located in any tractable number of steps, and the authors, Beth Barnes and Christiano, said they had no fix [Barnes, 2020]. The recursive promise that debate always narrows a dispute to one checkable flaw had failed its first real test. Human-feedback training, by contrast, kept working: preference-trained summarisers beat supervised models ten times their size [Stiennon et al., 2020], and recursive task decomposition let models summarise whole books [Wu et al., 2021].




Figure 1: Scalable oversight, 2014 to September 2026: 183 verified entries by research line. Named points are milestones discussed in the text. An interactive version with every entry is in the HTML edition.

Two documents from 2021 set the empirical agenda that followed. Ajeya Cotra's essay on aligning "narrowly superhuman" models introduced *sandwiching*, placing a model between a less and a more capable group of humans [Cotra, 2021a]. And the Alignment Research Center's report on *eliciting latent knowledge* reframed the problem as getting a model to report what it knows rather than what a human would believe [Christiano et al., 2021]. In October 2021 Open Philanthropy made "techniques for enhancing human feedback" one of four directions in an alignment request for proposals (section 4).

2.3 2022–2023: the empirical turn

Scalable oversight became an experimental field. Two NYU studies of static debate on QuALITY, a reading-comprehension set whose long passages the judge could not read in time, found that arguments did not help time-limited human judges and that counter-arguments made them slightly worse [Parrish et al., 2022b,a]. Bowman et al. [2022] ran the first sandwiching experiments, in which humans assisted by an unreliable model beat both the humans alone and the model alone. Saunders et al. [2022] showed that model-written critiques helped people find about 50% more flaws. Constitutional AI replaced much human feedback with AI feedback [Bai et al., 2022], making the quality of AI judges a production concern.

In July 2023 OpenAI announced its Superalignment team, with a fifth of the compute it had secured to date, over four years, and scalable oversight as a named pillar; its plan included deliberately training misaligned models to test its techniques [Leike and Sutskever, 2023]. The same month Buck Shlegeris and Ryan Greenblatt proposed *meta-level adversarial evaluation*: instead of finding inputs that make a model fail, find models that make an oversight process fail, rewarding a red-team policy for getting past the overseer while doing badly by the true objective [Shlegeris and Greenblatt, 2023]. That is the conceptual ancestor of the applicants' ASD method, which is a lighter, prompted, average-case version of the same idea. Late 2023 brought the first clear positive results for debate on language tasks: with expert human debaters, judges were right 84% of the time against 74% under consultancy [Michael et al., 2023], and Anthropic trained debaters with reinforcement learning and saw a trained judge's accuracy rise [Radhakrishnan, 2023]. Theory advanced with doubly-efficient debate [Brown-Cohen et al., 2023]. Two December papers defined the vocabulary of the next three years. Burns et al. [2023] introduced *weak-to-strong generalisation* and its metric, performance gap recovered (PGR); chess was one of their three settings, and the only one where PGR fell as the student grew. Greenblatt et al. [2023] introduced *AI control*, evaluating safety protocols against a red team that deliberately tries to subvert them.

2.4 2024: the debate wave and its limits

2024 opened with the field's best-known positive result. Khan et al. [2024] showed that debate between stronger models lifted non-expert judges to 76% accuracy (model judges) and 88% (human judges), against baselines of 48% and 60%, and that more persuasive debaters made judges *more* accurate; the paper won a best-paper award at ICML. Within months the result was narrowed. A nine-task study by Google DeepMind (GDM) found debate beat randomly assigned consultancy on every task, but reliably beat a judge answering alone only when the gap between debater and judge was one of *information*; where it was one of reasoning or capability, the results were mixed [Kenton et al., 2024]. The applicants' own GSM8K experiments found the same [Panickssery et al., 2024b], and NYU abandoned a code-debate study partly because safety-trained models would not argue competently for wrong answers [Rein, 2024]. Two results pointed forward. Self-play training of debaters raised judge accuracy by four points [Arnesen et al., 2024], an early sign that debate works as training. And Wen et al. [2024] showed why oversight matters in ordinary pipelines: RLHF made models better at convincing time-limited humans without making them more correct. OpenAI's critic model and prover–verifier games brought AI-assisted evaluation and legibility into production research [McAleese et al., 2024; Kirchner et al., 2024]; the Superalignment team itself was dissolved in May, and Jan Leike moved to Anthropic. Redwood argued that oversight should be judged as a cost frontier and must survive colluding models [Greenblatt and Shlegeris, 2024; Shlegeris, 2024].

2.5 2025: agendas, institutions and alternatives

Early 2025 brought agenda documents. Anthropic's recommended directions listed scalable oversight for outside researchers [Anthropic Alignment Science Team, 2025]. Google DeepMind's *Approach to Technical AGI Safety and Security* put "amplified oversight" in its first line of defence against misalignment [Shah et al., 2025]. The UK AI Security Institute (UK AISI) published an alignment agenda built on safety cases [Hilton et al., 2025] and a debate safety-case sketch with four explicit claims [Buhl et al., 2025]; with GDM theorists it published prover–estimator debate, which answers the obfuscated-arguments problem under a stability assumption [Brown-Cohen et al., 2025]; and in July it launched the Alignment Project, which grew from £15 million to £27 million and sixty grants by February 2026 [UK AI Security Institute, 2025a, 2026]. Measurement matured, and its results grew more sober. Engels et al. [2025] fitted scaling laws for oversight games, and found the success of nested oversight at a 400-point Elo gap to be 9–14% in three games and 51.7% in debate, where a judge picking at random scores 50%. The applicants' paper argued that judge accuracy was the wrong metric and proposed ASD [Pallavi Sudhir et al., 2025].

Alternatives gained ground. Anthropic's unsupervised elicitation method matched the performance of training on gold labels without using any [Wen et al., 2025], and chain-of-thought monitoring, backed by a multi-lab position paper, became the oversight channel with the broadest industry support [Korbak et al., 2025]. The plan to hand alignment research to AI systems met its critics: John Wentworth argued that the likely failure is plausible-looking "slop" rather than scheming [Wentworth, 2025], echoing UK AISI researchers' argument of October 2024 that empirically checked automation collapses back into human-designed algorithms [Irving et al., 2024]. Late in the year Anthropic showed that reward hacking in production RL generalises to broad misalignment [MacDiarmid et al., 2025], which made the quality of graders a safety problem rather than an efficiency one.

2.6 2026: training, fuzzy tasks and money

Theory kept advancing, but 2026 was the year debate became a training method. An open-model RL study found proposal accuracy rising while the critic learned to hack the judge [lennie et al., 2026]; Arcadia used best-of-N selection as a cheap proxy for training [Gould et al., 2026]; and at GDM Kenton et al. [2026] reported that debate training against a weaker judge recovered 45% of the performance gap relative to an AI-feedback baseline, provided critiques were capped at about 150 words. At the same time automation outran oversight on crisp problems. Anthropic's automated researchers reached a PGR of 0.97 on weak-to-strong supervision in five days, where two of the authors had reached 0.23 in seven, and the automated researchers found reward hacks in their own environment that none of the authors had predicted [Wen et al., 2026]. On fuzzy tasks the picture reversed: models trailed human agreement at judging safety-research proposals, 60% against 77% [Baig et al., 2026], and Arcadia found no gain from debate on two fuzzy tasks [Martin et al., 2026]. Institutions followed the ideas: Arcadia's alignment team (May), Resolution (June), Sampura (August), Palaestra's turn to RL self-play, and, in September, CG's Tailwind (section 5).

2.7 Where the field stands in September 2026

Five things now seem settled enough to build on. First, debate is no longer only a thought experiment or an inference-time trick. One frontier-lab result shows debate *training* resisting judge hacking on verifiable maths [Kenton et al., 2026], and several independent studies show how it fails [lennie et al., 2026; Gould et al., 2026; Martin et al., 2026]. Second, the live problem has moved from "can a weak judge check a proof?" to "can anyone oversee fuzzy, long-horizon work?", especially automated alignment research, where current protocols show little gain and even human agreement is hard to get. Third, the weak link in practice is the grader: rubric verifiers, LLM judges and monitors are exploitable, share errors with the models they grade [Goel

Table 2: Results this report leans on. Accuracy figures are judge accuracy unless stated.

Source	Result
Bowman et al. [2022]	Sandwiching on MMLU: humans 57%, model 66%, human with model 75%
Michael et al. [2023]	Expert human debate 84% vs consultancy 74%
Burns et al. [2023]	PGR defined; median NLP PGR about 25% naively, nearly 80% with a confidence loss; reward modelling about 10%; chess falling with student size
Khan et al. [2024]	Debate 76% (model judges) and 88% (human) vs 48% and 60% baselines, with information asymmetry
Kenton et al. [2024]	Debate reliably beats direct judging only when the gap is informational; mixed otherwise
Wen et al. [2024]	RLHF raises human false-positive rates by 24.1% and 18.3% (QuALITY, APPS)
Arnesen et al. [2024]	Training debaters: $+4$ points; training consultants: no gain
Engels et al. [2025]	Nested-oversight success at a 400-Elo gap: debate 51.7% (chance 50%); three other games 9–14%
Pallavi Sudhir et al. [2025]	ASD: debate 1.366–1.423, naive judge 1.235, consultancy 0.283–0.367 (Brier form)
Elasky and Nakasako [2026]; Elasky et al. [2026]	Debate below consultancy in 11 of 16 conditions; later, $+14$–16 points of macro-F1 when the critic out-classifies the judge
Wen et al. [2026]	Automated researchers reach PGR 0.97 in five days on a crisp task
Kenton et al. [2026]	Debate as RL reward: 45% of gap recovered, about 2 points absolute
Baig et al. [2026]	Judging safety-research proposals: best model 60%, human agreement 77%
Martin et al. [2026]	No debate gain on two fuzzy tasks

et al., 2025], and degrade under optimisation. Fourth, the field is split on method, between theory-first moonshots and catch-and-fix empiricism, but both camps now work on oversight. Fifth, money is no longer the constraint; experienced teams are. Resolution's launch post names the shortage of experienced researchers for founding teams as one of the bottlenecks to deploying its funding.

What is missing is a shared, protocol-agnostic measure of whether an oversight scheme rewards truth over persuasion, tracked across tasks, human and AI judges, and scales of compute, on realistic long-horizon and fuzzy work.




Figure 2: Twelve schools of scalable oversight (school 11, theory against empiricism, is the horizontal axis rather than a box). Positions are this report's reading of each school's published agenda. Dashed lines mark the schools this proposal would supply with measurements.

3 Schools of thought in September 2026

By September 2026 scalable oversight is not one research programme but a dozen, which disagree about what the problem is, which methods are worth money, and whether empirical work on today's models can say anything about superhuman ones. Table 3 lists twelve schools, with their core thesis, the organisations and people most associated with each, and how this proposal relates to them. Figure 2 places them on two axes that capture the main disagreements: how much weight a school puts on theory and guarantees as against catching and fixing problems empirically, and whether it treats oversight mainly as a training signal or as a check at deployment. The placements are this report's judgement. The unit is a research programme, not a person: several researchers, Jacob Pfau for one, publish in three schools at once.

Table 3: Schools of scalable oversight, September 2026: thesis, principal organisations and people, and relation to this proposal.

School	Core thesis	Organisations and people	Relation to this proposal
1. Debate as theory and safety case	Oversight needs protocols whose equilibria are honest, proved under explicit assumptions and assembled into safety cases; experiments should test those assumptions [Hilton et al., 2025; Buhl et al., 2025; Brown-Cohen et al., 2025]	UK AISI alignment team, now largely Resolution; Irving, Brown-Cohen, Piliouras, Pfau, Buhl, Hilton	Complement: ASD measures whether a protocol rewards honesty; also the source of the "weak empirics" critique
2. Protocol benchmarking and scaling	Whether a protocol helps is empirical and depends on the kind of judge–agent gap; standardise tasks, baselines, metrics and scaling curves [Kenton et al., 2024; Engels et al., 2025; Pallavi Sudhir et al., 2025]	GDM, MIT (Tegmark), the NYU lineage, Palaestra, Anti Entropy, the applicants; Kenton, Engels, Michael, Elasky, Recchia	Home school; crowded, with no common metric
3. Amplified oversight and human–AI complementarity	Humans stay necessary overseers for years; AI should amplify them through assistance, routing and hybrid judging [Shah et al., 2025; Jain et al., 2025; Xu et al., 2026]	GDM, Sampura; Jain, Jacob, Bridgers, Greig, Shah	Complement to the explanation strand; Sampura a partner or rival for human-judge budgets
4. Oversight as a training signal	Debate is a training procedure; the test is whether optimising against the protocol raises truth rather than judge hacking [Arnesen et al., 2024; Kenton et al., 2026; lennie et al., 2026]	GDM, Palaestra, Arcadia Impact; Kenton, Arnesen, Elasky, Feng, Pfau	Direct overlap with the RL strand; ASD during training is the differentiator
5. Weak-to-strong generalisation and elicitation	Strong models already know the answer; the task is to elicit it from weak or no labels, scored by PGR [Burns et al., 2023; Wen et al., 2025, 2026]	Anthropic, EleutherAI, NYU (Izmailov); Wen, Leike, Kirchner, Hase, Burns	Complement: report PGR beside ASD
6. Legibility and prover–verifier games	Train strong models to produce outputs a weak verifier can check, and pay a legibility tax [Kirchner et al., 2024; Hammond and Adam-Day, 2024]	OpenAI, the neural-interactive-proofs authors, LawZero; Kirchner, Hammond, Bengio	Complement to the explanation strand
7. AI-assisted evaluation in production	The practical problem is good-enough reward on unverifiable tasks now: critics, rubrics, judge panels [McAleese et al., 2024; Mahmoud et al., 2026; Goel et al., 2025]	OpenAI, Anthropic, Scale AI; McAleese, Gunjal	The demand side; the most plausible route to revenue

School	Core thesis	Organisations and people	Relation to this proposal
8. Control first	Near-term risk is mostly scheming, which control can handle without alignment; oversight matters for reward quality and as an audit layer, if it survives collusion [Greenblatt and Shlegeris, 2024; Shlegeris, 2024]	Redwood, UK AISI and GDM control teams; Greenblatt, Shlegeris, Roger	Critique target: collusion, sandbagging; supports cost-normalised metrics
9. Chain-of-thought monitorability	Reading the reasoning is today's cheapest oversight channel; preserve it and do not optimise it away [Baker et al., 2025; Korbak et al., 2025]	Multi-lab; Korbak, Baker, Emmons	Complement: whether the judge sees the reasoning is an ASD axis
10. Oversight of automated alignment research	The path to aligned superintelligence runs through AI researchers; the bottleneck is judging fuzzy research output [Carlsmith, 2025; Bowkis et al., 2026; Baig et al., 2026]	Anthropic, UK AISI, Resolution, Arcadia, Redwood; Leike, Carlsmith, Clymer, Bowkis	The strongest framing hook: fuzzy, human-graded testbeds
11. Moonshots against catch-and-fix (a cross-cutting axis)	Principled methods with guarantees are needed for superintelligence; or: iterate, catch and fix, then hand off to AI [Bowman, 2025; Greenblatt, 2025]	Resolution and Tailwind's moonshots against Anthropic's "bumpers", Redwood's plans and GDM's "midgame"	Position as the empirical bridge between the poles
12. Honesty-targeted oversight	Make honesty the target directly: lie detectors in the loop, separately rewarded confessions [Cundy and Gleave, 2025; Hollinsworth et al., 2026]	FAR.AI, OpenAI, UK AISI; Gleave, Cundy, Barak	Complement: another protocol for the library to score

3.1 The disagreements that matter for a funder

Four disagreements cut across the table, and a proposal has to take a side on each or explain why it need not.

Can empirics on today's models say anything about superhuman ones? School 1's answer is not much, on their own: oversight of superhuman systems needs protocols whose honest equilibrium is proved, and experiments are useful when they test a named assumption of such a proof. Geoffrey Irving's line on Tailwind's moonshot page, against muddling through with weak empirics, is aimed at programmes that measure without a theory. The answer for this proposal is to tie experiments to the assumptions of the debate safety case [Buhl et al., 2025]. ASD directly measures the quantity its second claim needs, whether good performance in the game implies mostly honest play; and the RL strand tests whether training actually reaches the equilibria theory predicts, which Resolution's own memo names as a condition for debate to be useful [Resolution, 2026c].

Does oversight matter if models scheme? The control school argues that the dominant near-term catastrophic risk is a model deliberately subverting its overseers, that control can address it without solving alignment, and that debate only helps if it is reliable when the debaters collude [Greenblatt and Shlegeris, 2024]. The answer is not to dispute this. The pitch should point instead to the failure already observed at scale, reward hacking against imperfect graders [MacDiarmid et al., 2025], which the control school itself agrees oversight addresses. It should include colluding and sandbagging conditions in the experiments, and report ASD per unit of oversight cost, which directly answers Shlegeris's framing of oversight as a cost frontier.

Is debate the protocol? Three of CG's four oversight grantees (Resolution, Palaestra and Arcadia) centre on debate; the fourth, Sampura, builds judges. The evidence of 2026 is mixed: debate training works on verifiable maths with constraints [Kenton et al., 2026], fails to beat consultancy in 11 of 16 inference-time conditions in one study [Elasky and Nakasako, 2026] while beating it for the strongest pairings in another [Elasky et al., 2026], and gives no gain, under a best-of-N proxy, on two fuzzy tasks [Martin et al., 2026]. A protocol-agnostic programme is the natural response: it measures where debate helps, where simpler critique recovers most of its benefit, and where something else (a market, a legibility constraint or a human–AI team) does better.

Where does human judgement fit? School 3 holds that humans will remain necessary overseers for years, while school 5 holds that for many tasks the model already knows the answer and human labels are the weak link. The two can both be right on different tasks, and the distinction is measurable: on crisp tasks automated overseers already beat people, and on fuzzy ones they trail. That is why this proposal pairs cheap machine-checkable settings with human-graded ones, and plots every result against evaluator effort.

3.2 Where this proposal sits

The proposal's home is school 2, protocol benchmarking, with a metric that is protocol-agnostic by construction and a library as infrastructure. Its four extensions map onto the live frontiers of five other schools: RL training (school 4), scaling curves for ASD and PGR (schools 2 and 5; Engels et al.'s are the only scaling laws fitted to oversight games, and PGR the only oversight metric measured across many orders of magnitude), explanation for oversight (schools 3 and 6), and realistic long-horizon and fuzzy tasks (school 10). The gap no one has filled, across all twelve, is a common metric and library spanning protocols, tasks and scales of compute, validated against human graders. By September 2026 at least five groups outside the labs publish oversight benchmarks or debate-training results, and each measures in its

own way. A common yardstick is something all of them could use, and its value is easy for a funder to see.

Part II

The funder

4 How Coefficient Giving sees scalable oversight

Coefficient Giving is the name Open Philanthropy took on 18 November 2025. Its AI programme was renamed *Navigating Transformative AI* in October 2025, and CG is now much the largest philanthropic funder of technical AI safety. This section traces how the funder has thought about scalable oversight since 2021, who inside it reads which kind of proposal, and what that implies for a pitch in September 2026. The argument is that CG's framing of oversight has taken three forms, and that the current framing fits the applicants' instrument better than any earlier one.

4.1 The money and the speed

The scale of CG's AI-safety spending has changed the arithmetic of any ask. By Emily Oehlsen's account in the post that launched Tailwind [Oehlsen, 2026], CG committed $168 million to technical safety, security and field-building in 2024 and $351 million in 2025, is on track for more than $1 billion in 2026, and committed $352 million in August 2026 alone. Within that, the technical AI safety team went from $40 million of grants in 2024 to more than $140 million in 2025 with, as Jake Mendel put it, only three grant investigators [Mendel, 2025]. Across the whole foundation, Nan Ransohoff puts 2025 giving at about $1 billion in some 1,000 grants, an average of roughly $1 million per grant [Ransohoff, 2026].

The money now moves fast and in large pieces. Most of CG's catastrophic-risk grants above $20 million were made in 2026. A typical grant needs sign-off from one person besides the grant investigator. Resolution's $160 million took six weeks from first conversation to confirmation, and an initial $10 million for Jacob Tsimerman's institute of mathematicians working on AI safety was approved twelve days after the first conversation [Oehlsen, 2026]. The same post says CG encourages grantees to plan larger budgets, naming compute and salaries. Mendel has told two versions of the same story. A researcher who asked him for $10,000 of compute ended up with a $1 million grant to found a formal-verification company [Mendel, 2025]. And Rishub Jain, who first came to CG for a small grant to cover research expenses, was, in Mendel's words to Bloomberg, encouraged "to come back

with a more ambitious proposal". That proposal became Sampura Research and its $11 million [Bloomberg, 2026]. The lesson for sizing an ask is taken up in section 9: at this funder, under-asking is a larger risk than over-asking, provided the money is tied to milestones.

4.2 Three framings of oversight, 2021–2026

2021: oversight as a headline direction. Ajeya Cotra's essay on "aligning narrowly superhuman models" coined *sandwiching*: put a model between a less capable and a more capable group of humans, and find ways to help the first group reproduce the second group's judgements [Cotra, 2021a]. She wrote it in a personal capacity, and said Open Philanthropy was not then seeking applications on the topic. Eight months later it was. The October 2021 request for proposals had four directions, and Cotra's *Techniques for enhancing human feedback* was one of them, with grants of up to $1 million over as much as two years [Bergal and Beckstead, 2021; Cotra, 2021b]. Two of its asks read like this proposal's. One of its example strategies was to train on human evaluations given after different amounts of reflection (one minute, ten minutes, an hour) and test whether the model generalises to evaluations made after five hours. And it asked for studies of how different feedback-enhancing techniques change the way performance *scales* with the amount of human labour put in. The appendix of the 2021 essay went further, to settings where models beat every human: checking outcomes in hindsight, as with stock picks against realised returns, and probing a superhuman game engine for lessons that professional players could learn. The chess setting of section 8.3 and the autonomous-business setting of section 6 echo that appendix, and the pitch should say so.

2025: oversight as something to stress-test. The $40 million Technical AI Safety request for proposals of February 2025 [Mendel et al., 2025] listed 21 research areas and no area called scalable oversight or debate. Grants were "typically" $50,000 to $5 million, and new research organisations faced a higher bar. Oversight survived in three reframed places. It appeared as an object to be red-teamed, within the starred *control evaluations* area, which asked in particular for evaluations of oversight protocols such as debate. It appeared as a failure mode to demonstrate, in the unstarred area *reward hacking of human oversight*. That area wanted cases where the mistakes come from the humans, not merely a hackable learned reward model, and prized four things: realism, models that actually exploit the errors, severe exploitability and the study of generalisation. And it appeared as a target for high-bar "moonshots" that might scale oversight to superhuman models. Weak-to-strong generalisation, sandwiching and the word "sandwich" did not appear at all. CG funded the first of these directly: a $218,513 grant to the University of Texas at Dallas for control evaluations of debate.

2026: oversight back by name. Tailwind restores scalable oversight as an agenda in its own right, in two places. The "unclaimed research labs" initiative lists it among the agendas still waiting for a team, and defines it as techniques for giving AIs high-quality rewards during training as training tasks get harder to oversee, or, alternatively, techniques that "fail loudly" when the quality of oversight becomes insufficient. The "alignment moonshots" initiative names debate, and scalable oversight generally, as one of four principled bets, each a high-value, low-probability shot on goal. The page carries a quotation from Geoffrey Irving that criticises muddling through with weak empirics until machines can take over alignment research. In between, CG's statement of approach in October 2025 had listed scalable oversight first among the technical research it values [Berger and Oehlsen, 2025]. There is currently no open technical-safety request for proposals: the programme's page sends people who want to found research organisations to Tailwind.

4.3 Who reads which initiative

Most Tailwind initiatives carry, in the page's data, the CG staff who endorse them. The technical-safety items are overwhelmingly Jake Mendel's: alignment moonshots, the two red teams, chain-of-thought monitorability, compute for safety, AI uplift for safety, AI for decision-makers, and (with Max Nadeau) training-run fault injections. Two of the items nearest this proposal's fuzzy-task and human-grader work, misleadingness evaluations and datasets for AI safety, are endorsed instead by Rohan Subramani of the short-timelines special-projects team. The unclaimed-research-labs item, which names scalable oversight, lists no endorser. So the likely readers of this proposal are the technical-safety programme officers, with Subramani a natural second reader for the misleadingness work.

Staff comments sketch how those readers think. Max Nadeau has described scalable oversight, eliciting latent knowledge and related work as attempts to mitigate Goodharting and reward hacking, which is the frame of the 2025 request [Nadeau, 2026]. Mendel, commenting in February 2026, placed debate on a spectrum of handing alignment work to AIs, from AI monitors of reward hacks (which labs already use) to having AIs design better debate algorithms, and asked whether today's most scalable alignment approaches will scale as far as capabilities do [Mendel, 2026]. That is a question about scaling curves, which is what strand 2 of this programme measures.

4.4 What this implies for the pitch

How to frame the proposal for this funder

1. **Lead with catastrophic risk.** Tailwind filters out proposals not directly about catastrophic risk. The link is reward quality. If oversight of hard tasks fails, training rewards models for fooling cheap or flawed metrics, and the models that labs hand safety work to during an intelligence explosion will be good at looking right.
2. **Present ASD as the instrument CG's framings need.** Both Tailwind definitions of scalable oversight, reward quality for hard-to-oversee training and oversight that fails loudly, require a way to measure how much a protocol rewards honest work over deceptive work, and to see where that advantage collapses. ASD is such a measure. Do not present it as just "a benchmark": CG staff file benchmarks under evaluations, which they value but do not count as safeguards.
3. **Put human effort and compute on the x-axis.** Cotra's 2021 question (how does oversight scale with human labour?) and the 2026 misleadingness item (how do ratings change with evaluation time?) are the same curve. Offer oversight-quality curves against evaluator effort and against model compute, on tasks with ground truth.
4. **Show real exploitation.** The 2025 criteria still describe what CG finds convincing: realistic settings, models that actually exploit the errors, severe exploitability, and generalisation. The RL-training strand provides the exploitation.
5. **Be ambitious and staged.** The pre-seed tier is explicitly a test, with an invitation to return for seed funding within months if it works.
6. **Name the right initiatives.** "Unclaimed research labs: scalable oversight" first, as the home; "misleadingness evaluations" second, as the first concrete deliverable; training-run fault injections and datasets for AI safety only in passing. Do not lead with "alignment moonshots": it asks for theory-led visionaries and is now anchored by Resolution's theory programme. The applicants are better placed as the empirical measurement layer that moonshot protocols need.

5 The scalable-oversight groups CG already funds

All four organisations named in the brief hold CG money for oversight work. Resolution, Sampura and Arcadia's alignment team were funded in 2026; Palaestra acknowledges CG support of undisclosed size and date. Together they define the space that a new proposal must fit into. Table 4 lists every CG grant this research found that is explicitly about scalable oversight or debate, with the large 2026 commitments at the bottom.

Table 4: Coefficient Giving grants explicitly for scalable oversight or debate, 2023–2026. Amounts in US dollars as published by CG or announced by the grantee; the 2026 organisation grants were not yet in CG's public database on 17 September 2026.

Date	Grantee	Purpose	Amount
Aug 2023	Modulo Research (Gabriel Recchia)	sandwiching experiments, datasets	408,255
Sep 2023	Berkeley Existential Risk Initiative	scalable-oversight dataset	70,000
Feb–Apr 2024	Michigan (Oymak), Princeton (Lee), Wisconsin (Papailiopoulos)	scalable-oversight research, three grants	$3 \times 100{,}000$
Sep 2025	University of Texas at Dallas (Xinya Du)	control evaluations of debate	218,513
Apr 2026	Kairos, for Rishub Jain	scalable-oversight research	50,000
Apr 2026	Arcadia Impact	alignment team (including debate)	1,900,000
Jul 2026	Resolution	new alignment organisation	160,000,000
Aug 2026	Sampura Research	human–AI judges	≈11,000,000
n.d.	Palaestra Research	debate via self-play	not public

5.1 Resolution

Resolution is Geoffrey Irving's new nonprofit, Resolution Alignment, Inc. [Resolution, 2026c,d]. It was announced on 10 June 2026 as Sequent Research, bringing together researchers from the alignment team of the UK AI Security Institute, where Irving was chief scientist, and from Timaeus, a nonprofit working on singular learning theory and developmental interpretability; it took its present name later that month. Legally it is the former Timaeus Research, Inc., and it is based in Berkeley with remote staff in London and Melbourne. CG's grant of $160 million, a $108 million base plus $52 million conditional on hiring and compute needs, is CG's largest AI-safety grant to date [Resolution, 2026a; Oehlsen, 2026]. OpenAI added $10 million in API credits. The launch memo aims at 40–80 staff within two years.

Resolution's agenda is a portfolio of theory and empirical bets, with heavy investment in automation. Scalable oversight is one of its programmes: complexity theory and empirics of amplification and debate, with the goal of asymptotic guarantees that a training protocol converges to a tolerably low chance of unsafe behaviour. Its memo also notes that a method like debate is useless if its safe equilibria cannot be reached by practical training. It plans no large training runs. Two facts matter for the applicants. As of 21 August 2026, scalable oversight was the *only* research area Resolution was

hiring for [Resolution, 2026b]. And its published salary ladder runs from $236,000 to $930,000 for in-person research staff ($141,000 to $558,000 remote), well above what most nonprofits pay and a useful anchor for budgets (section 9). Resolution also holds a small regranting budget for outside alignment research.

Relation to this proposal. Large overlap in topic, little in method. Resolution is theory-first. It is not building a general oversight benchmark, a protocol-agnostic metric or scaling curves across task families. An empirical programme that measures whether protocols' theoretical equilibria are actually reached, across compute and realistic tasks, is what a theory-first team needs and does not plan to build.

5.2 Sampura Research

Sampura was launched in London on 25 August 2026 by Rishub Jain, who spent seven years at Google DeepMind and co-led its scalable-oversight work, and Josh Jacob, who co-led DeepMind's human-data engineering organisation [Sampura Research, 2026a]. Its name comes from the Sanskrit for "complementary". The funding is $11 million from CG, described by Sampura as $7 million for the first year plus $4 million pledged, and by Bloomberg as $6.5 million raised plus $4.2 million pledged over about eighteen months [Bloomberg, 2026]. It was preceded by a $50,000 CG grant for Jain's research (April 2026), probably the small grant Mendel describes. Sampura is not its own charity: its site describes it as a fiscally sponsored project of Rethink Priorities, whose sponsorship service employs staff through US and UK entities. It is therefore the direct precedent for a seed-scale CG grant to a young, London-based oversight team with no entity of its own (section 11).

Its first six months go to building better *judges* (human, AI or hybrid) through human–AI complementarity. The centrepiece is a public leaderboard of more than twenty sub-datasets, some of which put judges under direct optimisation pressure from the models they oversee during RL; judges are to be hill-climbed on it with methods such as confidence estimation, routing to humans, task decomposition and generated assistance interfaces. It then plans to deploy its judges in labs' training, evaluation and monitoring. Its job advertisement discloses a budget of about $1 million a quarter for compute and human data, for a team of fewer than ten, and salaries of £100,000–£290,000 [Sampura Research, 2026b].

Relation to this proposal. Sampura measures judges, largely on classification-style data with paid human annotators. The applicants measure protocols with strategic agents, and how that measurement scales with compute and task horizon. ASD could be a column on Sampura's leaderboard, and a shared human-rating platform would serve the writing studies. The explanation

strand (section 8.1) sits close to Sampura's assistance interfaces, so the pitch should either propose collaboration there or say clearly where the two differ.

5.3 Palaestra Research

Palaestra is a small remote nonprofit founded by Ethan Elasky and Frank Nakasako, both from Berkeley [Palaestra Research, 2026]. Its near-term agenda is debate via RL self-play, organised around one question: when debaters are stronger than the judge, does optimising the debaters make the judge more accurate? It tests best-of-N selection and self-play against matched consultancy baselines, on three tasks that are easy for the debaters but hard for the judge: spotting sabotage in agent transcripts, reviewing code patches and giving domain advice. CG's support is acknowledged in its May 2026 preprint and on Elasky's site, but no amount is public and the grant is not in CG's database.

Its two write-ups show how much debate's benefit depends on the setting, which any new oversight proposal has to reckon with. The first, in February 2026, found debate *underperforming* consultancy in 11 of 16 conditions, with a judge shown no transcript at all matching or beating both [Elasky and Nakasako, 2026]. The second, in May 2026, found debate beating consultancy by about 14–16 points of macro-F1 on three of five model pairings, and working only when the critic classifies better than the judge and the judge treats the critic's speeches as claims to check rather than testimony to summarise [Elasky et al., 2026].

Relation to this proposal. Closest in topic of all CG's grantees: weak judges, strong models, consultancy baselines, a planned move to long, fuzzy tasks and to RL training. The difference is scope. Palaestra is debate-centred and measures judge accuracy. The applicants offer one metric across all protocols, scaling curves and long-horizon settings. The mixed results above are the kind of disagreement a common metric and shared tasks would help resolve, which makes Palaestra a natural user of the library rather than only a competitor.

5.4 Arcadia Impact and its alignment team

Arcadia Impact is a registered charity in England and Wales, founded in 2022 to support students and early-career researchers in London. It runs LASR Labs, a governance taskforce, the Orion governance programme and an engineering taskforce that builds evaluations for the UK AI Security Institute [Arcadia Impact, 2026a]. CG is its main funder, with grants totalling about $12.2 million. The most recent is $1.9 million in April 2026 for the "Arcadia Impact Alignment Project" (which publishes as Arcadia Alignment), a research group launched in May 2026 in close collaboration with the UK AISI alignment team. Scalable oversight, specifically debate protocols, is

Table 5: How the proposal differs from, and could complement, CG's oversight grantees.

Group	Focus	Difference	Complement
Resolution	theory-first portfolio; asymptotic guarantees; debate as training; no large runs	empirical, protocol-agnostic, scaling across compute and tasks	tests whether equilibria are reached; host for a team
Sampura	human–AI judges; judge leaderboard; human data at scale	protocols with strategic agents; long horizons; compute scaling	ASD as a leaderboard column; shared rater pool
Palaestra	debate vs consultancy; RL self-play; code and agent transcripts	all protocols on one metric; realistic firm tasks	library user; shared tasks
Arcadia Alignment	debate best-of-N; null on fuzzy tasks; decomposition bottleneck	explanation training as the missing piece	collaboration on fuzzy-task benchmarks

one of its three areas [Arcadia Impact, 2026b]. Researcher salaries start at £120,000.

The team has already produced two results that bear on this proposal. Using best-of-N sampling as a cheap proxy for debate training, it found accuracy gains of 20–40% on verifiable tasks (LiveCodeBench, ARC-AGI-1, miniF2F in Lean), with judge hacking already visible at best-of-10 [Gould et al., 2026]. Then, on 16 September 2026, it reported *no* gain from the same proxy on two fuzzier tasks, a text version of GeoGuessr and a pairwise scoring task. Its diagnosis was that on fuzzy tasks the answer is an aggregate of many individually weak, correlated claims, so debate's guarantee (that a dishonest argument can be reduced to one checkable flaw) does not bite, and that models will need training to produce good decompositions [Martin et al., 2026].

Relation to this proposal. Arcadia's stated bottleneck, models that can decompose and explain their reasoning so that a judge can check it, is close to the explanation strand of this programme. Arcadia does not appear to offer fiscal sponsorship to outside teams, so it is a potential collaborator or host for a team, not an administrative umbrella.

5.5 What the four grantees imply

Three conclusions follow (table 5).

The field is crowded, and the gap is measurement. CG now funds at least four oversight efforts, three of them started in 2026. Each measures its own proto-

cols in its own way: judge accuracy, macro-F1, leaderboard rank. None claims a common metric, public infrastructure for comparing protocols, or a scaling science of oversight across compute and task horizon. That is the applicants' opening, and the pitch should answer "why a new organisation?" with it.

Debate optimism now reads as naive. Palaestra's February result and Arcadia's fuzzy-task null, both CG-funded, are public. A pitch that assumes debate works will look uninformed; a pitch that promises to measure where each protocol fails, and to detect the failure, matches Tailwind's "fail loudly" framing and turns the negative results into motivation.

There is a real option to join rather than found. The Tailwind FAQ invites proposals for a new team at an existing organisation. Resolution is hiring only for scalable oversight and has a regranting budget. Arcadia has an oversight team, launched in May 2026, whose bottleneck the applicants address. Founding an independent organisation keeps control of the agenda and of the library as a neutral public good, which matters if the library is to be used by all four groups. But the pitch should show that the applicants have considered joining, since CG asks about it directly.

Part III

The programme

6 Strand 1: oversight experiments on realistic, long-horizon work

This is the programme's foremost strand: measure oversight protocols on the kind of work that agents now actually do, long, stateful and consequential, rather than on multiple-choice questions.

6.1 Why the old settings are not enough

Arjun's diagnosis of the settings used so far is blunt, and the literature bears it out. The "information asymmetry" settings, in which debaters see a long story that the judge cannot read, were chosen because they gave debate something to do, not because they resemble any real oversight problem; the gap between debater and judge was manufactured by hiding a passage [Pang et al., 2022; Khan et al., 2024]. When GDM replaced hidden passages with genuine reasoning or capability gaps, debate's advantage over a judge answering alone became inconsistent [Kenton et al., 2024]. Mathematics has the opposite problem. In the ASD paper's setting even a small judge, `gpt-4o-mini`, solved most problems unaided, putting about 0.81 on the

right answer, which left little room for any protocol to help (section 1); and a harder problem set would have needed a judge strong enough to follow the debate, narrowing the gap to the debaters.

Meanwhile the world the protocols are meant for has arrived. METR's latest measurement puts the length of task that the best frontier agent completes half the time at about 17 hours of human expert time, with the trend doubling roughly every four months [METR, 2026]; METR itself calls measurements above 16 hours unreliable. Agents now run businesses, in simulation and for real: Andon Labs' Vending-Bench, Anthropic's Project Vend and Project Deal, and Sage's AI Village [Backlund and Petersson, 2025; Anthropic, 2025, 2026; AI Digest, 2025]. Warp says its software factories handle about 30% of its engineering work (section 6.2).

These deployments keep producing oversight failures that no one set out to produce or measure. In Project Vend's second phase, a "CEO" agent built on the same model as the shopkeeper it supervised approved the shopkeeper's requests for lenient treatment of customers about eight times as often as it denied them, and shared its blind spots [Anthropic, 2025]. In Project Deal, people represented by weaker negotiating agents got worse prices but rated their deals just as fair, 4.05 against 4.06 on a seven-point scale [Anthropic, 2026]. In a June 2026 study of about a hundred developers working with a coding agent for roughly five hours, 94% missed the agent's sabotage, and 56% accepted it despite a monitor's warning [Ye et al., 2026]. In SHADE-Arena, human monitors, who took an average of 103 minutes per transcript with no time limit, reached an area under the curve of 0.65, below the best LLM monitor's 0.87 [Kutasov et al., 2025].

None of the business settings measures oversight as such. The business benchmarks score the business outcome; where an overseer exists, it is an uninstrumented part of the scaffold. No setting that this review found pairs an honest agent with an instructed-deceptive agent on the same business task and asks whether a reviewer can tell them apart. That is the gap the paired-branch design is meant to fill.

The nearest existing structure is in AI control. UK AISI's ControlArena runs every task in an honest mode and an attack mode and scores a monitor [UK AI Security Institute, 2025b]; SHADE-Arena and BashArena do the same with side tasks [Kutasov et al., 2025; Kaufman et al., 2025]. What they report is different: worst-case safety and usefulness, or attack success and a monitor's discrimination, not the *reward gap* between honest and dishonest behaviour under a protocol, which is what matters if the protocol is used as a training signal. ASD is therefore not a rival to these benchmarks but another read-out of the same paired design, and most of them could report it from their existing logs at almost no cost. Computing ASD on ControlArena's logs is the natural first deliverable of the programme (section 10).

6.2 The Warp Factory analogy

Abhimanyu describes the programme's core experiment as "the equivalent of Warp Factory benchmarks on a range of different protocols". The analogy is apt, but it holds for a different reason from the one he supposed, and the difference strengthens the pitch.

What Warp built. Warp, the company behind the agentic terminal of the same name, launched *Factories* in closed beta on 18 August 2026 [Lloyd, 2026a]. A factory is an automation loop around software development in which cloud agents triage, specify, implement, review and verify work, with humans at chosen decision points. The whole configuration is code: a `factory.yaml`, one Markdown file per agent (each pinned to a model or to a harness such as Claude Code or Codex), sandbox "runners", and "scorers". Warp says its own factories handle about 30% of its engineering tasks. On 3 September 2026 it added *Factory Benchmarks* [Lloyd, 2026b]. A benchmark task is a prompt, natural-language success criteria and a set of repositories pinned to exact 40-character commit hashes, usually mined from the company's own past runs. A *trial* is one task under one configuration. Each runs in its own sandbox on its own branch, cut from the pinned commit, with the push remote removed or pointed at a mirror repository, so trials cannot touch production. The run's inputs are frozen, so later edits to the suite do not change past results. Warp used the system to move its main implementation agent from an automatic router that mostly chose Opus 5 to a cheaper model, cutting its cost per pull request from $80 to $30 with an unchanged merge rate. Its own write-up of a 30-task, five-model run reports a bill of $2,130.57 and a wall-clock time of 3 hours 46 minutes [Lloyd, 2026c].

Where the analogy holds. The mapping is close (table 6). A factory configuration corresponds to an oversight protocol; more precisely, the protocol is the review-and-verify part of a factory, the agents and gates that decide what gets merged. A task pinned to a commit corresponds to a question. Warp's machinery for running several configurations on the same starting state in isolated branches is exactly what the paired design needs: the honest agent and the deceptive agent are two trials from the same commit, which is Abhimanyu's "two mostly-independent versions of the task".

Where it breaks, and why that helps. Abhimanyu supposed that Warp's scorers are ground truth. They are not. Warp's built-in *Correctness Scorer* is a language model that reads the stored transcript, diff and pull request after the trial and classifies it against the task's success criteria [Warp, 2026]. The shipped example scorer runs on a Haiku-class model and decides even whether tests were run by reading the transcript. The only non-model quality

Table 6: Warp Factory benchmarks and ASD protocol benchmarks compared.

	Warp Factory benchmark	ASD protocol benchmark
What varies (treatment)	factory configuration: models, harnesses, skills	oversight protocol: reviewer, consultancy, debate, market-making; judge model
Unit of work	task pinned to a commit; one trial per configuration and repetition	the same, run twice: an honest and a deceptive agent from the same commit
Isolation	sandbox, own branch, push remote removed or mirrored	the same, plus branched databases, payment sandboxes and simulated counterparties
Scorer	LLM judge reading the trace against success criteria	the protocol's verdict, which is the object under test
Ground truth	merge rate and human review, after the fact	the instructed intent, checked by an audit that confirms the deceptive branch really misbehaved
Headline number	cost against judged quality	ASD (paired, honest minus deceptive), with its worst case

signal in Warp's published results is the merge rate. Warp's benchmark is therefore itself a weak-judge oversight arrangement: a cheap judge grades the work of stronger agents, and a "self-improvement" loop then edits the factory to raise those grades. That is the scalable-oversight problem in production, with money riding on it.

This inverts what is being measured. Warp holds the scorer fixed and varies the worker. An ASD experiment holds the task set fixed, controls the worker's intent (honest or deceptive) as the experimental manipulation, and varies the *overseer* as the treatment, with ground truth supplied by construction. In one line: *Warp benchmarks the worker against a trusted grader; ASD benchmarks the grader against a known worker*. The practical consequence is an early experiment that any factory operator will recognise: measure the ASD of a software factory's reviewer. Run instructed saboteurs through the same replayed tasks as honest implementers, and measure how much more the Correctness Scorer, or a debate-based replacement, rewards the honest branch.

Three further breaks need design work, and they set the agenda for the rest of this section. First, ground truth comes from intent, and intent can fail: a "deceptive" agent may refuse, may fail to do any harm, or may do harm so clumsily that any reviewer catches it. The Propaganda bug in the original




Figure 3: One experimental unit of an ASD benchmark on firm work. The same task is run twice from the same starting state, by an honest and a deceptive agent, and the protocol under test decides whether to accept each result. Ground truth is fixed by which agent was told to deceive, confirmed by an audit.

code (section 1) is this failure: the agent was not told its role. Every deceptive branch therefore needs a *manipulation check*. Second, stateful side effects such as emails, payments and third parties do not branch the way git does. Third, graded quality needs a ground-truth judge after all.

6.3 The paired-branch design

Figure 3 shows one experimental unit. A task τ is drawn from a firm's backlog, with a starting state S_0 that fixes the repository commit and everything else the task can touch. Two agents start from S_0: one instructed to do the task properly, one instructed to fake success. Each works in its own branch and leaves a diff, logs, a final state and a report. The oversight protocol P sees what it is allowed to see (only the report, the diff, a debate between the agent and a critic, or an audit with query access to the logs) and returns a probability of acceptance. The paired difference of log acceptance probabilities is the ASD of that protocol on that task.

Making stateful actions branchable. Code branches, replays and discards cheaply. Abhimanyu's cold-email example does not: in the naive version the two worlds share one outside world, the same prospects are contacted twice, sent mail cannot be recalled and company money really moves. The fix is to branch or sandbox every stateful dependency, so that a trial is a tuple of a git commit, a database branch, a payment sandbox and seeded simulated counterparties. Copy-on-write database branching exists off the shelf: Neon for Postgres, and Dolt, which versions SQL tables like git and so makes the difference between the honest and deceptive worlds' data itself an object a

reviewer can inspect [Neon, 2026; DoltHub, 2026]. Stripe's sandboxes process nothing through card networks [Stripe, 2026]. Simulated counterparties can follow τ-bench, which grades a conversation by comparing the final database state with an annotated goal state [Yao et al., 2024]. Warp already lets a task seed one stateful external system, the issue tracker, per trial. The cost of sandboxing is realism. A fraud such as paying for burner sign-ups with the company card is only detectable if the sandbox models identity and the provenance of payments, so building a sandbox rich enough to express the deceptions is part of the research, not overhead.

Economies in the design. For protocols that do not interact with the agent (a reviewer reading a pull request, the naive judge, Propaganda), the expensive work stage runs once per task and intent, and every such protocol can be applied to the stored artefacts. Only interactive protocols, such as consultancy, debate or cross-examination, need the agent live, and Warp-style replay from a stored initial state covers them. ASD is also a paired difference on the same task, which is statistically efficient: the task's own difficulty cancels, and confidence intervals should be computed on the pairs.

6.4 From binary to graded: generalising ASD

Binary good-or-bad agents are where the method starts, not where it can stop. Real work varies continuously in quality, and the most dangerous failures are subtle. The library's answer-value scoring points to the generalisation; the centred form below is this report's. Let a task admit behaviour cases $c \in C_\tau$ (an honest completion, a lazy one, one that misreports a metric, one that commits fraud), each with a ground-truth value v_c. Run an agent instructed to realise each case, and let the protocol return a score $s_P(c)$. Then

$$\mathrm{ASD}_P(\tau) \;=\; \sum_{c \in C_\tau} (v_c - \bar{v})\, \log s_P(c), \tag{2}$$

where $\bar{v}$ is the mean value. With two cases valued $+1$ and -1 this is (1). With graded values it is, up to a constant, the covariance between the protocol's log-scores and the true values, and it rewards protocols whose acceptance tracks value rather than merely separating the best from the worst.

Worst-case ASD and the ground-truth drift problem. The paper's future-work section asks for worst-case rather than average ASD, and for alignment this matters most: one accepted sabotage can outweigh a thousand correctly rejected ones. The natural way to find the worst case is to search: optimise the deceptive agent's instructions, or train it, to maximise its acceptance under the protocol. Here Abhimanyu's remark about prompt optimisation bites. An optimiser pushed to raise a deceptive agent's acceptance may discover that the best way to be accepted is to do the task honestly. Once the

deceptive branch has been optimised, it is no longer deceptive *by construction*, and its label must be re-established by an independent audit that is more expensive, and more reliable, than the protocol it audits: hidden tests, a planted-bug oracle, a stronger model with more compute, human experts, or the eventual real outcome. Roth et al. [2026] take the complementary route of building ground truth into the environment rather than the prompt: their *Hack-Verifiable Terminal Bench* plants detectable hacks in tasks, so that reward hacking is identified automatically. Both approaches belong in the benchmark, because they fail in different ways.

The audit's cost sets the budget. If the ground-truth judge is a human expert who needs an hour per item, a sweep of a few thousand items costs $100,000 or more in human time alone, at $40–$100 an hour. This is why the proposal pairs cheap, machine-checkable settings (section 8.3) with a smaller number of expensive, human-audited ones (section 6.5).

6.5 Four task families

The paired-branch design is the same everywhere; what changes is the environment, the forms deception takes, and where ground truth comes from. Four families cover the programme.

Existing control settings (the first milestone). ControlArena, SHADE-Arena and their relatives already run honest and attack modes on the same tasks. Re-reading their logs as ASD, protocol by protocol, costs almost nothing, makes the metric immediately comparable with the control literature, and could give the library its first external users. It is also a fair test of whether ASD tells a funder anything that safety and usefulness scores do not.

Software and internet firms. The environment is a small software-as-a-service company: a web-application repository, a Postgres database of users, trials and subscriptions, a Stripe sandbox, a mail sink, an allow-listed network proxy, and a population of a thousand or more simulated prospects, each with a mailbox and a hidden willingness to pay. State forks with a git worktree, a copy-on-write database branch and a sandbox snapshot. Tasks come with a key performance indicator the environment can verify: acquisition (Abhimanyu's cold-email task), growth engineering (ship a pricing page, fix onboarding), operations (refunds, support tickets) and reporting (the weekly investor update). The deceptive arm must still appear to finish the task, as in control side tasks, and it can misbehave in at least seven ways: burner sign-ups paid for with the company card; misleading claims in outreach; gaming a metric, for instance by redefining "active user"; self-dealing; under-delivering while calling the hard parts out of scope, which METR's Megan Kinniment reports seeing on fuzzy tasks; silently disabling unsubscribe links; and exfiltrating the customer list. A third, uninstructed arm

under high pressure estimates how often natural misbehaviour looks like the instructed kinds.

The protocols compared all see a standard dossier (the agent's report, the repository and database diffs, the mailbox and the ledger). They are: a single reviewer, weaker than, as strong as or stronger than the agent, and from the same or a different model family; consultancy; debate between the worker and an adversarial auditor from another family, with a word-limited critic; critique-assisted human review; a market in which several auditors bet on which claims survive a random full audit; and control baselines such as trusted monitoring. The reviewer's *access* is crossed with the protocol, from the report alone to the diffs to the ability to query the database and ledger, because access matters a great deal in the research family below. Ground truth is computed by the environment, which knows which addresses are burners and which card paid, with a human audit of a random tenth of cases to check the checker. At current list prices, with prompt caching, a task pair costs about $30–$190 including six protocols over both arms; 200 task pairs with three agent models, 600 pairs in all, come to roughly $20,000–$115,000 of API spend.

Writing, with human graders as ground truth. Writing is where LLM judges are least trustworthy and human ground truth is most contested. Zero-shot LLM judges are near chance on expert-labelled pairs of writing [Chakrabarty et al., 2025b], and reach 73% on Reddit-upvote pairs, 78% once trained [Fein et al., 2025]. The authors of the Writing Quality (WQ) benchmark [Chakrabarty et al., 2025b] attribute part of the judges' failure to self-preference, citing Arjun's NeurIPS paper, which makes the writing work a natural extension of his record. Human ground truth also depends on *which* humans: in a preregistered study, MFA-trained readers strongly disfavoured the quality of AI prose written in context (odds ratio 0.13) while general readers favoured it (1.82) [Chakrabarty et al., 2025a]. An ASD study must therefore fix its panels in advance and report each separately, because they can disagree in sign.

The main contribution here maps directly onto Tailwind's misleadingness initiative. The figure it links to, by METR's Megan Kinniment, plots perceived quality against time spent judging, for successive models: a model that is getting better at fooling evaluators is rated highly at short evaluation times and badly at long ones, with the drop moving later each generation [Kinniment, 2026]. ASD measured at several evaluation budgets traces that curve, which no study this review found has measured. The design: honest and misleading versions of explainers, summaries of technical documents and persuasive essays (the misleading version overstates results, omits limitations or invents a citation), with literary pieces as a control where ASD should be near zero; expert and target-reader panels; ratings at budgets of 2,

10 and 30 minutes and, for a subset, 120; and the time t^* at which ASD first exceeds a threshold, tracked across model generations. At about $40 an hour for expert raters, rating both versions of all 200 prompts, three raters each, at every budget would take about 3,200 expert-hours, roughly $130,000. A fractional design, with every piece rated at 2 and 10 minutes, half at 30 and a fifth at 120, needs about 1,000 hours, roughly $40,000, which fits the pre-seed grading line.

Research tasks. Research is the best-instrumented sabotage domain and the one where oversight by reading is weakest. Reviewers in classic peer-review studies caught on average 2.58 of 9 planted major errors [Schroter et al., 2008]; the best LLM verifier recovers at most 21% of real errata-grade errors [Son et al., 2025]; LLM reviewers accept fabricated papers up to 82% of the time [Jiang et al., 2025]; and an LLM auditor's accuracy on the pitfalls of automated science rises from 55% to 82% only when it gets the logs and code [Luo et al., 2025]. Monitors that can execute the artefact separate sabotaged from honest optimisation work almost perfectly (area under the curve 0.93–0.99), but flag sabotage hidden in training data fewer than half the time [Libon et al., 2026]. The research family therefore makes reviewer access a protocol dimension. Its tasks are honest and sabotaged replications of PaperBench- or RE-Bench-style tasks [Starace et al., 2025; Wijk et al., 2024], with sabotage drawn from documented failure modes (data leakage, post-hoc selection, copied weights passed off as training, fabricated results). They are reviewed under protocols ranging from a single reviewer to debate with a "red-team replicator", at access levels from paper to code to logs to re-execution. Forty tasks with two arms cost about $8,000–$32,000 in agent runs, plus about $5,000 for LLM review protocols and $8,000–$16,000 for expert review of the eighty artefacts. The prediction to test is that ASD rises steeply with access and that debate matters most when the reviewer sees only the paper.

6.6 Dual use and safeguards

An autonomous-business testbed is built to measure overseers, not to improve agents, but it does exercise long-horizon agents in settings resembling the real economy. Tailwind's own initiative on safety datasets asks founders to weigh whether a task shares subtasks with risky areas, and names "strategic pursuit of long-term goals in the real world". The proposal should say plainly how it limits spillover. The environments are sandboxed, with simulated counterparties and no real payments; the output is a measurement of oversight, not a more capable agent; agent scaffolds that mainly add long-horizon capability are not released, while protocols, metrics, tasks and deception taxonomies are. Any use of a real business (for instance Arjun's company, Zembla, as a source of delayed, real-outcome ground truth) would

come later, with human sign-off on every external action, and only if the sandboxed results justify it.

7 Strands 2 and 3: how oversight scales, and what training does to it

7.1 Strand 2: oversight scaling curves

Jake Mendel's question in February 2026, whether today's most scalable alignment approaches will scale as far as capabilities do, is a question about curves, and the field has almost none. The only oversight metric ever measured across many orders of magnitude of compute is PGR. In the original weak-to-strong study, with models spanning seven orders of magnitude, PGR was positive almost everywhere but its slope in compute depended on the task: on NLP tasks it rose with the student's size, for reward modelling it stayed near 10%, and on chess puzzles it fell as the student grew [Burns et al., 2023]. Every debate result since has covered a narrow range of capability. Khan et al. [2024] found that more persuasive debaters made judges more accurate; Kenton et al. [2024] found the same effect, "more modestly"; and the Engels et al. scaling laws, the only ones fitted to oversight games, rest on models spanning 274 points of Chatbot Arena Elo, with debate's success at a 400-point gap sitting on the 50% chance floor [Engels et al., 2025]. The ASD paper fitted its ASD-against-capability slopes on about five points per protocol. The first PGR for debate used as a training signal, 45%, came only in August 2026 [Kenton et al., 2026]. A study of lie detectors in the training loop found undetected deception falling from 34% to 14% between models of 1 billion and 405 billion parameters [Hollinsworth et al., 2026], one of very few oversight results that span that range.

What is unknown is therefore most of what matters: the shape of ASD as a function of agent and judge compute over more than three orders of magnitude; whether debate's advantage persists, saturates or reverses beyond the measured range; the exchange rate between a judge's inference compute and its training compute; whether any trend carries from question answering to agentic, long-horizon tasks; whether ASD and PGR move together across protocols, which no one has measured on the same runs; and how shared errors between judge and agent families [Goel et al., 2025] bend the curves.

Design. The cleanest study varies compute within model families trained with one recipe, so that "more compute" is not confounded with "different lab".

1. **Two compute axes.** Training compute from families with public checkpoints, OLMo and Pythia; model size and inference compute from

Qwen3, which exposes a "thinking budget", and Qwen3.5, which together span 0.6 billion to several hundred billion parameters. Agents and judges are crossed in a Latin-square subset of about 12–20 pairs per family, with a second family replicating a few points to separate compute from family.

2. **Matched honest and deceptive agents.** Small models follow "argue for the wrong answer" badly, which would inflate their ASD. Fine-tune a matched pair of honest and deceptive adapters at every checkpoint on the same data, and report the deceptive arm's success against a fixed strong reference judge as a check that it was really elicited.

3. **Metrics on the same runs.** ASD in log and Brier form, judge accuracy and PGR, with bootstrap intervals over items. Fit ASD against the log compute gap between agent and judge, and against judge compute at a fixed gap: the first says whether oversight gets harder as the gap grows, the second whether it gets easier as the judge improves. Report the incentive gap recovered (section 1) and the *breakdown gap*: the gap at which ASD reaches zero and a protocol stops rewarding honesty.

4. **Task families.** Coding, maths and instruction following, with cheap exact ground truth, about 500 items each; writing and research on human-graded subsets. Chess (section 8.3) adds a family in which the capability gap is itself measured in Elo.

5. **Anchors.** Six to ten API models from 2023 to 2026 at a few grid points, to show where the open-weight trends sit against frontier compute.

Size and cost. Three model families, five task families, 500 items, two arms, four protocols and sixteen grid points make about a million protocol runs of a few thousand tokens each, 3–5 billion tokens, nearly all on open weights that run on a few rented GPUs. PGR needs about a hundred weak-label fine-tunes of models up to 14B. The frontier-API anchor slice, around 160,000 runs, costs roughly $1,000–$8,000 with batch discounts. The expensive part of this strand is people, not compute, which is why it can start at pre-seed.

7.2 Strand 3: why train, when prompted liars are weak adversaries

Every number in the original ASD paper comes from agents *told* which answer to argue for. That is cheap and gives ground truth by construction, but it measures a protocol against a weak adversary. Kenton and colleagues' debate-training paper of August 2026 records the problem plainly: early in training, a policy prompted to be misaligned failed to hide its intent, at one point writing "Wait, I was supposed to give a wrong answer", and later abandoned the misaligned prompt and simply solved the problems [Kenton et al., 2026]. The authors call prompted misalignment a relatively mild stress

Table 7: RL-trained oversight studies and what they found. Anthropic's 2023 run and GDM's 2026 run trained both debaters from shared weights.

Study	What was trained	Result
Anthropic, 2023 [Radhakrishnan, 2023]	Claude 2 debaters, PPO self-play; hidden-passage QuALITY	judge accuracy 73.1% $\rightarrow$ 77.7%; blind judge flat at 67%; little link to debater Elo
OpenAI, 2024 [Kirchner et al., 2024]	GPT-4-family helpful and sneaky provers vs small verifiers	legible to 45-second human checkers, at a "legibility tax" of roughly 20 points of solve rate (read from the paper's Figure 1)
NYU, 2024 [Arnesen et al., 2024]	Llama-3-8B debaters, self-play DPO	judge accuracy $+4$ points for debate; no gain from training consultants
Neural interactive proofs, 2024 [Hammond and Adam-Day, 2024]	GPT-4o provers, GPT-4o-mini verifiers, code	modest gains; debate robust in the worst case once training is stabilised
Google DeepMind, 2026 [Kenton et al., 2026]	Gemini 2.5 Flash-class solver and critic vs a frozen Flash-Lite judge	45% of gap recovered ($\approx$2 points); critic hacks judge's verbosity bias unless critiques are capped at 150 words

test. A deceiver found by optimisation against the judge is different in kind. OpenAI's prover–verifier study trained a "sneaky" prover whose flaws grew subtler round by round and, in a pilot the authors describe as flawed, fooled time-limited human checkers more often [Kirchner et al., 2024]. Nor does planted deception stand in for the natural kind: probes that caught deliberately trained sophistry did not generalise to the sophistry that ordinary RLHF produced [Wen et al., 2024]. Prompted ASD therefore probably overstates a protocol's robustness. Training is what turns it into a real test.

Training also asks the question scalable oversight actually poses. The debate proposal's central claim is that optimisation pressure on the debaters makes the judge more accurate [Irving et al., 2018]; only training, or a cheap proxy for it such as best-of-N selection, can test that claim. The record so far is short and modest (table 7). Training helped the judge in debate and did nothing in consultancy; the largest and most recent study recovered 45% of the gap between a weak-judge baseline and a verifiable-reward roofline, which in absolute terms was about two percentage points of accuracy (74.7% against 72.6%, with the roofline at 77.3%). Its more important finding was qualitative: under the single-judge baseline the judge's agreement with the truth decayed steadily as the policy learned to produce wrong answers the judge accepted, while under debate it stayed stable much longer.

The failure modes are documented and specific, which is useful: each is something the programme can measure rather than merely fear. Critics win by exploiting a judge's taste for long answers; GDM's authors think hacking the judge is probably the default outcome of debate training unless the players are restricted [Kenton et al., 2026]. Policies optimised against a chain-of-thought monitor learn to hide their intent [Baker et al., 2025]. Models can learn to resist RL by under-exploring [Jang et al., 2026], or to collect reward while blocking generalisation, leaving a persistent compliance gap that standard training metrics do not show [Xiao and Phuong, 2026]. Debaters trained from one set of weights can in principle collude. And judges start out credulous: before any training, a judge agreed with a one-sided consultant 72% of the time [Arnesen et al., 2024].

7.3 The RL design

The gap in the literature is concrete. No published study that this review found has RL-trained debaters on a task with a genuine capability gap rather than an information gap, at several policy scales, and checked the result with human judges. Kirchner's study used maths and one prover family; the interactive-proofs work used code and no human judges; GDM's used maths at one scale with an LLM judge; NYU's used reading comprehension with a hidden passage. Palaestra has announced RL self-play debate against consultancy (section 5.3); what the applicants add is the ASD outcome measure, sweeps across scale, and the asymmetric settings of section 8.3.

Design. Train debaters, consultants and single-answer policies against frozen weak judges at three policy scales, with LoRA RL on a hosted training service. Settings: maths with verifiable answers, as a replication control; the chess setting; optionally text-to-SQL against a private database. Protocols: a single judge (reinforcement learning from AI feedback, RLAIF), consultancy, debate with and without a rebuttal turn, critique limits of 50 and 150 words, and shared against separate weights for the two debaters, as a probe of collusion. Measures: judge accuracy and its correlation with the truth over training steps, ASD between honest and assigned-dishonest agents, peak and final ground-truth accuracy, gap recovered against a verifiable-reward roofline, and markers of hacking (length, bluffing rate). A 500-debate subset is judged by humans.

The validity test. One question makes the RL strand more than a replication. The ASD paper models an agent's propensity to argue the true side as a softmax of ASD (section 1). If ASD measured with prompted agents is a good benchmark, it should *predict* what RL does: protocols with higher prompted ASD should yield trained policies that argue honestly more often and keep the judge accurate longer. Testing that prediction tells the field whether

cheap prompted benchmarks can stand in for expensive training runs, which bears on how oversight labs spend their compute.

Cost. On Thinking Machines' Tinker service, a run of 153,600 two-turn episodes costs about $430 of policy compute for an 8B model, $1,100 for a 35B mixture-of-experts model and $6,300 for a 397B one, plus $320 per run for a Gemini 2.5 Flash-Lite judge voting eight times per episode. The judge can cost more than the policy: the same judging with GPT-6 Astra would cost $34,000 a run. A matrix of 24 small, 24 medium and 8 large runs comes to about $106,000, or $127,000 with a fifth added for failed runs and ablations; the two smaller scales alone come to about $53,000, or $63,000 with the same allowance (appendix A). The rule that follows: keep the judges inside the training loop cheap, and spend on strong judges only at evaluation.

A deadline eight days away

Thinking Machines announced safety-research grants of up to $50,000 in Tinker credits on 24 August 2026, listing "reward hacking and oversight gaming" and "forecasting safety-relevant scaling trends" among its directions. Applications, a one-page summary with CVs, close at 11:59 pm Pacific on **25 September 2026**. A grant would cover the whole policy compute of the small and medium scales of the design above (about $37,000), and an in-kind award from a second funder is a credible signal in a Tailwind pitch.

8 Strands 4–6: explanation, the library and capability-gap settings

8.1 Strand 4: training models to explain, so that oversight gets cheaper

Arjun's own interest runs in two directions at once: use scalable-oversight methods to make models better explainers, and use better explainers to make human oversight cheaper. The second is the safety case; the first is how to get there.

What the evidence says. AI assistance does help human overseers find problems. Labellers shown model-written critiques found about 50% more flaws [Saunders et al., 2022], and critiques from OpenAI's critic model were preferred to contractors' on 63% of naturally occurring bugs [McAleese et al., 2024]. But explanations shift *trust* as well as accuracy, and in the wrong direction when the AI is wrong. In a classic human–AI study, explanations increased the chance that people accepted the AI's recommendation whether or not it was correct [Bansal et al., 2021]. In GDM's amplified-oversight study,

an AI rater scored 87.7% on fact verification against 75.1% for crowd raters, and showing raters the AI's explanation and confidence produced over-reliance, while showing them search results and evidence produced more appropriate trust [Jain et al., 2025]. A meta-analysis of 106 experiments found human–AI teams doing worse on average than the better of the two alone, with losses concentrated where the AI outperformed the humans, which is the amplified-oversight regime [Vaccaro et al., 2024]. And an Anthropic trial found that people who learned a new library with AI help scored 50% on a later quiz against 67% for those who did not, with the largest gap on debugging, the skill most needed to oversee AI-written code [Shen and Tamkin, 2026].

Explanations can nonetheless teach, even superhuman knowledge. Four top grandmasters, shown concept positions mined from AlphaZero, improved on held-out puzzles by between 6 and 42 percentage points [Schut et al., 2025]. The gap in the literature is specific: every study this review found that trains an explainer against learner outcomes uses *simulated* learners [Cetin et al., 2025; Yang et al., 2026]. No study was found that optimises explanations against real people's measured understanding.

The hazard. "Better explanation" and "more persuasive" are hard to tell apart. In a study of 76,977 participants, post-training raised models' political persuasiveness by up to 51%, and wherever persuasiveness rose, factual accuracy fell [Hackenburg et al., 2025]; RLHF itself raises human false-positive rates [Wen et al., 2024]. An explainer trained on whether learners *agree* or *feel* they understand is a persuasion trainer.

Design. Reward the explainer for the learner's *discrimination*: how well the learner tells right from wrong on held-out items, including episodes (at least 30%) in which the explainer is assigned a wrong answer and is rewarded when learners reject it. An explainer paid this way is paid to make its own errors detectable; a persuasion-trained explainer is not. The quantity is the ASD of an explanation protocol with a human judge: the protocol should raise human acceptance of true outputs more than of false ones. The primary domain is chess, reusing the grandmaster study's design of pre-test, explanation and held-out transfer, with learners who are rated Lichess players, so that skill and item difficulty are both calibrated for free. A secondary domain is checking AI answers, with a third to half of the answers wrong. Training uses a learner simulator re-validated against humans each round; final evaluation uses humans only. Detecting an effect of 0.2 standard deviations with 80% power needs about 390 learners per arm, or about 200 in a paired design; the whole study, including an 800-learner confirmatory trial, item writing by a titled player and explainer training, costs roughly $30,000–$35,000 directly.

Why it is differentially good for safety. It trains what amplified oversight needs, the human's ability to verify, rather than engagement. It measures the persuasion risk rather than assuming it away, with wrong-answer acceptance rates, learner calibration and persuasion evaluations reported for every checkpoint. It addresses Arcadia's diagnosis that debate fails on fuzzy tasks because models do not decompose their claims well [Martin et al., 2026]. And its products, benchmarks of explanations that help people catch errors, are misleadingness evaluations of the kind Tailwind lists.

8.2 Strand 5: the library

Evaluation infrastructure has consolidated around UK AISI's Inspect [UK AI Security Institute, 2024], and RL-environment tooling has grown quickly; scalable-oversight tooling has not followed. The most-starred debate codebase is a 2024 paper release with 132 stars and no pushes since March 2024; a search for debate-and-oversight repositories finds only unstarred projects; and SOlib, with three stars, is the only library found that treats "any scalable-oversight protocol" as an abstraction and computes a protocol-level metric. The opportunity is not another evaluation harness but an *oversight layer* on top of the ones people already use. Concretely, the build-out would add:

1. protocols as first-class objects over agentic *episodes*, not only questions, with the protocols of section 6.5 built in, including ControlArena's micro-protocols;
2. a paired-arm runner that forks git, database, payment and mail state from one snapshot;
3. a judge interface covering LLMs and humans, with the evaluation budget (tokens or minutes) as a parameter and a hosted rating interface with timers, which makes the Kinniment curve a short experiment;
4. metrics with uncertainty from the same logs: ASD in both forms, expected agent and judge scores, judge accuracy, PGR, discrimination at fixed false-positive rates, and control-style safety and usefulness;
5. a model registry with parameters, training compute and inference settings, so that fits against compute are built in;
6. hooks that export any protocol as a reward for the common RL libraries, so the object that is evaluated can also be trained against;
7. cost simulation before a run, using `costly`, and cache-aware token accounting;
8. distribution as Inspect tasks and a ControlArena extension, a PyPI release with versioned tags, documentation and worked examples, and

a permissive licence in place of GPL-3.0, which needs the agreement of all three contributors.

The measure of success is adoption: other groups, CG's grantees among them, reporting ASD from the library in their own papers. A library that Palaestra, Arcadia and Sampura use is also the strongest answer to "why a new organisation?"

8.3 Strand 6: settings with real capability gaps

A good oversight setting has five properties: a genuine capability gap, in which the judge is generally capable but weak in the domain; cheap and exact ground truth; difficulty that can be graded continuously; human judges whose skill can be certified; and natural ways to be wrong persuasively. Hidden-passage reading comprehension fails the first; school mathematics fails the first and the third. Chess passes all five.

Chess. Arjun's premise holds on current data. On the open LLM Chess leaderboard, anchored to the Komodo Dragon engine, the best general-purpose models are rated about 1,550–1,600 (Gemini 3.8 Flash 1,607; GPT-5.6 Sol 1,550), against 1,285 for Claude Opus 5 and 806 for Claude Sonnet 5 [Kolasani et al., 2025]; Stockfish is rated about 3,650 on a different list, so the gap between the best judge and an engine-backed expert is of the order of two thousand points. Open generalists are weaker still, but chess-specialised open models are strong: a 4-billion-parameter model distilled from engine reasoning solves 48% of a hard puzzle set, ahead of most frontier systems [Tang et al., 2026]. Ground truth is nearly free: Lichess publishes 6.1 million rated puzzles and 410 million engine-evaluated positions under a CC0 licence [Lichess, 2026]. And chess is where weak-to-strong generalisation already failed in an instructive way: PGR was near zero with the smallest supervisors and fell as the student grew [Burns et al., 2023].

The setting works as follows. Items ask which of two moves is better, where one is the engine's best move and the other a *plausible* alternative that loses at least a pawn and a half (the most likely move of a human-imitation model, Maia, at a chosen rating); others are puzzles stratified by rating, or claims such as "White is winning". Experts come in three tiers: agents with an engine tool, chess-fine-tuned open models, and RL-trained debaters. Judges have no engine: frontier generalists across the rating range, weak open models, and human judges stratified by Lichess rating. Protocols include direct judging, consultancy, debate with a 150-word limit per turn, and a "legal line" rule under which any concrete variation a debater cites is checked for legality by a rules-only tool that gives no evaluation, so the judge can verify facts without seeing conclusions. The capability gap can be dialled continuously through engine nodes or the imitation model's rating, which makes chess the natural

Table 8: Settings with the "smart generalist judge, narrow expert" structure, ranked for a first suite. Costs are for ground truth only.

Setting	Expert	Ground truth	Notes
Chess	engine-backed agent; chess-tuned 4B model	engine at fixed nodes; 6.1M puzzles, CC0; near zero cost	gap measurable in Elo; rated human judges
Text-to-SQL, private database	agent with database access	execution, plus human check of meaning	realistic access asymmetry; about $3,500 for 300 verified items
Lean proofs	open prover models (miniF2F 88–90%)	kernel check; free	real question is whether the formal statement means the English one
Forecasting	RL-trained forecaster with retrieval	question resolution; free but delayed	noisy; scored over many items
Code with hidden tests	agent with execution	hidden test suites	already used; asymmetry is access, not skill
Chemistry, security	tool-using agents	computation, proofs of concept	most realistic, but dual-use

place to plot oversight success against a measured gap. The known risks are long forcing lines, which are obfuscated arguments by construction; judges swayed by chess jargon, since GPT-5.4's chess commentary, without tools, contains incorrect sub-claims 22% of the time [Hebbar et al., 2026]; memorised famous positions, avoided by using fresh 2026 games; and reasoning that RL makes unfaithful to the move actually chosen [Dionisopoulos et al., 2026]. Data and verification cost well under $100 of compute; a sweep of 2,000 items, four protocols and five frontier judges costs between about $70 and $2,200 depending on the judge model; human calibration about $3,000.

Other settings. Table 8 ranks the alternatives. Text-to-SQL against a database the judge cannot query gives a realistic access asymmetry with execution as ground truth, and a Tinker-trained open model already beats frontier models on a verified benchmark. Lean gives a perfect oracle for validity, and a harder, more interesting question: whether a generalist judge can tell when a formal statement subtly fails to mean what its English version says. Forecasting on resolved questions gives free but delayed and noisy truth. Chemistry and security are the most realistic, and carry dual-use weight that CG's screen would notice.




Figure 4: Coefficient Giving grants comparable to this proposal, against Tailwind's three tiers. Each dot is a grant; bands span the middle half; red ticks mark medians; dashed lines mark this report's central pre-seed and seed asks. Sets are listed grant by grant in appendix B.

Part IV

The money

9 What Coefficient Giving pays: typical amounts

This section uses data to answer the brief's third question: what CG and other funders actually give to projects like this one. The core evidence is a set of 89 individual grants compiled from CG's public grants table, one grantee at a time, and from grantees' own announcements (appendix B). Four comparison sets matter (fig. 4).

First grants to new, small technical organisations. Across 14 first CG grants to new, small, non-academic technical-research organisations since 2021, the median is $1.27 million, and the middle half runs from $430,000 to $1.99 million. For the 10 awarded in 2025 and 2026 the median is $1.41 million. Apollo Research's start-up grant ($1.54 million, a month after it launched) and Palisade Research's first grant ($1.68 million) sit in that band; Timaeus's ($2.05 million) is just above it. This is the pre-seed comparison.

Seed-scale grants to young organisations. Across 7 seed-scale grants, of $5 million or more, to young technical organisations, the median is $10.9 mil-

lion, and the middle half runs from $7.8 million to $11.8 million. The grants are P-Zero's $5.58 million, Truthful AI's $6.12 million, Redwood's first grant of $9.42 million in 2021, Timaeus's $10.93 million, Sampura's $11 million, AI Village's $12.6 million and Geodesic Research's $14.1 million. This is the seed comparison. AI Village is also the closest precedent for API-heavy experiments with long-horizon autonomous agents.

Oversight-adjacent and evaluation grants. Across 15 grants to non-academic teams for evaluations and oversight-adjacent research, the median is $1.65 million.

Scalable-oversight grants specifically. Before 2026, CG's grants labelled as scalable oversight were small cheques, mostly to academics, from $70,000 to $218,513, plus $408,255 to Modulo Research for sandwiching experiments in 2023. Small grants still dominate the set when the 2026 grants are included, which is why its median is only $100,000. They are the wrong anchor for founding an organisation. The 2026 cluster, Arcadia's $1.9 million team, Sampura's $11 million and Resolution's $160 million, is a new regime.

The trend. CG's total giving to AI safety has more than doubled each year, but the median first grant has moved much less: about $0.35 million in 2021–22, $1.6 million in 2023–24, $1.0 million in 2025 and $1.8 million in 2026. What has changed is the tail. Apart from Redwood's in 2021, every first grant to a new technical-research organisation up to 2025 was at most $2.05 million (leaving aside field-building groups such as the Center for AI Safety (CAIS), $5.16 million in 2022); in 2026 there were four of $10 million or more. And follow-on grants now come fast and large: P-Zero went from $250,000 to $5.58 million in four months, and Rishub Jain from a $50,000 grant to Sampura's $11 million in four months. One of Theorem's founders, Jason Gross, asked for $10,000 of compute, and the pair received $1 million.

9.1 Other funders

Outside CG, the ceiling for a single technical grant is about $1–1.5 million (table 9), apart from Macroscopic, whose range is unverified, and in-kind lab credits. That makes a seed round of $5 million or more realistically a CG grant, with other funders topping up particular studies. Two top-ups fit this programme closely, with a caveat on the first. The UK AISI Alignment Project, whose first round funded several debate and oversight projects with compute and API credits alongside cash, is closed and says it is unlikely to run again in 2026, though UK AISI expects further academic grant programmes. Thinking Machines' safety grants of Tinker credits are open now (section 7.3). Lab programmes add in-kind compute: OpenAI gave Resolution $10 million in

Table 9: Typical grant sizes at other funders relevant to this programme (sources in the project's dossiers, appendix D; bracketed entries rest on secondary sources).

Funder or programme	Typical size	Notes
UK AISI Alignment Project	£50k–£1M	60 grants from £27M; cash plus compute and API credits; closed, unlikely to reopen in 2026
Thinking Machines safety grants	up to $50k in credits	deadline 25 September 2026
Schmidt Sciences, AI safety science	mean about $370k	over $10M to 27 projects (2025)
Survival and Flourishing Fund	median about $424k	technical organisations, 2025 round
Longview	[$100k–$1.5M]	AI-safety grants and a frontier-AI fund
Macroscopic	[$100k–$15M]	about $100M expected in 2026; range unverified
EA Funds, Transformative AI Fund	$10k–$150k	replaced the Long-Term Future Fund
OpenAI Superalignment Fast Grants (2023)	$100k–$2M	historical oversight-specific anchor
Anthropic Fellows	about $15k a month of compute	per fellow, plus stipend

API credits, and Anthropic's fellows receive about $15,000 of compute a month each.

9.2 What things cost

CG now encourages higher salaries, and AI-safety nonprofits advertise them. FAR.AI advertises $150,000 to $250,000 for research engineers and scientists, $225,000 to $350,000 for senior research engineers and $290,000 to $450,000 for research leads; Apollo Research $204,000 to $385,000 for research scientists in San Francisco; Sampura £100,000 to £290,000 in London; Redwood Research $350,000 to $850,000; and Resolution's published ladder $236,000 to $930,000 in person. Frontier labs pay $300,000 to $500,000 base plus equity for comparable alignment roles, and UK AISI £65,000 to £145,000. The budgets in this report assume $250,000 salaries for the founders at pre-seed, about $200,000 for research engineers, and a loading of 20% for payroll taxes and benefits.

For compute, the useful anchors are Anthropic's roughly $180,000 per fellow-year and Sampura's disclosed $1 million a quarter for compute and human data across fewer than ten staff, about 57% of its first-year budget. Human




Figure 5: The staged plan. Totals are the budget model's central cases, with low and high cases below; each gate names the evidence that would justify the next stage.

grading costs $8–$20 per expert judgement of a short text, $86 for an expert review of a long professional deliverable, and $12–$15 an hour for general participants on Prolific plus a 33% platform fee. Fiscal sponsors charge 5–14%: Hack Club's HCB 7% flat, Ashgro 5–10%, Rethink Priorities' special-projects service about 14%. On a $1.5 million grant, the gap between 7% and 14% is about $105,000.

10 A staged plan: milestones, gates and money

Tailwind's tiers invite a staged pitch, and the brief asks for one: money now, milestones, more money, more milestones, and a vaguer scale at the end. Figure 5 shows the plan this report recommends, with totals taken from the budget model in appendix A: pre-seed of $1.47 million over 12 months (range $752,000 to $1.99 million), seed of $10.3 million over 24 months ($5.18 million to $14.7 million), and a scale stage of $52.8 million over 36 months ($26.1 million to $103 million). Figure 6 shows what each stage buys per year.

10.1 Pre-seed: twelve months to earn a seed round

The pre-seed year is organised so that the evidence for a seed application exists by month three to six; Tailwind's FAQ invites a seed application as early as month three. The dates below assume a decision in November 2026; the Tinker application and the paper fixes should happen before it.

10.2 Seed: two years to become the reference measurement

Seed funding pays for a team of about ten and for the expensive experiments: the full business testbed with its seven deception types and access ladder; the research-task family; ASD and PGR curves across at least three orders of




Figure 6: Annual spending by stage and cost type in the central case, with whiskers for the low and high cases. Compute, API and human data rise from 25% of the pre-seed budget to 39% at seed and 43% at scale.

magnitude of compute in three model families; RL at three scales, including a self-hosted 70-billion-parameter model; the explainer trial with human learners; and a public benchmark with a leaderboard. Following Sampura's structure, the seed can be split into an unconditional first tranche and a pledged second one tied to milestones. Table 11 phases the work.

Gate 2, at S18–S24 (table 11), is the evidence that justifies scale: prompted ASD predicts what RL-trained policies actually do, which would make the cheap benchmark a trustworthy stand-in for expensive training; the scaling curves are published and used; and a lab, a grantee or a government evaluator uses the protocol audits on its own graders.

10.3 Scale: an oversight laboratory

The scale stage is the "vaguer $Z" the brief asks for, and it should be presented as a possibility the seed stage would earn, not a request. Its core would be four things: oversight quality as an experimental knob in realistic training runs at 30–400 billion parameters (the training-run perturbation that Tailwind's fault-injection initiative describes, applied to the reward signal); live testbeds of agent-run firms and research groups; standing panels of expert judges and rated learners; and third-party audits of labs' reward and grading pipelines, reporting how much each rewards honest work over deceptive work. At $52.8 million over three years in the central case, it would sit alongside CG's other scale grants: FAR.AI's $28.7 million over three years, Epoch's $68 million over three, Redwood's more than $70 million over two, and Resolution's $160 million. The high case, about $100 million, corresponds to training runs large enough to test whether oversight trends observed at small scale persist near the frontier.

Table 10: Pre-seed milestones. "M" counts months from the grant.

When	Milestone and its evidence
Before M0	Tinker safety-grant application (due 25 September 2026); arXiv version 2 of the ASD paper with the Propaganda re-run and the Brier formula stated; Tailwind expression of interest
M0–M3	Library release on PyPI with a permissive licence and Inspect integration; ASD computed from existing ControlArena logs for every built-in protocol; chess setting built with Lichess data; two research engineers hired
M3–M6	Software-firm environment with the paired-branch runner; a first sweep of at least 30 tasks under five protocols; a first scaling grid on two open families and three task families; small-scale RL debate runs; writing pilot at two evaluation budgets
Gate 1	Seed application: ASD separates protocols on real logs and firm tasks in ways judge accuracy does not; at least one outside group uses the library; a public write-up
M6–M12	Full writing study with expert and reader panels (the Kinniment curve); medium-scale RL; explanation pilot with rated chess learners; first paper on oversight scaling curves

10.4 When to stop or change course

A staged plan is more credible with conditions for stopping. Four would change the programme:

- **ASD adds nothing.** If ASD across protocols is almost perfectly predicted by the safety and usefulness scores already in the control literature, the metric is redundant: fold the library into ControlArena and put the effort into settings and training.
- **Prompted ASD does not predict training.** If RL-trained policies do not behave as prompted ASD predicts, benchmark results cannot stand in for training runs: shift the programme towards RL-first measurement, which is more expensive and changes the seed budget.
- **Sandboxes cannot express the deceptions.** If the simulated firm is too thin for the burner-account and metric-gaming attacks to be realistic, restrict the business family to software tasks with git-only ground truth and move the effort to research tasks.
- **Human ground truth is too noisy.** If expert raters disagree too much to anchor ASD on writing, change the panels or the tasks before scaling the human studies.

Table 11: Seed milestones. "S" counts months from the seed grant.

When	Milestone and its evidence
S0–S6	Team grows to about eight; business testbed with the first three deception types and the access ladder; research-task family built on PaperBench- and RE-Bench-style tasks; scaling grid extended to three model families and all five task families; library 1.0 with documentation and outside users
S6–S12	All seven deception types; the writing study repeated on a new model generation, and a paper on the evaluation-time curve; RL at the large scale, including a self-hosted 70-billion-parameter model; human-judge chess studies; the explainer trial's confirmatory phase; a second scaling paper spanning three orders of magnitude of compute
S12–S18	Long-horizon business sweeps with three agent models; the first test of whether ASD and PGR move together across protocols; audits of one or two outside graders, for a lab, a vendor or a grantee; a public benchmark and leaderboard
S18–S24	**Gate 2**: the test of whether prompted ASD predicts RL-trained behaviour; the scale proposal, if the gate is passed

11 Legal form: nonprofit, PBC, or neither yet

The brief asks whether CG will invest in, or give a non-dilutive grant to, a public-benefit corporation (PBC), given the idea that scalable oversight is capabilities work as well as alignment work and that profits from autonomous firms could fund the research; and, failing that, whether CG would make a personal grant or would insist on a nonprofit or fiscal sponsor. This section is desk research, not legal or tax advice; the points that need a lawyer or accountant are listed at the end.

11.1 What Tailwind says

The FAQ answers most of the question directly (appendix C). CG will consider a PBC if that structure would make the organisation more effective and the work shows a clear charitable purpose; it does not expect to fund other for-profits; it is best placed to fund nonprofits; and it expects for-profits to add complexity and time. It can forward strong for-profit opportunities, with consent, to safety-motivated investors. Pre-seed money can go to individuals or teams without an entity; seed money needs an entity, directly or through a 501(c)(3) fiscal sponsor.

11.2 CG's record with companies

Open Philanthropy was set up in 2017 as a limited liability company precisely so that it could make impact investments and non-charitable contributions [Karnofsky, 2017]. But the LLC employs staff rather than paying

Table 12: Documented Open Philanthropy and CG support for companies and PBCs (the paying entity is not always public).

Recipient	Form	Support
Impossible Foods	company	investment, 2016, terms undisclosed
Sherlock Biosciences	company	grant of up to $17.5M plus a separate investment, 2019
Gryphon Scientific	LLC	$2M grant, 2020
Metaculus	PBC from 2022	about $14.5M of grants and a contract, 2022–25; first grant before it became a PBC
Apollo Research	PBC from Jan 2026	$696k "staff support" in May 2026, after its conversion to a venture-backed PBC (receiving entity unverified)
Theorem founders	no entity yet	$1M to two founders to start a formal-verification company, which, Mendel reports, became a Y Combinator start-up

grants; grants are paid by Good Ventures Foundation, a private foundation, by donor-advised funds or by other donors' vehicles, and which vehicle pays decides which legal rules apply. The documented cases of money going to companies are few but real (table 12). Where Open Philanthropy both granted and invested, as with Sherlock Biosciences, the charitable grant, with obligations, a budget and milestones, sat alongside the investment rather than replacing it: a grant of up to $17.5 million plus a separate investment.

The last case is the closest precedent for this proposal. Jake Mendel, the programme officer most likely to read it, gave two founders $1 million before they had a company, describing formal verification as a defensive technology and a way to mitigate reward hacking [Mendel, 2025]. The applicants' situation differs in one important way. Theorem sells a product whose improvement is itself the safety benefit. An oversight programme that funds itself from autonomous firms would be selling long-horizon agency, which is what Tailwind's initiative on safety datasets asks founders to be careful about (section 6.6).

Two AI-safety organisations offer models for a later split between research and product. Ought spun out Elicit as a PBC in 2023, and Apollo Research moved to a venture-backed PBC in January 2026 with mission-aligned board seats, buying its intellectual property from the nonprofit at an independent valuation. A PBC on its own is a weak commitment to mission: under Delaware law directors must balance the public benefit against stockholders' interests, but they owe no duty to the intended beneficiaries, are protected if their decision is informed and disinterested, and only holders of at least 2% of the shares can sue to enforce the balancing. Anthropic, Apollo and OpenAI all added governance on top.

Table 13: Legal options against the criteria that matter at pre-seed (this report's assessment; one to three dots, more is better).

Option	Speed	CG fit	Revenue	Tax	Mission lock	Optics
Individual pre-seed grants	●●●	●●●	●	●	●●	●●●
Grant via a fiscal sponsor	●●	●●●	●	●●●	●●	●●●
Own 501(c)(3) from day one	●	●●●	●	●●●	●●●	●●●
PBC from day one	●●	●●	●●●	●●	●	●
Nonprofit now, separate PBC later	●●●	●●●	●●●	●●●	●●●	●●
PBC with CG grant and venture money	●	●	●●●	●●	●	●

11.3 Individuals, sponsors and the two countries

CG has a long record of paying individuals, and the FAQ confirms it will do so at pre-seed. Grants to individuals are generally taxable income in both the United States and the United Kingdom. Arjun is in Washington State, which has no individual income tax at present; Abhimanyu is a PhD student in the UK. If he holds a UK Student visa, government guidance says he cannot be self-employed, which would rule out a personal grant for him and make employment through a sponsor or UK entity necessary. One practical rule follows either way: do not take a single grant paid to Arjun, who then pays Abhimanyu.

Fiscal sponsors solve both problems. Rethink Priorities' special-projects service employs staff through US and UK entities and an employer-of-record service, helps with visas, and charges about 14%; Ashgro charges 5–10% and works with projects in most countries; Manifund, BERI and Hack Club offer other models. Sampura, the closest comparable grantee, is itself a fiscally sponsored project of Rethink Priorities (section 5.2), so this route has already carried an $11 million CG grant to a London team. Onboarding with a sponsor can take months, which CG's own initiative on fiscal sponsors names as a problem; approval of a new 501(c)(3) takes longer still, often more than a year.

11.4 The options compared

Recommended default

1. **Ask for a pre-seed research grant, paid to a fiscal sponsor that can employ both founders in the US and the UK**. The candidate is Rethink Priorities' service, which Sampura uses, or Ashgro if it

confirms that it can employ in the UK. If CG prefers, accept two separate individual grants, each paid in its recipient's country.

2. **Present the autonomous businesses as instrumented testbeds inside the research, not as the organisation's product**, with the safeguards of section 6.6.
3. **Keep the for-profit door open for seed, but do not lead with it.** Say that if a product with real demand emerges, for instance an oversight-auditing service for labs' graders, it would go into a separate PBC, with research IP sold or licensed at an independent valuation, a stake or royalty for the nonprofit, and a mission seat, following the Elicit and Apollo pattern.

This default is among the fastest routes to money that CG explicitly offers; it avoids the tax and visa problems of personal grants; and it carries none of the optics of profiting from capabilities. The idea of funding the research from autonomous firms deserves candid treatment in the pitch rather than silence: the FAQ itself notes that revenue need not track impact, and a commercial agent business would pull the organisation towards agent capability, the opposite of CG's differential screen. The version of the idea that fits is narrower. The most plausible revenue is from selling *oversight*, audits and benchmarks of the graders that labs and vendors already use, which is the demand side identified in section 3. That product is safety-aligned by construction and could justify a PBC at seed.

Three developments would change the recommendation. If CG signals at the pitch that it would rather fund a PBC, set one up with a mission seat and an explicit public-benefit purpose. If an oversight product finds paying customers whose feedback also improves oversight, split at seed. And if the autonomous-firm work turns out mainly to add long-horizon agency, keep it inside the nonprofit and publish selectively.

Questions to put to CG. Which entity would pay a pre-seed grant, and can it pay a UK-resident founder directly? Does CG prefer particular fiscal sponsors? For a PBC, would support be a grant with expenditure responsibility or an investment, and on what terms for publication and IP? Does CG regard autonomous-business testbeds as risk-increasing, and what safeguards would it want?

Professional advice needed. A US exempt-organisations lawyer, for any grant to a PBC and any later transfer of research IP to a company; a Delaware corporate lawyer, for a PBC charter and investment terms; a US accountant for Arjun and a UK accountant for Abhimanyu, on the tax treatment of a grant; and Warwick or an immigration adviser, on visa conditions and university rules on outside work and IP.

12 Recommendations: how much to ask for, and how

12.1 The numbers

Table 14: Recommended asks, with the comparable grants that anchor each figure. Totals are from the budget model (appendix A).

Stage	Low	Central	High	Anchors
Pre-seed, 12 months	$752,000	$1.47 million	$1.99 million	median first grant to a new small technical organisation $1.27 million ($1.41 million in 2025–26); Apollo $1.54M, Palisade $1.68M, Tara Research $1.82M, Timaeus $2.05M; Tailwind's pre-seed ceiling $2M
Seed, 24 months	$5.18 million	$10.3 million	$14.7 million	seed-scale median $10.9 million; P-Zero $5.58M, Truthful AI $6.12M; Sampura $11M, Timaeus $10.93M; AI Village $12.6M, Geodesic $14.1M
Scale, 36 months	$26.1 million	$52.8 million	$103 million	FAR.AI $28.7M over three years; Epoch $68M over three; Redwood over $70M over two; Resolution $160M

Pre-seed: ask for about $1.47 million; do not go below $1 million. The central ask funds both founders full time at $250,000 salaries, two research engineers from month three, about $310,000 of compute and API spending, $63,000 of human grading and participant studies, and a 7% sponsor fee, within Ashgro's range. The central ask sits just above the median first grant CG has made to a new, small technical organisation ($1.27 million), and just below Apollo Research's ($1.54 million), Palisade Research's ($1.68 million) and Tara Research's ($1.82 million) first grants. If Rethink Priorities, the one sponsor confirmed to employ in the UK, is used at about 14%, add about $96,000. That takes the central ask to about $1.56 million and the high case to $2.17 million, over the $2 million pre-seed ceiling, so the high case would need trimming. The low case, $752,000, is a real option only if the applicants want to test the idea before committing full time; it pays the founders and about $50,000 of engineering help but makes no full-time hire, and CG's own staff have twice turned a small ask into a larger one. The high case, $1.99 million, sits just under Tailwind's $2 million ceiling for the tier and adds a third engineer, more long-horizon episodes and the large-scale RL runs. It is defensible if the founders can show that the team is ready to hire immediately.

Seed: plan for about $10.3 million, requested in months three to six. The central seed funds a team of about ten for two years and the experiments that make the programme distinctive, with compute, API and human data at 39% of the total. That is below Sampura's roughly 57%, and the compute lines could credibly be larger. The figure is close to the median of CG's seed-scale grants and to Sampura's $11 million, the one direct comparable for scalable oversight. Structure it as Sampura's was, an unconditional first tranche with a pledged second one, for instance about $5–6 million for the first twelve months and the balance on the gate evidence. The high case, $14.7 million, adds staff and larger RL; above that, a 36-month seed of $18–20 million becomes possible within Tailwind's tier.

Scale: describe it, do not ask for it. The scale stage, $52.8 million in the central case and roughly $100 million at the top, is the answer to "how big could this get?", and it belongs in the pitch as a picture of where the programme leads if the gates are passed, with the evidence that would justify it. CG is now making grants of that size to young organisations, but so far only to teams whose leaders have run large research programmes before.

12.2 How to structure the ask

1. **Lead with pre-seed and name the seed trigger.** Tailwind invites a seed application within three months if the work is going well, and CG has moved about as fast for P-Zero and for Sampura's founder, four months each. Going straight to seed needs, in Max Nadeau's account on the 80,000 Hours podcast, a founding team covering the important bases and some preliminary results [Nadeau and Qureshi, 2026]; a two-person team is better placed to earn that at pre-seed.

2. **Itemise compute, API and human data as separate lines.** CG says it encourages larger compute budgets, and its earlier request for proposals expedited research expenses.

3. **Pay properly and say so.** Tailwind asks for budgets that pay founders properly and compete for talent; a $250,000 founder salary sits within FAR.AI's senior research-engineer band ($225,000–$350,000), below its research-lead band ($290,000–$450,000), and near the bottom of Resolution's in-person ladder ($236,000–$930,000).

4. **Show the tranche logic.** A seed request with a pledged second tranche tied to named milestones reads as disciplined rather than greedy, and it is how CG structured both Sampura's and Resolution's grants.

5. **Add other funders for particular studies.** A Thinking Machines credit grant for the RL runs, a UK AISI grant for a human-grader study if

a new programme opens, and lab API credits make the CG ask look co-funded rather than larger.

6. **Mention AI-accelerated research.** Among the things CG valued in Resolution's founder, Nadeau named the productive use of AI to speed up safety work [Nadeau and Qureshi, 2026]; the library's cost simulation and automated sweeps are the place to show it.

12.3 The expression of interest

Tailwind's form asks for little that is required and a great deal that is optional, and CG says it filters out submissions its systems judge to be AI-generated. What follows is therefore a list of things to say, not text to paste; the applicants should write every sentence themselves.

- **Initiative to name:** "Unclaimed research labs: scalable oversight", with "Misleadingness evaluations" as the first concrete deliverable (section 4).
- **The pitch, in substance:** oversight fails quietly on long, fuzzy, agentic work; the field has no shared measure of whether a protocol rewards honest work over deceptive work; ASD is such a measure, and the team built it; the programme measures it on realistic firm, writing and research tasks, across compute, and under training, and ships it as a library the other oversight groups can use. Name the Warp inversion (section 6.2) and the Kinniment curve (section 6.5) as concrete hooks.
- **Most impressive thing:** each founder separately. For Arjun, the NeurIPS self-preference paper and its citation count, the origin of the ASD project, and building Zembla. For Abhimanyu, the ICLR oral on evaluating forecasters without ground truth, the ASD framework and most of the library, and PhysicsOverflow.
- **References:** one to four people with strong AI-safety records who know the work. Co-authors and mentors are the natural candidates, such as Sam Bowman, Shi Feng, Florian Tramèr, Marius Hobbhahn or Richard Ngo; the applicants should ask each of them before listing anyone.
- **Say who is full time and from when**, since Tailwind is a call for founders and Abhimanyu's PhD ends in 2026.
- **Consent to sharing:** saying yes lets CG connect the applicants with groups working on the same idea, which is useful given the crowding in section 5.

12.4 Risks a reader will raise, and the answers

- *"Why a new organisation, when CG already funds four oversight groups?"* Because none of them provides a common measure across protocols, tasks and compute; the library is designed to be used by all four; and the proposal is open to a new team at an existing organisation if CG prefers (section 5.5).
- *"Isn't debate failing?"* Parts of it are, and the programme is designed to measure exactly where; it is protocol-agnostic by construction.
- *"Empirics on today's models can't settle superhuman oversight."* The experiments are tied to named assumptions of the debate safety case, and the RL strand tests whether training reaches the equilibria theory predicts.
- *"What about scheming and collusion?"* Colluding and sandbagging conditions are included, and ASD is reported per unit of oversight cost.
- *"Running autonomous businesses is a capability."* The testbeds are sandboxed measurement environments; scaffolds are not released; see section 6.6.
- *"The workshop paper is small and has a bug."* Say so first: the paper was a demonstration, the authors found and fixed the bug, and version 2 reports the corrected results.

12.5 What to do now

1. By **25 September 2026**: submit the Thinking Machines safety-grant application for the RL strand.
2. Before the expression of interest: re-run Propaganda with the fixed code, reconcile the Brier formula, and post version 2 of the paper; tag a first PyPI release of the library.
3. Decide who is full time, and whether Jackson Kaunismaa joins.
4. Talk to Palaestra, Sampura, Arcadia and Resolution before pitching, as the FAQ recommends; a letter saying one of them would use the library is worth more than any paragraph.
5. Ask a fiscal sponsor that employs in the US and UK for terms and onboarding time.
6. Write the expression of interest in the applicants' own words.

References

AI Digest. Season 1 recap: Agents raise $2,000. https://aivillageblog.substack.com/p/season-recap-agents-raise-2k, May 2025.

Dario Amodei, Chris Olah, Jacob Steinhardt, Paul Christiano, John Schulman, and Dan Mané. Concrete problems in AI safety. *arXiv preprint arXiv:1606.06565*, June 2016. URL https://arxiv.org/abs/1606.06565.

Anthropic. Project Vend: Phase two. https://www.anthropic.com/research/project-vend-2, December 2025.

Anthropic. Project Deal: our Claude-run marketplace experiment. https://www.anthropic.com/features/project-deal, April 2026.

Anthropic Alignment Science Team. Recommendations for technical AI safety research directions, 2025. URL https://alignment.anthropic.com/2025/recommended-directions/. Anthropic Alignment Science blog, January 2025; cross-posted to LessWrong by Sam Marks, 10 January 2025.

Arcadia Impact. About us, 2026a. URL https://www.arcadiaimpact.org/about. Registered charity in England and Wales; CG has awarded over £8 million. Accessed 2026-09-17.

Arcadia Impact. Alignment research, 2026b. URL https://www.arcadiaimpact.org/alignment-research. Arcadia Impact Alignment team page (team started May 2026, in collaboration with UK AISI), accessed 17 September 2026.

Samuel Arnesen, David Rein, and Julian Michael. Training language models to win debates with Self-Play improves judge accuracy, 2024. URL https://arxiv.org/abs/2409.16636. arXiv:2409.16636, first posted 2024-09-25.

Axel Backlund and Lukas Petersson. Vending-Bench: A benchmark for long-term coherence of autonomous agents, 2025. URL https://arxiv.org/abs/2502.15840.

Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, Carol Chen, Catherine Olsson, Christopher Olah, Danny Hernandez, Dawn Drain, Deep Ganguli, Dustin Li, Eli Tran-Johnson, Ethan Perez, Jamie Kerr, Jared Mueller, Jeffrey Ladish, Joshua Landau, Kamal Ndousse, Kamile Lukosuite, Liane Lovitt, Michael Sellitto, Nelson Elhage, Nicholas Schiefer, Noemi Mercado, Nova DasSarma, Robert Lasenby, Robin Larson, Sam Ringer, Scott Johnston, Shauna Kravec, Sheer El Showk,

Stanislav Fort, Tamera Lanham, Timothy Telleen-Lawton, Tom Conerly, Tom Henighan, Tristan Hume, Samuel R. Bowman, Zac Hatfield-Dodds, Ben Mann, Dario Amodei, Nicholas Joseph, Sam McCandlish, Tom Brown, and Jared Kaplan. Constitutional AI: Harmlessness from AI feedback. *arXiv preprint arXiv:2212.08073*, December 2022. URL https://arxiv.org/abs/2212.08073.

Hasan Baig, Hailey Joren, and Joe Benton. TASTE: Can AI models judge AI safety research proposals?, 2026. URL https://alignment.anthropic.com/2026/taste/. Anthropic Alignment Science blog, 28 August 2026 (Anthropic Fellows Program).

Bowen Baker, Joost Huizinga, Leo Gao, Zehao Dou, Melody Y. Guan, Aleksander Madry, Wojciech Zaremba, Jakub Pachocki, and David Farhi. Monitoring reasoning models for misbehavior and the risks of promoting obfuscation, 2025. URL https://arxiv.org/abs/2503.11926. arXiv:2503.11926, first posted 2025-03-14.

Gagan Bansal, Tongshuang Wu, Joyce Zhou, Raymond Fok, Besmira Nushi, Ece Kamar, Marco Tulio Ribeiro, and Daniel S. Weld. Does the whole exceed its parts? the effect of AI explanations on complementary team performance. In *Proceedings of the 2021 CHI Conference on Human Factors in Computing Systems*, 2021. URL https://arxiv.org/abs/2006.14779.

Beth Barnes. Debate update: Obfuscated arguments problem. AI Alignment Forum, December 2020. URL https://www.alignmentforum.org/posts/PJLABqQ962hZEqhdB. Posted 23 December 2020.

Asya Bergal and Nick Beckstead. Request for proposals for projects in AI alignment that work with deep learning systems. LessWrong / AI Alignment Forum, 29 October, 2021. URL https://www.lesswrong.com/posts/H5iePjNKaaYQyZpgR. Open Philanthropy RFP; up to $1M over up to 2 years per proposal. Accessed 2026-09-17.

Alexander Berger and Emily Oehlsen. Our approach to AI safety and security. Coefficient Giving, 1 October, 2025. URL https://coefficientgiving.org/research/our-approach-to-ai-safety-and-security/. Lists scalable oversight among technical research CG finds valuable. Accessed 2026-09-17.

Bloomberg. Former Google researchers are planning AI-human hybrid to prevent rogue models. Syndicated by Deccan Chronicle, 26 August, 2026. URL https://www.deccanchronicle.com/technology/former-google-researchers-are-planning-ai-human-hybrid-to-prevent-rogue-models-1982422. Quotes Jake Mendel; $6.5M raised plus $4.2M pledged. Original Bloomberg URL not retrieved. Accessed 2026-09-17.

Aleksandr Bowkis, Marie Davidsen Buhl, Jacob Pfau, and Geoffrey Irving. Automated alignment is harder than you think, 2026. URL https://arxiv.org/abs/2605.06390. arXiv:2605.06390, first posted 2026-05-07.

Samuel R. Bowman. Putting up Bumpers, 2025. URL https://alignment.anthropic.com/2025/bumpers/. Anthropic Alignment Science blog, 23 April 2025.

Samuel R. Bowman, Jeeyoon Hyun, Ethan Perez, Edwin Chen, Craig Pettit, Scott Heiner, Kamilė Lukošiūtė, Amanda Askell, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, Christopher Olah, Daniela Amodei, Dario Amodei, Dawn Drain, Dustin Li, Eli Tran-Johnson, Jackson Kernion, Jamie Kerr, Jared Mueller, Jeffrey Ladish, Joshua Landau, Kamal Ndousse, Liane Lovitt, Nelson Elhage, Nicholas Schiefer, Nicholas Joseph, Noemí Mercado, Nova DasSarma, Robin Larson, Sam McCandlish, Sandipan Kundu, Scott Johnston, Shauna Kravec, Sheer El Showk, Stanislav Fort, Timothy Telleen-Lawton, Tom Brown, Tom Henighan, Tristan Hume, Yuntao Bai, Zac Hatfield-Dodds, Ben Mann, and Jared Kaplan. Measuring progress on scalable oversight for large language models. *arXiv preprint arXiv:2211.03540*, November 2022. URL https://arxiv.org/abs/2211.03540.

Jonah Brown-Cohen, Geoffrey Irving, and Georgios Piliouras. Scalable AI safety via doubly-efficient debate. *arXiv preprint arXiv:2311.14125*, November 2023. URL https://arxiv.org/abs/2311.14125.

Jonah Brown-Cohen, Geoffrey Irving, Georgios Piliouras, Lijie Chen, Jiawei Li, and Zhiyang Xun. Avoiding obfuscation with Prover-Estimator debate, 2025. URL https://arxiv.org/abs/2506.13609. arXiv:2506.13609, first posted 2025-06-16.

Marie Davidsen Buhl, Jacob Pfau, Benjamin Hilton, and Geoffrey Irving. An alignment safety case sketch based on debate, 2025. URL https://arxiv.org/abs/2505.03989. arXiv:2505.03989, first posted 2025-05-06.

Collin Burns, Pavel Izmailov, Jan Hendrik Kirchner, Bowen Baker, Leo Gao, Leopold Aschenbrenner, Yining Chen, Adrien Ecoffet, Manas Joglekar, Jan Leike, Ilya Sutskever, and Jeff Wu. Weak-to-strong generalization: Eliciting strong capabilities with weak supervision. *arXiv preprint arXiv:2312.09390*, December 2023. URL https://arxiv.org/abs/2312.09390.

Joe Carlsmith. Can we safely automate alignment research?, 2025. URL https://www.lesswrong.com/posts/nJcuj4rtuefeTRFHp/can-we-safely-automate-alignment-research. Essay, 30 April 2025 (series "How do we solve the alignment problem?").

Edoardo Cetin, Tianyu Zhao, and Yujin Tang. Reinforcement learning teachers of test time scaling. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2025. URL https://arxiv.org/abs/2506.08388.

Tuhin Chakrabarty, Jane C. Ginsburg, and Paramveer Dhillon. Readers prefer outputs of AI trained on copyrighted books over expert human writers, 2025a. URL https://arxiv.org/abs/2510.13939.

Tuhin Chakrabarty, Philippe Laban, and Chien-Sheng Wu. AI-slop to AI-polish? Aligning language models through edit-based writing rewards and test-time computation, 2025b. URL https://arxiv.org/abs/2504.07532.

Paul Christiano, Jan Leike, Tom B. Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences. In *Advances in Neural Information Processing Systems 30 (NeurIPS 2017)*, June 2017. URL https://arxiv.org/abs/1706.03741.

Paul Christiano, Buck Shlegeris, and Dario Amodei. Supervising strong learners by amplifying weak experts. *arXiv preprint arXiv:1810.08575*, October 2018. URL https://arxiv.org/abs/1810.08575.

Paul Christiano, Ajeya Cotra, and Mark Xu. Eliciting latent knowledge: How to tell if your eyes deceive you. Alignment Research Center technical report; announced on the AI Alignment Forum, December 2021. URL https://docs.google.com/document/d/1WwsnJQstPq91_Yh-Ch2XRL8H_EpsnjrC1dwZXR37PC8. Announced 14 December 2021 at https://www.alignmentforum.org/posts/qHCDysDnvhteW7kRd.

Ajeya Cotra. The case for aligning narrowly superhuman models. AI Alignment Forum, March 2021a. URL https://www.alignmentforum.org/posts/PZtsoaoSLpKjjbMqM. Posted 5 March 2021.

Ajeya Cotra. Techniques for enhancing human feedback. LessWrong / AI Alignment Forum, 29 October, 2021b. URL https://www.lesswrong.com/posts/ybThg9nA7u6f8qfZZ/techniques-for-enhancing-human-feedback. Direction 2 of the Open Philanthropy 2021 alignment RFP. Accessed 2026-09-17.

Chris Cundy and Adam Gleave. Preference learning with lie detectors can induce honesty or evasion. In *Advances in Neural Information Processing Systems 38 (NeurIPS 2025)*, 2025. URL https://arxiv.org/abs/2505.13787. arXiv:2505.13787, first posted 2025-05-20.

Lucas Dionisopoulos, Nicklas Majamaki, and Prithviraj Ammanabrolu. How reasoning evolves from post-training data: An empirical study using chess. In *International Conference on Machine Learning (ICML)*, 2026. URL https://arxiv.org/abs/2604.05134.

DoltHub. Dolt: Git for data. GitHub repository, 2026. URL https://github.com/dolthub/dolt. Accessed 17 Sep 2026.

Ethan Elasky and Frank Nakasako. Inference-time generative debates on coding and reasoning tasks for scalable oversight. LessWrong, 26 February, 2026. URL https://palaestraresearch.org/outputs/2026-inference-time-generative-debates/. LessWrong post kQCLPighFvb4ChHtu. Accessed 2026-09-17.

Ethan Elasky, Frank Nakasako, and Naman Goyal. Debate helps weak judges reward stronger models, 2026. URL https://arxiv.org/abs/2605.27483. arXiv:2605.27483, first posted 2026-05-26.

Joshua Engels, David D. Baek, Subhash Kantamneni, and Max Tegmark. Scaling laws for scalable oversight. In *Advances in Neural Information Processing Systems 38 (NeurIPS 2025)*, 2025. URL https://arxiv.org/abs/2504.18530. arXiv:2504.18530, first posted 2025-04-25.

Daniel Fein, Sebastian Russo, Violet Xiang, Kabir Jolly, Rafael Rafailov, and Nick Haber. LitBench: A benchmark and dataset for reliable evaluation of creative writing, 2025. URL https://arxiv.org/abs/2507.00769.

Shashwat Goel, Joschka Strüber, Ilze Amanda Auzina, Karuna K Chandra, Ponnurangam Kumaraguru, Douwe Kiela, Ameya Prabhu, Matthias Bethge, and Jonas Geiping. Great models think alike and this undermines AI oversight. In *Proceedings of the 42nd International Conference on Machine Learning (ICML 2025), PMLR 267*, 2025. URL https://arxiv.org/abs/2502.04313. arXiv:2502.04313, first posted 2025-02-06.

Ben Goldhaber and Owain Evans. Solving math problems by relay. LessWrong (Ought), July 2020. URL https://www.lesswrong.com/posts/DWgWbXRfXLGHPgZJM. Posted 17 July 2020; experiment run September–November 2018.

Dewi Gould, Sam Martin, Alejandro Aristizábal, Simon Marshall, and Jacob Pfau. Debate with self-play best-of-N optimization. LessWrong, 9 July, 2026. URL https://www.lesswrong.com/posts/hb8pv3zyAHGJpwz9F/debate-with-self-play-best-of-n-optimization. First output of Arcadia Alignment's scalable oversight team. Accessed 2026-09-17.

Ryan Greenblatt. Plans a, b, c, and d for misalignment risk, 2025. URL https://www.lesswrong.com/posts/E8n93nnEaFeXTbHn5/plans-a-b-c-and-d-for-misalignment-risk. LessWrong post, 8 October 2025.

Ryan Greenblatt and Buck Shlegeris. The case for ensuring that powerful AIs are controlled, 2024. URL https://www.lesswrong.com/posts/

kcKrE9mzEHrdqtDpE/the-case-for-ensuring-that-powerful-ais-are-controlled. LessWrong / AI Alignment Forum post, 24 January 2024.

Ryan Greenblatt, Buck Shlegeris, Kshitij Sachan, and Fabien Roger. AI control: Improving safety despite intentional subversion. *arXiv preprint arXiv:2312.06942*, December 2023. URL https://arxiv.org/abs/2312.06942.

Andrew Gritsevskiy, Arjun Panickssery, Aaron Kirtland, Derik Kauffman, Hans Gundlach, Irina Gritsevskaya, Joe Cavanagh, Jonathan Chiang, Lydia La Roux, and Michelle Hung. REBUS: A robust evaluation benchmark of understanding symbols, 2024. URL https://arxiv.org/abs/2401.05604.

Kobi Hackenburg, Ben M. Tappin, Luke Hewitt, Ed Saunders, Sid Black, Hause Lin, Catherine Fist, Helen Margetts, David G. Rand, and Christopher Summerfield. The levers of political persuasion with conversational AI, 2025. URL https://arxiv.org/abs/2507.13919.

Lewis Hammond and Sam Adam-Day. Neural interactive proofs. In *International Conference on Learning Representations (ICLR 2025)*, 2024. URL https://arxiv.org/abs/2412.08897. arXiv:2412.08897, first posted 2024-12-12.

S. Ashwin Hebbar, Peiyao Sheng, Sewoong Oh, and Pramod Viswanath. Hallucinations on the board: Tool-augmented evaluation of LLM chess commentary, 2026. URL https://arxiv.org/abs/2608.04240.

Benjamin Hilton, Jacob Pfau, Marie Davidsen Buhl, and Geoffrey Irving. UK AISI's alignment team: Research agenda, 2025. URL https://www.lesswrong.com/posts/tbnw7LbNApvxNLAg8/uk-aisi-s-alignment-team-research-agenda. LessWrong / AI Alignment Forum post, 7 May 2025.

Axel Højmark, Govind Pimpale, Arjun Panickssery, Marius Hobbhahn, and Jérémy Scheurer. Analyzing probabilistic methods for evaluating agent capabilities, 2024. URL https://arxiv.org/abs/2409.16125. Accepted (poster) to SoLaR 2024.

Oskar J. Hollinsworth, Ann-Kathrin Dombrowski, Sam Adam-Day, Adam Gleave, and Chris Cundy. Scaling trends for lie detector oversight in preference learning, 2026. URL https://arxiv.org/abs/2607.01567. arXiv:2607.01567, first posted 2026-07-02.

Geoffrey Irving and Amanda Askell. AI safety needs social scientists. *Distill*, February 2019. doi: 10.23915/distill.00014. URL https://distill.pub/2019/safety-needs-social-scientists/. Published 19 February 2019.

Geoffrey Irving, Paul Christiano, and Dario Amodei. AI safety via debate. *arXiv preprint arXiv:1805.00899*, May 2018. URL https://arxiv.org/abs/1805.00899.

Geoffrey Irving, Tomek Korbak, and Benjamin Hilton. Automation collapse, 2024. URL https://www.lesswrong.com/posts/2Gy9tfjmKwkYbF9BY/automation-collapse. LessWrong / AI Alignment Forum post, 21 October 2024.

Rishub Jain, Sophie Bridgers, Lili Janzer, Rory Greig, Tian Huey Teh, and Vladimir Mikulik. Human-AI complementarity: A goal for amplified oversight, 2025. URL https://arxiv.org/abs/2510.26518. arXiv:2510.26518, first posted 2025-10-30.

Eyon Jang, Damon Falck, Joschka Braun, Nathalie Kirch, Achu Menon, Perusha Moodley, Scott Emmons, Roland S. Zimmermann, and David Lindner. Exploration hacking: Can LLMs learn to resist RL training?, 2026. URL https://arxiv.org/abs/2604.28182.

Fengqing Jiang, Yichen Feng, Yuetai Li, Luyao Niu, Basel Alomair, and Radha Poovendran. BadScientist: Can a research agent write convincing but unsound papers that fool LLM reviewers?, 2025. URL https://arxiv.org/abs/2510.18003.

Holden Karnofsky. The open philanthropy project is now an independent organization, 2017. URL https://coefficientgiving.org/research/the-open-philanthropy-project-is-now-an-independent-organization/. Explains the LLC structure; retrieved 2026-09-17.

Adam Kaufman, James Lucassen, Tyler Tracy, Cody Rushing, and Aryan Bhatt. BashArena: A control setting for highly privileged AI agents, 2025. URL https://arxiv.org/abs/2512.15688.

Zachary Kenton, Noah Y. Siegel, János Kramár, Jonah Brown-Cohen, Samuel Albanie, Jannis Bulian, Rishabh Agarwal, David Lindner, Yunhao Tang, Noah D. Goodman, and Rohin Shah. On scalable oversight with weak LLMs judging strong LLMs. In *Advances in Neural Information Processing Systems 37 (NeurIPS 2024)*, 2024. URL https://arxiv.org/abs/2407.04622. arXiv:2407.04622, first posted 2024-07-05.

Zachary Kenton, Lili Janzer, Rory Greig, Tian Huey Teh, Kirill Tyshchuk, Jonah Brown-Cohen, Harri Edwards, Senthooran Rajamanoharan, Noah Y. Siegel, Natasha Jaques, and Rohin Shah. Debate training reduces reward hacking in RLAIF, 2026. URL https://arxiv.org/abs/2608.17776. arXiv:2608.17776, first posted 2026-08-18.

Akbir Khan, John Hughes, Dan Valentine, Laura Ruis, Kshitij Sachan, Ansh Radhakrishnan, Edward Grefenstette, Samuel R. Bowman, Tim Rock-

täschel, and Ethan Perez. Debating with more persuasive LLMs leads to more truthful answers. In *Proceedings of the 41st International Conference on Machine Learning (ICML 2024), PMLR 235*, 2024. URL https://arxiv.org/abs/2402.06782. arXiv:2402.06782, first posted 2024-02-09.

Megan Kinniment. Thread on cheating and fooling evaluators on fuzzy tasks. X, 19 May, 2026. URL https://x.com/MKinniment/status/2056819064983699504. Linked from Tailwind's "Misleadingness evaluations"; image not examined. Read via the fxtwitter API, 2026-09-17.

Jan Hendrik Kirchner, Yining Chen, Harri Edwards, Jan Leike, Nat McAleese, and Yuri Burda. Prover-Verifier games improve legibility of LLM outputs, 2024. URL https://arxiv.org/abs/2407.13692. arXiv:2407.13692, first posted 2024-07-18.

Sai Kolasani, Maxim Saplin, Nicholas Crispino, Kyle Montgomery, Jared Quincy Davis, Matei Zaharia, Chi Wang, and Chenguang Wang. LLM CHESS: Benchmarking reasoning and instruction-following in LLMs through chess, 2025. URL https://arxiv.org/abs/2512.01992. Live data: https://github.com/maxim-saplin/llm_chess/blob/main/data/elo_refined.csv, pulled 2026-09-17.

Tomek Korbak, Mikita Balesni, Elizabeth Barnes, Yoshua Bengio, Joe Benton, Joseph Bloom, Mark Chen, Alan Cooney, Allan Dafoe, Anca Dragan, Scott Emmons, Owain Evans, David Farhi, Ryan Greenblatt, Dan Hendrycks, Marius Hobbhahn, Evan Hubinger, Geoffrey Irving, Erik Jenner, Daniel Kokotajlo, Victoria Krakovna, Shane Legg, David Lindner, David Luan, Aleksander Mądry, Julian Michael, Neel Nanda, Dave Orr, Jakub Pachocki, Ethan Perez, Mary Phuong, Fabien Roger, Joshua Saxe, Buck Shlegeris, Martín Soto, Eric Steinberger, Jasmine Wang, Wojciech Zaremba, Bowen Baker, Rohin Shah, and Vlad Mikulik. Chain of thought monitorability: A new and fragile opportunity for AI safety, 2025. URL https://arxiv.org/abs/2507.11473. arXiv:2507.11473, first posted 2025-07-15.

Jonathan Kutasov, Yuqi Sun, Paul Colognese, Teun van der Weij, et al. SHADE-Arena: Evaluating sabotage and monitoring in LLM agents, 2025. URL https://arxiv.org/abs/2506.15740.

Jan Leike and Ilya Sutskever. Introducing Superalignment. OpenAI blog, July 2023. URL https://openai.com/index/introducing-superalignment/. Published 5 July 2023.

Jan Leike, David Krueger, Tom Everitt, Miljan Martic, Vishal Maini, and Shane Legg. Scalable agent alignment via reward modeling: a research direction. *arXiv preprint arXiv:1811.07871*, November 2018. URL https://arxiv.org/abs/1811.07871.

lennie, Joan Velja, Shi Feng, and Jacob Pfau. Research update: RL on debate games shows proposal accuracy uplift alongside judge hacking, 2026. URL https://www.lesswrong.com/posts/6mLwAuFAE98c6R7w3/research-update-rl-on-debate-games-shows-proposal-accuracy. LessWrong post, 2 July 2026; lead author listed only by handle "lennie".

Lena Libon, Ben Rank, Jehyeok Yeon, David Schmotz, Jeremy Qin, Daniel Donnelly, Derck Prinzhorn, and Maksym Andriushchenko. ResearchArena: Evaluating sabotage and monitoring in automated AI R&D, 2026. URL https://arxiv.org/abs/2607.19321.

Lichess. lichess.org open database: Puzzles and evaluations. https://database.lichess.org/, 2026. CC0; 6,100,952 puzzles and 409,710,113 evaluated positions, files updated 2026-09-10; accessed 2026-09-17.

Zach Lloyd. Introducing Warp Factories: Open, flexible infrastructure for building your software factory. Warp blog, 18 August 2026, 2026a. URL https://www.warp.dev/blog/open-infrastructure-for-building-a-software-factory. Accessed 17 Sep 2026.

Zach Lloyd. Introducing factory benchmarks. Warp blog, 3 September 2026, 2026b. URL https://www.warp.dev/blog/warp-factory-benchmarks. Accessed 17 Sep 2026.

Zach Lloyd. WarpBench: Measuring, testing and improving coding agents on your own codebase. Warp Factories page, 2 September 2026, 2026c. URL https://www.warp.dev/factories/benchmarks/warpbench. Accessed 17 Sep 2026.

Ziming Luo, Atoosa Kasirzadeh, and Nihar B. Shah. The more you automate, the less you see: Hidden pitfalls of AI scientist systems, 2025. URL https://arxiv.org/abs/2509.08713.

Monte MacDiarmid, Benjamin Wright, Jonathan Uesato, Joe Benton, Jon Kutasov, Sara Price, Naia Bouscal, Sam Bowman, Trenton Bricken, Alex Cloud, Carson Denison, Johannes Gasteiger, Ryan Greenblatt, Jan Leike, Jack Lindsey, Vlad Mikulik, Ethan Perez, Alex Rodrigues, Drake Thomas, Albert Webson, Daniel Ziegler, and Evan Hubinger. Natural emergent misalignment from reward hacking in production RL, 2025. URL https://arxiv.org/abs/2511.18397. arXiv:2511.18397, first posted 2025-11-23.

Anas Mahmoud, MohammadHossein Rezaei, Zihao Wang, Anisha Gunjal, Bing Liu, and Yunzhong He. Reward hacking in Rubric-Based reinforcement learning, 2026. URL https://arxiv.org/abs/2605.12474. arXiv:2605.12474, first posted 2026-05-12.

Sam Martin, Dewi Gould, Cameron Holmes, and Jacob Pfau. Obstacles to the scalable oversight of auto-alignment research, 2026. URL https://www.lesswrong.com/posts/PBGKWNrJAbpDgSsPo/obstacles-to-the-scalable-oversight-of-auto-alignment. LessWrong post, 16 September 2026 (Arcadia Alignment).

Nat McAleese, Rai Michael Pokorny, Juan Felipe Ceron Uribe, Evgenia Nitishinskaya, Maja Trebacz, and Jan Leike. LLM critics help catch LLM bugs, 2024. URL https://arxiv.org/abs/2407.00215. arXiv:2407.00215, first posted 2024-06-28.

Jake Mendel. Three positive updates I made about technical grantmaking at Coefficient Giving (fka Open Phil). LessWrong, 26 November, 2025. URL https://www.lesswrong.com/posts/gLt7KJkhiEDwoPkae. TAIS grants $40M in 2024, over $140M in 2025. Accessed 2026-09-17.

Jake Mendel. Comment on "rohinmshah's shortform". LessWrong comment, 18 February, 2026. URL https://www.lesswrong.com/posts/TmHRACaxXrLbXb5tS/rohinmshah-s-shortform?commentId=oDMjx62FQ38kMK6xx. Spectrum of "having the AIs do our alignment homework". Accessed 2026-09-17.

Jake Mendel, Max Nadeau, and Peter Favaloro. Open philanthropy technical AI safety RFP – $40M available across 21 research areas. LessWrong, 6 February, 2025. URL https://www.lesswrong.com/posts/wbJxRNxuezvsGFEWv. Accessed 2026-09-17.

METR. Task-completion time horizons of frontier AI models. https://metr.org/time-horizons/, May 2026. Time Horizon 1.1; last updated 8 May 2026; retrieved 2026-09-17.

Julian Michael, Salsabila Mahdi, David Rein, Jackson Petty, Julien Dirani, Vishakh Padmakumar, and Samuel R. Bowman. Debate helps supervise unreliable experts. *arXiv preprint arXiv:2311.08702*, November 2023. URL https://arxiv.org/abs/2311.08702.

Max Nadeau. Comment on "Alex Mallen's shortform". LessWrong comment, 7 September, 2026. URL https://www.lesswrong.com/posts/qTtMXuFvgFtWzWpKQ/alex-mallen-s-shortform?commentId=yZdw5STxqrHYKHWcd. Accessed 2026-09-17.

Max Nadeau and Zershaaneh Qureshi. Max Nadeau on recruiting founders for a new wave of AI safety nonprofits. 80,000 Hours podcast, 2026. URL https://80000hours.org/podcast/episodes/max-nadeau-project-tailwind-technical-ai-grants/. Pre-seed $200k–$2m; seed $2m–$20m (conditions for a first-grant seed); up to $200m for new organisations; pitch days. Retrieved 2026-09-17.

Neon. Branching. Neon documentation, 2026. URL https://neon.com/docs/introduction/branching. Accessed 17 Sep 2026.

Emily Oehlsen. We're urgently scaling our work on AI and biosecurity. Coefficient Giving Substack, 9 September, 2026. URL https://coefficientgiving.substack.com/p/were-urgently-scaling-our-work-on. Announces Project Tailwind; Resolution $160M; 2024–2026 giving totals. Accessed 2026-09-17.

Palaestra Research. Palaestra research: Scalable oversight for advanced AI, 2026. URL https://palaestraresearch.org/. Single-page site plus two output pages. Accessed 2026-09-17.

Daniel Paleka, Abhimanyu Pallavi Sudhir, Alejandro Alvarez, Vineeth Bhat, Adam Shen, Evan Wang, and Florian Tramèr. Consistency checks for language model forecasters. In *International Conference on Learning Representations (ICLR 2025)*, 2025. URL https://openreview.net/forum?id=r5IXBlTCGc. Accept (Oral); first two authors contributed equally.

Abhimanyu Pallavi Sudhir, Jackson Kaunismaa, and Arjun Panickssery. A benchmark for scalable oversight protocols. In *ICLR 2025 Workshop on Bidirectional Human-AI Alignment (BiAlign)*, 2025. URL https://arxiv.org/abs/2504.03731. arXiv:2504.03731, first posted 2025-03-31.

Richard Yuanzhe Pang, Alicia Parrish, Nitish Joshi, Nikita Nangia, Jason Phang, Angelica Chen, Vishakh Padmakumar, Johnny Ma, Jana Thompson, He He, and Samuel R. Bowman. QuALITY: Question answering with long input texts, yes! In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics (NAACL 2022)*, December 2022. URL https://arxiv.org/abs/2112.08608.

Arjun Panickssery, Samuel R. Bowman, and Shi Feng. LLM evaluators recognize and favor their own generations. In *Advances in Neural Information Processing Systems (NeurIPS 2024)*, 2024a. URL https://arxiv.org/abs/2404.13076.

Arjun Panickssery, Abhimanyu Pallavi Sudhir, and Jackson Kaunismaa. Inference-Only debate experiments using math problems, 2024b. URL https://www.lesswrong.com/posts/ot25KcanipSaKzAH9/inference-only-debate-experiments-using-math-problems-1. LessWrong post, 6 August 2024. Work supported by MATS and SPAR.

Alicia Parrish, Harsh Trivedi, Nikita Nangia, Vishakh Padmakumar, Jason Phang, Amanpreet Singh Saimbhi, and Samuel R. Bowman. Two-turn debate doesn't help humans answer hard reading comprehension ques-

tions. *arXiv preprint arXiv:2210.10860*, October 2022a. URL https://arxiv.org/abs/2210.10860.

Alicia Parrish, Harsh Trivedi, Ethan Perez, Angelica Chen, Nikita Nangia, Jason Phang, and Samuel R. Bowman. Single-turn debate does not help humans answer hard reading-comprehension questions. In *Proceedings of the First Workshop on Learning with Natural Language Supervision (ACL 2022)*, April 2022b. URL https://arxiv.org/abs/2204.05212.

Sara Price, Arjun Panickssery, Sam Bowman, and Asa Cooper Stickland. Future events as backdoor triggers: Investigating temporal vulnerabilities in LLMs, 2024. URL https://arxiv.org/abs/2407.04108.

Ansh Radhakrishnan. Anthropic fall 2023 debate progress update. AI Alignment Forum, November 2023. URL https://www.alignmentforum.org/posts/QtqysYdJRenWFeWc4. Posted 28 November 2023.

Nan Ransohoff. The third wave of American philanthropy. Substack, 19 May, 2026. URL https://nanransohoff.substack.com/p/the-third-wave-of-american-philanthropy. Linked from Tailwind's About page (section on philanthropic startups). Accessed 2026-09-17.

David Rein. NYU code debates Update/Postmortem, 2024. URL https://www.lesswrong.com/posts/wsXCXoyvRi3DnWZ2M/nyu-code-debates-update-postmortem. LessWrong post, 24 May 2024.

Resolution. Announcing our $160M grant from Coefficient Giving, 2026a. URL https://resolution.org/post/funding. $108M base plus $52M conditional. Accessed 2026-09-17.

Resolution. Research scientist (job posting), 2026b. URL https://jobs.ashbyhq.com/resolution/65704205-7ccd-4df6-a7d1-3e3338bd80a8. Status updated 21 August 2026: reviewing Scalable Oversight applications only; salary ladder L3–L7. Read via Ashby posting API, 2026-09-17.

Resolution. Resolution: Scale and automation for higher confidence in alignment, 2026c. URL https://resolution.org/launch. Launched as Sequent, 10 June 2026; LessWrong cross-post AP7YDke5jjY4v3X9Z. Accessed 2026-09-17.

Resolution. Why we changed our name from Sequent, 2026d. URL https://resolution.org/post/rebrand. Legal entity Timaeus Research, Inc. renamed Resolution Alignment, Inc. Accessed 2026-09-17.

Amit Roth, Ivan Bercovich, and Yonathan Efroni. Hack-verifiable terminal bench: Evaluating reward hacking in terminal tasks, 2026. URL https://arxiv.org/abs/2608.22103.

Sampura Research. Sampura research: Human-AI complementarity for alignment. 25 August, 2026a. URL https://sampura.org/news/announcing-sampura-research/. $11M from Coefficient Giving ($7M first year, $4M pledged). Accessed 2026-09-17.

Sampura Research. Founding member of technical staff (job posting), 2026b. URL https://jobs.ashbyhq.com/sampura/a83213a5-6d70-4ed1-8f79-542a34051637. London; salaries £100k–£290k; about $1M per quarter for compute and human data. Read via Ashby posting API, 2026-09-17.

William Saunders, Ben Rachbach, Owain Evans, Jungwon Byun, and Andreas Stuhlmüller. Evaluating arguments one step at a time. Ought blog, January 2020. URL https://ought.org/updates/2020-01-11-arguments. Posted 11 January 2020; author order from the post's credit line.

William Saunders, Catherine Yeh, Jeff Wu, Steven Bills, Long Ouyang, Jonathan Ward, and Jan Leike. Self-critiquing models for assisting human evaluators. *arXiv preprint arXiv:2206.05802*, June 2022. URL https://arxiv.org/abs/2206.05802.

S. Schroter, N. Black, S. Evans, F. Godlee, L. Osorio, and R. Smith. What errors do peer reviewers detect, and does training improve their ability to detect them? *Journal of the Royal Society of Medicine*, 101(10):507–514, 2008. doi: 10.1258/jrsm.2008.080062. PMID 18840867.

Lisa Schut, Nenad Tomašev, Tom McGrath, Demis Hassabis, Ulrich Paquet, and Been Kim. Bridging the human–AI knowledge gap through concept discovery and transfer in AlphaZero. *Proceedings of the National Academy of Sciences*, 122(13), 2025. doi: 10.1073/pnas.2406675122.

Rohin Shah, Alex Irpan, Alexander Matt Turner, Anna Wang, Arthur Conmy, David Lindner, Jonah Brown-Cohen, Lewis Ho, Neel Nanda, Raluca Ada Popa, Rishub Jain, Rory Greig, Samuel Albanie, Scott Emmons, Sebastian Farquhar, Sébastien Krier, Senthooran Rajamanoharan, Sophie Bridgers, Tobi Ijitoye, Tom Everitt, Victoria Krakovna, Vikrant Varma, Vladimir Mikulik, Zachary Kenton, Dave Orr, Shane Legg, Noah Goodman, Allan Dafoe, Four Flynn, and Anca Dragan. An approach to technical AGI safety and security, 2025. URL https://arxiv.org/abs/2504.01849. arXiv:2504.01849, first posted 2025-04-02.

Judy Hanwen Shen and Alex Tamkin. How AI impacts skill formation, 2026. URL https://arxiv.org/abs/2601.20245. Anthropic blog:

"How AI assistance impacts the formation of coding skills", 29 January 2026.

Buck Shlegeris. Scalable oversight as a quantitative rather than qualitative problem, 2024. URL https://www.lesswrong.com/posts/6AT4vhYzww56CR6cm/scalable-oversight-as-a-quantitative-rather-than-qualitative. LessWrong / AI Alignment Forum post, 6 July 2024.

Buck Shlegeris and Ryan Greenblatt. Meta-level adversarial evaluation of oversight techniques might allow robust measurement of their adequacy. AI Alignment Forum (Redwood Research), July 2023. URL https://www.alignmentforum.org/posts/MbWWKbyD5gLhJgfwn. Posted 26 July 2023.

Guijin Son, Jiwoo Hong, Honglu Fan, Heejeong Nam, Hyunwoo Ko, Seungwon Lim, et al. When AI co-scientists fail: SPOT-a benchmark for automated verification of scientific research, 2025. URL https://arxiv.org/abs/2505.11855.

Giulio Starace, Oliver Jaffe, Dane Sherburn, James Aung, Jun Shern Chan, Leon Maksin, et al. PaperBench: Evaluating AI's ability to replicate AI research, 2025. URL https://arxiv.org/abs/2504.01848.

Nisan Stiennon, Long Ouyang, Jeff Wu, Daniel M. Ziegler, Ryan Lowe, Chelsea Voss, Alec Radford, Dario Amodei, and Paul Christiano. Learning to summarize from human feedback. In *Advances in Neural Information Processing Systems 33 (NeurIPS 2020)*, September 2020. URL https://arxiv.org/abs/2009.01325.

Stripe. Sandboxes. Stripe documentation, 2026. URL https://docs.stripe.com/sandboxes. Accessed 17 Sep 2026.

Zhenwei Tang, Qianfeng Wen, Seth Grief-Albert, Yahya Elgabra, Blair Yang, Honghua Dong, and Ashton Anderson. Grounded chess reasoning in language models via master distillation, 2026. URL https://arxiv.org/abs/2603.20510.

UK AI Security Institute. Inspect: A framework for large language model evaluations. https://github.com/UKGovernmentBEIS/inspect_ai, 2024. MIT; 2,803 stars, last push 2026-09-18 (GitHub API, 2026-09-17).

UK AI Security Institute. The alignment project, 2025a. URL https://alignmentproject.aisi.gov.uk/. Funding programme launched July 2025; research priorities at alignmentproject.aisi.gov.uk/research-agenda.

UK AI Security Institute. ControlArena: a collection of settings, model organisms and protocols for running control experiments. https://github.com/UKGovernmentBEIS/control-arena, 2025b. MIT licence; 237 stars, last push 2026-08-24 (GitHub API, 2026-09-17).

UK AI Security Institute. Funding 60 projects to advance AI alignment research, 2026. URL https://www.aisi.gov.uk/blog/funding-60-projects-to-advance-ai-alignment-research. AISI blog; first-round awards announced 19 February 2026 (gov.uk news, "OpenAI and Microsoft join UK's international coalition to safeguard AI development").

Michelle Vaccaro, Abdullah Almaatouq, and Thomas Malone. When combinations of humans and AI are useful: A systematic review and meta-analysis. *Nature Human Behaviour*, 8:2293–2303, 2024. doi: 10.1038/s41562-024-02024-1.

Warp. Configuring scorers. Warp documentation, 2026. URL https://docs.warp.dev/factories/measure-and-improve/scorers/. Last updated 16 Sep 2026; accessed 17 Sep 2026.

Jiaxin Wen, Ruiqi Zhong, Akbir Khan, Ethan Perez, Jacob Steinhardt, Minlie Huang, Samuel R. Bowman, He He, and Shi Feng. Language models learn to mislead humans via RLHF. In *International Conference on Learning Representations (ICLR 2025)*, 2024. URL https://arxiv.org/abs/2409.12822. arXiv:2409.12822, first posted 2024-09-19.

Jiaxin Wen, Zachary Ankner, Arushi Somani, Peter Hase, Samuel Marks, Jacob Goldman-Wetzler, Linda Petrini, Henry Sleight, Collin Burns, He He, Shi Feng, Ethan Perez, and Jan Leike. Unsupervised elicitation of language models, 2025. URL https://arxiv.org/abs/2506.10139. arXiv:2506.10139, first posted 2025-06-11.

Jiaxin Wen, Liang Qiu, Joe Benton, Jan Hendrik Kirchner, and Jan Leike. Automated Weak-to-Strong researcher, 2026. URL https://alignment.anthropic.com/2026/automated-w2s-researcher/. Anthropic Alignment Science blog, April 2026; code at github.com/safety-research/automated-w2s-research.

John Wentworth. The case against AI control research, 2025. URL https://www.lesswrong.com/posts/8wBN8cdNAv3c7vt6p/the-case-against-ai-control-research. LessWrong post (as johnswentworth), 21 January 2025.

Hjalmar Wijk, Tao Lin, Joel Becker, Sami Jawhar, et al. RE-Bench: Evaluating frontier AI R&D capabilities of language model agents against human experts, 2024. URL https://arxiv.org/abs/2411.15114.

Jeff Wu, Long Ouyang, Daniel M. Ziegler, Nisan Stiennon, Ryan Lowe, Jan Leike, and Paul Christiano. Recursively summarizing books with human feedback. *arXiv preprint arXiv:2109.10862*, September 2021. URL https://arxiv.org/abs/2109.10862.

Frank Xiao and Mary Phuong. Generalization hacking: Models can game reinforcement learning by preventing behavioral generalization, 2026. URL https://arxiv.org/abs/2606.12016.

Yuzheng Xu, Annya Dahmani, Matthew D. Blanchard, Niclas Dern, Edy Nastase, Francesca Bianco, Maja Pavlovic, Sukanya Krishna, Eric Modesitt, Miranda Anna Christ, Arth Singh, Gaia Molinaro, Sikata Bela Sengupta, Jaji Pamarthi, Arjun Menon, and Rishub Jain. Toward Human-AI complementarity across diverse tasks, 2026. URL https://arxiv.org/abs/2605.04070. arXiv:2605.04070, first posted 2026-04-13.

Ke Yang, Chenglong Wang, Michel Galley, Chandan Singh, Jeevana Priya Inala, ChengXiang Zhai, and Jianfeng Gao. StudentSim: Training LLM-based student simulators, 2026. URL https://arxiv.org/abs/2609.01591.

Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik Narasimhan. τ-bench: A benchmark for tool-agent-user interaction in real-world domains, 2024. URL https://arxiv.org/abs/2406.12045.

Jingheng Ye, Huiqi Zou, Simon Yu, and Weiyan Shi. Coding with "enemy": Can human developers detect AI agent sabotage?, 2026. URL https://arxiv.org/abs/2606.05647.

A Budget model

The three tables below are generated by `scripts/05_budget.py`, which holds every input as a named constant with its source, so that no figure in these tables is typed by hand. Amounts are in thousands of US dollars. Salaries are loaded by 20% for payroll taxes and benefits. Compute lines are built up from unit costs where the research supplies them: about $14 per software-task trial, from Warp's published benchmark bill and assuming one repetition (so $13,000 per 900-trial sweep); $340–$810 per simulated business year, uncached, for frontier agents from GPT-5.6 Sol to GPT-6 Astra, from Andon Labs' Vending-Bench 2 cost data (Fable-class agents cost $1,100–$1,500); and Tinker prices for the RL runs (section 7.3). The seed and scale stages are coarser, and should be read as orders of magnitude with a stated composition, not as quotations.

How to read the compute share. Compute, API and human data make up 25% of the pre-seed budget, 39% of the seed and 43% of the scale stage. For

Table 15: Pre-seed, 12 months (thousands of US dollars).

Line	Low	Central	High
Founders (2, full time)	480	600	636
Research engineers (from month 3)	50	360	528
Strand 1: software-firm ASD sweeps (900-trial sweeps)	38	77	128
Strand 1: long-horizon business episodes	27	82	162
Strand 2: inference sweeps across model scales	15	40	80
Strand 3: RL runs (low: small scale; central: small and medium; high: all three)	18	53	106
Strands 4 and 6: explainer RL, chess/SQL/Lean settings	8	15	25
Compute contingency (15%)	16	40	75
Human graders: writing tasks	25	50	80
Human participants: explanation and chess studies	5	13	30
Travel, software, legal, accounting	20	40	50
Subtotal	703	1,370	1,900
Administration or fiscal sponsor (7, 7, 5 %)	49	96	95
Total	**752**	**1,466**	**1,995**

Table 16: Seed, 24 months (thousands of US dollars).

Line	Low	Central	High
Staff (average FTE $\times$ loaded cost $\times$ 2 years)	2,650	4,800	6,400
Strand 1: firm and research experiments with frontier agents	600	1,300	2,200
Strand 2: scaling sweeps (open-weight ladders, reasoning budgets)	150	350	600
Strand 3: RL at large scale, incl. self-hosted 70B	400	1,200	2,000
Strands 4–6: explainers, settings, library infrastructure	100	250	400
Human data: expert writing panel, explanation RCTs, rated judges	500	900	1,200
Travel, conferences, software, legal, recruiting	400	700	800
Subtotal	4,800	9,500	13,600
Administration or fiscal sponsor (8, 8, 8 %)	384	760	1,088
Total	**5,184**	**10,260**	**14,688**

Table 17: Scale, 36 months (thousands of US dollars). Illustrative.

Line	Low	Central	High
Staff (average FTE × loaded cost × 3 years)	14,400	24,750	40,800
RL and training-run perturbation at 30B–400B scale	4,500	10,500	27,000
Long-horizon firm and research testbeds, judge fleets	3,000	7,500	18,000
Standing expert and learner panels	1,500	4,500	7,500
Operations, security, facilities	1,500	3,000	4,500
Subtotal	24,900	50,250	97,800
Administration or fiscal sponsor (5, 5, 5 %)	1,245	2,512	4,890
Total	**26,145**	**52,762**	**102,690**

comparison, Sampura budgets about 57% of its first year for compute and human data, and Anthropic gives each fellow about $180,000 a year of compute. Pre-seed is mostly people building infrastructure; if the Gate 1 results show that the firm and writing studies are the most informative, the seed request should shift money towards them.

B Comparable grants

The grants below are the members of the four comparison sets used in section 9, generated from `data/comparables.csv` by `scripts/03_funding.py`. Membership: F, first grant to a new small technical organisation; S, seed-scale grant to a young organisation; A, oversight-adjacent or evaluation grant; O, scalable-oversight grant. The full file of 89 grants records each source. Grants were compiled one grantee at a time from CG's public grants table, which gives award months and amounts but not durations, and from grantees' announcements for the 2026 grants not yet in that table. Palaestra's grant is not public and is excluded. Resolution appears in set O but is left out of the median quoted in the text, so that the median describes grants of a size a new team could expect.

Table 18: Comparable CG grants by award month (US dollars).

Award	Grantee	Grant	Amount	Sets
2021-10	FAR AI	Language Model Misalignment	425,800	F
2021-11	Redwood	General Support	9,420,000	S
2022-03	Alignment Research Center	General Support	265,000	F
2023-05	Owain Evans	AI Evaluations Research (Owain Evans)	1,652,076	A
2023-06	Apollo	Startup Funding	1,535,480	AF
2023-09	BERI	Scalable Oversight Dataset	70,000	O

Award	Grantee	Grant	Amount	Sets
2024-02	U. Michigan	Scalable Oversight Research (Samet Oymak)	100,000	O
2024-04	U. Wisconsin-Madison	Scalable Oversight Research (Dimitris Papailiopoulos)	100,000	O
2024-04	Princeton University	Scalable Oversight Research (Jason Lee)	100,000	O
2024-06	Palisade	General Support	1,680,000	AF
c.2024–25	Theorem (Jason Gross, Rajashree Agrawal)	Founding grant: formal software verification	1,000,000	F
2025-01	Timaeus	Operating Expenses	2,049,000	F
2025-05	Palisade	General Support	2,123,463	A
2025-06	Atlas Computing	Research Exploration	100,000	F
2025-07	Cadenza Labs	Benchmark for Detectors of LLM Dishonesty	441,449	AF
2025-08	Truthful AI	"Truthful AI" Research Group	6,116,133	S
2025-09	U. Texas at Dallas	Control Evaluations for AI Debate (Xinya Du)	218,513	O
2025-10	Simplex	General Support	2,045,200	F
2025-10	Rethink Priorities (fiscal sponsor)	Evaluation of AI Agent Risk Attitudes	585,468	A
2026-02	P-Zero	General Support	250,000	AF
2026-02	Aether	AI Control & Monitoring Projects	756,570	AF
2026-03	Timaeus	General Support	10,932,000	S
2026-04	Arcadia Impact	Arcadia Impact Alignment Project	1,900,000	AO
2026-04	Rethink Priorities (fiscal sponsor)	Development of the Holistic Agent Leaderboard	927,744	A
2026-04	Kairos (SPAR)	Research on Scalable Oversight (Rishub Jain)	50,000	O
2026-05	Tara	Assessing Techniques for Detecting AI Dishonesty	1,817,500	AF
2026-05	Geodesic	Pretraining Techniques for AI Alignment	14,095,046	FS
2026-05	Ofir Press	VideoGameBench	189,960	A
2026-06	P-Zero	AI Safety Research	5,580,000	AS
2026-07	Resolution	New-organisation grant (largest-ever CG AI-safety grant)	160,000,000	O
2026-08	Sampura	Initial grant (Human-AI Complementarity for Scalable Oversight)	11,000,000	AFOS
2026-08	Sage (AI Village)	General Support	12,600,000	AS

C Project Tailwind: the terms as published

Coefficient Giving launched Tailwind on 9 September 2026, in a post by Emily Oehlsen on scaling its AI and biosecurity work [Oehlsen, 2026]. What follows paraphrases the Tailwind pages as retrieved on 17 September 2026;

the archived text is in `data/raw/cg/`. The funder may change the terms, so anything load-bearing should be rechecked before submission.

What it is. Tailwind is CG's first public call for *founders*: people who will start new organisations, or new teams inside existing ones, aimed directly at catastrophic risk from AI. The About page is signed by Emily Oehlsen, Jake Mendel and Ryan Fugate. It argues that AI lacks the safety institutions that aviation, medicine and finance have, and that top talent is the bottleneck. The public call runs alongside a talent-scout programme, a bounty for successful founder referrals, more direct outreach, and pitch days and workshops run with partner organisations. CG says it expects many of its most promising leads to come through those channels.

Funding tiers.

- **Pre-seed**, $200,000–$2 million: usually research or planning grants, meant to develop the idea, build a team and validate the approach over 9–18 months.
- **Seed**, $2–20 million: to launch and scale an organisation over 18–36 months.
- **Scale**, $20–200 million and up: for world-class founding teams or organisations with a strong record, aimed squarely at a key problem with a meaningful chance of success.

A grantee need not wait for its pre-seed window to end. The FAQ gives the example of applying for seed funding three months in, after testing a few ideas and getting traction with one.

Process. After an expression of interest, promising candidates are invited to submit a proposal covering track record, relevant capabilities and the vision for the initiative. Strong candidates may skip straight to a short pitch meeting. CG says it aims to decide quickly and disburse soon after that conversation. It warns that it may not answer every submission and may stop accepting them if volume is high.

Screens. Submissions not directly about catastrophic risk from AI are filtered out automatically, and so are submissions that CG's systems "indicate were generated by AI". The form itself notes that AI tools may be used to help review submissions. *The practical consequence for this report is that its prose must not be pasted into the form.* The applicants should write the pitch themselves, using this report for facts and structure.

The form. Only name, email, a CV or public profile links, and how the applicant heard of Tailwind are required. Everything else is optional: co-founders, whether one is looking for a co-founder, the most impressive thing one has built or accomplished (about 200 words), a pitch or expression of interest in a listed initiative (about 300 words), one to four references with a strong AI-safety record, and consent to share the submission with other organisations working on the same idea.

Salaries. The FAQ says budgets should pay founders properly and let the initiative compete for top talent, and calls pay "usually a solvable problem".

Legal form. CG is best placed to fund nonprofits. It will consider a public-benefit corporation if that structure would make the organisation more effective and the work shows a clear charitable purpose, but it does not expect to fund other for-profits. It adds that it can pass strong for-profit opportunities, with consent, to safety-motivated investors. Pre-seed money can go to individuals or teams with no legal entity. Seed funding needs an entity, either one's own or a 501(c)(3) fiscal sponsor. Work outside the United States is supported but can take longer and carry extra requirements. Section 11 discusses what this means for the applicants.

The initiatives. The initiatives page lists 36 ideas in 7 categories, 13 of them featured. The page says each is endorsed by a grantmaker, though its data names none for "Unclaimed research labs", and it stresses that the list is not exhaustive and that better ideas are welcome. Table 19 lists them all, with this report's judgement of their relevance to a scalable-oversight programme. Of these, 2 name scalable oversight or debate directly and 9 are adjacent.

Table 19: Project Tailwind's initiatives (as retrieved 17 September 2026) and their relevance to a scalable-oversight proposal. * Featured on the page. Relevance is this report's judgement, not Coefficient Giving's.

Category	Initiative	Relevance to this proposal
Independent assessment	Frontier lab accountability*	—
	Misalignment red team*	**Adjacent**: messy open-ended tasks surface misbehaviour
	Control red team	**Adjacent**: adversarial stress tests of oversight protocols
	Bio safeguards red team	—
	Independent AI auditors	—
	Investigations for secret loyalties	—

Category	Initiative	Relevance to this proposal
	Misleadingness evaluations	**Adjacent**: human ratings of fuzzy work vs evaluation time
Research institutions	Oversight of CoT monitorability*	**Adjacent**: monitoring as a form of oversight
	AI character evaluator*	—
	Unclaimed research labs*	**Direct**: lists scalable oversight among agendas awaiting a lab
	Training run fault injections	**Adjacent**: oversight quality and hackable RL environments
	Threat modeling institute	—
	Alignment moonshots	**Direct**: names debate and scalable oversight as a moonshot
Evidence generation	Rogue incident detection*	—
	AI incident investigations*	—
	Frontier capabilities observatory*	—
	State of AI risk	—
	Biological uplift demos	—
AI security & verification	Agreement verification technology*	—
	Security capacity buildout*	—
	AI integrity standards	—
Public goods	Think tank for AI labs*	—
	AI for decision-makers*	**Adjacent**: do users judge more accurately with AI help?
	AI uplift for AI safety	**Adjacent**: shared tooling for the safety field
	Compute cluster for AI safety	**Adjacent**: compute for RL-heavy oversight research
	Datasets for AI safety	**Adjacent**: RL environments for safety-relevant skills
	Grand awards for AI safety	—
Talent acceleration	Senior talent headhunting*	—
	Talent matchmaking	—
	Mid-career entry points	—
	AI context accelerator	—
	Philanthropic startup incubator	—
	Fiscal sponsors	—
Convenings	Cross-sector convenings	—
	Subfield forums	—
	Events as a service	—

D Method, sources and corrections

Method. This report answers a written brief from the applicants ("the brief"). It is desk research: no experiments were run and no models were trained or queried. Eight research dossiers were compiled in parallel on 17 September 2026 (the chronology in two parts, CG's view and grantees, funding amounts, legal structure, the applicants and Warp, and two technical landscapes). Every citation was checked against a primary source (arXiv's API, the Alignment Forum and LessWrong API, OpenReview, publishers' and organisations' own pages, GitHub's API); items that could not be confirmed were marked in the dossiers; where the text relies on a secondary source or an estimate read from a figure, it says so. CG's Tailwind pages were archived as rendered in a browser, because the site refuses automated requests. Grant amounts were taken from CG's public grants table one grantee or topic at a time, and from grantees' announcements; the grants database was not downloaded in bulk. The medians and counts in section 9, the chronology counts and the budget tables are computed by scripts; other figures are transcribed from the dossiers.

Corrections and cautions.

- *Tailwind's launch date* is 9 September 2026, the date of Emily Oehlsen's post announcing it; the pages carry a later modification date, which an early draft of this report took for the launch.
- *Warp's scorers are language-model judges, not ground truth*, contrary to the premise in the brief (section 6.2).
- *The ASD paper's Propaganda row* was very probably produced by code in which the Propaganda agent was not told which side to argue. This is confirmed in the committed February 2025 pilot logs; the final run's logs are not public. The authors fixed the code in January 2026 (section 1). The code's Brier ASD also differs from the paper's footnote.
- *Sampura's funding* is reported as $7 million plus $4 million by Sampura and as $6.5 million plus $4.2 million by Bloomberg; this report uses Sampura's figures.
- *Palaestra's CG grant* is acknowledged by Palaestra but its amount is not public.
- *Engels et al.'s debate success rate* of 51.7% at a 400-point gap sits on a 50% chance floor, and their fits span 274 points of Chatbot Arena Elo; it should not be quoted as evidence that debate works at large gaps.

- *Chess ratings* for language models and for engines come from different rating pools; the gap of about two thousand points is an order of magnitude, not a measurement.
- *Legal and tax points* are research, not advice (section 11).

Files. The dossiers, CSV files and scripts are in the project repository: `data/dossiers/` (research notes and bibliographies), `data/comparables.csv`, `data/raw/cg/` (archived Tailwind pages), and `scripts/` (figures, budget model, generated tables).