

SalesPort – SAP B1

Integration API Documentation

Version 1.2

February 2026

Prepared by

Sort String Solutions LLP

CONFIDENTIAL

Document Information

Document Title	SalesPort – SAP B1 Integration API Documentation
Version	1.2
Status	Final
Last Updated	February 21, 2026

Revision History

Version	Date	Author	Description
1.0	Feb 15, 2026	Sort String Solutions LLP	Initial Draft — 13 modules
1.1	Feb 21, 2026	Sort String Solutions LLP	Added Products (Variants) and Delivery Order
1.2	Feb 21, 2026	Sort String Solutions LLP	Balance Status Update & Order Status Sync changed to PUT only; status string mapping added

Table of Contents

Document Information.....	2
Revision History.....	2
Table of Contents.....	3
1. Introduction.....	8
1.1 Purpose.....	8
1.2 Scope.....	8
1.3 Integration Architecture.....	8
1.4 Base URL.....	8
2. Authentication & Security.....	10
2.1 Authentication Method.....	10
2.2 API Credentials.....	10
2.3 Request Header Format.....	10
2.4 Sample cURL Request.....	10
2.5 Security Guidelines.....	10
2.6 HTTP Response Codes.....	10
3. API Endpoints Reference.....	12
3.0 API Endpoints Summary.....	12
3.1 Business Partner (BP) Master.....	13
Endpoints.....	13
Business Rules & Validation.....	13
Request Schema.....	13
Sample Request Payload (POST).....	14
Responses.....	15
3.2 Blanket Agreement.....	16
Endpoints.....	16
Business Rules & Validation.....	16

Request Schema.....	16
Sample Request Payload (POST).....	16
Responses.....	17
3.3 Greater Circles.....	18
Endpoints.....	18
Business Rules & Validation.....	18
Request Schema.....	18
Sample Request Payload (POST).....	18
Responses.....	18
3.4 Circles.....	19
Endpoints.....	19
Business Rules & Validation.....	19
Request Schema.....	19
Sample Request Payload (POST).....	19
Responses.....	19
3.5 Container.....	20
Endpoints.....	20
Business Rules & Validation.....	20
Request Schema.....	20
Sample Request Payload (POST).....	20
Responses.....	20
3.6 Matrix.....	21
Endpoints.....	21
Business Rules & Validation.....	21
Request Schema.....	21
Sample Request Payload (POST).....	21
Responses.....	21

3.7 Product Class.....	22
Endpoints.....	22
Business Rules & Validation.....	22
Request Schema.....	22
Sample Request Payload (POST).....	22
Responses.....	22
3.8 Product Name.....	23
Endpoints.....	23
Business Rules & Validation.....	23
Request Schema.....	23
Sample Request Payload (POST).....	23
Responses.....	23
3.9 Payment Terms.....	24
Endpoints.....	24
Business Rules & Validation.....	24
Request Schema.....	24
Sample Request Payload (POST).....	24
Responses.....	24
3.10 Price List Group.....	25
Endpoints.....	25
Business Rules & Validation.....	25
Request Schema.....	25
Sample Request Payload (POST).....	25
Responses.....	25
3.11 Price List.....	26
Endpoints.....	26
Business Rules & Validation.....	26

Request Schema.....	26
Sample Request Payload (POST).....	26
Responses.....	26
3.12 Special Price List.....	27
Endpoints.....	27
Business Rules & Validation.....	27
Request Schema.....	27
Sample Request Payload (POST).....	27
Responses.....	28
3.13 Products (Variants).....	29
Endpoints.....	29
Business Rules & Validation.....	29
Request Schema.....	29
Sample Request Payload (POST).....	30
Responses.....	30
3.14 Delivery Order.....	31
Endpoints.....	31
Business Rules & Validation.....	31
Request Schema.....	31
Delivery Order Details (Nested Object).....	31
Sample Request Payload (POST).....	32
Responses.....	32
3.15 Balance Status Update.....	33
Endpoints.....	33
Business Rules & Validation.....	33
Request Schema.....	33
Sample Request Payload (PUT).....	33

Responses.....	33
3.16 Order Status Sync.....	34
Endpoints.....	34
Business Rules & Validation.....	34
Request Schema.....	34
Sample Request Payload (PUT).....	34
Responses.....	34
4. Data Conventions & Status Mapping.....	35
4.1 Status Field Mapping.....	35
4.2 Date Format.....	35
4.3 Decimal Fields.....	35
4.4 Naming Conventions.....	35
5. Error Handling.....	36
5.1 Error Response Format.....	36
5.2 Common Error Scenarios.....	36
5.3 Retry Strategy.....	36
6. Appendix.....	37
6.1 Glossary.....	37
6.2 Contact Information.....	37

1. Introduction

1.1 Purpose

This document provides a comprehensive technical reference for the RESTful API integration between SAP Business One (SAP B1) and SalesPort DMS. It details every endpoint, request schema, validation rule, sample payload, and expected response to enable the integration team to implement the data push with confidence.

1.2 Scope

The integration covers the synchronization of master data and transactional data from SAP B1 into SalesPort, including:

- Business Partner (BP) Master
- Blanket Agreements
- Greater Circles
- Circles
- Containers
- Matrix
- Product Class
- Product Name
- Payment Terms
- Price List Group
- Price List
- Special Price List
- Products (Variants)
- Delivery Order
- Balance Status Update
- Order Status Sync

1.3 Integration Architecture

The integration follows a push-based architecture where SAP B1 initiates HTTP requests to SalesPort's REST API endpoints. For creating new records, SAP sends POST requests; for updating existing records, SAP sends PUT requests with the record ID in the URL path.

Source System	SAP Business One (SAP B1)
Target System	SalesPort DMS
Direction	SAP → SalesPort (push-based)
Protocol	HTTPS (TLS 1.2+)

1.4 Base URL

All API endpoints are relative to the following base URL:


```
http://dms.salesport.in/
```

For example, to create a Business Partner, the full endpoint URL would be:

```
POST http://dms.salesport.in/sap/bp-master/
```

2. Authentication & Security

2.1 Authentication Method

All API endpoints are secured using HTTP Basic Authentication. Every request must include an Authorization header with Base64-encoded credentials.

2.2 API Credentials

The following credentials must be used for all POST and PUT requests to the SalesPort API:

Username	SujalFoods
Password	SujalFoods@123

2.3 Request Header Format

Every API request must include the following headers:

```
Authorization: Basic U3VqYWxGb29kczpTdWphbEZvb2RzQDEyMw==  
Content-Type: application/json
```

The Base64 encoded value above is derived from:

```
Base64("SujalFoods:SujalFoods@123") = U3VqYWxGb29kczpTdWphbEZvb2RzQDEyMw==
```

2.4 Sample cURL Request

```
curl -X POST http://dms.salesport.in/sap/bp-master/ \  
-u "SujalFoods:SujalFoods@123" \  
-H "Content-Type: application/json" \  
-d '{"customer_code": "CUST1001", ...}'
```

2.5 Security Guidelines

- Credentials must never be embedded in URLs or query parameters.
- Failed authentication returns HTTP 401 Unauthorized.
- All API requests must include the Authorization header with every call.
- Credentials should be stored securely and not hard-coded in client applications.

2.6 HTTP Response Codes

Code	Status	Description
200	OK	Resource updated successfully
201	Created	Resource created successfully
400	Bad Request	Validation failed — see response body for details

401	Unauthorized	Missing or invalid Basic Auth credentials
404	Not Found	Resource with the given ID does not exist
405	Method Not Allowed	HTTP method not supported on this endpoint
500	Internal Server Error	Unexpected server-side error
201	Created	Resource created successfully

3. API Endpoints Reference

This section documents each API endpoint with its request schema, validation rules, sample payloads, and expected responses.

3.0 API Endpoints Summary

#	Module	POST (Create)	PUT (Update)
3.1	BP Master	/sap/bp-master/	/sap/bp-master/{id}/
3.2	Blanket Agreement	/sap/blanket-agreement/	/sap/blanket-agreement/{id}/
3.3	Greater Circles	/sap/greater-circles/	/sap/greater-circles/{id}/
3.4	Circles	/sap/circles/	/sap/circles/{id}/
3.5	Container	/sap/container/	/sap/container/{id}/
3.6	Matrix	/sap/matrix/	/sap/matrix/{id}/
3.7	Product Class	/sap/product-class/	/sap/product-class/{id}/
3.8	Product Name	/sap/product-name/	/sap/product-name/{id}/
3.9	Payment Terms	/sap/payment-terms/	/sap/payment-terms/{id}/
3.10	Price List Group	/sap/price-list-group/	/sap/price-list-group/{id}/
3.11	Price List	/sap/price-list/	/sap/price-list/{id}/
3.12	Special Price List	/sap/special-price-list/	/sap/special-price-list/{id}/
3.13	Products (Variants)	/sap/products/	/sap/products/{id}/
3.14	Delivery Order	/sap/delivery-order/	/sap/delivery-order/{id}/
3.15	Balance Status Update	—	/sap/balance-status-update/
3.16	Order Status Sync	—	/sap/order-status-sync/

3.1 Business Partner (BP) Master

Creates or updates a single Business Partner record from SAP. If customer_code already exists in SalesPort, the record is updated; otherwise a new record is created.

Endpoints

Method	Endpoint	Description
POST	/sap/bp-master/	Create new Business Partner (BP) Master
PUT	/sap/bp-master/{id}/	Update Business Partner (BP) Master by ID

Business Rules & Validation

- customer_code is the unique identifier – only one record per customer_code.
- email_id and contact_number must be unique across all BPs.
- contact_country_code must be in valid international format (e.g., +977, +91).
- Status supports Y/N or 1/0 values.
- Only single record payloads are allowed (bulk disabled).
- cost_center_master is optional; accepts alphanumeric + space + dot; normalized to uppercase.

Request Schema

Field	Type	Required	Description
customer_code	string	Yes	Unique SAP customer/dealer code
store_name	string	Yes	Business/store display name
first_name	string	Yes	Contact first name
middle_name	string	No	Contact middle name
last_name	string	Yes	Contact last name
contact_number	string	Yes	Primary phone number (unique)
email_id	string	No	Email address (unique, nullable)
date_of_birth	string	No	Date of birth (YYYY-MM-DD)
organization_name	string	No	Parent organization
department_name	string	No	Department name
role_name	string	No	Assigned role / designation
reporting_to_emp	string	No	SAP ID of the reporting employee
cost_center_master	string	No	Cost center code (alphanumeric, optional)
status	string	Yes	Active status: Y/N or 1/0
payment_term_name	string	No	Payment terms reference

			name
rate_group_name	string	No	Pricing / rate group name
bill_to_address_line_1	string	Yes	Billing address
bill_to_country_name	string	Yes	Billing country
ship_to_address_line_1	string	Yes	Shipping address
ship_to_country_name	string	Yes	Shipping country
contact_country_code	string	Yes	International dialing code (e.g. +977)
greater_circle_name	string	No	Zone / region name (must exist)
circle_name	string	No	Town / area name (must exist)
vat_number	string(15)	Yes	VAT registration number
pan_number	string(15)	Yes	PAN / tax ID number
date_of_joining	string	Yes	Date of onboarding (YYYY-MM-DD)
bank_guarantee_amount	string	No	Bank guarantee value
bank_guarantee_expiry	string	No	BG expiry date (YYYY-MM-DD)

Sample Request Payload (POST)

```
{
  "store_name": "Param Dairy Store",
  "first_name": "Ram",
  "middle_name": "Kumar",
  "last_name": "Sharma",
  "contact_country_code": "+977",
  "contact_number": "9800000000",
  "email_id": "",
  "date_of_birth": "1995-06-15",
  "bill_to_address_line_1": "Kathmandu Main Road",
  "bill_to_country_name": "Nepal",
  "ship_to_address_line_1": "Warehouse Area",
  "ship_to_country_name": "Nepal",
  "role_name": "Dealer Incharger",
  "vat_number": "123456789",
  "pan_number": "123456789",
  "customer_code": "CUST1013",
  "date_of_joining": "2026-01-15",
  "bank_guarantee_amount": "100000",
  "reporting_to_emp": "EMP001",
  "bank_guarantee_expiry": "2026-06-15",
  "greater_circle_name": "Zone A",
  "circle_name": "Town X",
  "payment_terms": "Net 30",
  "rate_group": "Standard",
  "status": "Y",
  "cost_center_master": "CC.100"
```

```
}
```

Responses

Code	Description
201	BP Master created successfully
200	Record updated successfully
400	Validation error – see response body
401	Unauthorized – invalid or missing credentials

3.2 Blanket Agreement

Creates a new Blanket Agreement with line items. Blanket Agreements define quantity or financial commitments between the organization and a Business Partner over a defined period.

Endpoints

Method	Endpoint	Description
POST	/sap/blanket-agreement/	Create new Blanket Agreement
PUT	/sap/blanket-agreement/{id}/	Update Blanket Agreement by ID

Business Rules & Validation

- bp_code is unique – only one agreement per business partner.
- agreement_method accepts: qty (Quantitative) or financial.
- Quantitative – General: requires line_number, item_code, item_name, planned_quantity, portion_of_returns.
- Quantitative – Specific: all general fields plus unit_price.
- Financial: requires line_number, planned_amount, portion_of_returns.
- start_date cannot be greater than end_date.
- Duplicate line_number values in the same agreement are rejected.
- Status supports A/T (Approved/Terminated).

Request Schema

Field	Type	Required	Description
id	integer	Yes	Auto-generated primary key
bp_code	string(20)	Yes	Business partner customer code
bp_name	string(255)	Yes	Business partner name
agreement_method	object	Yes	Method: qty (Quantitative) or financial
agreement_type	string	No	Type: general or specific
scheme_name	string(255)	No	Scheme / agreement name
status	string(20)	Yes	Active status: Y/N or 1/0
start_date	string	Yes	Agreement start date (YYYY-MM-DD)
end_date	string	Yes	Agreement end date (YYYY-MM-DD)
blanket_agreement_lines	array	Yes	Array of line items

Sample Request Payload (POST)

```
{
  "bp_code": "CUST1001",
  "agreement_method": "qty",
  "agreement_type": "general",
```



```
"start_date": "2026-01-01",
"end_date": "2026-12-31",
"status": "A",
"lines": [
  {
    "line_number": 1,
    "item_code": "FR0001",
    "item_name": "Fresh Milk 500ml",
    "planned_quantity": "1000",
    "portion_of_returns": "5"
  }
]
```

Responses

Code	Description
201	Blanket Agreement created successfully
200	Record updated successfully
400	Validation error – see response body
401	Unauthorized – invalid or missing credentials

3.3 Greater Circles

Manages zone-level geographic groupings for territory management.

Endpoints

Method	Endpoint	Description
POST	/sap/greater-circles/	Create new Greater Circles
PUT	/sap/greater-circles/{id}/	Update Greater Circles by ID

Business Rules & Validation

- name must be unique (case-insensitive).
- Purely numeric names are rejected.
- Status supports Y/N or 1/0.

Request Schema

Field	Type	Required	Description
id	integer	Yes	Auto-generated primary key
greater_circle	string(50)	Yes	Zone / region name (unique)
status	string(1)	Yes	Active status: Y/N or 1/0

Sample Request Payload (POST)

```
{
  "name": "Zone A",
  "status": "Y"
}
```

Responses

Code	Description
201	Created
200	Updated
400	Validation error
401	Unauthorized

3.4 Circles

Manages town/area-level geographic groupings within a Greater Circle.

Endpoints

Method	Endpoint	Description
POST	/sap/circles/	Create new Circles
PUT	/sap/circles/{id}/	Update Circles by ID

Business Rules & Validation

- name must be unique (case-insensitive).
- greater_circle_name must exist.
- Status supports Y/N or 1/0.

Request Schema

Field	Type	Required	Description
id	integer	Yes	Auto-generated primary key
circle	string(50)	Yes	Town / area name (unique)
status	string(1)	Yes	Active status: Y/N or 1/0

Sample Request Payload (POST)

```
{
  "name": "Town X",
  "greater_circle_name": "Zone A",
  "status": "Y"
}
```

Responses

Code	Description
201	Created
200	Updated
400	Validation error
401	Unauthorized

3.5 Container

Manages container (packaging) master data.

Endpoints

Method	Endpoint	Description
POST	/sap/container/	Create new Container
PUT	/sap/container/{id}/	Update Container by ID

Business Rules & Validation

- name must be unique (case-insensitive).
- Purely numeric names are rejected.
- Status supports Y/N or 1/0.

Request Schema

Field	Type	Required	Description
container	string(50)	Yes	Container / packaging name (unique)
status	string(1)	Yes	Active status: Y/N or 1/0

Sample Request Payload (POST)

```
{
  "name": "CRATE",
  "status": "Y"
}
```

Responses

Code	Description
201	Created
200	Updated
400	Validation error
401	Unauthorized

3.6 Matrix

Manages custom grouping/attribute master for reporting and assignment.

Endpoints

Method	Endpoint	Description
POST	/sap/matrix/	Create new Matrix
PUT	/sap/matrix/{id}/	Update Matrix by ID

Business Rules & Validation

- name must be unique (case-insensitive).
- Status supports Y/N or 1/0.

Request Schema

Field	Type	Required	Description
id	integer	Yes	Auto-generated primary key
sujal_matrix_name	string(50)	Yes	Matrix grouping name (unique)
status	string(1)	Yes	Active status: Y/N or 1/0

Sample Request Payload (POST)

```
{
  "name": "Matrix Group 1",
  "status": "Y"
}
```

Responses

Code	Description
201	Created
200	Updated
400	Validation error
401	Unauthorized

3.7 Product Class

Manages product category classifications with measurement units.

Endpoints

Method	Endpoint	Description
POST	/sap/product-class/	Create new Product Class
PUT	/sap/product-class/{id}/	Update Product Class by ID

Business Rules & Validation

- name must be unique (case-insensitive).
- unit accepts: Kg, Ltr, Pcs, etc.
- Status supports Y/N or 1/0.

Request Schema

Field	Type	Required	Description
product_class	string(50)	Yes	Product category name (unique)
unit	string(50)	Yes	Measurement unit (Kg, Ltr, Pcs, etc.)
status	string(1)	Yes	Active status: Y/N or 1/0

Sample Request Payload (POST)

```
{
  "name": "Dairy Products",
  "unit": "Ltr",
  "status": "Y"
}
```

Responses

Code	Description
201	Created
200	Updated
400	Validation error
401	Unauthorized

3.8 Product Name

Manages the primary product identifier in the catalog.

Endpoints

Method	Endpoint	Description
POST	/sap/product-name/	Create new Product Name
PUT	/sap/product-name/{id}/	Update Product Name by ID

Business Rules & Validation

- name must be unique (case-insensitive).
- product_class_name must exist.
- Status supports Y/N or 1/0.

Request Schema

Field	Type	Required	Description
product_name	string(50)	Yes	Product catalog name (unique)
status	string(1)	Yes	Active status: Y/N or 1/0

Sample Request Payload (POST)

```
{
  "name": "Fresh Milk",
  "product_class_name": "Dairy Products",
  "status": "Y"
}
```

Responses

Code	Description
201	Created
200	Updated
400	Validation error
401	Unauthorized

3.9 Payment Terms

Manages credit policies and payment due-date calculations.

Endpoints

Method	Endpoint	Description
POST	/sap/payment-terms/	Create new Payment Terms
PUT	/sap/payment-terms/{id}/	Update Payment Terms by ID

Business Rules & Validation

- payment_term_name must be unique.
- Status supports Y/N or 1/0.

Request Schema

Field	Type	Required	Description
payment_term_name	string(50)	Yes	Payment terms reference name
term_days	string	No	Number of credit days
status	string(1)	Yes	Active status: Y/N or 1/0

Sample Request Payload (POST)

```
{
  "payment_term_name": "Net 30",
  "status": "Y"
}
```

Responses

Code	Description
201	Created
200	Updated
400	Validation error
401	Unauthorized

3.10 Price List Group

Manages pricing group master records.

Endpoints

Method	Endpoint	Description
POST	/sap/price-list-group/	Create new Price List Group
PUT	/sap/price-list-group/{id}/	Update Price List Group by ID

Business Rules & Validation

- name must be unique.
- Status supports Y/N or 1/0.

Request Schema

Field	Type	Required	Description
rate_group_name	string(50)	Yes	Pricing / rate group name
status	string(1)	Yes	Active status: Y/N or 1/0

Sample Request Payload (POST)

```
{
  "name": "Standard",
  "status": "Y"
}
```

Responses

Code	Description
201	Created
200	Updated
400	Validation error
401	Unauthorized

3.11 Price List

Manages item-level pricing entries mapping rate groups to item codes.

Endpoints

Method	Endpoint	Description
POST	/sap/price-list/	Create new Price List
PUT	/sap/price-list/{id}/	Update Price List by ID

Business Rules & Validation

- rate_group and item_code combination must be unique.
- container_price must be a valid decimal.
- Status supports Y/N or 1/0.

Request Schema

Field	Type	Required	Description
rate_group_name	string(50)	Yes	Pricing / rate group name
item_code	string(20)	Yes	Product variant SKU code (must exist)
container_price	string(20)	Yes	Unit price per container / SKU
status	string(1)	Yes	Active status: Y/N or 1/0

Sample Request Payload (POST)

```
{
  "rate_group": "Standard",
  "item_code": "FR0001",
  "container_price": "1585.54",
  "status": "Y"
}
```

Responses

Code	Description
201	Created
200	Updated
400	Validation error
401	Unauthorized

3.12 Special Price List

Manages party-specific pricing with discounts and validity periods.

Endpoints

Method	Endpoint	Description
POST	/sap/special-price-list/	Create new Special Price List
PUT	/sap/special-price-list/{id}/	Update Special Price List by ID

Business Rules & Validation

- party_code and item_code combination must be unique.
- discount must be between 0 and 100.
- start_date cannot be greater than end_date.
- Status supports Y/N or 1/0.

Request Schema

Field	Type	Required	Description
rate_group_name	string(50)	Yes	Pricing / rate group name
item_code	string(20)	Yes	Product variant SKU code (must exist)
container_price	string(20)	Yes	Unit price per container / SKU
discount	string(10)	Yes	Discount percentage (0–100)
party_code	string(20)	Yes	Business partner customer code
start_date	string	Yes	Agreement start date (YYYY-MM-DD)
end_date	string	Yes	Agreement end date (YYYY-MM-DD)
status	string(1)	Yes	Active status: Y/N or 1/0

Sample Request Payload (POST)

```
{
  "item_code": "FR0123",
  "container_price": "1585.54",
  "discount": "10",
  "party_code": "CUST1000",
  "start_date": "2022-01-01",
  "end_date": "2022-12-31",
  "status": "Y"
}
```

Responses

Code	Description
201	Created
200	Updated
400	Validation error
401	Unauthorized

3.13 Products (Variants)

Manages SKU-level product variants with tax codes and packaging details.

Endpoints

Method	Endpoint	Description
POST	/sap/products/	Create new Products (Variants)
PUT	/sap/products/{id}/	Update Products (Variants) by ID

Business Rules & Validation

- product_name must reference an existing Product Name.
- variant_code must be unique (case-insensitive).
- sujal_matrix must reference an existing Matrix.
- primary_selling_unit_name and secondary_selling_unit_name must reference existing Containers.
- tax_code must be a non-empty list of {country_name, tax_name, tax_percentage} objects.
- tax_percentage must be between 0 and 100.
- is_packaging_allow supports Y/N or 1/0.
- Only single payload allowed (bulk disabled).
- Status supports Y/N or 1/0.

Request Schema

Field	Type	Required	Description
product_name	string(100)	Yes	Product catalog name (unique)
hsn_code	string(50)	Yes	HSN/SAC code for tax classification
variant_code	string(25)	Yes	Unique SKU / variant identifier
sujal_matrix	string(255)	Yes	Matrix name (must exist in Matrix master)
primary_selling_unit_name	string(100)	Yes	Primary container (e.g. CRATE)
secondary_selling_unit_name	string(100)	Yes	Secondary container (e.g. POUCH)
no_of_secondary_in_primary	integer	Yes	Secondary units per primary unit
uom_type	string(50)	Yes	Unit of measure type
mrp	string	Yes	Maximum retail price
production_unit	integer	Yes	Manufacturing / production unit name
tax_code	array	Yes	Tax entries [{country_name, tax_name, tax_percentage}]
is_packaging_allow	string	Yes	Packaging permitted (Y/N or 1/0)

status	string(1)	Yes	Active status: Y/N or 1/0
--------	-----------	-----	---------------------------

Sample Request Payload (POST)

```
{
  "product_name": "SAMPLE PRODUCT",
  "hsn_code": "0401",
  "variant_code": "SKU001",
  "sujal_matrix": "Matrix Group 1",
  "primary_selling_unit_name": "CRATE",
  "primary_selling_unit_quantity": 12,
  "secondary_selling_unit_name": "POUCH",
  "secondary_selling_unit_quantity": 1,
  "is_packaging_allow": "Y",
  "status": "Y",
  "tax_code": [
    {
      "country_name": "Nepal",
      "tax_name": "VAT",
      "tax_percentage": "13"
    }
  ]
}
```

Responses

Code	Description
201	Created
200	Updated
400	Validation error
401	Unauthorized

3.14 Delivery Order

Creates or updates a Delivery Order with nested item details from SAP. Delivery Orders represent goods dispatched from warehouse to distributors.

Endpoints

Method	Endpoint	Description
POST	/sap/delivery-order/	Create new Delivery Order
PUT	/sap/delivery-order/{id}/	Update Delivery Order by ID

Business Rules & Validation

- do_entry, do_number, doc_entry, doc_number_so are required identifiers.
- do_amount, do_tax, do_total cannot be negative.
- do_details must contain at least one item detail entry.
- Duplicate item_code values within the same order are rejected.
- item_code in do_details must reference an existing Product Variant.
- rate and amount in do_details cannot be negative.
- quantity must be greater than 0.
- expiry_date cannot be before mfg_date.
- On update (PUT), existing do_details are replaced with the new set.

Request Schema

Field	Type	Required	Description
id	integer	Yes	Auto-generated primary key
invoice_number	string(50)	No	Invoice reference number
do_entry	string(50)	Yes	Delivery Order entry identifier
do_number	string(50)	Yes	Delivery Order number
doc_entry	string(50)	Yes	SAP document entry reference
doc_number_so	string(50)	Yes	SAP Sales Order document number
do_date	string	Yes	Delivery date (YYYY-MM-DD)
do_amount	string	Yes	Delivery order amount (≥ 0)
do_tax	string	Yes	Tax amount (≥ 0)
do_total	string	Yes	Total amount incl. tax (≥ 0)
production_unit	string(100)	Yes	Manufacturing / production unit name
do_details	array	Yes	Array of delivery order line items

Delivery Order Details (Nested Object)

Field	Type	Required	Description
-------	------	----------	-------------

item_code	string(50)	Yes	Product variant SKU code (must exist)
rate	string	Yes	Unit rate (≥ 0)
quantity	string	Yes	Quantity delivered (> 0)
uom	string(20)	Yes	Unit of measure
batch_number	string(100)	No	Batch identifier (nullable)
mfg_date	string	No	Manufacturing date (YYYY-MM-DD, nullable)
expiry_date	string	No	Expiry date (YYYY-MM-DD, nullable)
amount	string	Yes	Line item amount (≥ 0)

Sample Request Payload (POST)

```
{
  "invoice_number": "INV001",
  "do_entry": "DOE001",
  "do_number": "DO-001",
  "doc_entry": "DOC001",
  "doc_number_so": "DOC-SO-001",
  "do_date": "2026-02-20",
  "do_amount": "5000.00",
  "do_tax": "650.00",
  "do_total": "5650.00",
  "production_unit": "Unit A",
  "do_details": [
    {
      "item_code": "SKU001",
      "rate": "100.00",
      "quantity": "50",
      "uom": "PCS",
      "batch_number": "B001",
      "mfg_date": "2026-01-01",
      "expiry_date": "2026-06-01",
      "amount": "5000.00"
    }
  ]
}
```

Responses

Code	Description
201	Delivery Order created successfully
200	Record updated successfully
400	Validation error – see response body
401	Unauthorized – invalid or missing credentials

3.15 Balance Status Update

Updates the outstanding balance amount for a Business Partner in SalesPort using the party_code as the lookup key. SAP triggers this endpoint whenever a distributor's account balance changes.

Endpoints

Method	Endpoint	Description
PUT	/sap/balance-status-update/	Update Balance Status Update

Business Rules & Validation

- party_code must reference an existing Business Partner in SalesPort.
- updated_amount must be a valid decimal number (positive or negative).
- Both fields are required – missing either returns HTTP 400.

Request Schema

Field	Type	Required	Description
party_code	string(50)	Yes	Business partner customer code
updated_amount	number	Yes	New outstanding balance (decimal)

Sample Request Payload (PUT)

```
{
  "party_code": "PARTY001",
  "updated_amount": 1500.5
}
```

Responses

Code	Description
200	Balance updated successfully.
400	Validation error – missing or invalid fields.
401	Unauthorized – invalid or missing credentials.
404	Business Partner (party_code) not found.

3.16 Order Status Sync

Updates the status of a Sales Order in SalesPort using doc_entry and doc_number_so as identifiers. SAP triggers this endpoint when an order is Cancelled, Closed, or re-Opened.

Endpoints

Method	Endpoint	Description
PUT	/sap/order-status-sync/	Update Order Status Sync

Business Rules & Validation

- doc_entry and doc_number_so must reference an existing Sales Order.
- status is required. Supported values: Cancel, Close, Open.
- All three fields are required – missing any returns HTTP 400.

Request Schema

Field	Type	Required	Description
doc_entry	string(50)	Yes	SAP document entry reference
doc_number_so	string(50)	Yes	SAP Sales Order document number
status	string	Yes	Order status. Supported: Cancel, Cancelled, Close, Closed, Open, Pending, Approved

Sample Request Payload (PUT)

```
{
  "doc_entry": "DOC001",
  "doc_number_so": "DOC-SO-001",
  "status": "Cancel"
}
```

Responses

Code	Description
200	Order status updated successfully.
400	Validation error – missing or invalid fields.
401	Unauthorized – invalid or missing credentials.
404	Sales Order not found.

4. Data Conventions & Status Mapping

4.1 Status Field Mapping

All modules support flexible status values. The following mappings are applied:

Input Value	Interpreted As	Description
Y	Active	Record is active
N	Inactive	Record is inactive
1	Active	Numeric equivalent of Y
0	Inactive	Numeric equivalent of N
A / Approved	Active	Blanket Agreement approved
T / Terminated	Inactive	Blanket Agreement terminated

4.2 Date Format

All date fields must follow the ISO 8601 format: YYYY-MM-DD (e.g., 2026-02-13).

4.3 Decimal Fields

Decimal fields (unit_price, planned_quantity, planned_amount, portion_of_returns, container_price, discount, tax_percentage) use dot (.) as the decimal separator.

4.4 Naming Conventions

- Names for Greater Circles, Circles, and Tax Master must contain at least one alphabetic character.
- Purely numeric names are rejected by the validation layer.
- Allowed characters: letters (a–z, A–Z), numbers (0–9), spaces, and underscores.
- Name uniqueness is enforced case-insensitively.

5. Error Handling

5.1 Error Response Format

When a validation error occurs, the API returns HTTP 400 with a JSON response body:

```
{
  "field_name": [
    "Error message describing the validation failure."
  ],
  "another_field": [
    "Another error message."
  ]
}
```

5.2 Common Error Scenarios

Scenario	HTTP Code	Example Error
Missing required field	400	{"customer_code": ["This field is required."]}
Duplicate unique value	400	{"customer_code": ["This value already exists."]}
Invalid email format	400	{"email_id": ["Enter a valid email address."]}
Invalid date format	400	{"date_of_birth": ["Date has wrong format. Use YYYY-MM-DD."]}
Invalid credentials	401	Authentication credentials were not provided.
Resource not found	404	{"detail": "Not found."}

5.3 Retry Strategy

For transient errors (HTTP 500 or network timeouts), SAP should implement an exponential backoff retry strategy with a maximum of 3 retries.

6. Appendix

6.1 Glossary

Term	Definition
SAP B1	SAP Business One – the ERP system acting as the data source
SalesPort (SP)	The sales distribution management platform (target system)
BP	Business Partner – a customer or dealer in the system
Greater Circle	A geographic zone or region for territory management
Circle	A town or sub-region within a Greater Circle
Matrix	A custom grouping attribute used for reporting
Container	A packaging/unit type (Crate, Pouch, Bottle, etc.)
Blanket Agreement	A contractual commitment for quantities or financial targets
Price List	A set of item-level pricing entries
Variant	A specific SKU under a Product Name

6.2 Contact Information

For technical queries, integration support, or credential requests, please contact:

Organization	Sort String Solutions LLP
Email	info@sortstring.com
Subject	SalesPort – SAP B1 Integration Support

— End of Document —