

Wi-Fi

FileEditViewGoCaptureAnalyzeStatisticsTelephonyWirelessToolsHelp

icmp

No.	Time	Source	Destination	Protocol	Length	Info
49730	153.315258	172.18.57.11	224.0.0.1	ICMP	60	Mobile IP Advertisement (Normal router advertisement)
51479	160.483025	172.18.54.196	224.0.0.1	ICMP	60	Mobile IP Advertisement (Normal router advertisement)

> Frame 49730: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface \Device\NPF_{6B3559D3-DF67-4336-A88E-7E1E6E16C2B3}, id 0

> Ethernet II, Src: Netgear_bf:4f:3e (c0:ff:d4:bf:4f:3e), Dst: IPv4mcast_01 (01:00:5e:00:00:01)

> Internet Protocol Version 4, Src: 172.18.57.11, Dst: 224.0.0.1

> Internet Control Message Protocol

- Type: 9 (Mobile IP Advertisement)
- Code: 0 (Normal router advertisement)
- Checksum: 0x09d8 [correct]
- [Checksum Status: Good]
- Number of addresses: 1
- Address entry size: 2
- Lifetime: 1800 (30 minutes)
- Router address: 172.18.57.11
- Preference level: 0

0000010005e00001c0ffd4bf4f3e08004500..^.....0>..E

001000241c3200000101d888ac12390be000-\$.2.....9...

00200001090009d801020708ac12390b0000.....9...

00300000000000000000000000000000.....

wireshark_Wi-Fi_ZA6S1.pcapng

Packets: 53743 · Displayed: 2 (0.0%)

Profile: Default