

BLOWERS FOR INFLATABLES

COMPACT MS BLOWER WITHOUT FLANGE



PLASTIC ENCLOSURE BLOWERS



SKY DANCER BLOWERS



LED ROTATING BLOWERS



BOX BLOWER



Technical Specification\*

| TYPE        | I/P SUPPLY     | AMPS (A) | WATTS (W) | RPM  | AIRFLOW (CMH) | STATIC-PR (mm-wc) | dBA | WEIGHT Kg |
|-------------|----------------|----------|-----------|------|---------------|-------------------|-----|-----------|
| 5EC1BT W/F  | 230V, 1Ø, 50Hz | 0.35     | 60        | 2700 | 275           | 36                | 64  | 2.00      |
| 6EC1BT W/F  | 230V, 1Ø, 50Hz | 0.40     | 120       | 2600 | 400           | 38                | 68  | 3.00      |
| 9EC1BT W/F  | 230V, 1Ø, 50Hz | 0.65     | 160       | 2550 | 450           | 40                | 69  | 4.25      |
| 10EC1BT W/F | 230V, 1Ø, 50Hz | 1.00     | 230       | 2350 | 600           | 55                | 72  | 4.50      |
| SKD 400 S2  | 230V, 1Ø, 50Hz | 3.20     | 1500      | 2880 | 11000         | 55                | 65  | 18.0      |
| LED 450 S2  | 230V, 1Ø, 50Hz | 0.60     | 150       | 2800 | 400           | 28                | 60  | 10.0      |
| SPI 30 S2   | 230V, 1Ø, 50Hz | 1.00     | 250       | 2800 | 240           | 180               | 66  | 2.5       |
| SPI 36 S2   | 230V, 1Ø, 50Hz | 1.20     | 370       | 2800 | 360           | 200               | 69  | 3.5       |
| SPI 43 S2   | 230V, 1Ø, 50Hz | 1.60     | 610       | 2800 | 600           | 210               | 73  | 7.2       |

\*Tolerance ±5% on Specified values