

BACKWARD CURVED RADIAL FANS



Technical Specification*

TYPE	I/P SUPPLY	AMPS (A)	WATTS (W)	RPM	AIRFLOW		STATIC-PR (mm-wc)	dBA	CAP. μf	ADMISSIBLE AMBIENT TEMP	WEIGHT Kg
					(CMH)	(CFM)					
SBC 14 S2	230V, 1Ø, 50Hz	0.08	25	2800	290	171	17	50	1	60	0.9
SBC 14 T2	415V, 3Ø, 50Hz	0.10	35	2800	290	170	17	50	..	60	0.9
SBC 19 S2	230V, 1Ø, 50Hz	0.35	75	2550	570	335	32	62	2	60	1.2
SBC 19 S4	230V, 1Ø, 50Hz	0.21	28	1340	300	176	12	54	2	60	1.2
SBC 19 T2	415V, 3Ø, 50Hz	0.20	80	2550	570	335	32	55	..	60	1.2
SBC 22 S2	230V, 1Ø, 50Hz	0.40	110	2700	885	521	42	72	2	60	2.0
SBC 23 S2	230V, 1Ø, 50Hz	0.55	130	2650	1200	706	55	70	4	60	2.5
SBC 23 T2	415V, 3Ø, 50Hz	0.45	135	2650	1200	706	55	70	..	60	2.5
SBC 23 T2/60Hz	415V, 3Ø, 60Hz	0.42	145	3000	1275	750	60	72	..	60	2.7
SBC 25 S4/35	230V, 1Ø, 50Hz	0.20	100	1400	810	476	18	61	2	60	2.2
SBC 25 S2/35	230V, 1Ø, 50Hz	0.60	140	2650	1230	724	52	73	4	60	2.6
SBC 25 T2/35	415V, 3Ø, 50Hz	0.25	130	2600	1200	705	51	72	..	60	2.6
SBC 25 S2/45	230V, 1Ø, 50Hz	0.70	175	2600	1450	853	57	75	5	60	3.1

*Tolerance ±5% on Specified values