

BLOWERS FOR INFLATABLES

COMPACT MS BLOWER WITHOUT FLANGE



5EC

9EC

PLASTIC ENCLOSURE BLOWERS



SPI 36 S2

SPI 43 S2

SPI 30 S2

SKY DANCER BLOWERS



SKD 400 S2



SKD 400 S2



LED ROTATING BLOWERS




LED 450 S2



LED 450 S2

BOX BLOWER



Technical Specification*

TYPE	I/P SUPPLY	AMPS (A)	WATTS (W)	RPM	AIRFLOW (CMH)	STATIC-PR (mm-wc)	dBA	WEIGHT Kg
5EC1BT W/F	230V, 1Ø, 50Hz	0.35	60	2700	275	36	64	2.00
6EC1BT W/F	230V, 1Ø, 50Hz	0.40	120	2600	400	38	68	3.00
9EC1BT W/F	230V, 1Ø, 50Hz	0.65	160	2550	450	40	69	4.25
10EC1BT W/F	230V, 1Ø, 50Hz	1.00	230	2350	600	55	72	4.50
SKD 400 S2	230V, 1Ø, 50Hz	3.20	1500	2880	11000	55	65	18.0
LED 450 S2	230V, 1Ø, 50Hz	0.60	150	2800	400	28	60	10.0
SPI 30 S2	230V, 1Ø, 50Hz	1.00	250	2800	240	180	66	2.5
SPI 36 S2	230V, 1Ø, 50Hz	1.20	370	2800	360	200	69	3.5
SPI 43 S2	230V, 1Ø, 50Hz	1.60	610	2800	600	210	73	7.2

*Tolerance ±5% on Specified values