

Scenario 2 — Standard Plan (\$22), Mid-Size Claim, Approved

Full mechanics: see Step-1 through Step-5 . Deltas only, below.

Values used

	Value
Policyholder	Bob, 0x1212...bbbb
templateId	2 (Standard)
coverageAmount	5_000 ether
Premium paid	22 ether (\$22)
policyId assigned	2 (Alice already took 1 in the main trace — IDs auto-increment across all subscribers, per InsurancePolicy.nextPolicyId)
Claim amount	150 ether (\$150)
Oracle decision	Approved
Final payout	150 ether to Bob

Walkthrough (deltas)

- **Step 2:** caller is Bob, not Alice — `msg.sender = 0x1212...bbbb` throughout. `_policies[2].holder = 0x1212...bbbb` . This is the concrete case demonstrating InsurancePolicy 's auto-incrementing `nextPolicyId` across *different* subscribers, not just repeated purchases by one person — Bob gets `policyId = 2` regardless of whether Alice's `subscribeToPolicy` call happened moments before or long before his.
- **Step 3:** `holder != claimant` check compares against Bob's address, not Alice's — `_policies[2].holder (0x1212...bbbb) == msg.sender (0x1212...bbbb)` . Coverage check: `0 + 150 ether <= 5_000 ether` — passes.
- **Step 4/5:** mechanically identical, just Bob's address and `150 ether` in place of Alice's and `221 ether` .

What this scenario demonstrates that Scenario 1 and 3 don't

Two independent policyholders' records never interfere with each other — `_policies[1]` (Alice) and `_policies[2]` (Bob) are entirely separate storage entries, and `ClaimRegistry` 's `_consumedCoverage` check for Bob's policy only ever sums claims in *Bob's* `policyClaims[2]` array, never Alice's.