

# **Hive 2.3.7 Installation on** **AWS EC2**

## **Step 1: Login as hduser**

su hduser

## **Step 2: Download the Hive tar.gz file** (<https://hive.apache.org/downloads.html>)

sudo wget <https://mirrors.estointernet.in/apache/hive/hive-2.3.7/apache-hive-2.3.7-bin.tar.gz>

## **Step 3: Extract the .tar.gz file to /usr/local**

sudo tar xvzf apache-hive-2.3.7-bin.tar.gz -C /usr/local

## **Step 4: Configure environment variables in .bashrc file**

**sudo vim ~/.bashrc**

```
export HIVE_HOME=/usr/local/apache-hive-2.3.7-bin
export HIVE_CONF_DIR=/usr/local/apache-hive-2.3.7-bin/conf
export PATH=$HIVE_HOME/bin:$PATH
export CLASSPATH=$CLASSPATH:/usr/local/hadoop/lib/*:.
export CLASSPATH=$CLASSPATH:/usr/local/apache-hive-2.3.7-bin/lib/*:.
```

## **Step 5: Apply the changes to bashrc file.**

**source ~/.bashrc**

## **Step 6: Creating Hive warehouse directory**

Check Hadoop path

echo \$HADOOP\_INSTALL

check hduser user in supergroup or not

start-all.sh

jps

hdfs dfs -ls /

### Step 7: Create Hive directories within HDFS.

The directory **warehouse** is the location to store the table or data related to hive, and the temporary directory **tmp** is the temporary location to store the intermediate result of processing.

```
hdfs dfs -mkdir -p /user/hive/warehouse
```

```
hdfs dfs -mkdir -p /tmp
```

### Step 8: Set read/write permissions for table.

In this command, we are giving write permission to the group:

```
hdfs dfs -chmod g+w /tmp
```

```
hdfs dfs -chmod g+w /user/hive/warehouse
```

check hduser user in supergroup or not

hdfs dfs -ls /

hdfs dfs -ls /user

## Configuring Hive

### Step 9:

To configure Hive with Hadoop, we need to edit the **hive-env.sh** file, which is placed in the **\$HIVE\_HOME/conf** directory.

### Redirect to conf folder

```
cd $HIVE_HOME/conf
```

create hive-env.sh from hive-env.sh. template

```
sudo cp hive-env.sh.template hive-env.sh
```

### Step 10: Edit the hive-env.sh file by appending the following line

```
sudo vim hive-env.sh
```

### appending the following line

```
export HADOOP_INSTALL=/usr/local/hadoop
```

### Step 11: Downloading Apache Derby

Now we need an external database server to configure **Metastore**. We use **Apache Derby** database.

```
cd /tmp
```

```
sudo wget http://archive.apache.org/dist/db/derby/db-derby-10.13.1.1/db-derby-10.13.1.1-bin.tar.gz
```

```
sudo tar xvzf db-derby-10.13.1.1-bin.tar.gz -C /usr/local
```

cd ..

## Step 12: set up the Derby environment by appending the following lines to ~/.bashrc file

**sudo vim ~/.bashrc**

```
export DERBY_HOME=/usr/local/db-derby-10.13.1.1-bin
export PATH=$PATH:$DERBY_HOME/bin
export
CLASSPATH=$CLASSPATH:$DERBY_HOME/lib/derby.jar:$DERBY_HOME/lib/derbytools.jar
```

## Step 12.a: Apply the changes to bashrc file.

**source ~/.bashrc**

## Step 13: To create a directory named data in \$DERBY\_HOME directory to store Metastore data.

**sudo mkdir \$DERBY\_HOME/data**

## Configuring Hive Metastore

Configuring **Metastore** - specifying to Hive where the database is stored.

## Step 14: Edit the hive-site.xml file, which is in the \$HIVE\_HOME/conf directory.

**cd \$HIVE\_HOME/conf**

**sudo cp hive-default.xml.template hive-site.xml**

**sudo vim hive-site.xml**

In **hive-site.xml** check the following supposed to be there in between the <configuration> and </configuration> tags

```
<property>
  <name>javax.jdo.option.ConnectionURL</name>
  <value>jdbc:derby::databaseName=metastore_db;create=true</value>
  <description>
    JDBC connect string for a JDBC metastore.
    To use SSL to encrypt/authenticate the connection, provide database-
specific SSL flag in the connection URL.
    For example, jdbc:postgresql://myhost/db?ssl=true for postgres
database.
  </description>
</property>
```

## Step 15: Set permission to Hive folder

```
cd /usr/local/
```

```
sudo chown -R hduser:hadoop apache-hive-2.3.7-bin
```

## Step 16:Metastore schema initialization

From Hive 2.1, we need to run the **schematool** command below as an initialization step.

```
cd apache-hive-2.3.7-bin/bin
```

```
schematool -dbType derby -initSchema
```

## Step 17:Verifying Hive Installation by running Hive CLI

```
echo $HIVE_HOME
```

```
$HIVE_HOME/bin/hive
```

## If you get Error:

```
cd ..
```

```
cd conf
```

sudo vim hive-site.xml

## Error:

Exception in thread "main" java.lang.RuntimeException: Couldn't create directory \${system:java.io.tmpdir}/\${hive.session.id}\_resources

edit **hive-site.xml**:

```
<property>
  <name>hive.downloaded.resources.dir</name>
  <!--
  <value>${system:java.io.tmpdir}/${hive.session.id}_resources</value>
  -->
  <value>/home/hduser/hive/tmp/${hive.session.id}_resources</value>
  <description>Temporary local directory for added resources in the remote
file system.</description>
</property>
```

## Error:

java.net.URISyntaxException: Relative path in absolute URI:  
\${system:java.io.tmpdir%7D/\${system:user.name%7D

```
<property>
  <name>hive.exec.local.scratchdir</name>
  <!--
  <value>${system:java.io.tmpdir}/${system:user.name}</value>
  -->
  <value>/tmp/mydir</value>
  <description>Local scratch space for Hive jobs</description>
</property>
```