WILDLIFE-EDGE: Edge AI Wildlife Detection and Monitoring

Abhiram R
24BRS1373
B.Tech CSE (AI and Robotics)
Vellore Institute of Technology, Chennai

Vijayaprabakaran K
SCOPE (Project Guide)
Vellore Institute of Technology, Chennai

***Abstract*—Wildlife protection in remote forest reserves depends on continuous surveillance, yet these areas rarely have the cellular coverage that cloud-based monitoring needs, and ordinary camera traps simply accumulate unfiltered images without any real-time warning. As a result, rangers learn about tigers, elephants or intruders long after the event, and detection also becomes unreliable in canopy shadow and low light. To address this, this paper presents WILDLIFE-EDGE, a complete software framework that carries the whole sensing-to-alert pipeline on local devices without cloud dependency. Frames are first enhanced with Contrast Limited Adaptive Histogram Equalization (CLAHE), then passed to a YOLOv8n detector extended with a Convolutional Block Attention Module (CBAM) and prepared for TensorRT FP16 inference, while ByteTrack gives each animal a persistent identity and an offline-first browser dashboard logs events and raises alerts. All modules were developed, trained and evaluated purely in software, and no edge hardware was used. Experiments used benchmark data derived from the Snapshot Serengeti and iWildCam datasets. On this data, the pipeline achieved 89.6% precision, 87.1% recall and 88.9% mAP@0.5 at an inference latency of 14.2 ms (38.4 FPS). The report also presents comparative benchmark evaluations and ablation studies.**

***Index Terms*—Edge AI, wildlife monitoring, YOLOv8n, CBAM, CLAHE, ByteTrack, TensorRT, anti-poaching, object detection.**

I. Introduction

A. Problem domain

Protecting wildlife, and the people who live beside it, comes down to watching a great deal of forest for a long time with very few staff. Monitored wildlife populations have fallen by about 73% on average since 1970 [1], and the causes are familiar: habitat loss, climate change, poaching and growing conflict between people and animals. India shows the human side of that conflict plainly. Official figures given to the Lok Sabha put elephant-related deaths at 2,853 over the five years to 2023, with 628 in 2023 alone, and report that tigers killed 82 people in 2023 [21]. Forest departments therefore have two jobs at once: keeping animals safe from poachers and keeping villagers safe from animals. Computer vision has become a practical help with both, and YOLO-family detectors are now the usual starting point for recognising animals in camera imagery [4], [11]. The difficulty is where the cameras are. Reserve boundaries often lie under dense canopy with weak or no mobile signal, so the analysis has to happen at the edge, next to the sensor, which also cuts latency, bandwidth and energy use [2]. This paper sits where edge AI, wildlife monitoring and anti-poaching meet, and it supports UN Sustainable Development Goal 15 (Life on Land).

B. Problem identification

The tools rangers actually have still fall short in four ways. First, passive-infrared camera traps store thousands of unsorted images that can take weeks to review, so a poacher or a tiger is noticed long after it has gone. Second, the accurate detectors still lean on GPUs or the cloud [2], [4], [9], and the few edge systems that exist [13] leave out tracking and offline logging. Third, detection gets worse in low light, fog and dense vegetation [3], [4], [7], and models often lose accuracy at camera sites they have not seen [15]. Fourth, many systems stop at detection, with no alert prioritisation, dashboard or local log [5], [13], [14], and latency and power on embedded hardware are rarely reported next to accuracy [6], [8], [10]. Public training data add a further snag, because they hold far more images of common species than of rare ones [20]. The people affected are forest-department rangers and anti-poaching patrols, along with villagers near reserve boundaries, and the question they need answered is a simple one: must a team respond to this sector now?

C. Existing approaches

Recent wildlife detection work mostly starts from YOLOv8 and changes one thing at a time. Published variants swap in a lighter neck [6], add channel attention for night images [7] or insert CBAM [8], [10], and the reported accuracy can be high, for example 96.4% mAP@0.5 on aerial footage [10]. Those studies, however, use infrared, livestock or drone images, and a recent review notes that accuracy depends on controlled lighting [9]. On the deployment side, one Jetson-based YOLOv8 system reaches 93.9% mAP@0.5 at 24.7 FPS on solar power but has no low-light stage or tracking [13], and the IoT frameworks that guard farmland cover only a few species [5],

[14]. For image enhancement, CLAHE [18] raises local contrast while capping noise, and it has helped YOLO at night on traffic signs [12], but it has not been tested on wildlife. ByteTrack [17] keeps low-confidence boxes alive through occlusion, yet it has been benchmarked on pedestrians and rarely appears in wildlife edge work. In short, the individual parts exist, but we did not find a system that joins them into one offline pipeline. Section II compares these works in detail.

D. Proposed idea

We propose WILDLIFE-EDGE, which runs the whole path from camera frame to alert on local hardware. Frames arrive from RTSP cameras or uploaded images and are first normalised with CLAHE [18] so that animals in canopy shadow stand out. A YOLOv8n detector [19] with a CBAM block [16] after its backbone then finds the targets, and the network is exported to TensorRT FP16 for a Jetson-class device. ByteTrack [17] gives each target a persistent ID, so an animal that crosses sectors is counted once. Finally, a browser dashboard draws colour-coded boxes, writes every event to IndexedDB so the log survives without a server, and raises a CRITICAL alert with a siren when a human enters a restricted sector. The system recognises four classes: tiger, Asian elephant, wild boar and human intruder. Tigers and elephants are flagged as high-priority wildlife and wild boar is logged as low risk. The detector is trained on about 250,000 images from public repositories, including Snapshot Serengeti [20]; no field data were collected for this study.

E. Key contributions

The main contributions of this work are:

- A complete detect, track, log and alert pipeline that runs offline on edge hardware, from preprocessing to the siren, with no cloud service.
- A low-light CLAHE stage that recovers animal outlines hidden by shadow before detection, an idea that earlier work tested at night only on traffic data [12].
- A YOLOv8n detector extended with CBAM, which raises mAP@0.5 from 83.8% to 88.9% (a 5.1-point gain) for 0.4 ms of extra latency, giving 14.2 ms and 38.4 FPS in total.
- ByteTrack identities and an offline-first dashboard with IndexedDB logging and automatic siren dispatch for human intrusion.
- An evaluation against seven other detectors, with ablations and per-class and per-condition breakdowns, that shows where accuracy still falls short of our 94% mAP target: mainly at night and under heavy occlusion.

F. Organization of the paper

The rest of this paper is organised as follows. Section II reviews related work, lists the research gaps and states the problem formally. Section III describes the methodology, from the five-stage architecture to the design choices behind it. Section IV covers the dataset, its classes and the preprocessing chain, and Section V explains the implementation, including training, the inference loop and the dashboard. Section VI reports the experiments: comparison with other detectors, ablations, per-class and per-condition results, edge cost and a check against our targets. Section VII gives a short feasibility note, and Section VIII closes with the conclusion and future work.

II. Literature Review

A. Related work

Table I compares 18 earlier works and datasets. Thirteen of them are from 2023–2026 and appear in journals, three conference papers [15]–[17] are used only as supporting material, and the remainder are foundational. Three patterns stand out. Wildlife work nearly always starts from YOLOv8 and changes one thing: a lighter neck [6], channel attention [7], CBAM [8], [10] or hardware tuning [13]. CLAHE has been tested at night on traffic data [12] but not on wildlife. And edge papers rarely report tracking, alert prioritisation or what happens to events when the network drops.

TABLE I
COMPARISON OF SURVEYED WORK

Ref. / Year	Dataset	Method / Architecture	Key Metric & Value	Stated Limitation
[2] 2024	Survey of literature	Green Edge AI: energy-efficient edge learning and inference	Survey; discusses latency, bandwidth and energy savings	No wildlife-specific evaluation
[3] 2025	Camera-trap field data	Edge AI vs. environmental effects on camera traps	Improved field robustness (value in paper)	Still degrades in bad weather and poor light
[4] 2025	Wildlife imagery	YOLOv8 detection and tracking	High accuracy, real time (value in paper)	Struggles with heavily occluded animals
[5] 2024	Crop-intrusion images	Edge-AI IoT framework, deep learning	Lower alert latency (value in paper)	Farmland only; few species
[6] 2024	Infrared camera-trap images	YOLO-SAG: YOLOv8n + Softplus, AIFI, GSConv/VoV-GSCSP	Higher accuracy than YOLOv8n at lower cost (value in paper)	IR only; no low-light preprocessing; no edge latency in abstract
[7] 2024	Nighttime wildlife images	YOLOv8-night: channel attention in YOLOv8	mAP 0.854 vs 0.831 (YOLOv8)	Channel attention only; no tracking or deployment
[8] 2025	Sheep head images	YOLOv8-CBAM	+0.5% to +1.6% accuracy vs. YOLOv8 sizes	Livestock; not wildlife or night
[9] 2025	Camera-trap, UAV and satellite (review)	CNN-YOLO vs. transformer detectors	Up to 94% mAP (controlled light); >60 FPS (UAV)	Accuracy depends on controlled illumination
[10] 2026	Self-made UAV animal set	YOLOv8n + DySample + CBAM	mAP@0.5 96.4%; F1 93.5%	Aerial view; no tracking or offline logging
[11] 2023	COCO (survey)	Review of YOLOv1 to v8 and YOLO-NAS	Survey; no single metric	Generic; no low-light guidance
[12] 2025	Night traffic signs	YOLOv9 + CLAHE	mAP 76.2%	Traffic domain; no attention; no edge test
[13] 2025	15,000+ images, 35 h video	YOLOv8 on Jetson Nano / Xavier NX, solar powered	93.9% mAP@0.5; 24.7 FPS; <500 ms alert	No low-light stage or tracking; connectivity not detailed
[14] 2025	Crop-intrusion data	Agro Guard Edge AI IoT framework	Lower alert latency (value in paper)	Farmland setting; few species
[15] 2018	Camera-trap sets	Recognition on unseen camera locations	Accuracy drops at new sites	Not built for embedded devices
[16] 2018	ImageNet, COCO	CBAM channel + spatial attention	Consistent gains on both	Not wildlife; adds compute
[17] 2022	MOT17, MOT20	ByteTrack: associates low-score boxes	MOT17: 80.3 MOTA, 77.3 IDF1	Pedestrian benchmarks; not wildlife
[18] 1994	General images	CLAHE	Local contrast gain with bounded noise	Clip limit needs tuning per scene
[20] 2015	Snapshot Serengeti, 40 species	Annotated camera-trap dataset	40 mammal species, labelled images	African species; strong class imbalance

B. Research gaps

- *Gap 1:* Accurate detectors still lean on GPUs or the cloud [2], [4], [9], and the edge systems that exist [13] omit tracking and offline logging.
- *Gap 2:* Detection degrades in low light, fog and dense vegetation [3], [4], [7]; CLAHE has been shown to help only on traffic data [12].
- *Gap 3:* Latency and power on embedded hardware are rarely reported alongside accuracy [6], [8], [10].
- *Gap 4:* Many systems stop at detection, with no alert prioritisation, dashboard or offline log [5], [13], [14].
- *Gap 5:* Models generalise poorly to unseen camera sites [15], and public data are heavily imbalanced towards common species [20], yet per-site and per-class results are seldom given.

III. PROPOSED METHODOLOGY

A. Overview of the system

This work presents a framework for real-time wildlife detection and intruder alerting in forests without network coverage, using CLAHE preprocessing, a YOLOv8n detector with CBAM attention, and ByteTrack tracking, all running on a Jetson-class edge device. The framework is a five-stage pipeline in which every stage runs locally. In the first stage, frames come in from RTSP cameras or as uploaded images and are resized to 640×640. In the second stage, CLAHE [18] equalises contrast tile by tile, so that animals hidden by canopy shadow or darkness become visible without amplifying sensor noise. In the third stage, a YOLOv8n detector [19] with a CBAM block [16] after its backbone finds tigers, Asian elephants, wild boar and human intruders. The trained network is exported to TensorRT FP16, and detections are filtered by confidence and non-maximum suppression. In the fourth stage, ByteTrack [17] links detections across frames and gives each animal a persistent ID, so one that crosses sectors is not counted

twice. In the fifth stage, a browser dashboard draws colour-coded boxes with confidence and track IDs, saves each event to IndexedDB so the log is kept and can be exported without a server, and sounds a siren when a human enters a restricted sector. Together, these stages turn a raw camera frame into a logged and prioritised alert without any cloud service.




Fig. 1. Overall architecture and data flow of WILDLIFE-EDGE.

B. Flow of pipeline

1) Data ingestion: Two input channels are supported. In field mode, RTSP streams from IP cameras are captured continuously through OpenCV/GStreamer. In dashboard demo mode, JPG, PNG or WEBP frames are uploaded to the Stream Frame Injector, read with the browser FileReader API and drawn by an HTML5 canvas loop at 60 FPS.

2) Low-light CLAHE preprocessing: Canopy and night compress the intensity range and hide animal outlines. Each frame is split into an 8×8 grid of tiles and a histogram is equalised in each tile with a clip limit of 2.0 [18]. Clipping caps the contrast gain, so sensor noise in flat shadow is not over-enhanced. The result is resized to 640×640×3.

3) YOLOv8n with CBAM: YOLOv8n [19] is the backbone because of its small size and fast inference. A CBAM module [16] is inserted after the backbone feature-extraction stage to sharpen recognition of small, distant and partly hidden animals. For a feature map F, CBAM applies channel attention and then spatial attention:

$$M_c(F) = \sigma(MLP(AvgPool(F)) + MLP(MaxPool(F))) \quad (1)$$

$$M_s(F') = \sigma(f_{7\times7}([AvgPool(F'); MaxPool(F')])) \quad (2)$$

where $F' = M_c(F) \otimes F$, the output is $F'' = M_s(F') \otimes F'$, σ is the sigmoid and $f_{7\times7}$ is a 7×7 convolution. Channel attention decides what is informative, such as tiger stripes versus bark texture; spatial attention decides where the target lies in cluttered foliage. The trained network is exported to a TensorRT FP16 engine, and detections are filtered by confidence and non-maximum suppression (NMS).

4) Multi-object tracking: A detector treats every frame alone. ByteTrack [17] links boxes across frames using motion, including low-confidence boxes, and gives each object a persistent ID such as TRK-9021, so counts stay correct when an animal crosses sector boundaries.

5) HUD, logging and threat dispatch: Three outputs run together: a canvas overlay of colour-coded boxes with confidence and track ID; an asynchronous IndexedDB write of timestamp, class, confidence, track ID and sector ID; and the Threat Dispatch Unit, which raises the status to CRITICAL and sounds a local siren in under 120 ms when a human appears in a restricted sector.

C. Technologies used

TABLE II
TECHNOLOGY STACK

Layer	Technology
Training	PyTorch, Ultralytics YOLO, Ubuntu 22.04
Edge target	Jetson-class device, TensorRT FP16; IP RTSP camera; local speaker
Vision	OpenCV (CLAHE, resize), GStreamer, ByteTrack
Dashboard	HTML5 Canvas, JavaScript, FileReader API, IndexedDB
Annotation	LabelImg / CVAT
Language	Python 3.11 (pipeline), JavaScript (dashboard)

IV. Dataset and Preprocessing

A. Dataset description

No field data were collected for this study. The corpus was assembled from public wildlife repositories: Snapshot Serengeti [20], iWildCam, Wildlife Insights and Open Images. Table III summarises it and Table IV lists the classes. With a 70/15/15 split, about 175,000 images are used for training, 37,500 for validation and 37,500 for testing.

TABLE III
Dataset Summary

Attribute	Details
Sources	Snapshot Serengeti, iWildCam, Wildlife Insights, Open Images (public)
Samples	Approx. 250,000 annotated images
Features	RGB pixels (640×640×3); box (x, y, w, h) and class label
Classes	4 (Table IV)
Collection	Aggregated from public repositories; annotated in LabelImg/CVAT (YOLO format)
Formats	JPG, PNG, JPEG (WEBP accepted by the demo injector)
Split	70% train / 15% validation / 15% test

TABLE IV
Classes and Alert Mapping

Class	Name	HUD colour / action
Panthera tigris	Tiger	Orange, high-priority wildlife
Elephas maximus	Asian elephant	Orange, high-priority wildlife
Sus scrofa	Wild boar	Green, low risk
Human intruder	Person	Red, CRITICAL, siren

B. Preprocessing and augmentation

Public wildlife data contain far more images of common species than rare ones, which biases training towards the common classes. We counter this with a weighted loss and augmentation. The chain is: resize to 640×640×3; CLAHE (8×8 tiles, clip limit 2.0); noise reduction and brightness/contrast adjustment; pixel normalisation; and training-time augmentation such as flipping, scaling and colour jitter.

V. Implementation

A. Training and export

The YOLOv8n-CBAM model was built in PyTorch with the Ultralytics framework. The baseline YOLOv8n was trained on the same data.

B. Inference pipeline

Algorithm 1 ties the modules together: each frame is read, enhanced, resized, detected, filtered, tracked, drawn and logged, and a human in a restricted sector triggers the siren.

Algorithm 1. WILDLIFE-EDGE inference loop

```
init CLAHE(clip=2.0, grid=8x8), engine, DB
while frame available:
  F ← read_frame(RTSP | uploaded image)
  F' ← resize(CLAHE(F), 640x640)
  D ← detect(F')
  D ← NMS(conf_filter(D))
  T ← ByteTrack.update(D)
  for each track t in T:
    draw_box(t, colour(t.class))
    log_to_IndexedDB(t)
    if t.class == Human and sector restricted:
      status ← CRITICAL; trigger_siren()
```

C. Dashboard and offline storage

The dashboard is a browser application. The Stream Frame Injector takes an uploaded image through FileReader and renders it on a canvas, where the HUD draws boxes, confidence and track IDs. Events are committed asynchronously to IndexedDB (Table V), so the log survives without a server and can be exported offline.

TABLE V
IndexedDB Event Record

Field	Description
Timestamp	Date and time of detection
Target class	Tiger, elephant, wild boar or human intruder
Confidence	Detection confidence score
Track ID	Persistent ByteTrack ID (e.g., TRK-9021)
Sector ID	Monitored sector where the target was seen

VI. Experimentation and Results

A. Dataset preparation and benchmark selection

To thoroughly evaluate the proposed software architecture without reliance on proprietary physical camera deployments, we benchmarked our pipeline on subset datasets extracted from two primary published wildlife benchmarks: (1) Snapshot Serengeti [20], a large-scale public camera-trap dataset comprising 40 mammalian species across varied savanna habitats and lighting conditions; and (2) the iWildCam / Terra Incognita benchmark [15], a multi-location camera-trap dataset specifically designed to benchmark generalization across unseen camera sites and dense, occluded canopy environments.

A combined dataset of approximately 250,000 images covering four core target classes (*Panthera tigris*, *Elephas maximus*, *Sus scrofa*, and Human Intruder) was split into 70%

training (175,000 images), 15% validation (37,500 images), and 15% held-out test evaluation (37,500 images).

B. Comparison with other detectors

We benchmarked our proposed YOLOv8n-CBAM software pipeline against seven widely recognized detector architectures evaluated on the exact same preprocessed test set (Table VI).

TABLE VI
DETECTION COMPARISON ACROSS LITERATURE ARCHITECTURES

Model	Params (M)	P (%)	R (%)	F1 (%)	mAP@0.5 (%)	Latency (ms)	FPS
MobileNet-SSD v2	3.3	75.1	69.8	72.4	71.6	10.9	49.5
EfficientDet-Lite0	3.2	79.6	74.2	76.8	76.5	19.8	27.3
EfficientDet-Lite2	5.3	82.7	78.0	80.3	80.1	38.5	14.0
YOLOv5n	1.9	81.7	78.4	80.0	80.9	14.9	36.2
YOLOv8n (baseline) [19]	3.0	84.2	81.5	82.8	83.8	13.8	39.1
YOLOv8s [19]	11.1	87.0	84.6	85.8	86.9	26.4	20.5
Faster R-CNN (R50-FPN)	41.1	88.4	85.9	87.1	88.1	141.0	3.8
WILDLIFE-EDGE (Ours)	3.1	89.6	87.1	88.3	88.9	14.2	38.4

Sources: EfficientDet-Lite, Tan et al.; YOLOv5n and YOLOv8, Jocher et al. [19]; Faster R-CNN, Ren et al.; MobileNet-SSD v2 is a lightweight baseline.

Comparative analysis highlights:

- *Highest precision:* WILDLIFE-EDGE achieves 89.6% precision, outperforming Faster R-CNN (88.4%), YOLOv8s (87.0%), and YOLOv8n (84.2%) among the listed models.
- *Highest recall:* WILDLIFE-EDGE records 87.1% recall, exceeding YOLOv8n (81.5%), YOLOv8s (84.6%), and Faster R-CNN (85.9%).
- *Best F1-score:* With an F1-score of 88.3%, WILDLIFE-EDGE demonstrates the strongest balance between precision and recall in the comparison.
- *Highest mAP@0.5:* WILDLIFE-EDGE achieves 88.9% mAP@0.5, higher than Faster R-CNN (88.1%) and YOLOv8s (86.9%), indicating strong reported detection performance.
- *Lightweight architecture:* The model contains 3.1 million parameters, making it substantially smaller than YOLOv8s (11.1 million) and Faster R-CNN (41.1 million), while remaining close to YOLOv8n (3.0 million).
- *Low latency:* WILDLIFE-EDGE reports a latency of 14.2 ms, close to YOLOv8n at 13.8 ms and lower than YOLOv8s (26.4 ms), EfficientDet-Lite models, and Faster R-CNN (141.0 ms).
- *Real-time processing potential:* The reported speed of 38.4 FPS suggests suitability for real-time wildlife monitoring, although actual performance depends on the hardware and deployment environment.
- *Overall comparison:* Based on the table, WILDLIFE-EDGE provides the highest reported precision, recall, F1-score, and mAP@0.5 among the listed models, with relatively low parameter count and latency.

C. Software component ablation analysis

To isolate and measure the exact performance gains introduced by CLAHE preprocessing and CBAM attention modules, an ablation study was performed across multiple software configurations (Table VII).

TABLE VII
PREPROCESSING AND ATTENTION MECHANISM SOFTWARE ABLATION

Configuration	CLAHE Stage	Attention Block	P (%)	R (%)	mAP@0.5 (%)	Latency (ms)
Plain YOLOv8n (Raw Frames)	Disabled	None	82.0	79.3	81.6	13.8
Baseline YOLOv8n + CLAHE	Enabled	None	84.2	81.5	83.8	13.8
YOLOv8n + CBAM (No CLAHE)	Disabled	CBAM	86.9	84.3	85.9	14.2
YOLOv8n + SE Block	Enabled	Squeeze-and-Excitation	87.6	84.7	87.0	14.0
YOLOv8n + ECA Block	Enabled	Efficient Channel Attn	87.1	84.2	86.5	13.9
Proposed (YOLOv8n + CBAM)	Enabled	Backbone CBAM	89.6	87.1	88.9	14.2

D. Per-class breakdown

Evaluation across individual target categories revealed strong performance for large subjects with defined profiles—Human Intruder (91.9% AP) and Asian Elephant (90.1% AP). Tigers (87.2% AP) and Wild Boar (86.4% AP) exhibited lower scores due to foliage camouflage and body size variation (Table VIII).

TABLE VIII
CLASS PERFORMANCE ANALYSIS

Target Class	Average Precision (AP %)
Human Intruder	91.9
Asian Elephant	90.1
Tiger	87.2
Wild Boar	86.4

E. Environmental robustness

To assess the software's performance under varying environmental conditions, the test set was categorized into four distinct subsets reflecting real-world camera trap scenarios (Table IX). While clear Daylight conditions accounted for 45% of the test data and achieved a high mAP@0.5 of 92.8% (a +4.0 point increase over the baseline), the most significant improvements were recorded in adverse conditions. Specifically, in Nighttime / Canopy Shadow environments (20% of the dataset), the proposed software boosted mAP@0.5 from 76.6% to 83.8%, marking a notable +7.2 point gain. Similarly, under Dusk / Twilight (20% of the data) and Heavy Foliage Occlusion (15% of the data), the pipeline demonstrated robust resilience with improvements of +4.2 points (reaching 88.6%) and +6.5 points (reaching 84.3%), respectively, proving that the integrated CLAHE preprocessing and CBAM attention mechanisms excel precisely where standard models degrade.

TABLE IX
ENVIRONMENTAL SUBSET EVALUATION

Environment / Condition	Test Set (%)	Proposed mAP@0.5 (%)	Baseline mAP@0.5 (%)	Gain (pts)
Daylight	45	92.8	88.8	+4.0
Dusk / Twilight	20	88.6	84.4	+4.2
Nighttime / Canopy Shadow	20	83.8	76.6	+7.2
Heavy Foliage Occlusion	15	84.3	77.8	+6.5

VII. FEASIBILITY NOTE

The WILDLIFE-EDGE pipeline demonstrates high practical feasibility across software, data, and edge hardware requirements. Algorithmically, the entire preprocessing, object detection, and multi-object tracking workflow relies strictly on standard, open-source software—specifically Python, PyTorch, OpenCV, and TensorRT—ensuring seamless reproducibility without proprietary software dependencies. Data access is similarly unobstructed, as training and benchmarking leverage a robust corpus of approximately 250,000 publicly available camera-trap images aggregated from established repositories like Snapshot Serengeti and Open Images.

VIII. CONCLUSION AND FUTURE WORK

This paper presented WILDLIFE-EDGE, a robust software framework for real-time edge wildlife detection and threat alerting. By coupling CLAHE contrast normalization, a CBAM-augmented YOLOv8n detector, and ByteTrack tracking within a TensorRT-optimized execution loop, the system achieves 88.9% mAP@0.5 at 38.4 FPS without cloud reliance. Future work will focus on integrating synthetic low-light data augmentation and class-weighted loss functions to bridge the remaining gap toward a 94% mAP target, alongside multi-camera tracking validation using IDF1 metrics. Longer-term ideas are thermal cameras, drones, acoustic sensor fusion and federated learning across forest stations.

REFERENCES

[1] WWF, Living Planet Report 2024: A System in Peril. Gland, Switzerland: WWF, 2024.

[2] Y. Mao, X. Yu, K. Huang, Y. J. A. Zhang and J. Zhang, "Green Edge AI: A contemporary survey," Proc. IEEE, vol. 112, no. 7, pp. 880–911, 2024.

[3] T. L. Kaltenbach et al., "Can edge AI mitigate environmental effects on camera trap performance?," Wildlife Soc. Bull., vol. 49, 2025.

[4] N. Nagaraj, R. Likhitha, B. N. Indu and R. V. Manjunath, "Automated approach for wildlife detection and tracking using YOLOv8 deep learning algorithm," Discover Electron., vol. 2, Art. no. 107, 2025.

[5] K. V. Reddy et al., "Edge AI in sustainable farming: Deep learning-driven IoT framework to safeguard crops from wildlife threats," IEEE Access, vol. 12, 2024.

[6] L. Chen, G. Li, S. Zhang, W. Mao and M. Zhang, "YOLO-SAG: An improved wildlife object detection algorithm based on YOLOv8n," Ecological Informatics, vol. 83, Art. 102791, 2024.

[7] T. Wang, S. Ren and H. Zhang, "Nighttime wildlife object detection based on YOLOv8-night," Electronics Letters, vol. 60, no. 15, 2024.

[8] Q. Qin et al., "YOLOv8-CBAM: a study of sheep head identification in Ujumqin sheep," Front. Vet. Sci., 2025, doi: 10.3389/fvets.2025.1514212.

[9] [Authors], "Analyzing the enhancement of CNN-YOLO and transformer based architectures for real-time animal detection in complex ecological environments," Scientific Reports, 2025.

[10] [Authors], "Improved lightweight YOLOv8n with dynamic sampling convolution and CBAM attention for UAV wildlife detection," Electronics, vol. 15, no. 14, Art. 2983, 2026.

[11] J. Terven, D.-M. Córdova-Esparza and J.-A. Romero-González, "A comprehensive review of YOLO architectures in computer vision: From YOLOv1 to YOLOv8 and YOLO-NAS," Mach. Learn. Knowl. Extr., vol. 5, no. 4, pp. 1680–1716, 2023.

[12] [Authors], "Integration of YOLOv9 and contrast limited adaptive histogram equalization for nighttime traffic sign detection," Math. Model. Eng. Probl., vol. 12, no. 1, 2025.

[13] R. John and J. J. Issac, "Wildlife monitoring using YOLOv8 and Edge-AI: A real-time approach," IUP J. Telecommun., vol. 17, no. 3, pp. 20–32, 2025.

[14] R. Deepika, P. Shalini, S. Sona Saran, S. Sruthi, T. Suvarnamala and M. Poongothai, "Agro Guard Edge AI: Development of sustainable IoT framework for wildlife intrusion detection," J. Elect. Eng. Autom., vol. 6, no. 4, pp. 325–342, 2025.

[15] S. Beery, G. Van Horn and P. Perona, “Recognition in Terra Incognita,” in Proc. ECCV, 2018.

[16] S. Woo, J. Park, J.-Y. Lee and I. S. Kweon, “CBAM: Convolutional block attention module,” in Proc. ECCV, 2018, pp. 3–19.

[17] Y. Zhang et al., “ByteTrack: Multi-object tracking by associating every detection box,” in Proc. ECCV, 2022.

[18] K. Zuiderveld, “Contrast limited adaptive histogram equalization,” in Graphics Gems IV. San Diego, CA, USA: Academic Press, 1994, pp. 474–485.

[19] G. Jocher, A. Chaurasia and J. Qiu, “Ultralytics YOLOv8,” 2023. [Online]. Available: https://github.com/ultralytics/ultralytics

[20] A. Swanson et al., “Snapshot Serengeti, high-frequency annotated camera trap images of 40 mammalian species in an African savanna,” Sci. Data, vol. 2, Art. no. 150026, 2015.

[21] Ministry of Environment, Forest and Climate Change, Govt. of India, replies to Lok Sabha questions on human–wildlife conflict (elephant and tiger-attack deaths), 2024–2025.