

alert_actions.conf	Create an alert.
app.conf	Configure app properties
audit.conf	Configure auditing and event hashing. This feature is not available for this release.
authentication.conf	Toggle between Splunk's built-in authentication or LDAP, and <a href="#">configure LDAP</a> .
authorize.conf	Configure roles, including <a href="#">granular access controls</a> .
bookmarks.conf	<a href="#">Bookmark monitoring console URLs</a> .
checklist.conf	<a href="#">Customize monitoring console health check</a> .
collections.conf	Configure KV Store collections for apps.
commands.conf	Connect search commands to any custom search script] using in the <a href="#">Developer Guide</a> on the <a href="#">Developer Portal</a> .
datamodels.conf	<a href="#">Attribute/value pairs for configuring data models</a> .
default.meta	<a href="#">Set permissions for objects in a Splunk app</a> .
deploymentclient.conf	<a href="#">Specify behavior for clients of the deployment server</a> .

<a href="#">distsearch.conf</a>	Specify behavior for distributed search.
<a href="#">event_renderers.conf</a>	Configure event-rendering properties.
<a href="#">eventtypes.conf</a>	Create event type definitions.
<a href="#">fields.conf</a>	Create <a href="#">multivalue fields</a> and add search capability for indexed fields.
<a href="#">global-banner.conf</a>	Display a <a href="#">global banner</a> on all pages in Splunk Web.
<a href="#">health.conf</a>	Set the default thresholds for <a href="#">proactive Splunk component monitoring</a> .
<a href="#">indexes.conf</a>	Manage and configure <a href="#">index settings</a> .
<a href="#">inputs.conf</a>	Set up <a href="#">data inputs</a> .
<a href="#">instance.cfg</a>	Designate and manage settings for specific instances of Splunk. This can be handy, for example, when identifying forwarders for internal searches.
<a href="#">limits.conf</a>	Set various limits (such as maximum result size or <a href="#">concurrent real-time searches</a> ) for search commands.
<a href="#">literals.conf</a>	Customize the text, such as search error strings, displayed in Splunk Web.
<a href="#">macros.conf</a>	Define <a href="#">search macros</a> in Settings.

<a href="#">messages.conf</a>	Customize Splunk Web messages.
<a href="#">metric_rollups.conf</a>	Set attribute/value pairs for metric rollup policy entries.
<a href="#">multikv.conf</a>	Configure <a href="#">extraction</a> rules for table-like events (ps, netstat, ls).
<a href="#">outputs.conf</a>	Set up forwarding behavior.
<a href="#">passwords.conf</a>	Maintain the credential information for an app.
<a href="#">procmon-filters.conf</a>	Monitor Windows process data.
<a href="#">props.conf</a>	Set indexing property configurations, including <a href="#">timezone offset</a> , custom source type rules, and pattern collision priorities. Also, map <a href="#">transforms</a> to event properties.
<a href="#">pubsub.conf</a>	Define a custom client of the <a href="#">deployment server</a> .
<a href="#">restmap.conf</a>	Create custom REST endpoints.
<a href="#">savedsearches.conf</a>	Define <a href="#">ordinary reports</a> , <a href="#">scheduled reports</a> , and <a href="#">alerts</a> .
<a href="#">searchbnf.conf</a>	Configure the <a href="#">search assistant</a> .
<a href="#">segmenters.conf</a>	Configure segmentation.

<code>server.conf</code>	Contains a variety of settings for configuring the overall state of a Splunk Enterprise instance. For example, the file includes settings for enabling <a href="#">SSL</a> , configuring nodes of an <a href="#">indexer cluster</a> or a <a href="#">search head cluster</a> , configuring <a href="#">KV store</a> , and setting up a <a href="#">license manager</a> .
<code>serverclass.conf</code>	Define <a href="#">deployment server classes</a> for use with deployment server.
<code>serverclass.seed.xml.conf</code>	Configure how to seed a <a href="#">deployment client</a> with apps at start-up time.
<code>source-classifier.conf</code>	Terms to ignore (such as sensitive data) when creating a <a href="#">source type</a> .
<code>sourcetypes.conf</code>	Machine-generated file that stores source type learning rules.
<code>tags.conf</code>	<a href="#">Configure tags for fields</a> .
<code>telemetry.conf</code>	Enable apps to collect telemetry data about app usage and other properties.
<code>times.conf</code>	Define <a href="#">custom time ranges</a> for use in the Search app.
<code>transactiontypes.conf</code>	Add additional <a href="#">transaction types</a> for transaction search.
<code>transforms.conf</code>	Configure <a href="#">regex transformations</a> to perform on data inputs. Use in tandem with <code>props.conf</code> .

<a href="#">ui-prefs.conf</a>	Change UI preferences for a view. Includes changing the default earliest and latest values for the time range picker.
<a href="#">user-seed.conf</a>	Set a <a href="#">default user and password</a> .
<a href="#">visualizations.conf</a>	List the visualizations that an app makes available to the system.
<a href="#">viewstates.conf</a>	Use this file to set up UI views (such as charts).
<a href="#">web.conf</a>	Configure Splunk Web, <a href="#">enable HTTPS</a> .
<a href="#">web-features.conf</a>	Configure some Splunk Web settings.
<a href="#">wmi.conf</a>	Set up <a href="#">Windows management instrumentation (WMI) inputs</a> .
<a href="#">workflow_actions.conf</a>	Configure <a href="#">workflow actions</a> .
<a href="#">workload_policy.conf</a>	Enable or disable admission rules in workload management.
<a href="#">workload_pools.conf</a>	Configure <a href="#">workload pools</a> (compute and memory resource groups) that you can assign to searches in workload management.
<a href="#">workload_rules.conf</a>	Configure <a href="#">workload rules</a> to define access and priority for workload pools in workload management.